

Product Submittal Sheet

Technical Services: 888-437-3244 Engineering Services: 877-832-3206

Sales: 800-543-7140 clarkdietrich.com

T125 (1-1/4" Lea Structural Track) **Product category: Product name:** 550T125-54 (50ksi, CP60) - Unpunched

> 54mils (16ga) Coating: CP60 per ASTM C955

> > Color coding: Green

Geometric Properties

Web depth 5.698 in Lea width 1.25 in

Design thickness 0.0566 in Min. steel thickness 0.0538 in Yield strength, Fy 50 ksi *Fy with Cold-Work, Fya 50.0 ksi

Ultimate, Fu 65.0 ksi

Gross Section Properties of Full Section, Strong Axis

Cross sectional area (A)	0.452 in ²
Member weight per foot of length	1.54 lb/ft
Moment of inertia (Ix)	1.904 in⁴
Section modulus (Sx)	0.668 in ³
Radius of gyration (Rx)	2.052 in
Gross moment of inertia (ly)	0.053 in⁴
Gross radius of gyration (Ry)	0.342 in

Effective Section Properties, Strong Axis

Effective Area (Ae)	0.233 in ²
Moment of inertia for deflection (Ix)	1.811 in⁴
Section modulus (Sx)	0.535 in ³
Allowable bending moment (Ma)	16.01 in-k
Allowable shear force in web	2980 lb

Torsional Properties

St. Venant torsion constant (J x 1000)	0.483 in ⁴
Warping constant (Cw)	0.315 in ⁶
Distance from shear center to neutral axis (Xo)	-0.532 in
Distance between shear center and web centerline (m)	0.345 in
Radii of gyration (Ro)	2.147 in
Torsional flexural constant (Beta)	0.939

ASTM & Code Standards:

- AISI North American Specification [NASPEC] S100-12
- * Effective properties incorporate the strength increase from the cold work of forming
- Gross properties are based on the cross section away from the punchouts
- Structural framing is produced to meet or exceed ASTM C955
- Sheet steel meets or exceeds mechanical and chemical requirements of ASTM A1003
- · ClarkDietrich's structural and nonstructural framing comply with the SFIA Code Compliance Certification Program, ICC-ES ESR-1166P and Intertek CCRR-0206
- For installation & storage information refer to ASTM C1007
- SDS & Product Certification Information is available at itools.clarkdietrich.com

Sustainability Credits: For more details and LEED letters contact Technical Services at 888-437-3244 or visit www.clarkdietrich.com/LEED

Fax:

LEED v4 MR Credit -- Building Product Disclosure and Optimization: EPD (1 point) - Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) - Innovation Credit (up to 2 points).

LEED 2009 Credit MR 2 & MR 4 - Clark Dietrich's steel products are 100% recyclable and have a national average recycled content of 34.2% (19.8% post-consumer and 14.4% pre-consumer). If seeking a higher number to meet Credit MR 5, please contact us at (info@clarkdietrich.com / 888-437-3244)

(t)

05.40.00 (Cold-Formed Metal Framing)

Used in framing applications:

- Load-bearing walls
- Curtain walls
- Tall interior walls
- Floor & ceiling joists
- Trusses

Project Information	Contractor Information	Architect Information
Name:	Name:	Name:
Address:	Contact:	Contact:
	Phone:	Phone:

Fax:

CD-STRT © 07/18 ClarkDietrich Building Systems