

Product Submittal Sheet

Technical Services: 888-437-3244 Engineering Services: 877-832-3206 Sales: 800-543-7140 clarkdietrich.com

Product category:		T125 (1-1/4" Leg Structural Track)			05.40.00 (Cold-Formed Metal Framing)	
Product name:	-	•	68 (50ksi, CP60) - Unr	ounched CP60 per ASTM C955		
Geometric Pro	perties	5	3			×
Web depth Leg width	14.250 1.25 ir) in I		0.0077	± •	Track
Design thickness Yield strength, Fy Ultimate, Fu	0.0713 50 ksi 65.0 ks	*Fy	n. steel thickness / with Cold-Work, Fya	0.0677 in 50.0 ksi		Structural
Gross Section	Proper	ties of Fu	Il Section, Strong	Axis		nci
Cross sectional area (A)			, 5	1.175 in ²		it
Member weight per foot of length				4.00 lb/ft	(t)	S
Moment of inertia (Ix)				25.208 in ⁴		
Section modulus (Sx)				3.538 in ³	Ý	
Radius of gyration (Rx)				4.631 in	WIDTH	
Gross moment of inertia (ly) Gross radius of gyration (Ry)				0.076 in ⁴		
Gross radius of gy	ration (F	(y)		0.254 in	Used in framing applications:	
Effective Section Properties, Strong Axis					 Load-bearing walls 	
Effective Area (Ae)				0.374 in ²	Curtain walls	
Moment of inertia for deflection (Ix)				22.623 in ⁴	Tall interior walls	
Section modulus (Sx)				2.293 in ³		

- Floor & ceiling joists
- Trusses

Moment of inertia for deflection (Ix)	22.623 in⁴
Section modulus (Sx)	2.293 in ³
Allowable bending moment (Ma)	68.65 in-k
Allowable shear force in web	2322 lb

Torsional Properties

St. Venant torsion constant (J x 1000)	1.992 in ⁴
Warping constant (Cw)	3.189 in ⁶
Distance from shear center to neutral axis (Xo)	-0.296 in
Distance between shear center and web centerline (m)	0.206 in
Radii of gyration (Ro)	4.648 in
Torsional flexural constant (Beta)	0.996

ASTM & Code Standards:

- AISI North American Specification [NASPEC] S100-12
- * Effective properties incorporate the strength increase from the cold work of forming
- Gross properties are based on the cross section away from the punchouts
- Structural framing is produced to meet or exceed ASTM C955
- Sheet steel meets or exceeds mechanical and chemical requirements of ASTM A1003 ClarkDietrich's structural and nonstructural framing comply with the SFIA Code Compliance Certification Program, ICC-ES ESR-1166P and Intertek CCRR-0206
- For installation & storage information refer to ASTM C1007
- SDS & Product Certification Information is available at itools.clarkdietrich.com

Sustainability Credits:

For more details and LEED letters contact Technical Services at 888-437-3244 or visit www.clarkdietrich.com/LEED

LEED v4 MR Credit -- Building Product Disclosure and Optimization: EPD (1 point) - Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) - Innovation Credit (up to 2 points).

LEED 2009 Credit MR 2 & MR 4 -- Clark Dietrich's steel products are 100% recyclable and have a national average recycled content of 34.2% (19.8% post-consumer and 14.4% pre-consumer). If seeking a higher number to meet Credit MR 5, please contact us at (info@clarkdietrich.com / 888-437-3244)

Project Information	Contractor Information	Architect Information
Name:	Name:	Name:
Address:	Contact:	Contact:
	Phone:	Phone:
	Fax:	Fax: