

Product Submittal Sheet

Technical Services: 888-437-3244 Engineering Services: 877-832-3206 Sales: 800-543-7140 clarkdietrich.com

Product catego	ory: T150	T150 (1-1/2" Leg Structural Track) 1150T150-68 (50ksi, CP60) - Unpunched		05.40.00 (Cold-Formed Meta
Product name				Y
	68mi	ls (14ga) Coating Color coding	: CP60 per ASTM C955 : Orange	
Geometric Pro	perties			
Web depth	11.750 in			
Leg width	1.5 in			m
Design thickness	0.0713 in	Min. steel thickness	0.0677 in	
Yield strength, Fy	50 ksi	*Fy with Cold-Work, Fya	50.0 ksi	
Ultimate, Fu	65.0 ksi			ž - Xo
Gross Section	Properties	of Full Section, Strong	Axis	
Cross sectional ar	ea (A)		1.033 in ²	
Member weight pe	er foot of lengt	h	3.51 lb/ft	(t) <u>- </u>
Moment of inertia	(Ix)		16.290 in⁴	
Section modulus (Sx)		2.773 in ³	Y
Radius of gyration			3.972 in	
Gross moment of			0.127 in ⁴	
Gross radius of gy	ration (Ry)		0.350 in	Used in framing application
Effective Secti	on Properti	ies, Strong Axis		 Load-bearing walls
		les, Strong Axis	0.378 in ²	 Curtain walls
Effective Area (Ae)		(12)	14.987 in ⁴	Tall interior walls
Moment of inertia for deflection (Ix) Section modulus (Sx)			1.895 in ³	
Allowable bending moment (Ma)			56.75 in-k	 Floor & ceiling joists
, nowable bending		/	00.10 III K	T

Trusses

Torsional Properties

Allowable shear force in web

St. Venant torsion constant (J x 1000)	1.750 in⁴
Warping constant (Cw)	3.450 in ⁶
Distance from shear center to neutral axis (Xo)	-0.463 in
Distance between shear center and web centerline (m)	0.314 in
Radii of gyration (Ro)	4.014 in
Torsional flexural constant (Beta)	0.987

ASTM & Code Standards:

- AISI North American Specification [NASPEC] S100-12
- * Effective properties incorporate the strength increase from the cold work of forming
- · Gross properties are based on the cross section away from the punchouts
- Structural framing is produced to meet or exceed ASTM C955
- Sheet steel meets or exceeds mechanical and chemical requirements of ASTM A1003 ClarkDietrich's structural and nonstructural framing comply with the SFIA Code Compliance
- Certification Program, ICC-ES ESR-1166P and Intertek CCRR-0206
- For installation & storage information refer to ASTM C1007
- SDS & Product Certification Information is available at itools.clarkdietrich.com

Sustainability Credits:

For more details and LEED letters contact Technical Services at 888-437-3244 or visit www.clarkdietrich.com/LEED


LEED v4 MR Credit -- Building Product Disclosure and Optimization: EPD (1 point) - Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) - Innovation Credit (up to 2 points).

2832 lb

LEED 2009 Credit MR 2 & MR 4 -- ClarkDietrich's steel products are 100% recyclable and have a national average recycled content of 34.2% (19.8% post-consumer and 14.4% pre-consumer). If seeking a higher number to meet Credit MR 5, please contact us at (info@clarkdietrich.com / 888-437-3244)

Project Information	Contractor Information	Architect Information
Name:	Name:	Name:
Address:	Contact:	Contact:
	Phone:	Phone:
	Fax:	Fax:

al Framing)



ons:

- Floor & ceiling joists