

Product Submittal Sheet

Technical Services: 888-437-3244 Engineering Services: 877-832-3206 Sales: 800-543-7140 clarkdietrich.com

Product category: Product name:		T250 (2-1/2" Leg Structural Track)		05.40.00 (Cold-Formed Metal Framing)		
		250T250-68 (50ksi, CP60) - Unpunched			Y	
				: CP60 per ASTM C955		
Geometric Pro	pertie	S				×
Web depth	2.750					Track
Leg width	2.5 in				m	Ë
Design thickness	0.071	3 in	Min. steel thickness	0.0677 in		
Yield strength, Fy	50 ks	i	*Fy with Cold-Work, Fya	50.0 ksi		a
Ultimate, Fu	65.0 l	ksi			₩ - ו	t di
Gross Section	Prope	rties o	f Full Section, Strong	Axis		Structural
Cross sectional area (A)				0.534 in ²		
Member weight per foot of length				1.82 lb/ft	(t) <u></u>	S
Moment of inertia (Ix)				0.728 in⁴		
Section modulus (Sx)				0.530 in ³	Y	
Radius of gyration (Rx)				1.168 in	UEG WIDTH	
Gross moment of inertia (ly)				0.360 in⁴		_
Gross radius of gy	ration (Ry)		0.821 in	Used in framing applications:	
Effective Section Properties, Strong Axis					 Load-bearing walls 	
Effective Area (Ae)				0.334 in ²	 Curtain walls 	
Moment of inertia for deflection (Ix)				0.576 in ⁴	 Tall interior walls 	
Section modulus (Sx)			,	0.310 in ³		
Allowable bending moment (Ma)				9 27 in-k	 Floor & ceiling joists 	

Trusses

Effective Area (Ae)	0.334 in ²
Moment of inertia for deflection (Ix)	0.576 in⁴
Section modulus (Sx)	0.310 in ³
Allowable bending moment (Ma)	9.27 in-k
Allowable shear force in web	3199 lb

Torsional Properties

St. Venant torsion constant (J x 1000)	0.904 in⁴
Warping constant (Cw)	0.466 in ⁶
Distance from shear center to neutral axis (Xo)	-1.855 in
Distance between shear center and web centerline (m)	1.043 in
Radii of gyration (Ro)	2.341 in
Torsional flexural constant (Beta)	0.372

ASTM & Code Standards:

- AISI North American Specification [NASPEC] S100-12
- * Effective properties incorporate the strength increase from the cold work of forming
- · Gross properties are based on the cross section away from the punchouts
- Structural framing is produced to meet or exceed ASTM C955
- Sheet steel meets or exceeds mechanical and chemical requirements of ASTM A1003 ClarkDietrich's structural and nonstructural framing comply with the SFIA Code Compliance
- Certification Program, ICC-ES ESR-1166P and Intertek CCRR-0206
- For installation & storage information refer to ASTM C1007
- SDS & Product Certification Information is available at itools.clarkdietrich.com

Sustainability Credits:

For more details and LEED letters contact Technical Services at 888-437-3244 or visit www.clarkdietrich.com/LEED

LEED v4 MR Credit -- Building Product Disclosure and Optimization: EPD (1 point) - Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) - Innovation Credit (up to 2 points).

LEED 2009 Credit MR 2 & MR 4 -- Clark Dietrich's steel products are 100% recyclable and have a national average recycled content of 34.2% (19.8% post-consumer and 14.4% pre-consumer). If seeking a higher number to meet Credit MR 5, please contact us at (info@clarkdietrich.com / 888-437-3244)

Project Information	Contractor Information	Architect Information
Name:	Name:	Name:
Address:	Contact:	Contact:
	Phone:	Phone:
	Fax:	Fax: