

Product Submittal Sheet

Technical Services: 888-437-3244 Engineering Services: 877-832-3206 Sales: 800-543-7140 clarkdietrich.com

Product catego	ory: T2	T250 (2-1/2" Leg Structural Track)		05.40.00 (Cold-Formed Metal Framing)	
Product name:	35	0T250-33 (33ksi, CP60) - Unp	unched :CP60 per ASTM C955		
Geometric Pro Web depth	perties 3.646 in		. White		Γrack
Leg width Design thickness Yield strength, Fy Ultimate, Fu	2.5 in 0.0346 in 33 ksi 45.0 ksi	Min. steel thickness *Fy with Cold-Work, Fya	0.0329 in 33.0 ksi		
Member weight per foot of length 1.0			0.294 in² 1.00 lb/ft	(1)	Structural
Moment of inertia (Ix) Section modulus (Sx) Radius of gyration (Rx) Gross moment of inertia (Iy)			0.687 in ⁴ 0.377 in ³ 1.528 in 0.198 in ⁴		
Gross radius of gyration (Ry)			0.821 in	Used in framing applications:	
Effective Section Properties, Strong Axis Effective Area (Ae)			0.112 in² 0.468 in⁴	• Curtain walls	
Moment of inertia for deflection (Ix)			0.400 11	 Tall interior walls 	

- Floor & ceiling joists
 - Trusses

Effective Area (Ae)	0.112 in ²
Moment of inertia for deflection (Ix)	0.468 in⁴
Section modulus (Sx)	0.188 in ³
Allowable bending moment (Ma)	3.71 in-k
Allowable shear force in web	1024 lb
This section does not meet the requirements of AISI North American Specificat	one Increase the thickness (

This section does not meet the requirements of AISI North American Specifications. Increase the thickness or contact ClarkDietrich Technical Services @ 888-437-3244 for design solutions.

Torsional Properties

St. Venant torsion constant (J x 1000)	0.117 in⁴
Warping constant (Cw)	0.456 in ⁶
Distance from shear center to neutral axis (Xo)	-1.725 in
Distance between shear center and web centerline (m)	0.999 in
Radii of gyration (Ro)	2.446 in
Torsional flexural constant (Beta)	0.503

ASTM & Code Standards:

- AISI North American Specification [NASPEC] S100-12
- * Effective properties incorporate the strength increase from the cold work of forming
- Gross properties are based on the cross section away from the punchouts
- Structural framing is produced to meet or exceed ASTM C955
- Sheet steel meets or exceeds mechanical and chemical requirements of ASTM A1003
- ClarkDietrich's structural and nonstructural framing comply with the SFIA Code Compliance
- Certification Program, ICC-ES ESR-1166P and Intertek CCRR-0206
- For installation & storage information refer to ASTM C1007
- SDS & Product Certification Information is available at itools.clarkdietrich.com

Sustainability Credits:

For more details and LEED letters contact Technical Services at 888-437-3244 or visit www.clarkdietrich.com/LEED

LEED v4 MR Credit -- Building Product Disclosure and Optimization: EPD (1 point) - Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) - Innovation Credit (up to 2 points).

LEED 2009 Credit MR 2 & MR 4 -- ClarkDietrich's steel products are 100% recyclable and have a national average recycled content of 34.2% (19.8% post-consumer and 14.4% pre-consumer). If seeking a higher number to meet Credit MR 5, please contact us at (info@clarkdietrich.com / 888-437-3244)

Project Information	Contractor Information	Architect Information
Name:	Name:	Name:
Address:	Contact:	Contact:
	Phone:	Phone:
	Fax:	Fax:
1		

