

Product Submittal Sheet

Technical Services: 888-437-3244 Engineering Services: 877-832-3206 Sales: 800-543-7140 clarkdietrich.com

Product category: T250 (2-1/2" Leg Structural Track)
Product name: 925T250-68 (50ksi, CP60) - Unpunched

68mils (14ga) Coating: CP60 per ASTM C955

Color coding: Orange

Geometric Properties

Web depth 9.500 in Leg width 2.5 in

Design thickness 0.0713 in Min. steel thickness 0.0677 in Yield strength, Fy 50 ksi *Fy with Cold-Work, Fya 50.0 ksi

Ultimate, Fu 65.0 ksi

Gross Section Properties of Full Section, Strong Axis

Cross sectional area (A)	015 in²
Member weight per foot of length 3.4	45 lb/ft
Moment of inertia (Ix) 12	2.597 in⁴
Section modulus (Sx) 2.6	652 in³
Radius of gyration (Rx) 3.5	523 in
Gross moment of inertia (ly) 0.5	526 in⁴
Gross radius of gyration (Ry) 0.7	720 in

Effective Section Properties, Strong Axis

Effective Area (Ae)	0.386 in ²
Moment of inertia for deflection (Ix)	10.855 in⁴
Section modulus (Sx)	1.781 in ³
Allowable bending moment (Ma)	53.34 in-k
Allowable shear force in web	3528 lb

Torsional Properties

St. Venant torsion constant (J x 1000)	1.720 in⁴
Warping constant (Cw)	8.569 in ⁶
Distance from shear center to neutral axis (Xo)	-1.179 in
Distance between shear center and web centerline (m)	0.752 in
Radii of gyration (Ro)	3.784 in
Torsional flexural constant (Beta)	0.903

ASTM & Code Standards:

- AISI North American Specification [NASPEC] S100-12
- * Effective properties incorporate the strength increase from the cold work of forming
- Gross properties are based on the cross section away from the punchouts
- Structural framing is produced to meet or exceed ASTM C955
- Sheet steel meets or exceeds mechanical and chemical requirements of ASTM A1003
- ClarkDietrich's structural and nonstructural framing comply with the SFIA Code Compliance Certification Program, ICC-ES ESR-1166P and Intertek CCRR-0206
- For installation & storage information refer to ASTM C1007
- SDS & Product Certification Information is available at itools.clarkdietrich.com

Sustainability Credits:

For more details and LEED letters contact Technical Services at 888-437-3244 or visit www.clarkdietrich.com/LEED

LEED v4 MR Credit -- Building Product Disclosure and Optimization: EPD (1 point) - Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) - Innovation Credit (up to 2 points).

LEED 2009 Credit MR 2 & MR 4 — ClarkDietrich's steel products are 100% recyclable and have a national average recycled content of 34.2% (19.8% post-consumer and 14.4% pre-consumer). If seeking a higher number to meet Credit MR 5, please contact us at (info@clarkdietrich.com / 888-437-3244)

05.40.00 (Cold-Formed Metal Framing)

Used in framing applications:

- Load-bearing walls
- Curtain walls
- Tall interior walls
- Floor & ceiling joists
- Trusses

Project Information	Contractor Information	Architect Information
Name:	Name:	Name:
Address:	Contact:	Contact:
	Phone:	Phone:
	Fax:	Fax:

CD-STRT © 07/18 ClarkDietrich Building Systems