

3/4" Bullnose J-Bead

Bullnose Corner Bead

Covers raw edges of drywall with 3/4" radius bullnose corner. Ideal for finishing door and window openings. The perforated flange accepts joint compound or veneer plaster for a flush finish. Designed to be applied after the wallboard is installed.

Product Data & Ordering Information:

Material: 0.028" PVC (Polyvinyl Chloride)

Dimensions: 7/8" perforated flanges with short back leg

Product code	Board thickness	Radius	Flange	Length	Pcs./Ctn.
BJB50S-8	1/2"	3/4"	7/8"	8'	30
BJB50S-10	1/2"	3/4"	7/8"	10'	30
BJB58S-10	5/8"	3/4"	7/8"	10'	30

Code Approvals & Performance Standards

- [ASTM C840](#) Standard Specification for Application and Finishing of Gypsum Board
- [ASTM C841](#) Standard Specification for Installation of Interior Lathing and Furring
- [ASTM C1047](#) Standard Specification for Accessories for Gypsum Wallboard and Gypsum Veneer Base
- [ASTM D3678](#) Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) Interior - Profile Extrusions
- [SDS Vinyl Corp](#) PVC Compounds

Storage:

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.



- Moisture and dent resistant
- Produces finished edges at panel terminations
- Nail or slip on

