

# CONCRETESEALERSUSA

Professional Concrete Solutions You Can Trust

32 US Ounces

**Product Description:** CS401 Color Tint is a high solids, concentrated, solvent based acrylic tint system specially formulated for adding to clear solvent based acrylic sealers for achieving a desired color for the sealer. CS401 is formulated with high quality, ultra fine particle pigments that easily disperse in solvent based acrylic sealers. CS401 is a superior choice to obtain a semi transparent stain or a solid opaque colored finish in most solvent based acrylic sealer systems. CS401 is a very economical and user friendly alternative to other color and staining systems on the market. Color tints are available in a selection of 14 colors.

**Recommended Uses:** CS401 is recommended for use with clear solvent based acrylic sealers. It is ideal for adding color to commercial and residential surfaces such as interior concrete floors, garages, driveways, sidewalks, walkways, porches, steps, pool decking, patios, and any other concrete surface where a colored sealer is desired.

**Limitations:** CS401 is designed to work only with solvent based acrylic sealers and is not intended for water based acrylic sealers or other water or solvent based topical coatings like epoxies, urethanes, etc. This product may damage vegetation. Avoid contact with glass, vinyl, plastic, wood, and metal. Color tint may be damaged if frozen prior to use. Not intended to seal cracks or for use where severe hydrostatic pressure is present. The coefficient of friction of the surface may decline with each sealer application. This can be offset by applying an anti skid compound (ex. sand) when sealer is still wet and prior to it drying. Certain tile adhesives may not bind to CS401. Always conduct test to confirm adhesion. The Company does not warranty specific performance results or compatibility with products manufactured by others. The Company shall bear no liability, other than replacement of defective product. A small test must be conducted prior to application. Based upon this test, the purchaser shall determine for themselves the suitability of this product for the intended use.

REFER TO SAFETY DATA SHEET PRIOR TO USE.

## CS401 Acrylic Color Tint

*Color Tint for  
Solvent Based Acrylic Sealers*

- Professional Grade
- Exterior & Interior
- Dries Clear

- ▶ 14 Colors Available
- ▶ Concentrated Formula
- ▶ Ultra Fine Pigments
- ▶ Mixes into Sealers

- ▶ Semi Transparent
- ▶ Opaque Finish
- ▶ Solvent Based Sealers
- ▶ Simple & Easy to Use

*Great for*  
Solvent Based Acrylic Sealers

**Surface Preparation:** Follow instructions from the manufacturer of the coating or sealer.

**Application:** Always test in small area prior to full application. Stir CS401 into solvent based acrylic sealer thoroughly before and during application. For a semi transparent appearance, mix up to 16 oz. of CS401 into 5 gallons of sealer. For a solid opaque appearance, mix 32 oz. of CS401 into 5 gallons of sealer. Actual usage rates may vary for different sealers and substrates depending on porosity, absorption, surface texture, and desired appearance. Do not add more than the recommended amount of color tint to the sealer. Excess tint can cause over pigmentation which may result in color float or streaking. Follow instructions from the sealer manufacturer on the proper application of the sealer once the color tint is mixed into the sealer.

**Usage Rate:** Mix up to 16 oz. of tint with 5 gallons of solvent based acrylic sealer for semi transparent appearance. Mix 32 oz. with 5 gallons of solvent based acrylic sealer for solid opaque appearance.

**Shelf Life:** 1 year unopened.

**Safety & First Aid Precautions:** Eyes: Flush with water for at least 15 minutes. Skin: Wash thoroughly with soap and water. Inhalation: Move subject to fresh air. Digestion: Consult physician immediately.

**Environmental & Regulatory:** CS401 contains petroleum distillates and is flammable. This product is considered a hazardous chemical under OSHA Hazard Communication Standard (29CFR 1910.1200). Keep away from heat, sparks, and open flames. Keep containers closed until ready to use. Provide adequate ventilation. To prevent vapor build up and possible explosion, open door and windows and provide cross ventilation. Do not smoke when using. Solvent vapors can cause respiratory irritation. Contact may cause skin or eye irritation. Using with adequate air ventilation, eye protection, and gloves is recommended. Do not reuse container without commercial cleaning. Dispose of in accordance with applicable federal, state, and local regulations.



Concrete Sealers USA  
P.O. Box 5464 | De Pere, WI 54115  
Toll-Free: 888.583.2991 | Emergency: 800.424.9300  
info@concretesealersusa.com | www.concretesealersusa.com

Sustainable  
**GREEN**  
Product



10"

5"

**CS401**  
32oz Label 10" x 5"