



CONTINENTAL™
BUILDING PRODUCTS

Benefiting
susan g. komen.



Applications

Weather Defense Shaftliner Type X is tested in a series of designs for a wide range of wall and enclosure applications.

- Elevator enclosures
- Stairwell enclosures
- Mechanical enclosures for electrical, plumbing, HVAC and venting services
- Unlined shafts for return air handling
- Area separation fire walls

Advantages

Low Installation Cost: Compared to block construction, installs easily and quickly. It is lightweight and scores, cuts and fastens with ease.

Mold Resistance: Offers enhanced protection against the growth of mold and mildew on its surface and in its core.

Moisture Resistance: Core treated for moisture resistance.

Weather Resistance: Provides protection in most applications from exposure to the elements for up to 12 months (subject to terms, conditions and exclusions of Continental's limited warranty).

FIBERGLASS MAT, MOLD-, MILDEW-, MOISTURE- AND FIRE-RESISTANT SHAFTLINER BOARD

WEATHER DEFENSE® SHAFTLINER TYPE X

Continental Building Products Weather Defense Shaftliner Type X is designed for use in lining elevator shafts, ventilation shafts, stairwells, for area separation walls in residential housing and for other interior building applications requiring fire resistance.

Weather Defense Shaftliner Type X has a specially formulated, non-combustible, moisture-, mildew- and mold-resistant gypsum core enhanced with glass fibers for strength and additional fire resistance. Its fiberglass matting eliminates paper, a potential food source for mold, and may help reduce remediation and scheduling delays making Weather Defense Shaftliner Type X a great alternative to traditional paper-faced shaftliners.

Weather Defense Shaftliner Type X panels are only one component of a shaft or area separation wall assembly. For fire-rated resistance, the panels must be used as required in the listed design. See the Continental Shaftwall and Area Separation Wall literature, or the Underwriters Laboratories (UL) listings.

As with any building material, avoiding exposure to water during handling, storage and installation is the best way to avoid the formation of mold and mildew. Weather Defense Shaftliner Type X offers enhanced protection against the growth of mold and mildew on its surface compared to ordinary drywall products. Under controlled testing conditions, Weather Defense Shaftliner Type X achieved an average panel score of 10 out of a possible 10, the highest level of performance for mold resistance using ASTM D3273.*

Note: Weather Defense Shaftliner Type X should not be used where temperatures exceed 125° F for extended periods or in areas of extreme humidity. Likewise, the board should be protected from exposure to adverse conditions during storage and construction. Weather Defense Shaftliner Type X is not designed for exterior use or for the exposed element of an unlined air supply duct.

JOB NAME:

CONTRACTOR:

DATE:

Sustainability

Can contribute to the U.S. Green Building Council's LEED Credit Qualification in several credit categories to assist in obtaining LEED certification.



Limitations: Weather Defense is not designed as a finished surface or for the direct application of textures, paints or coatings. Weather Defense is not designed as a nailing base. Mechanical fastening should pass through Weather Defense and fasten to the framing members. Do not immerse Weather Defense in water or subject to cascading water.

*Weather Defense provides extra resistance against the formation of mold, but no product may be considered "mold proof." The most effective way to avoid the formation of mold and mildew in drywall products is to limit or avoid water exposure during storage and construction, and after construction is complete. Used in combination with appropriate design, handling, construction and installation practices, Weather Defense drywall can provide increased mold and mildew resistance on its surface. ASTM D3273 is the "Standard Test Method for Resistance to Growth of Mold on the Surface of Interior Coatings in an Environmental Chamber" and is performed under controlled laboratory conditions. Actual storage, handling, construction and installation conditions may vary from the environment created in the independent lab, and the use of the product in actual conditions may not replicate the ASTM results.



CONTINENTAL BUILDING PRODUCTS

USA (800) 237-5505
Canada (866) 649-7786
www.continentalbp.com

Physical Characteristics

Core: Non-combustible, dimensionally stable, inert gypsum, enhanced with glass fibers for strength and fire resistance and a moisture-resistant additive, and chemically treated to resist mold and mildew in the core

Facer: Coated fiberglass; Water-repellent; Chemically treated to resist mold and mildew on the surface; Front = Susan G. Komen pink and white, edges = white, back = platinum

Long Edges: Double beveled for ease of

Standards and Codes

Formulated to conform with ASTM C1658/C1658M, Section 6, Type X and meets the properties of ASTM C1396, Section 6, Gypsum Shaftliner Board, Type X;

Technical Specifications

UL classified for surface burning (File No. R16102) (per ASTM E84 and CAN/ULC-S102) Flame spread = 0; Smoke developed = 0; Meeting IBC, Section 803.1, Class A

Core combustibility (per ASTM E136) Non-combustible

UL classified for fire resistance (File No. R18482) as Type LGFCSL per ASTM E119 and CAN/ULC-S101; For use in UL designs U388, U428, U429, V481 and others

Mold and mildew resistant (10 out of 10 score, ASTM D3273)*

Moisture resistant per ASTM C1177 Section 5.2.5 <10%

Installation

Install all components as specified by the listed designs. Consult the Gypsum Association GA-600 Fire Resistance Design Manual and the UL Fire Resistance Directory. For general practices see GA-216 and ASTM C840.

Handling Recommendations

Stack flat, keep dry and lift (do not drag) to avoid scuffing. Avoid damage to edges. For detailed recommendations, refer to GA-216, GA-238 and GA-801.

Safety Precautions

Wear safety glasses and NIOSH-approved respirators during cutting, breaking, rasping or other dust-producing activities.

Safety Data Sheets (SDS) are available for all Continental products upon request.

installation

Recycled Content: 94% by weight

Asbestos free

Available Sizes:

Nominal thickness	1 in.
Nominal width	2 ft.
Standard length	8 ft.-12 ft.
Nominal weight	4 lbs./ft. ²

