



Safety Data Sheet

According to OSHA Communication Standard, 29 CFR 1910.1200

DOT Repair Mix

SECTION 1: Identification

Product identifier

Product name: DOT Repair Mix

Product code: 171010055, 171012000, 171013000, 171013300, 171040055

Recommended use of the product and restriction on use

Relevant identified uses: Use for cement applications

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

CTS Cement Manufacturing Corporation

12442 Knott St.

Garden Grove, CA 92841

800-929-3030

info@ctscement.com

Emergency telephone number:

United States

INFOTRAC 1-800-535-5053

International

INFOTRAC 1-352-323-3500

SECTION 2: Hazard(s) identification

GHS classification:

Skin irritation, category 2

Serious eye damage, category 1

Specific target organ toxicity - single exposure, category 3, respiratory irritation

Carcinogenicity, category 1A

Specific target organ toxicity - repeated exposure, category 2

Label elements

Hazard

Pictograms:



Signal word: Danger

Hazard statements:

H315 Causes skin irritation.

**Safety Data Sheet**

According to OSHA Communication Standard, 29 CFR 1910.1200

DOT Repair Mix

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H350 May cause cancer.

H373 May cause damage to lungs through prolonged or repeated exposure by inhalation.

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash hands/eyes/mouth/skin/clothing thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P233 Keep container tightly closed.

P281 Use personal protective equipment as required.

P321 Specific treatment (see supplemental first aid instructions on this label).

P362 Take off contaminated clothing and wash before reuse

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P308+P313 If exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazards not otherwise classified: None.**SECTION 3: Composition/information on ingredients**

Identification	Name	Weight %
CAS number: 12004-14-7	Aluminum calcium oxide sulfate	10-30
CAS number: 10034-77-2	Dicalcium silicate	10-40
CAS number: 7778-18-9	Calcium sulfate	1-15
CAS number: 14808-60-7	Silica, crystalline quartz	0-0.1
CAS number: 50-00-0	Formaldehyde	<0.01

Additional Information:



Safety Data Sheet

According to OSHA Communication Standard, 29 CFR 1910.1200

DOT Repair Mix

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200).

*Cement is primarily comprised of calcium compounds with oxides of aluminum, iron, sulfur, and silica. Trace amounts of naturally occurring, potentially harmful chemicals might be detected during chemical analysis. Trace constituents may include, but are not limited to, magnesium, potassium, sodium oxides, and hexavalent chromium.

SECTION 4: First aid measures

Description of first aid measures

General notes:

Not determined or not applicable.

After inhalation:

Loosen clothing as necessary and position individual in a comfortable position. Maintain an unobstructed airway. Get medical advice/attention if you feel unwell. Take precautions to ensure your own safety. Remove source of exposure or move person to fresh air. Get medical advice if you feel unwell or concerned.

After skin contact:

Rinse affected area with soap and water. If symptoms develop or persist, seek medical attention. Take off all contaminated clothing. Gently blot or brush away excess product. Wash with plenty of lukewarm, gently flowing water. Get medical advice if skin irritation occurs or you feel unwell.

After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes. If symptoms develop or persist, seek medical attention. Avoid direct contact and wear chemical protective gloves, if necessary. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do so. Continue rinsing until medical aid is available. Immediately call a POISON CONTROL CENTER or seek medical attention.

After swallowing:

Rinse mouth thoroughly. Seek medical attention if irritation, discomfort, or vomiting persists.

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Not determined or not applicable.

Delayed symptoms and effects:

Not determined or not applicable.

Immediate medical attention and special treatment Specific treatment:

Not determined or not applicable.

Notes for the doctor:

Not determined or not applicable.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

**Safety Data Sheet**

According to OSHA Communication Standard, 29 CFR 1910.1200

DOT Repair Mix

Use appropriate fire suppression agents for adjacent combustible materials or sources of ignition.

Unsuitable extinguishing media:

Not determined or not applicable.

Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors.

Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit.

Special precautions:

Carbon monoxide and carbon dioxide may form upon combustion. Heating causes a rise in pressure, risk of bursting and combustion.

SECTION 6: Accidental release measures**Personal precautions, protective equipment and emergency procedures:**

Ensure adequate ventilation. Ensure air handling systems are operational. Wear protective eyewear, gloves, and clothing.

Environmental precautions:

Should not be released into the environment. Prevent from reaching drains, sewer or waterway.

Methods and material for containment and cleaning up:

Wear protective eyewear, gloves and clothing. Sweep or scoop up solid material while minimizing dust generation. Dispose of contents / container in accordance with local regulations.

Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage**Precautions for safe handling:**

Use only with adequate ventilation. Avoid breathing dust. Do not eat, drink, smoke or use personal products when handling chemical substances.

Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed. Keep container dry. Store locked up. Store in a cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Silica, crystalline quartz (Respirable)	14808-60-7	ACGIH TLV TWA 0.025 mg/m ³ (Respirable fraction)
	Total Silica, crystalline quartz	14808-60-7	TWA 0.025000 mg/m ³ USA. ACGIH
	Formaldehyde	50-00-	ACGIH TLV 0.3 ppm (ceiling)
United States (OSHA)	Silica, crystalline quartz (Respirable)	14808-60-7	OSHA 8-hour TWA PEL: 0.025 mg/m ³ (Respirable fraction, action level)
	Silica, crystalline quartz (Respirable)	14808-60-7	OSHA 8-hour TWA PEL: 0.05

**Safety Data Sheet**

According to OSHA Communication Standard, 29 CFR 1910.1200

DOT Repair Mix

			mg/m ³ (Respirable fraction, exposure limit level)
	Total Silica, crystalline quartz	14808-60-7	TWA 30.000000 mg/m ³ / %SiO ₂ +2 USA. OSHA
	Total Silica, crystalline quartz	14808-60-7	TWA 0.050000 mg/m ³ USA. NIOSH
	Formaldehyde	50-00-0	OSHA PEL TWA 0.75 mg/m ³
	Formaldehyde	50-00-0	OSHA STEL 2 ppm

Country (Legal Basis)	Substance	Identifier	Permissible concentration
NIOSH	Silica, crystalline quartz (Respirable)	14808-60-7	NIOSH TWA 0.05 mg/m ³
	Formaldehyde	50-00-0	NIOSH REL TWA 0.016 ppm
	Formaldehyde	50-00-0	NIOSH REL C 0.1 ppm

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. Biological monitoring may also be appropriate for some substances.

Appropriate engineering controls:

Emergency eyewash fountains and safety showers should be available in the immediate vicinity of use or handling. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

Personal protection equipment**Eye and face protection:**

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance. Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygienic measures:

Avoid contact with skin, eyes and clothing. Wash hands before breaks and at the end of work. Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

**Safety Data Sheet**

According to OSHA Communication Standard, 29 CFR 1910.1200

DOT Repair Mix**Information on basic physical and chemical properties**

Appearance	Solid; tan powder
Odor	Low
Odor threshold	Not available
pH	11 - 12 when wet
Melting point/freezing point	Not available
Initial boiling point/range	Not applicable
Flash point (closed cup)	Not available
Evaporation rate	Not applicable
Flammability (solid, gas)	Not available
Upper flammability/explosive limit	Not available
Lower flammability/explosive limit	Not available
Vapor pressure	Not applicable
Vapor density	Not applicable
Density	Not available
Relative density	2.96 – 2.98 at 20°C
Solubilities	Partially soluble
Partition coefficient (n-octanol/water)	Not available
Auto/Self-ignition temperature	Not available
Decomposition temperature	2460°F (1350°C)
Dynamic viscosity	Not applicable
Kinematic viscosity	Not applicable
Explosive properties	Not available
Oxidizing properties	Not available

Other information

Bulk density	60 lb/ft ³
VOC (Weight %)	0 g/l when mixed with water

SECTION 10: Stability and reactivity**Reactivity:**

Does not react under normal conditions of use and storage.

Chemical stability:

Stable under normal conditions of use and storage.

Possibility of hazardous reactions:

None under normal conditions of use and storage.

Conditions to avoid:

None known.

Incompatible materials:

**Safety Data Sheet**

According to OSHA Communication Standard, 29 CFR 1910.1200

DOT Repair Mix

None known.

Hazardous decomposition products:

None known.

SECTION 11: Toxicological information**Information on toxicological effects:****Acute toxicity****Assessment:** Based on available data, the classification criteria are not met.**Product data:** No data is available.**Substance data:**

Name	Route	Result
Formaldehyde	Oral	LD50 Rat: 100 mg/kg
	Dermal	LD50 Rabbit: 270 mg/kg

Skin corrosion/irritation**Assessment:** Causes skin irritation.**Product data:** No data is available.**Substance data:**

Name	Result
Dicalcium silicate	Causes skin irritation.
Formaldehyde	Causes severe skin burns and eye damage.

Serious eye damage/irritation**Assessment:** Causes serious eye damage.**Product data:** No data is available.**Substance data:**

Name	Result
Dicalcium silicate	Causes serious eye damage.

Respiratory or skin sensitization**Assessment:** Based on available data, the classification criteria are not met.**Product data:** No data is available.**Substance data:**

Name	Result
Formaldehyde	May cause an allergic skin reaction.

Carcinogenicity**Assessment:** May cause cancer.**Product data:** No data is available.**Substance data:**

Name	Species	Result
------	---------	--------

**Safety Data Sheet**

According to OSHA Communication Standard, 29 CFR 1910.1200

DOT Repair Mix		
Silica, crystalline quartz (Respirable)	Not applicable	Component may cause cancer.
Total Silica, crystalline quartz		1 - Group 1: Carcinogenic to humans (Quartz)
Formaldehyde		May cause cancer.

International Agency for Research on Cancer (IARC):

Name	Classification
Silica, crystalline quartz (Respirable)	Group 1 - Carcinogenic to humans
Formaldehyde	Group 1 - Carcinogenic to humans

National Toxicology Program (NTP):

Name	Classification
Silica, crystalline quartz (Respirable)	Known to be human carcinogens
Formaldehyde	Known to be human carcinogens

Germ cell mutagenicity**Assessment:** Based on available data, the classification criteria are not met.**Product data:** No data is available.**Substance data:**

Name	Result
Formaldehyde	Suspected of causing genetic defects

Reproductive toxicity**Assessment:** Based on available data, the classification criteria are not met.**Product data:** No data is available.**Substance data:** No data is available.**Specific target organ toxicity (single exposure)****Assessment:** May cause respiratory irritation**Product data:** No data is available.**Substance data:**

Name	Result
Dicalcium silicate and Calcium Sulfate	May cause respiratory irritation.

Aspiration toxicity**Assessment:** Based on available data, the classification criteria are not met.**Product data:** No data is available.

**Safety Data Sheet**

According to OSHA Communication Standard, 29 CFR 1910.1200

DOT Repair Mix**Substance data:** No data is available.**Information on likely routes of exposure:**

No data is available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data is available.

Other information:

No data is available.

SECTION 12: Ecological information**Acute (short-term) toxicity****Assessment:** Based on available data, the classification criteria are not met.**Product data:** No data available.**Substance data:** No data available.**Chronic (long-term) toxicity****Assessment:** Based on available data, the classification criteria are not met.**Product data:** No data available.**Substance data:** No data available.**Persistence and degradability****Product data:** No data available.**Substance data:**

Name	Result
Formaldehyde	Readily biodegradable in water.

Bioaccumulative potential**Product data:** No data available.**Substance data:**

Name	Result
Formaldehyde	BCF (aquatic species): 0.396 dimensionless

Mobility in soil**Product data:** No data available.**Substance data:**

Name	Result
Formaldehyde	Mobile (Calculated log Koc: 1.202)

Other adverse effects: No data available.**SECTION 13: Disposal considerations****Disposal methods:**

**Safety Data Sheet**

According to OSHA Communication Standard, 29 CFR 1910.1200

DOT Repair Mix

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities.

SECTION 14: Transport information**United States Transportation of dangerous goods (49 CFR DOT)**

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Maritime Dangerous Goods (IMDG)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

SECTION 15: Regulatory information**United States regulations Inventory listing (TSCA):**

12004-14-7	Aluminum calcium oxide sulfate	Listed
10034-77-2	Dicalcium silicate	Listed
7778-18-9	Calcium sulfate	Listed
14808-60-7	Silica, crystalline quartz	Listed
50-00-0	Formaldehyde	Listed

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export notification under TSCA Section 12(b): None of the ingredients are listed.

**Safety Data Sheet**

According to OSHA Communication Standard, 29 CFR 1910.1200

DOT Repair Mix**SARA Section 302 extremely hazardous substances:** None of the ingredients are listed.**SARA Section 313 toxic chemicals:** None of the ingredients are listed.**CERCLA:** None of the ingredients are listed.**RCRA:** None of the ingredients are listed.**Section 112(r) of the Clean Air Act (CAA):** None of the ingredients are listed.**Massachusetts Right to Know:**

14808-60-7	Silica, crystalline quartz (Respirable)	Listed
50-00-0	Formaldehyde	Listed

New Jersey Right to Know:

14808-60-7	Silica, crystalline quartz (Respirable)	Listed
50-00-0	Formaldehyde	Listed

New York Right to Know:

14808-60-7	Silica, crystalline quartz (Respirable)	Listed
50-00-0	Formaldehyde	Listed

Pennsylvania Right to Know:

14808-60-7	Silica, crystalline quartz (Respirable)	Listed
50-00-0	Formaldehyde	Listed

California Proposition 65:

 **WARNING:** Cancer and Reproductive Harm – www.P65Warning.ca.gov.

SECTION 16: Other information**Abbreviations and Acronyms:**

ACGIH: American Conference of Governmental Industrial Hygienists
 ADR: European Road Transport
 AU: Australia
 CA: Canada
 CAS: Chemical Abstracts Service
 CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act
 CN: China
 CPR: Controlled Products Regulations
 DFG: Deutsche Forschungsgemeinschaft
 DOT: Department of Transportation

**Safety Data Sheet**

According to OSHA Communication Standard, 29 CFR 1910.1200

DOT Repair Mix

DSL: Domestic Substances List
EEC: European Economic Community
ECHA: European Chemicals Agency
EINECS: European Inventory of Existing Commercial Chemical Substances
EPA: Environmental Protection Agency
EU: European Association
IARC: International Agency for Reach on Cancer
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
JP: Japan
COD: Chemical Oxygen Demand
BOD5: 5-day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
CL50: Lethal Concentration 50
EC50: Effective concentration 50
Log-POW: Octanol-water partition coefficient
Koc: Partition coefficient of organic carbon
Kow: Octanol/water partition coefficient
KR: Korea
LEL: Lower Explosive Limit
UEL: Upper Explosive Limit
NIOSH: National Institute for Occupational Safety and Health Administration
PH: Philippines
RCRA: Resource Conservation and Recovery Act
OSHA: Occupational Safety and Health Administration
RID: European Rail Transport
SARA: Superfund Amendments and Reauthorization Act
STEL: Short Term Exposure Limit
TDG: Transportation of Dangerous Goods
TSCA: Toxic Substances Control Act
TWA: Time Weighted Average
US: United States

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 3-0-0**HMIS:** 3*-0-0**Initial preparation date:** 11/01/18**Version #:** 3**Revision Date:** 04/11/22**End of Safety Data Sheet**