



According to OSHA Communication Standard, 29 CFR 1910.1200

Rapid Set TXP Super Fast

SECTION 1: Identification

Product identifier

Product name: TXP Super Fast Part A

Product code:

Recommended use of the product and restriction on use

Relevant identified uses: Use for epoxy primer applications Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

CTS Cement Manufacturing Corporation 12442 Knott St. Garden Grove, CA 92841 800-929-3030 info@ctscement.com

Emergency telephone number:

United States

INFOTRAC 800-535-5053

Information Telephone Number 800-282-5828

SECTION 2: Hazard(s) identification

GHS classification:

Corrosion / skin irritation: Category2 Severe eye damage / irritation: Category2A

Sensitization of the skin: Category 1 Chronic aquatic toxicity: category 2

Label elements

Hazard Pictograms:



Signal word: Warning

Hazard statements:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes severe eye irritation.

H401 Toxic to aquatic life.





According to OSHA Communication Standard, 29 CFR 1910.1200

Rapid Set TXP Super Fast

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P261 Avoid breaking dust, smoke, gas, fog, vapors, spray.
- P264 Wash hands/eyes/mouth/skin/clothing thoroughly after handling.
- P270 Do not eat, drink or smoke while handling this product.
- P272 Contaminated work clothing cannot be removed from the workplace.
- P273 Do not disperse in the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P331 Do not induce vomiting.
- P360 Rinse immediately contaminated clothing and skin with plenty of water before removing clothes.
- P362 Take off contaminated clothing and wash before reuse
- P363 Wash contaminated clothing before reuse.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazards not otherwise classified: None.

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 25068-38-6; 5095-03-6	Modified epoxy resin	80-100

Additional Information:

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200).

SECTION 4: First aid measures

Description of first aid measures

General notes:

Seek medical advice. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately.





According to OSHA Communication Standard, 29 CFR 1910.1200

Rapid Set TXP Super Fast

After inhalation:

Move to fresh air.

After skin contact:

Immediately remove contaminated clothing, and any extraneous chemical, if possible, to do so without delay. Flush immediately with copious amounts of water. Initiate and maintain continuous irrigation until the patient receives medical care. If medical care is not promptly available, continue to irrigate for one hour. Cover wound with sterile dressing. NOTE TO PHYSICIANS: Application of corticosteroid cream has been effective in treating skin irritation.

After eye contact:

Hold eyelids apart, initiate and maintain gentle and continuous irrigation until the patient receives medical care. If medical care is not promptly available, continue to irrigate for one hour.

After swallowing:

Never give anything by mouth to an unconscious person. Do not induce vomiting without medical advice. Prevent aspiration of vomit. Turn victim's head to the side.

Most important symptoms and effects, both acute and delayed

Acute and delayed symptoms and effects:

Eye disease. Skin disorders and Allergies.

Immediate medical attention and special

treatment Specific treatment:

Not determined or not applicable.

Notes for the doctor:

Not determined or not applicable.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Use foaming agent in use or water spray. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function but will be less effective.

Unsuitable extinguishing media:

Do not use direct water stream. May spread fire.

Specific hazards during fire-fighting:

During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Phenolic compounds. Nitrogen oxides. Carbon monoxide. Carbon dioxide. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

Special protective equipment for firefighters:

Wear positive-pressure self-contained breathing apparatus (SCBA) and protective firefighting clothing (includes firefighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during firefighting operations. If contact is likely, change to full chemical resistant firefighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.





According to OSHA Communication Standard, 29 CFR 1910.1200

Rapid Set TXP Super Fast

Special precautions:

Keep people away. Isolate fire and deny unnecessary entry. Do not use direct water stream. May spread fire. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Use self-contained breathing apparatus and chemically protective clothing. Evacuate personnel to safe areas.

Environmental precautions:

Should not be released into the environment. Prevent from reaching drains, sewer or waterway.

Methods and material for containment and cleaning up:

Approach suspected leak areas with caution. Place in appropriate chemical waste container. If in solid state, contain and clean mechanically, waste according local regulations. If in liquid state, clean with inert absorbent material (sand, silica powder, etc). If possible stop the flow of the product. Material is slippery when spilled.

Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage

Precautions for safe handling:

Ensure good ventilation in the workplace. Avoid all sources of ignition: heat, sparks, flame.

Conditions for safe storage, including any incompatibilities:

Keep container tightly closed. Keep the container in a well-ventilated place. Protect from temperatures below 0 C (32 F). Protect from temperatures above 40 C (104 F).

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

ACGIH TLV: Not available.

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. Biological monitoring may also be appropriate for some substances.

Appropriate engineering controls:

Ensure adequate ventiliation.

Personal protection equipment

Eye and face protection:

Eye protection such as splash-resistant safety goggles with a secondary face shield.

Skin and body protection:





According to OSHA Communication Standard, 29 CFR 1910.1200

Rapid Set TXP Super Fast

Wear the appropriate glove resistant to chemical products. Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

Respiratory protection may be required.

General hygienic measures:

Avoid contact with skin, eyes and clothing. Wash hands before breaks and at the end of work. Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Liquid; Yellow
Odor	Not determined
Odor threshold	Not available
рН	Not soluble.
Melting point/freezing point	-16°C (at 1013 hPA)
Initial boiling point/range	Not applicable
Flash point (closed cup)	Not available
Evaporation rate	Not applicable
Flammability (solid, gas)	Not available
Upper flammability/explosive limit	Not available
Lower flammability/explosive limit	Not available
Vapor pressure	4.6x10 ⁻⁸ Pa (at 25°C)
Vapor density	Not applicable
Density	Not available
Relative density	1.13 kg/L at 25°C
Solubilities	6.9 mg/L at 20°C - Insoluble
Partition coefficient (n-octanol/water)	Not available
Auto/Self-ignition temperature	Not available
Decomposition temperature	Not available
Dynamic viscosity	Not applicable
Kinematic viscosity	Not applicable
Explosive properties	Not available
Oxidizing properties	Not available

Other information

VOC (Weight %)	0 g/l
----------------	-------





According to OSHA Communication Standard, 29 CFR 1910.1200

Rapid Set TXP Super Fast

SECTION 10: Stability and reactivity

Reactivity:

Does not react under normal conditions of use and storage.

Chemical stability:

Stable under normal conditions of use and storage.

Possibility of hazardous reactions:

None under normal conditions of use and storage.

Conditions to avoid:

Exposure to elevated temperatures can cause product to decompose. Avoid moisture. Reaction with carbon dioxide may form an amine carbamate. Smoke may be generated depending on vapor pressure of mixture. Product absorbs carbon dioxide from the air.

Incompatible materials:

Reactive metals (e.g. sodium, calcium, zinc etc). Materials reactive with hydroxyl compounds. Organic acids (i.e. acetic acid, citric acid etc). Mineral acids. Sodium hypochlorite. Product slowly corrodes copper, aluminum, zinc, and galvanized surfaces. Reaction with peroxides may result in violent decomposition of peroxide possibly creating an explosion. Avoid contact with strong oxidizing agent, heat, spark, and flame.

Hazardous decomposition products:

May produce hazardous carbon oxides, chloro hydrogen, carbon monoxide, carbon dioxide, aldehydes and flammable hydrocarbon fragments.

SECTION 11: Toxicological information

Information on toxicological effects:

Acute toxicity

Assessment:

Irritation/eye corrosion: Severe eye irritation.

Irritation/acute dermic corrosion: Severe skin irritation.

Product data: Substance data:

> - Oral: LS50: 3,800 mg/kg Specie: Rat - Dermal: LD50: 8,500 mg/kg Specie: Rat

Skin corrosion/irritation

Assessment: Causes severe skin irritation.
Product data: No data is available.
Substance data: No data is available.

Serious eye damage/irritation

Assessment: Causes serious eye irritation.

Product data: No data is available.

Substance data: No data is available.

Respiratory or skin sensitization

Assessment: Sensitization has occurred in laboratory animals after repeated exposures. May cause sensitization by skin contact.

Product data: No data is available.





According to OSHA Communication Standard, 29 CFR 1910.1200

Rapid Set TXP Super Fast

Substance data: No data is available.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data is available. **Substance data:** No data is available.

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data is available. **Substance data:** No data is available.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data is available.
Substance data: No data is available.
Specific target organ toxicity (single exposure)
Assessment: May cause respiratory irritation

Product data: No data is available.

Substance data: No data is available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data is available.

Substance data: No data is available.

Information on likely routes of exposure:

The routes of entry of solids and liquids are ingestion and inhalation but may include contact with the eyes or skin. Gas entry routes include inhalation and eye contact. Skin contact may be an entry route for liquefied gases. Main routes of entry: inhalation, dermal contact, ingestion.

Symptoms related to the physical, chemical and toxicological characteristics:

No data is available.

Other information:

No data is available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available. Substance data: No data available.

Chronic (long-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.





According to OSHA Communication Standard, 29 CFR 1910.1200

Rapid Set TXP Super Fast

Persistence and degradability

Product data: No data available.

Substance data: No data available.

Bioaccumulative potential

Product data: No data available. Substance data: No data available.

Mobility in soil

Product data: No data available.

Substance data: No data available.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

Waste must be disposed of in accordance with local regulations. This product, if disposed of properly, is not a hazardous waste as specified in 40 CFR261. Contaminated packaging: Due to the empty container retaining product residues, all hazard precautions must be observed on labels. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities.

SECTION 14: Transport information

United States Transportation of dangerous goods (49 CFR DOT)

UN number	3082
UN proper shipping name	Environmentally hazardous substances, liquids, modified epoxy resin
UN transport hazard class(es)	9
Packing group	III
Environmental hazards	Maine pollutant
Special precautions for user	None

International Maritime Dangerous Goods (IMDG)

UN number	3082
UN proper shipping name	Environmentally hazardous substances, liquids, modified epoxy resin
UN transport hazard class(es)	9
Packing group	III
Environmental hazards	Marine pollutant
Special precautions for user	None





According to OSHA Communication Standard, 29 CFR 1910.1200

Rapid Set TXP Super Fast

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	3082
UN proper shipping name	Environmentally hazardous substances, liquids, modified epoxy resin
UN transport hazard class(es)	9
Packing group	III
Environmental hazards	Marine pollutant
Special precautions for user	None

SECTION 15: Regulatory information

United States regulations Inventory listing (TSCA): 25068-38-6: Observational

OSHA Hazard Communication Standard Act: No data

Chemical Safety Control Dangerous Substance Act: Class 4, Class 3 Petroleum 2000L

Waste Control Act: No data

California Proposition 65: Not listed/Not regulated.

SECTION 16: Other information

Abbreviations and Acronyms:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Road Transport

AU: Australia CA: Canada

CAS: Chemical Abstracts Service

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

CN: China

CPR: Controlled Products Regulations DFG: Deutsche Forschungsgemeinschaft DOT: Department of Transportation DSL: Domestic Substances List EEC: European Economic Community ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances

EPA: Environmental Protection Agency

EU: European Association

IARC: International Agency for Reach on Cancer IMDG: International maritime dangerous goods code IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

JP: Japan

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50





According to OSHA Communication Standard, 29 CFR 1910.1200

Rapid Set TXP Super Fast

CL50: Lethal Concentration 50 EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon Know: Octanol/water partition coefficient

KR: Korea

LEL: Lower Explosive Limit UEL: Upper Explosive Limit

NIOSH: National Institute for Occupational Safety and Health Administration

PH: Philippines

RCRA: Resource Conservation and Recovery Act OSHA: Occupational Safety and Health Administration

RID: European Rail Transport

SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit TDG: Transportation of Dangerous Goods TSCA: Toxic Substances Control Act TWA: Time Weighted Average

US: United States

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

Initial preparation date: 05/04/22

Version #: 1
Revision Date: -/-/-

End of Safety Data Sheet





According to OSHA Communication Standard, 29 CFR 1910.1200

Rapid Set TXP Super Fast

SECTION 1: Identification

Product identifier

Product name: TXP Super Fast Part B

Product code:

Recommended use of the product and restriction on use

Relevant identified uses: Use for epoxy primer applications Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

CTS Cement Manufacturing Corporation 12442 Knott St. Garden Grove, CA 92841 800-929-3030 info@ctscement.com

Emergency telephone number:

United States

INFOTRAC 800-535-5053

Information Telephone Number 800-282-5828

SECTION 2: Hazard(s) identification

GHS classification:

Skin corrosion - Category 1B Skin sensitization - Category 1 Serious Eye Damage - Category 1 Acute inhalation toxicity: Category 4 Germ cell mutagenicity- Category 2 Chronic aquatic toxicity— Category 2

Label elements

Hazard Pictograms:



Signal word: Danger

Hazard statements:

H314 Harmful in contact with skin.

H317 May cause an allergic skin reaction.





According to OSHA Communication Standard, 29 CFR 1910.1200

Rapid Set TXP Super Fast

- H318 Causes severe skin burns and eye damage.
- H332 Harmful if inhaled.
- H341 Suspected of causing genetic defects.
- H411 Toxic to aquatic life with long-lasting effects.

Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P260 Do not breath dust/fume/gas/mist/vapor/spray.
- P261 Avoid breaking dust, smoke, gas, fog, vapors, spray.
- P264 Wash hands/eyes/mouth/skin/clothing thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing cannot be removed from the workplace.
- P273 Do not disperse in the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
- P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER or doctor/physician.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P333+P311: If skin irritation or rash occurs: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazards not otherwise classified: None.

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 8007-24-7	Cashew nut liquid	10-25
CAS number: 90-72-2	Tris (dimethylamidomethyl) Phenol	<4
CAS number: 1477-55-0	1,3-Bis (amidomethyl)benzene	<4
CAS number: 108-95-2	Phenol	<2
CAS number: 109-55-7	3-Aminopropyldimethylamine	1-2





According to OSHA Communication Standard, 29 CFR 1910.1200

CAS number: Trade secret Proprietary ingredient 45-55 CAS number: Aliphatic amine 15-25

Additional Information:

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200).

SECTION 4: First aid measures

Description of first aid measures

General notes:

Seek medical advice. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately.

After inhalation:

Move to fresh air.

After skin contact:

Immediately remove contaminated clothing, and any extraneous chemical, if possible, to do so without delay. Flush immediately with copious amounts of water. Initiate and maintain continuous irrigation until the patient receives medical care. If medical care is not promptly available, continue to irrigate for one hour. Cover wound with sterile dressing. NOTE TO PHYSICIANS: Application of corticosteroid cream has been effective in treating skin irritation.

After eye contact:

Hold eyelids apart, initiate and maintain gentle and continuous irrigation until the patient receives medical care. If medical care is not promptly available, continue to irrigate for one hour.

After swallowing:

Never give anything by mouth to an unconscious person. Do not induce vomiting without medical advice. Prevent aspiration of vomit. Turn victim's head to the side.

Most important symptoms and effects, both acute and delayed

Acute and delayed symptoms and effects:

Eye disease. Skin disorders and Allergies.

Immediate medical attention and special

treatment Specific treatment:

Not determined or not applicable.

Notes for the doctor:

Not determined or not applicable.





According to OSHA Communication Standard, 29 CFR 1910.1200

Rapid Set TXP Super Fast

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Alcohol-resistant foam. Carbon dioxide. Dry chemical. Dry sand. Limestone powder.

Unsuitable extinguishing media:

Do not use direct water stream. May spread fire.

Specific hazards during fire-fighting:

Incomplete combustion may form carbon monoxide. May generate ammonia gas. May generate toxic nitrogen oxide gases. Do not allow run-off from firefighting to enter drains or watercourses. Burning produces noxious and toxic fumes. Downwind personnel must be evacuated.

Special protective equipment for firefighters:

Avoid contact with the skin. A face shield should be worn. Wear self-contained breathing apparatus for firefighting if necessary.

Special precautions:

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Do not allow run-off from firefighting to enter drains or watercourses.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Use self-contained breathing apparatus and chemically protective clothing. Evacuate personnel to safe areas.

Environmental precautions:

Should not be released into the environment. If spilled, construct a dike to prevent spread. Prevent from reaching drains, sewer or waterways.

Methods and material for containment and cleaning up:

Approach suspected leak areas with caution. Place in appropriate chemical waste container. If possible, stop the flow of the product.

Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage

Precautions for safe handling:

Do not use sodium nitrite or other nitrosant agents in formulations containing this product. Nitrosamines could form. Avoid skin and eye contact. Emergency showers and eye wash stations must be easily accessible. Adhere to work practice rules established by government regulations. Use personal protective equipment. When using, do not eat, drink or smoke.

Conditions for safe storage, including any incompatibilities:

Do not store near acids. Keep container tightly closed. Keep the container in a well-ventilated place. Protect from temperatures below 0 C (32 F). Protect from temperatures above 40 C (104 F).





According to OSHA Communication Standard, 29 CFR 1910.1200

Rapid Set TXP Super Fast

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

ACGIH TLV: Not available.

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. Biological monitoring may also be appropriate for some substances.

Appropriate engineering controls:

Provide readily accessible eyewash stations and safety showers. Provide natural or explosion-proof ventilation adequate to ensure concentrations are kept below exposure limits. Normal room ventilation is enough, however, mechanical ventilation provides better results. Ensure adequate ventilation.

Personal protection equipment

Eye and face protection:

Full face googles. Eye protection such as splash-resistant safety goggles with a secondary face shield.

Skin and body protection:

Wear the appropriate glove resistant to chemical products. Wear appropriate clothing to prevent any possibility of skin contact, examples such as rubber or plastic boots, slicker suit. Waterproof chemical resistant gloves must be worn at all times. Use neoprene, butyl rubber or plastic gloves.

Respiratory protection:

Wear an appropriate respirator when ventilation is inadequate. Respiratory protection may be required.

General hygienic measures:

Avoid contact with skin, eyes and clothing. Wash hands before breaks and at the end of work. Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Liquid; Amber
Odor	Ammoniacal
Odor threshold	Not available
рН	10
Melting point/freezing point	Not available
Initial boiling point/range	230°C
Flash point (closed cup)	Not available
Evaporation rate	Not applicable
Flammability (solid, gas)	Not available
Upper flammability/explosive limit	Not available





According to OSHA Communication Standard, 29 CFR 1910.1200

Rapid Set TXP Super Fast

Lower flammability/explosive limit	Not available
Vapor pressure	0.2 mm Hg
Vapor density	Not applicable
Density	Not available
Relative density	0.99 kg/L at 25°C
Solubilities	Not available
Partition coefficient (n-octanol/water)	Not available
Auto/Self-ignition temperature	Not available
Decomposition temperature	Not available
Dynamic viscosity	650 cP at 25°C
Kinematic viscosity	Not applicable
Explosive properties	Not available
Oxidizing properties	Not available

Other information

VOC (Weight %)	0 g/l
, o o (,, o ig., o)	- 5/ ·

SECTION 10: Stability and reactivity

Reactivity:

Does not react under normal conditions of use and storage.

Chemical stability:

Stable under normal conditions of use and storage.

Possibility of hazardous reactions:

None under normal conditions of use and storage.

Conditions to avoid:

Reactive metals (e.g. sodium, calcium, zinc etc). Materials reactive with hydroxyl compounds. Organic acids (i.e. acetic acid, citric acid etc). Mineral acids. Sodium hypochlorite. Product slowly corrodes copper, aluminum, zinc and galvanized surfaces. Reaction with peroxides may result in violent decomposition of peroxide possibly creating an explosion. Oxidizing agents.

Incompatible materials:

Reactive metals (e.g. sodium, calcium, zinc etc). Materials reactive with hydroxyl compounds. Organic acids (i.e. acetic acid, citric acid etc). Mineral acids. Sodium hypochlorite. Product slowly corrodes copper, aluminum, zinc, and galvanized surfaces.Reaction with peroxides may result in violent decomposition of peroxide possibly creating an explosion. Avoid contact with strong oxidizing agent, heat, spark, and flame.

Hazardous decomposition products:

Nitric acid. Ammonia. Nitrogen oxides(NOx). Nitrogen oxide can react with water vapors to form corrosive nitric acid. Carbon monoxide (CO). Carbon dioxide (CO2). Aldehydes. Flammable hydrocarbon fragments.





According to OSHA Communication Standard, 29 CFR 1910.1200

Rapid Set TXP Super Fast

SECTION 11: Toxicological information

Information on toxicological effects:

Acute toxicity

Assessment:

Irritation/eye corrosion: Severe eye irritation.

Irritation/acute dermic corrosion: Severe skin irritation.

Product data: Substance data:

- Oral: LD50: 2,200 mg/kg Specie: Rat

- Dermal: LD50: 1,000 mg/kg Specie: Rabbit. Calculation method.

Skin corrosion/irritation

Assessment: Causes moderate skin irritation.
Product data: No data is available.
Substance data: No data is available.

Serious eye damage/irritation

Assessment: Causes serious eye irritation.

Product data: No data is available.

Substance data: No data is available.

Respiratory or skin sensitization

Assessment: May cause respiratory irritation. Inhalation of vapor and aersol in high concentration may cause irritation of the respiratory system. Repeated and/or prolonged exposure to low concentrations of vapor may cause: sore throat which are transient. Liver disorders (such as jaundice or liver enlargement), kidney disorders (such as edema or proteinuria), asthma, adverse respiratory effects such as cough, chest tightness, or difficulty breathing, skin disorders and allergies, adverse skin effects (such as rash, irritation or corrosion), adverse eye effects (such as

conjunctivitis or corneal damage), eye damage.

Product data: No data is available. **Substance data:** No data is available.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data is available. **Substance data:** No data is available.

Germ cell mutagenicity

Assessment: The results of a short-term genotoxicity test bacterium on this material or its components indicate mutagenic activity.

Product data: No data is available. **Substance data:** No data is available.

Reproductive toxicity

Assessment: No data available on the product itself.

Product data: No data is available.
Substance data: No data is available.
Specific target organ toxicity (single exposure)





According to OSHA Communication Standard, 29 CFR 1910.1200

Rapid Set TXP Super Fast

Assessment: May cause respiratory irritation

Product data: No data is available.

Substance data: No data is available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data is available.

Substance data: No data is available.

Information on likely routes of exposure:

The routes of entry of solids and liquids are ingestion and inhalation but may include contact with the eyes or skin. Gas entry routes include inhalation and eye contact. Skin contact may be an entry route for liquefied gases. Main routes of entry: inhalation, dermal contact, ingestion.

Symptoms related to the physical, chemical and toxicological characteristics:

No data is available.

Other information:

This product does not contain carcinogens listed according to IARC, ACGIH, NTP and OSHA in concentrations of 0.1 percent or more. Repeated and/or prolonged exposure to low concentrations of vapor may cause: sore throat which are transient. Liver disorders (such as jaundice or liver enlargement), kidney disorders (such as edema or proteinuria), asthma, adverse respiratory effects such as cough, chest tightness, or difficulty breathing, skin disorders and allergies, adverse skin effects (such as rash, irritation or corrosion), adverse eye effects (such as conjunctivitis or corneal damage), eye damage.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Not available on the product itself.

Product data: No data available.

Substance data:

Daphnia toxicity - Components

Phenol EC50 (48h): 4-7 mg / species: Daphnia toxicity to other organisms: No available data.

Chronic (long-term) toxicity

Product data: No data available. Substance data: No data available.

Persistence and degradability

Product data: No data available.

Substance data: No data available.

Bioaccumulative potential

Product data: No data available.

Substance data: No data available.

Mobility in soil





According to OSHA Communication Standard, 29 CFR 1910.1200

Rapid Set TXP Super Fast

Product data: No data available.

Substance data: No data available.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

Waste must be disposed of in accordance with local regulations. This product, if disposed of properly, is not a hazardous waste as specified in 40 CFR261. Contaminated packaging: Due to the empty container retaining product residues, all hazard precautions must be observed on labels. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities.

SECTION 14: Transport information

United States Transportation of dangerous goods (49 CFR DOT)

UN number	2735
UN proper shipping name	Polyamines, liquid, corrosive, n.o.s. (fenalcamine)
UN transport hazard class(es)	8
Packing group	III
Environmental hazards	Maine pollutant
Special precautions for user	None

International Maritime Dangerous Goods (IMDG)

UN number	2735
UN proper shipping name	Polyamines, liquid, corrosive, n.o.s. (fenalcamine)
UN transport hazard class(es)	8
Packing group	III
Environmental hazards	Marine pollutant
Special precautions for user	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	2735
UN proper shipping name	Polyamines, liquid, corrosive, n.o.s. (fenalcamine)
UN transport hazard class(es)	8
Packing group	III
Environmental hazards	Marine pollutant
Special precautions for user	None





According to OSHA Communication Standard, 29 CFR 1910.1200

Rapid Set TXP Super Fast

SECTION 15: Regulatory information

National Inventory TSCA: Ingredients of this mixture are included on the TSCA inventory.

OSHA Hazard Communication Standard (29 CFR 1910.1200) Hazard Class(es): Corrosive

EPA SARA Title III Section 312 (40 CFR 370) Component(s) above'de minimus' level: None

WHIMIS HAZARD Classification: Toxic material causing other toxic effects, corrosive material.

California Proposition 65: Not listed/Not regulated.

SECTION 16: Other information

Abbreviations and Acronyms:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Road Transport

AU: Australia CA: Canada

CAS: Chemical Abstracts Service

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

CN: China

CPR: Controlled Products Regulations DFG: Deutsche Forschungsgemeinschaft DOT: Department of Transportation DSL: Domestic Substances List EEC: European Economic Community ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances

EPA: Environmental Protection Agency

EU: European Association

IARC: International Agency for Reach on Cancer IMDG: International maritime dangerous goods code

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

JP: Japan

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50

CL50: Lethal Concentration 50 EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon Know: Octanol/water partition coefficient

KR: Korea

LEL: Lower Explosive Limit UEL: Upper Explosive Limit

NIOSH: National Institute for Occupational Safety and Health Administration

PH: Philippines

RCRA: Resource Conservation and Recovery Act OSHA: Occupational Safety and Health Administration





According to OSHA Communication Standard, 29 CFR 1910.1200

Rapid Set TXP Super Fast

RID: European Rail Transport

SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit

TDG: Transportation of Dangerous Goods TSCA: Toxic Substances Control Act TWA: Time Weighted Average

US: United States

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

Initial preparation date: 05/04/22

Version #: 1

Revision Date: -/-/-

End of Safety Data Sheet