Printing date 05/30/2023 Reviewed on 05/30/2023

1 Identification

- · Product identifier
- · Trade name: CreteFill Crack Repair EZE Shave Part A
- · Details of the supplier of the safety data sheet
- · Information department: Technical Services
- · Emergency telephone number:

(800) 633-8253 (United States/Canada)

+1 (801) 629-0667 International Emergency Number

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Sensitization - Respiratory 1 H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Carcinogenicity 2 H351 Suspected of causing cancer.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or

repeated exposure.



Acute Toxicity - Inhalation 4 H332 Harmful if inhaled.
Skin Irritation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

diphenylmethanediisocyanate,isomeres and homologues

4,4'-methylenediphenyl diisocyanate

methylenediphenyl diisocyanate

· Hazard statements

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 2)

Printing date 05/30/2023 Reviewed on 05/30/2023

Trade name: CreteFill Crack Repair EZE Shave Part A

(Contd. of page 1)

Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *2 Fire = 1

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

>25-50%

101-68-8 4,4'-methylenediphenyl diisocyanate

>10-25%

26447-40-5 methylenediphenyl diisocyanate

>2.5-<5% US -

(Contd. on page 3)

Printing date 05/30/2023 Reviewed on 05/30/2023

Trade name: CreteFill Crack Repair EZE Shave Part A

(Contd. of page 2)

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**
- PAC-1:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues: 0.15 mg/m³

101-68-8 4,4'-methylenediphenyl diisocyanate: 0.45 mg/m³

26447-40-5 methylenediphenyl diisocyanate: 29 mg/m³

· PAC-2:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues: 3.6 mg/m³

101-68-8 4,4'-methylenediphenyl diisocyanate: 5 mg/m³

26447-40-5 methylenediphenyl diisocyanate: 40 mg/m³

PAC-3:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues: 22 mg/m³

101-68-8 4,4'-methylenediphenyl diisocyanate: 55 mg/m³

(Contd. on page 4)

Printing date 05/30/2023 Reviewed on 05/30/2023

Trade name: CreteFill Crack Repair EZE Shave Part A

(Contd. of page 3)

26447-40-5 methylenediphenyl diisocyanate: 240 mg/m³

7 Handling and storage

- Handling:
- · Precautions for safe handling

Thorough dedusting.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

- Information about protection against explosions and fires: Keep respiratory protective device available.
- Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

101-68-8 4,4'-methylenediphenyl diisocyanate

PEL Ceiling limit value: 0.2 mg/m³, 0.02 ppm REL Long-term value: 0.05 mg/m³, 0.005 ppm Ceiling limit value: 0.2* mg/m³, 0.02* ppm

*10-min

TLV Long-term value: 0.005 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Printing date 05/30/2023 Reviewed on 05/30/2023

Trade name: CreteFill Crack Repair EZE Shave Part A

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information

· Appearance:

Form: Fluid
Color: Dark brown

Odor: Musty, slight odour
Odor threshold: Not determined.

· pH-value:

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:

Flash point:

Flammability (solid, gaseous):

Auto igniting:

Decomposition temperature:

Undetermined.

200 °C (392 °F)

Not determined.

· **Ignition temperature:** Product is not selfigniting.

• **Danger of explosion:** Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.
Upper: Not determined.

· Vapor pressure at 20 °C (68 °F): 0 hPa

Density at 20 °C (68 °F): 1.14195 g/cm³ (9.52957 lbs/gal)

Relative density

Vapor density

Vapor density

Evaporation rate

Not applicable.

Not applicable.

· Solubility in / Miscibility with

Water: Insoluble.

(Contd. on page 6)

Printing date 05/30/2023 Reviewed on 05/30/2023

Trade name: CreteFill Crack Repair EZE Shave Part A

(Contd. of page 5)

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not applicable. **Kinematic:** Not applicable.

· Solvent content:

 VOC content:
 0.00 %

 Solids content:
 100.0 %

· Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:
- · LD/LC50 values that are relevant for classification:

Oral LD50 mg/kg (rat)

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

Inhalative LC50/4h 1.5 g/m3 (ATE)

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral LD50 2,200 mg/kg (mouse)

Inhalative LC50/4h 1.5 g/m3 (ATE)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- on the eye:

Strong irritant with the danger of severe eye injury.

Irritating effect.

· Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful Irritant

- Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues: 3

101-68-8 4,4'-methylenediphenyl diisocyanate: 3

NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 7)

Printing date 05/30/2023 Reviewed on 05/30/2023

Trade name: CreteFill Crack Repair EZE Shave Part A

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water May cause or intensify fire; oxidizer.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

DOT, IMDG, IATA not regulated

· UN proper shipping name

· DOT, IMDG, IATA not regulated

Transport hazard class(es)

· DOT, ADN, IMDG, IATA

· Class not regulated

· Packing group

DOT, IMDG, IATA not regulated
 Environmental hazards: Not applicable.
 Special precautions for user Not applicable.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.
UN "Model Regulation": not regulated

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

(Contd. on page 8)

Printing date 05/30/2023 Reviewed on 05/30/2023

Trade name: CreteFill Crack Repair EZE Shave Part A

(Contd. of page 7)

- · Sara
- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

101-68-8 4,4'-methylenediphenyl diisocyanate

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

101-68-8 4,4'-methylenediphenyl diisocyanate

- · Proposition 65
- Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues: CBD

101-68-8 4,4'-methylenediphenyl diisocyanate: D, CBD

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

diphenylmethanediisocyanate,isomeres and homologues

4,4'-methylenediphenyl diisocyanate

methylenediphenyl diisocyanate

· Hazard statements

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 9)

Printing date 05/30/2023 Reviewed on 05/30/2023

Trade name: CreteFill Crack Repair EZE Shave Part A

(Contd. of page 8)

Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Technical Services
- · Contact:
- Date of preparation / last revision 05/30/2023

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Toxicity - Inhalation 4: Acute toxicity - Category 4

Skin Irritation 2: Skin corrosion/irritation - Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Sensitization - Respiratory 1: Respiratory sensitisation - Category 1 Sensitization - Skin 1: Skin sensitisation - Category 1

Carcinogenicity 2: Carcinogenicity - Category 2

Printing date 05/30/2023 Reviewed on 05/30/2023

Trade name: CreteFill Crack Repair EZE Shave Part A

(Contd. of page 9)

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3 Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

— US —

Printing date 06/01/2023 Reviewed on 06/01/2023

1 Identification

- · Product identifier
- · Trade name: CreteFill Crack Repair EZE Shave Part B
- · Details of the supplier of the safety data sheet
- · Information department: Technical Services
- · Emergency telephone number:

(800) 633-8253 (United States/Canada)

+1 (801) 629-0667 International Emergency Number

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways.



Eye Irritation 2A H319 Causes serious eye irritation.

Flammable Liquids 4 H227 Combustible liquid.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Distillates (petroleum), hydrotreated light

Solvent naphta (petroleum) heavy aliph.

· Hazard statements

Combustible liquid.

Causes serious eye irritation.

May be fatal if swallowed and enters airways.

· Precautionary statements

Keep away from flames and hot surfaces. - No smoking.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Do NOT induce vomiting.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Printing date 06/01/2023 Reviewed on 06/01/2023

Trade name: CreteFill Crack Repair EZE Shave Part B

(Contd. of page 1)

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 2Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *2 Fire = 2REACTIVITY 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.
- Dangerous components:

64742-47-8 Distillates (petroleum), hydrotreated light 64742-96-7 Solvent naphta (petroleum) heavy aliph.

>10-25%

>10-25%

1305-78-8 calcium oxide 1-2.5%

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Drink 200-300ml of water
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

nitrous gases, fumes/smoke, isocyanate, vapour

- Advice for firefighters
- · Protective equipment: Firefighters should be equipped with self-contained breathing apparatus and turn out gear.

(Contd. on page 3)

Printing date 06/01/2023 Reviewed on 06/01/2023

Trade name: CreteFill Crack Repair EZE Shave Part B

(Contd. of page 2)

· Additional information

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Dispose of the collected material according to regulations

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- Protective Action Criteria for Chemicals
- PAC-1:

1305-78-8 calcium oxide: 6 mg/m³

· PAC-2:

1305-78-8 calcium oxide: 110 mg/m³

· PAC-3:

1305-78-8 calcium oxide: 660 mg/m³

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure thorough ventilation of stores and work area. Protect against moisture
- Information about protection against explosions and fires: Keep ignition sources away Do not smoke.
- · Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds. Segregate from acids and bases

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Carbon Steel, (Iron), High density polyethylene (HDPE), Low density polyethylene (LDPE)

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

1305-78-8 calcium oxide

PEL Long-term value: 5 mg/m³ REL Long-term value: 2 mg/m³

(Contd. on page 4)

Printing date 06/01/2023 Reviewed on 06/01/2023

Trade name: CreteFill Crack Repair EZE Shave Part B

(Contd. of page 3)

TLV Long-term value: 2 mg/m³

- · Additional information: The lists that were valid during the creation were used as basis.
- Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Color: clear to slightly cloudy

Odor: Slight OdourOdor threshold: Not determined.

· pH-value:

· Change in condition

Melting point/Melting range:Undetermined.Boiling point/Boiling range:200 °C (392 °F)• Flash point:61 °C (141.8 °F)

Flammability (solid, gaseous): Not applicable.
 Auto igniting: 210 °C (410 °F)

(Contd. on page 5)

Printing date 06/01/2023 Reviewed on 06/01/2023

Trade name: CreteFill Crack Repair EZE Shave Part B

(Contd. of page 4)

• **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not selfigniting.

· Danger of explosion: Not determined.

· Explosion limits:

Lower: 0.5 Vol % **Upper:** 6.5 Vol %

· Vapor pressure at 20 °C (68 °F): 2 hPa (1.5 mm Hg)

• **Density at 20 °C (68 °F):** 0.09958 g/cm³ (0.831 lbs/gal)

Relative density
 Vapor density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

VOC content: 0.00 %

0.0 g/l / 0.00 lb/gal

Solids content: 78.9 %

• Other information Flash Point Testing conducted as a closed cup test.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions

Contact with certain rubbers and plastics can cause brittleness of the substance/product with subsequent loss in strength.

· Conditions to avoid

Temperature < 0 degrees Celsius

Avoid moisture

· Incompatible materials:

acids, oxidizing agents, isocyanates

acids, amines, alcohols, water, Alkalines, strong bases, Products that react with isocyantes

· Hazardous decomposition products:

aromatic isocyanates, gases/vapours

carbon monoxide, carbon dioxide, nitrogen oxide, hydrogen cyanide

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- · on the skin: No irritant effect.

(Contd. on page 6)

Printing date 06/01/2023 Reviewed on 06/01/2023

Trade name: CreteFill Crack Repair EZE Shave Part B

(Contd. of page 5)

on the eye:

Strong irritant with the danger of severe eye injury. Irritating effect.

- Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · **Mobility in soil** No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

May cause or intensify fire; oxidizer.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Incinerate in a licensed facility. Dispose of in a licensed facility. Do not discharge substance/product into sewer system.

- **Uncleaned packagings:**
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· DOT, IMDG, IATA not regulated

· UN proper shipping name

DOT, IMDG, IATA not regulated

(Contd. on page 7)

Printing date 06/01/2023 Reviewed on 06/01/2023

Trade name: CreteFill Crack Repair EZE Shave Part B

(Contd. of page 6)

Transport hazard class(es)

· DOT, ADN, IMDG, IATA

· Class not regulated

· Packing group

DOT, IMDG, IATA not regulated
 Environmental hazards: Not applicable.
 Special precautions for user Not applicable.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

UN "Model Regulation": not regulated

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07 GHS08

· Signal word Danger

Printing date 06/01/2023 Reviewed on 06/01/2023

Trade name: CreteFill Crack Repair EZE Shave Part B

(Contd. of page 7)

Hazard-determining components of labeling:

Distillates (petroleum), hydrotreated light Solvent naphta (petroleum) heavy aliph.

· Hazard statements

Combustible liquid.

Causes serious eye irritation.

May be fatal if swallowed and enters airways.

Precautionary statements

Keep away from flames and hot surfaces. - No smoking.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Do NOT induce vomiting.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsina.

If eve irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Technical Services
- · Contact:
- Date of preparation / last revision 06/01/2023
- Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 4: Flammable liquids - Category 4

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Aspiration Hazard 1: Aspiration hazard - Category 1