

acc. to OSHA HCS

Printing date 12/29/2022

1 Identification

- · Product identifier
- [·] Trade name: RetroPel
- · Application of the substance / the mixture Concrete Impregnator
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Curecrete Chemical Company 1203 Spring Creek Place Springville, UT 84663 USA techsupport@curecrete.com (801) 489-5663
- · Information department: Technical Services
- Emergency telephone number:
- (800) 633-8253 (United States/Canada)
- +1 (801) 629-0667 International Emergency Number

2 Hazard(s) identification

· Classification of the substance or mixture

GHS06 Skull and crossbones

Acute Toxicity - Inhalation 2

H330 Fatal if inhaled.



GHS08 Health hazard

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.



Eye Irritation 2A

H319 Causes serious eye irritation.

· Label elements

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



Reviewed on 12/29/2022

Page 1/10

acc. to OSHA HCS

Printing date 12/29/2022

Reviewed on 12/29/2022

Trade name: RetroPel

| Signal word Danger | (Contd. of page 1) |
|---|--------------------------|
| Hazard-determining components of labeling: | |
| 2-butoxyethanol | |
| Substituted alkyl phosphate esters, | |
| ammonium salts | |
| Hazard statements | |
| Fatal if inhaled. | |
| Causes serious eye irritation. | |
| May cause damage to organs through prolonged or repeated exposure. | |
| Precautionary statements | |
| Do not breathe dust/fume/gas/mist/vapors/spray. | |
| Wash thoroughly after handling. | |
| Use only outdoors or in a well-ventilated area. | |
| Wear eye protection / face protection. | |
| [In case of inadequate ventilation] wear respiratory protection. | |
| IF INHALED: Remove person to fresh air and keep comfortable for breathing. | |
| If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, it | f present and easy to do |
| Continue rinsing. | |
| Immediately call a poison center/doctor. | |
| Specific treatment is urgent (see on this label). | |
| Get medical advice/attention if you feel unwell. | |
| If eye irritation persists: Get medical advice/attention. | |
| Store in a well-ventilated place. Keep container tightly closed. | |
| Store locked up. | C |
| Dispose of contents/container in accordance with local/regional/national/international regula | itions. |
| Classification system: | |
| NFPA ratings (scale 0 - 4) | |
| Health = 2 | |
| Fire = 0 | |
| 2 Reactivity = 0 | |

· HMIS-ratings (scale 0 - 4)

HEALTH*2FIRE0REACTIVITY0Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

| · Dangerous components: | |
|--|--------------------|
| 57-55-6 Propylene glycol | >4.25-≤4.5% |
| 111-76-2 2-butoxyethanol | >4.25-≤4.5% |
| Substituted alkyl phosphate esters, ammonium salts | >2.5-≤2.75% |
| | (Contd. on page 3) |

_ US ____

acc. to OSHA HCS

Printing date 12/29/2022

Trade name: RetroPel

Non-hazardous ingredients

7732-18-5 Potable Water

4 First-aid measures

· Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

- After inhalation:
- Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- \cdot Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- Reference to other sections
- See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

- See Section 13 for disposal information.
- Protective Action Criteria for Chemicals
- · PAC-1:

57-55-6 Propylene glycol: 30 mg/m³

- 111-76-2 2-butoxyethanol: 60 ppm
- · PAC-2:

57-55-6 Propylene glycol: 1,300 mg/m³

111-76-2 2-butoxyethanol: 120 ppm

(Contd. of page 2)

Reviewed on 12/29/2022

>80-<90%

acc. to OSHA HCS

Printing date 12/29/2022

Reviewed on 12/29/2022

Trade name: RetroPel

· PAC-3:

57-55-6 Propylene glycol: 7,900 mg/m³

111-76-2 2-butoxyethanol: 700 ppm

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires: Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

57-55-6 Propylene glycol

WEEL Long-term value: 10 mg/m³

111-76-2 2-butoxyethanol

- PEL Long-term value: 240 mg/m³, 50 ppm Skin
- REL Long-term value: 24 mg/m³, 5 ppm Skin
- TLV Long-term value: 20 ppm BEI, A3

Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

• Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

- Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.

(Contd. of page 3)

acc. to OSHA HCS

Printing date 12/29/2022

Reviewed on 12/29/2022

Trade name: RetroPel

(Contd. of page 4)

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.





Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information

| · Appearance: | |
|-----------------------|--|
| Form: | |
| Color: | |
| · Odor: | |
| · Odor threshold: | |
| · pH-value: | |
| • Change in condition | |

Melting point/Melting range: **Boiling point/Boiling range:**

- · Flash point:
- · Flammability (solid, gaseous):
- · Decomposition temperature:

· Auto igniting:

- · Danger of explosion:
- Explosion limits: Lower:

Not determined.

Undetermined.

Not applicable.

Not applicable.

Not determined.

Product is not selfigniting.

Product does not present an explosion hazard.

Fluid Whitish Solvent like Not determined.

110

acc. to OSHA HCS

Printing date 12/29/2022

Trade name: RetroPel

| | | (Contd. of page 5) |
|---|--|--------------------|
| Upper: | Not determined. | |
| · Vapor pressure: | Not determined. | |
| Density: Relative density Vapor density Evaporation rate | Not determined. Not determined. Not determined. Not determined. | |
| Solubility in / Miscibility with Water: | Not miscible or difficult to mix. | |
| · Partition coefficient (n-octanol/ | vater): Not determined. | |
| · Viscosity: Dynamic: Kinematic: | Not determined. Not determined. | |
| Solvent content: Organic solvents: Water: VOC content: | 9.0 % 88.3 % 9.00 % 90.0 g/l / 0.75 lb/gal | |
| · Other information | No further relevant information available. | |

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:
- · LD/LC50 values that are relevant for classification:

111-76-2 2-butoxyethanol

Oral LD50 1,200 mg/kg (ATE)

1,480 mg/kg (rat)

Dermal LD50 400 mg/kg (rab)

Inhalative LC50/4h 3 mg/l (ATE)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye:

Strong irritant with the danger of severe eye injury.

- Irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

5)

Reviewed on 12/29/2022

acc. to OSHA HCS

Printing date 12/29/2022

Trade name: RetroPel

Irritant

· Carcinogenic categories

- IARC (International Agency for Research on Cancer) 111-76-2 2-butoxyethanol: 3
- NTP (National Toxicology Program) None of the ingredients is listed.
- OSHA-Ca (Occupational Safety & Health Administration) None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- **Mobility in soil** No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water May cause or intensify fire; oxidizer.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

| 14 Transport information | | | | |
|----------------------------------|----------|--|------|--|
| · UN-Number · DOT, IMDG, IATA | UN2810 | | | |
| · UN proper shipping name | <u> </u> | | | |

· DOT

· IMDG, IATA

Toxic, liquids, organic, n.o.s. (Substituted alkyl phosphate esters, ammonium salts, 2-butoxyethanol) TOXIC LIQUID, ORGANIC, N.O.S. (Substituted alkyl phosphate esters, ammonium salts, 2-butoxyethanol)

(Contd. on page 8)

US

(Contd. of page 6)

Reviewed on 12/29/2022

Reviewed on 12/29/2022

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/29/2022

Trade name: RetroPel

| · Transport hazard class(es) | (Contd. of page 7 |
|---|--|
| ·DOT | |
| | |
| · Class · Label | 6.1 Toxic substances 6.1 |
| · IMDG, IATA | |
| | |
| Class | 6.1 Toxic substances |
| · Label · Packing group | 6.1 |
| · DOT, IMDG, IATA | II. |
| · Environmental hazards: | Not applicable. |
| Special precautions for user | Warning: Toxic substances |
| Hazard identification number (Kemler code) | |
| · EMS Number: · Stowage Category | F-A,S-A B |
| · Stowage Code | SW2 Clear of living quarters. |
| • Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| DOT | |
| · Quantity limitations | On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L |
| IMDG | 400 |
| Limited quantities (LQ) Excepted quantities (EQ) | 100 ml Code: E4 |
| LAUPIEU quantities (LQ) | Maximum net quantity per inner packaging: 1 ml |
| · UN "Model Regulation": | Maximum net quantity per outer packaging: 500 ml UN 2810 TOXIC LIQUID, ORGANIC, N.O.S. (SUBSTITUTED ALKY PHOSPHATE ESTERS, |
| | AMMONIUM SALTS, 2-BUTOXYETHANOL), 6.1, II |

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

- · Section 313 (Specific toxic chemical listings):
- 111-76-2 2-butoxyethanol
- TSCA (Toxic Substances Control Act):
- 7732-18-5 Potable Water: ACTIVE

acc. to OSHA HCS

Printing date 12/29/2022

Trade name: RetroPel

57-55-6 Propylene glycol: ACTIVE

111-76-2 2-butoxyethanol: ACTIVE Substituted alkyl phosphate esters, ammonium salts: Listed or exempt Hazardous Air Pollutants None of the ingredients is listed. · Proposition 65 · Chemicals known to cause cancer: None of the ingredients is listed. Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: None of the ingredients is listed. Carcinogenic categories · EPA (Environmental Protection Agency) 111-76-2 2-butoxyethanol: NL • TLV (Threshold Limit Value) 111-76-2 2-butoxyethanol: A3 NIOSH-Ca (National Institute for Occupational Safety and Health) None of the ingredients is listed. GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms GHS06 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labeling: 2-butoxyethanol Substituted alkyl phosphate esters,

ammonium salts

· Hazard statements

Fatal if inhaled. Causes serious eye irritation.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area. Wear eye protection / face protection.

[In case of inadequate ventilation] wear respiratory protection.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment is urgent (see on this label).

Get medical advice/attention if you feel unwell.

(Contd. of page 8)

Reviewed on 12/29/2022

(Contd. on page 10) - US -

acc. to OSHA HCS

Printing date 12/29/2022

Trade name: RetroPel

If eye irritation persists: Get medical advice/attention. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out. 16 Other information This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. · Department issuing SDS: Technical Services Contact: Roy Bowman Date of preparation / last revision 12/29/2022 Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL: Recommended Exposure Limit BEI: Biological Exposure Limit** Acute Toxicity - Inhalation 2: Acute toxicity - Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) - Category 2 us -

(Contd. of page 9)

Reviewed on 12/29/2022