



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® FAST DRY High Strength Spackling

### PRODUCT DESCRIPTION

**DAP® FAST DRY High Strength Spackling** is a professional-grade spackling compound uniquely formulated to provide strength and fast drying capabilities allowing some repairs to be painted in as little as 15 minutes. Its ready-to-use, smooth formula spreads easily and won't sink, shrink or crack, typically filling repairs in one coat. DAP® Fast Dry High Strength Spackling is 3X Stronger<sup>+</sup> with superior impact resistance over traditional spackling compounds.



PACKAGING	COLOR	UPC
16 fl. oz. (473 mL)	Off-White	7079818440
32 fl. oz (846 mL)	Off-White	7079818441

### KEY FEATURES & BENEFITS

- Ideal for large drywall repairs
- Finish Faster\*\* - 15-minute paint ready on repairs 1" x 1/8" in depth or smaller, depending on temperature and humidity
- 3X Stronger<sup>+</sup> – Superior Impact Resistance
- 1 Coat Application for repairs 1" wide by 1/8" in depth – Won't sink or shrink
- No priming required – Won't flash paint
- Easy-to-use, latex-based formula
- Easy water clean-up & low odor
- Interior/Exterior use

*\*\*based on comparison to paint and sand times of other DAP® heavyweight spackling*

*<sup>+</sup>than impact resistance of other DAP® heavyweight spackling.*



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## SUGGESTED USES

Ideal for filling holes, cracks, dents, defects and larger repairs in drywall and plaster.

## FOR BEST RESULTS

If spackling seems dry when opening, stir completely and evenly until it's a smooth, creamy consistency.

Do not apply when temperatures are below 40°F.

Do not apply outside if rain is expected within 24 hours.

### **DO NOT USE AS A SKIM COAT.**

For exterior applications, always topcoat with high quality exterior-grade paint before moisture contact.

## APPLICATION

### **APPLICATION:**

1. Surface must be clean, dry, structurally sound, and free of all foreign material. De-gloss surface, if necessary, for better adhesion to drywall surface.
2. If spackling seems dry when opening, stir completely and evenly until it's a smooth, creamy consistency.
3. Apply with a clean putty knife.
4. For a smooth finish, dip putty knife in water and lightly smooth spackling.
5. One application is usually sufficient for repairs 1" wide x 1/8" in depth.
6. May be painted in as little as 15 minutes on repairs 1" x 1/8" in depth or smaller, depending on temp., humidity and depth of fill. If sanding, additional dry time may be needed, approximately 60 minutes for repairs 1" x 1/8" in depth or smaller. If sanding is required, use medium-grit sandpaper and finish with fine-grit for a smooth finish. Wet sanding is recommended to avoid generation of dust.
7. Paint with latex or oil-based paints. Ensure that DAP® FAST DRY High Strength Spackling is thoroughly dry before applying oil-based paint.
8. Clean tools immediately with water. Dry material must be cut or scraped away.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency	Thick Paste; contents may appear dry when opening.
Vehicle	Latex Polymer
Volatile	Water
Filler	Inert Filler
Odor	Mild
Weight/Gallon	5.01-5.11 lbs./gal
Solids	63%
Application Temperature	Do not apply when temperatures are below 40°F
Service Temperature	0°F to 150°F
Shelf Life	12 months
Flash Point	100°C
Freezing	Freeze/thaw stable 5 cycles at 0°F
Dry Time	15 min time to paint (1" x 1/8" depth, depending on temperature, humidity)

## CLEAN UP & STORAGE

Clean tools immediately with water. Dry Material must be cut or scrapped away. Be sure container is closed and tightly sealed. Store container in a cool, dry place away from extreme heat or cold.

## SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at [dap.com](http://dap.com) or by calling 888-DAP-TIPS.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## WARRANTY

Limited Warranty: If product fails to perform when used as directed within one year of date of purchase, call 888-DAP-TIPS with your sales receipt and product container available for replacement product or sales price refund. DAP Global Inc. will not be responsible for incidental or consequential damage.

## COMPANY IDENTIFICATION

**Manufacturer:** DAP Global Inc., 2400 Boston Street, Baltimore, Maryland 21224

**Usage Information:** Call **888-DAP-TIPS** or visit [dap.com](http://dap.com) & click on "Ask the Expert"

**Order Information:** 800-327-3339 or [orders@dap.com](mailto:orders@dap.com)

**Fax Number:** 410-558-1068

**Also, visit the DAP website at [dap.com](http://dap.com)**