



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® KWIK SEAL ULTRA® Advanced Siliconized Sealant - Clear

PRODUCT DESCRIPTION

DAP® KWIK SEAL ULTRA® ADVANCED KITCHEN & BATH SEALANT is formulated with innovative ultra-hydrophobic technology that repels water, dirt and stains and offers a lifetime mold and mildew resistance guarantee so the sealant stays looking clean, fresh and new. It is 100% waterproof and crack resistant and can be exposed to water in as little as 4 hours after application without washing out. KWIK SEAL ULTRA has strong multi-surface adhesion and excellent flexibility for long lasting durability. Safe for granite and marble. The easy-to-use formula applies easily, tools smoothly, is low in odor and cleans up with water. Interior use.



PACKAGING	COLOR	UPC
10.1 fl oz (300 mL) Cartridge	Clear	7079818898
5.5 fl oz (162 mL) Tube	Clear	7079818895

KEY FEATURES & BENEFITS

- Ultra-hydrophobic technology repels water, dirt, soap scum and stains
- Limited Lifetime Warranty for Mold and Mildew.
- Sealant stays looking clean, fresh & new
- 100% waterproof, crack proof & stain proof
- 4 hour water ready
- Strong, multi-surface adhesion
- Easy application: easy gunning and smooth tooling
- Easy water clean-up & low odor
- Safe for granite & marble
- VOC compliant
- Interior use



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SUGGESTED USES

USE FOR CAULKING & SEALING:

- Tubs
- Showers
- Sinks
- Backsplashes
- Vanities
- Countertops
- Fixtures
- Sealing around pipes
- Repairing loose tiles

ADHERES TO:

- Wood – painted & unpainted
- Ceramic
- Porcelain
- Glass
- Most metals
- Most plastics
- Fiberglass
- Drywall
- Plaster
- Granite
- Cultured marble
- Brick
- Stone
- Most common building materials

FOR BEST RESULTS

- Apply in temperatures above 40°F.
- Not for continuous underwater use, high temperature surfaces or surface defects.
- Joint size should not exceed 3/8" wide x 3/8" deep. If joint depth exceeds 3/8", use backer rod material.
- **Sealant applies white and dries clear in 7-14 days depending on joint depth, temperature and humidity.**
- **Wait 4 hours before exposing to water.**
- Regular cleaning of surrounding areas is suggested.
- Store sealant away from extreme heat or cold.

APPLICATION

Surface Preparation

Surface must be clean, dry, structurally sound and free of all foreign material. Rubbing alcohol (Isopropyl alcohol) is recommended for removing soap film and soil.

Product Application

1. If using the squeeze tube, remove cap, and cut nozzle at 45° angle to desired bead size.
2. If using the cartridge, cut nozzle at 45° angle to desired bead size, puncture inner foil seal, load into caulk gun.
3. Fill gap or joint with sealant.
4. If necessary, tool or smooth the bead of sealant with a finishing tool before sealant skins over.
5. **Sealant applies white and dries clear in 7-14 days depending on joint depth, temperature and humidity.**



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

6. Clean up excess wet sealant with a damp sponge before it skins over. Excess dried sealant must be cut or scraped away. Clean hands and tools with warm water and soap.
7. Allow sealant to dry at least 4 hours (longer in cool or humid conditions) before exposing to water.
8. Reseal container for storage and reuse.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Appearance/Consistency	Gunnable, non-sag paste
Base Polymer	Acrylic copolymer
Filler	Not applicable
Volatile	Water
Weight % Solids	58%
Density (lbs per gallon)	8.6
Odor	Very mild
Clean Up	Water
Flash Point	>212°F (100°F)
Freeze Thaw Stability (ASTM C1183)	Passes 5 Cycles
Shelf Life	12 months
Coverage	10.1 fl oz: 55 linear feet at a 3/16" diameter bead 5.5 fl oz: 30 linear feet at 3/16" diameter bead
Typical Application Properties	
Application Temperature Range	40°F to 100°F
Tooling Time (Working Time)	5 minutes
Tack Free Time	10 minutes
Return to Service Time	4 hours
Full Dry Through	7-14 days
Vertical Sag (ASTM D2202)	0.05"
Typical Cured Performance Properties	
Service Temperature Range	0°F to 170°F
Water Ready Time	4 hours
Paint Ready Time	Not paintable
Mildew Resistance	Lifetime mold & mildew resistance



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

CLEAN UP & STORAGE

Clean up excess wet sealant with a damp sponge before it skins over. Excess dried sealant must be cut or scraped away. Clean hands and tools with warm water and soap. Store container in a cool, dry place away from extreme heat or cold.

SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request a SDS by visiting our website at dap.com or calling 888-DAP-TIPS.

LIMITED LIFETIME WARRANTY FOR MOLD & MILDEW

LIMITED ONE-YEAR WARRANTY & LIMITED LIFETIME WARRANTY FOR MOLD AND MILDEW: Warranty terms available at dap.com/warranty. For a free written copy, call (888)-DAP-TIPS.

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Suite 200, Baltimore, Maryland

21224

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on “Ask the Expert”

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com