



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® PATCH 'N PAINT® Lightweight Spackling

### PRODUCT DESCRIPTION

**DAP® PATCH 'N PAINT® Lightweight Spackling** lets you patch and prime in one easy step, saving time and money. It dries fast with no need to sand or prime, letting you paint with latex paint in 30 minutes. It is easy to apply with one strike of the putty knife. Won't shrink or crack. Ideal for repairing holes, cracks, and dents in drywall, plaster, wood, and stucco. DAP PATCH 'N PAINT Lightweight Spackling is low in odor and for interior or exterior use.



| PACKAGING | COLOR | UPC        |
|-----------|-------|------------|
| 3 oz.     | White | 7079812319 |
| ½ Pint    | White | 7079801602 |
| Quart     | White | 7079801611 |
| Gallon    | White | 7079801517 |

### KEY FEATURES & BENEFITS

- Patch & Prime in One Step
- Fast Drying – 30-Minute Latex Paint Ready
- No Sanding
- Won't Sink or Shrink
- Interior/Exterior use

### SUGGESTED USES

Ideal for filling holes, cracks, dents, and defects on: Drywall, Plaster, Wood, Stucco, Brick.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## FOR BEST RESULTS

- Do not apply when temperatures are below 40°F.
- Do not use on wear surfaces or where expansion & contraction occur.
- **DO NOT USE AS A SKIM COAT.**
- For exterior/moisture exposed applications, first apply waterproof primer, then apply waterproof coating or paint prior to moisture exposure. Do not use for tuck pointing applications on brick.

## APPLICATION

1. Surface must be free of grease, oil, and other foreign matter.
2. Stir thoroughly before use.  
(When using the 2.8 oz tube, remove top, grip tube bottom & twist up a very small amount (about 1/16") of filler. Either apply directly to surface or using built-in spackling knife, scrape off spackling from top of tube & apply to wall)
3. Using a clean putty knife, press spackling into hole or crack.
4. Draw blade firmly across the surface to remove excess material in one strike.
5. For a smoother finish, dip putty knife into water and lightly smooth spackling.
6. One application is usually sufficient for small repairs.  
For repairs deeper than 1/8", apply two or more layers allowing spackling to dry between applications.
7. May be painted within 30 minutes with a latex paint. Please follow paint manufacturer's instructions for application.
8. If sanding is desired, or if an oil-based paint is to be used, allow to dry thoroughly (approximately 24 hours).



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

|                         |                                                                  |
|-------------------------|------------------------------------------------------------------|
| Consistency             | Thick Paste                                                      |
| Vehicle                 | Latex Polymer                                                    |
| Volatile                | Water                                                            |
| Filler                  | Inert Filler                                                     |
| Odor                    | Mild                                                             |
| Paint                   | Takes either oil or latex-based paint                            |
| Solids                  | 75% by volume (or 42% by weight)                                 |
| Application Temperature | 40°F or higher                                                   |
| Service Temperature     | -20°F to 150°F                                                   |
| Shelf Life              | 12 months                                                        |
| Freezing                | Freeze/thaw stable 5 cycles at 0°F                               |
| Dry Time                | 30 minutes depending on temperature, humidity, and depth of fill |

## CLEAN UP & STORAGE

Wash tools immediately after use with water. Dried material must be removed by scraping or sanding. Be sure container lid/cap is closed and tightly sealed and store in a cool, dry place, away from extreme heat or cold.

## SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at [dap.com](http://dap.com) or by calling **888-DAP-TIPS**.

## WARRANTY

### **Limited Warranty:**

If product fails to perform when used as directed within one year of date of purchase, call 888-DAP-TIPS with your sales receipt and product container available for replacement product or sales price refund. DAP Global Inc. will not be responsible for incidental or consequential damages.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## COMPANY IDENTIFICATION

**Manufacturer:** DAP Global Inc., 2400 Boston Street, Baltimore, Maryland 21224 **Usage**

**Information:** Call **888-DAP-TIPS** or visit [dap.com](http://dap.com) & click on "Ask the Expert" **Order**

**Information:** 800-327-3339 or [orders@dap.com](mailto:orders@dap.com)

**Fax Number:** 410-558-1068

**Also, visit the DAP website at [dap.com](http://dap.com)**