




TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® PRESTO PATCH® Multi-Purpose Patching Compound (Ready to Use)

PRODUCT DESCRIPTION

DAP® PRESTO PATCH® Multi-Purpose Patching Compound is an easy-to-use, polymer-fortified, high performance patching compound formulated to fill holes & cracks in a multitude of interior & exterior surfaces. The product has a smooth working consistency, dries quickly with minimal shrinkage & sands easily. It is ready to paint in 1-5 hours depending on temperature, humidity, and depth of fill. Interior/Exterior use.



PACKAGING	COLOR	UPC
Gallon	Off-White	7079858555

KEY FEATURES & BENEFITS

- Patches cracks and holes in concrete, plaster, brick, wallboard & wood

SUGGESTED USES

Ideal for patching holes and cracks in Wallboard, Concrete, Plaster, Brick and Wood

FOR BEST RESULTS

- Do not apply at temperatures below 50°F.
- Use sandpaper to dull glossy surfaces before repairing.
- Not for use on traffic surfaces or for areas subject to movement.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

APPLICATION

1. Surface must be clean, dry and free of all foreign material.
2. Stir thoroughly before use.
3. Apply with clean putty knife, pushing product completely into crack or damaged area. For a smoother finish, dip putty knife in water & lightly smooth the surface.
4. For repairs deeper than ¼", apply 2 or more layers, allowing to dry between layers.
5. Presto Patch Multi-Purpose Patching Compound can be sanded or painted 1 to 5 hours after application, depending on temperature, humidity & depth of fill. For exterior applications always apply a high-quality exterior paint to fully cured patch surface, prior to water exposure.
6. Store away from extreme heat or cold.

DO NOT USE AS A SKIM COAT. Not recommended for areas that collect standing water or receive continuous moisture unless coated with a waterproofing product.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency	Heavy Paste
Vehicle	Latex Emulsion
Filler	Various Inerts
Odor	Mild
Weight/Gallon	15.40 lbs.
Solids	75.9% by weight
Application Temperature	50°F to 140°F
Service Temperature	-20°F to 120°F
Shelf Life	12 months
Dry Time	1 to 5 hours depending on temperature, relative humidity and depth of fill.
Paintable	1 to 5 hours depending on temperature, relative humidity and depth of fill.
Freezing	Protect from freezing
Coverage	1 gallon will cover approximately 12 sq. ft. at 1/8" thickness.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

CLEAN UP & STORAGE

Wash tools immediately after use with water. Dried material must be cut, scraped or sanded away. Be sure container lid is closed and tightly sealed. Store in a cool, dry place away from extreme heat or cold.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

WARRANTY

Limited Warranty:

If product fails to perform as directed, within one year from the date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products Inc. will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com