



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® Plaster Wall Patch Dry Mix

### PRODUCT DESCRIPTION

DAP® Plaster Wall Patch may be used to repair large holes in interior plaster walls and ceilings. It's easy-to-mix formula applies smoothly and dries to a durable, uniform finish. DAP Plaster Wall Patch is easy to sand and can be painted with any oil or latex-based paint.



PACKAGING	COLOR	UPC
25 lb. Bag	White	7079810304

### KEY FEATURES & BENEFITS

- Professional quality
- Long working time
- Easy to sand

### SUGGESTED USES

Ideal for patching large holes and cracks in plaster walls and ceilings.

### FOR BEST RESULTS

- Use cold water when mixing.
- Sand as needed before decorating.
- Wet sanding is recommended to avoid creating dust.
- Always use a good quality paint for a professional finish.
- For a faster setting plaster that's ideal for craft work, use **DAP Plaster of Paris**.
- To fill and conceal small cracks, nail holes and blemishes, use **DAP FAST 'N FINAL Lightweight Spackling**.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## APPLICATION

1. Surface must be clean and free of wallpaper, loose paint, plaster, wax, dust and dirt.
2. Under cut edges of existing plaster so patch anchors around opening. Dampen area to be patched with water.
3. Add DAP Plaster Wall Patch to clear water in clean container mixing 3 parts powder to 1-part cold water. Stir to a smooth consistency. (More water may be needed for large batches depending on consistency desired. Add small amounts at a time until desired consistency is achieved.) Do not mix more material than can be used in 2 hours. Discard any material that has begun to harden.
4. Apply DAP Plaster Wall Patch with a clean putty knife or trowel filling around edges. Remove excess material so that plaster is level and flush with the surface. For large, deep openings, apply a base layer and allow it to dry. When hard, wet surface and apply the finish layer of patch.
5. When thoroughly dry, sand smooth. Be sure plaster is completely dry and hard before painting (2 hours).

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Work Time	1.5 – 2 hours depending on humidity		
Setting Time	2 hours		
Final Curing Time	3 days		
Shelf Life	12 months stored in original package & tightly sealed.		
Coverage	<b>Wall Patch</b> 25 lb.	<b>Water</b> 3-1/2 to 4 qts.	<b>Coverage (at 1/4" thickness)</b> 13 sq. ft.

## CLEAN UP & STORAGE

Clean up with water before material hardens. Dried material must be scraped, cut or sanded away. Be sure container is closed and tightly sealed. Store in a cool, dry place away from extreme heat or cold.

## SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at [dap.com](http://dap.com) or by calling **888-DAP-TIPS**.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## WARRANTY

### **Limited Warranty:**

If product fails to perform as directed, within one year from the date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products Inc. will not be responsible for incidental or consequential damages.

## COMPANY IDENTIFICATION

**Manufacturer:** DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

**Usage Information:** Call **888-DAP-TIPS** or visit [dap.com](http://dap.com) & click on "Ask the Expert"

**Order Information:** 800-327-3339 or [orders@dap.com](mailto:orders@dap.com)

**Fax Number:** 410-558-1068

**Also, visit the DAP website at [dap.com](http://dap.com)**