



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® SEAL 'N PEEL® Original All Season Removable Weatherstrip Sealant

PRODUCT DESCRIPTION

DAP® SEAL 'N PEEL® Original Removable Weatherstrip Sealant is formulated for use as a seasonal weatherstripping product. It provides a watertight, weatherproof and fast drying seal against air and moisture, keeping homes warmer in winter, cooler in summer, while also reducing energy bills. Use it to seal drafty windows, seasonally used doors, around air conditioners, vents or fans. Then easily peel it away when no longer needed. Interior and exterior use.



PACKAGING	COLOR	UPC
10.1 fl oz	Clear	7079818351

KEY FEATURES & BENEFITS

- Provides temporary, removable seal
- Forms a tight, temporary seal
- Seals out drafts to save energy
- Peels away easily when no longer needed
- Interior/exterior use

SUGGESTED USES

USE FOR SEALING:

- Window and door frames
- Vents
- Fans
- Patio doors
- Air conditioners
- Louvers



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TEMPORARILY ADHERES TO:

- Glass
- Ceramic/Porcelain
- Aluminum
- Wood
- Metal
- Vinyl

FOR BEST RESULTS

- Apply in temperatures above 40°F.
- Not for continuous underwater use.
- Do not use on freshly painted surfaces. Product may peel or damage wallpaper, uncured or degraded coatings.
- Do not use on insulating panels or plastic materials which can be damaged by solvents.
- New metal and solvent resistant oily surfaces must be washed with acetone and dried.
- For unusual substrates, perform a test for adhesion prior to use.
- For gaps deeper than 1/4", use foam backer rod.
- The sealant should come into contact with each of the surfaces on a width of at least 1/8".
- **If applied indoors, the area must be ventilated during application and drying time.**
- Store below 80°F in dry place for optimal shelf life.

APPLICATION

Surface Preparation

Surface must be clean, dry, structurally sound and free of all old caulk, dirt, dust, & foreign material.

Product Application

1. Cut nozzle at a 45° angle to desired bead size.
2. Puncture inner foil seal.
3. Load into caulk gun.
4. Fill gap or crack with sealant.
5. Do not shape or tool the bead.
6. Clean up excess wet sealant from surface and tools with mineral spirits. Scrape or cut away excess dried sealant. Do not use mineral spirits to clean hands or skin. Wash hands or skin with soap and water.
7. Reseal cartridge for storage and reuse.
8. To remove bead when fully dry, peel sealant bead away from the application surface. Product left in place for more than one year may be more difficult to remove. Product may peel or damage wallpaper, uncured or degraded coatings and similarly weak and/or degraded surface materials.

DO NOT SEAL FIRE EXITS. CONSULT LOCAL FIRE OR CODE OFFICIAL WITH QUESTIONS ABOUT FIRE EXITS.

THIS PRODUCT HAS A VERY STRONG ODOR. ENSURE PROPER VENTILATION IS USED WHEN PRODUCT IS APPLIED AND CURING.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Appearance/Consistency	Smooth, gunnable paste
Base Polymer	Synthetic rubber
Filler	Not applicable
Volatile	Aliphatic and aromatic solvents
Weight % Solids	50%
Density (lbs per gallon)	7.0
Odor	Strong solvent
Flash Point	39°F
Freeze Thaw Stability (ASTM C1183)	Will not freeze
Shelf Life	12 months
Coverage	55 linear ft. at a 3/16" diameter bead size or 4 average size windows
Typical Application Properties	
Application Temperature Range	40°F to 100°F
Tooling Time (Working Time)	Do not tool or shape bead
Tack Free Time	10 minutes
Full Dry Through	7 days
Return to Service Time	12 hours
Vertical Sag (ASTM D2202)	0.15"
Typical Cured Performance Properties	
Service Temperature Range	-20°F to 122°F
Water Ready Time	12 hours
Paint Ready Time	Painting not recommended

CLEAN UP & STORAGE

Remove excess uncured sealant from surfaces and tools with mineral spirits. Excess cured sealant must be cut or scraped away. Do not use mineral spirits to clean hands or skin. Wash hands or skin with soap and water. Store container in temperatures below 80°F and in a dry place.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request a SDS by visiting our website at dap.com or calling **888-DAP-TIPS**.

WARRANTY

LIMITED WARRANTY: If product fails to perform when used as directed within one year of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products Inc. is not liable for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufactured for: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on “Ask the Expert”

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com