



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® Textured Concrete Premium Elastomeric Latex Filler & Sealant

### PRODUCT DESCRIPTION

**DAP® Textured Concrete Premium Elastomeric Latex Filler & Sealant** is used for repairing and sealing cracks and joints in concrete, masonry, stone, cinder block, and brick. The gray textured finish blends easily with concrete and provides excellent outdoor durability. Forms a durable, 100% waterproof and weatherproof seal. 2 Hour Paintability. Easy water clean up & won't stain or bleed onto the application surface. Interior/exterior use.



PACKAGING	COLOR	UPC
10.1 fl oz (300mL) Cartridge	Textured Gray	7079808676

### KEY FEATURES & BENEFITS

- Fills and seals cracks and holes in concrete surfaces
- Ready to use – needs no mixing or additives
- Provides a durable, long-lasting repair that is resistant to gasoline, salt, grease or oil when cured
- Cured sealant is mildew resistant
- 100% waterproof & weatherproof seal
- Excellent adhesion & flexibility for a durable seal
- Textured to blend with concrete & masonry surfaces
- Easy water clean up & low odor
- Won't stain or bleed
- 2 hour paint ready
- Safe for vehicle & foot traffic
- Exterior/Interior



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## SUGGESTED USES

### FILLING & SEALING CRACKS & GAPS IN:

- Concrete surfaces
- Patios
- Steps
- Above ground foundations
- Concrete driveways
- Sidewalks
- Garage floors
- Pavements

### ADHERES TO:

- Concrete
- Mortar
- Brick
- Stone
- Masonry
- Cinderblock
- Stucco
- Wood
- Most metals
- Other construction materials

## FOR BEST RESULTS

- Apply in temperatures above 40°F. Do not apply when rain or freezing temperatures are forecasted.
- Not for continuous underwater use.
- Joint size should not exceed 1/2" wide by 1/2" deep. If joint exceeds 1/2", use foam backer rod. Allow to cure 24 hours before direct exposure to water.
- Serviceable for pedestrian & vehicular traffic after 24 hours (minimum).
- Fully cures in 2-4 days, depending on temperature, humidity & depth of fill.
- Store sealant away from extreme heat or cold.

## APPLICATION

### Surface Preparation

Surface must be clean, dry, structurally sound and free of all old caulk, dirt, grease, damaged concrete & foreign material.

### Product Application

1. Apply in temperatures above 40°F. Do not apply when rain or freezing temperatures are forecasted within 24 hours. Cooler temperatures and higher humidity will slow down dry time.
2. Cut nozzle at 45° angle to desired bead size.
3. Load cartridge into caulk gun.
4. Fill cracks and gaps with sealant.
5. After application, a more uniform fill or neater appearance may be obtained by wetting a trowel or putty knife with water and tooling sealant lightly.
6. Allow to cure 24 hours before direct exposure to water (longer in cooler and/or humid conditions).
7. Paintable after 2 hours (longer in cool or humid conditions) with latex or oil-based paints.
8. Clean up excess sealant with a damp sponge before it skins over (30 minutes).



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

9. Excess cured sealant will need to be cut or scraped away.
10. Reseal cartridge for future use. Store away from extreme heat or cold.

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Appearance/Consistency	Smooth and creamy
Base Polymer:	Acrylic Latex
Filler:	Calcium carbonate
Volatile:	Water
Weight % Solids	73 % by weight
Density (lbs per gallon )	11.7 lbs/gal
Odor	Very mild
Clean Up	Water
Flash Point	>212°F
Freeze Thaw Stability:	Passes 5 Cycles
Shelf Life	12 months
Coverage	55 linear feet at 3/16" diameter bead
Typical Application Properties	
Application Temperature Range:	40°F to 100°F
Tooling Time (Working Time)	10 minutes
Tack Free Time	30 minutes
Full Cure Time	2 – 4 days
Return to Service Time	24 hrs
Vertical Sag (D2202)	0.05
Typical Cured Performance Properties	
Service Temperature Range:	-20°F to 180°F
Water Ready Time	24 hours
Paint Ready Time	2 Hours



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## CLEAN UP & STORAGE

Clean up excess uncured caulk with a damp sponge before it skins over (approximately 30 minutes). Excess dried caulk must be cut or scraped away. Clean hands and tools with warm, soapy water. Store in a cool, dry place away from extreme heat or cold.

## SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request a SDS by visiting our website at [dap.com](http://dap.com) or calling 888-DAP-TIPS.

## WARRANTY

**LIFETIME GUARANTEE:** DAP warrants this product for sealant purposes during the lifetime of your home, when used as directed, within one year of purchase. Call (888) DAP TIPS, with your sales receipt and product container available for replacement product or sales price refund. DAP is not liable for incidental or consequential damages.

## COMPANY IDENTIFICATION

**Manufacturer:** DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

**Usage Information:** Call 888-DAP-TIPS or visit [dap.com](http://dap.com) & click on “Ask the Expert”

**Order Information:** 800-327-3339 or [orders@dap.com](mailto:orders@dap.com)

**Fax Number:** 410-558-1068

**Also, visit the DAP website at [dap.com](http://dap.com)**