

## A58 Sure Plug™

### DESCRIPTION

Dayton Superior's A58 Sure Plugs are made from PVC soft vinyl and are used to plug holes left after taper tie is removed.



### FEATURES & BENEFITS

- Gray color blends well with concrete
- Position flush with the concrete face, or recess, depending on the architectural effect desired (1-1/2" maximum depth). When recessed, the sure plugs may also serve as backing for flush or recessed grouting
- No moving parts or metal to corrode in hard environments
- Highly chemical resistant



### PRODUCT DATA

- A58 Sure Plug should be installed ONLY with the A59 Insertion Tool
- When properly installed, the A58 Sure Plug will withstand a hydrostatic pressure equal to approximately a 277 ft. liquid head of water. Zero leakage at this pressure over a 24-hr period
- Independent test results available upon request.

SURE PLUG SELECTION		
PRODUCT CODE	SIZE CODE	SURE PLUG SIZE (Dia. X L)
66800	11	11/16" x 1"
66810	14	7/8" x 1-1/8"
66820	16	1" x 1-1/4"
66825	18	1-1/8" x 1-3/8"
66830	20	1-1/4" x 1-3/8"
66835	22	1-3/8" x 1-1/2"
66840	24	1-1/2" x 1-1/2"
220423	29	1-7/8" x 1-5/8"

SURE PLUG INSERTION TOOL SELECTION		
PRODUCT CODE	SIZE CODE	SIZE (Nom. Dia.)
44220 (Stem)	11	1/2"
44222 (Stem)	14	1/2"
44224 (Stem)	16	3/4"
44226 (Stem)	18-20	3/4"
44228 (Stem)	22-24	3/4"
44231 (Handle)	16-29	3/4"
44232 (Handle)	11-14	1/2"
44235 (Collar)	16-29	3/4"
44237 (Collar)	11-14	1/2"