

TECHNICAL DATA SHEET

DESCRIPTION

The Aztec Strongback Bolster Upper supports the top layer in double mat applications, rebar or wire mesh, slabs, heavy duty on-grade, corrugated decking, side-form spacer – below grade applications only, and Precast.

PRODUCT SPECIFICATION

- Cover Heights form 1" to 5" in 1/4" increments



FEATURES

- Designed for use with epoxy-coated/FRP/Stainless Steel and Galvanized rebar
- For use in corrosive environments
- Spans corrugations in elevated deck applications
- Suitable for use on vapor barriers or insulating foam
- No overlap required
- Manufactured in 30" lengths and packed in standard boxes
- Strong as metal SBU

APPROVALS / COMPLIANCE

- ACI315-99
- Meets all requirements to qualify as a CRSI Class 1 Bar Support.

RELATED PRODUCTS

- PSBB - Plastic Strongback Bolster
- PSB - E-Z Lok Slab Bolster

ORDERING INFORMATION

AZTEC® STRONGBACK BOLSTER UPPER

Product Code	Description	Weight
220165	1" X 2-1/2'	0.31 LB
220465	1" X 5'	0.31 LB
220335	1-1/4" X 2-1/2'	0.30 LB
220166	1-1/2" X 2-1/2'	0.30 LB
220469	1-1/2" X 5'	0.32 LB
129300	1-1/2" X 10'	0.32 LB
220312	1-3/4" X 2-1/2'	0.30 LB
220470	1-3/4" X 5'	0.30 LB
127513	1-3/4" X 5'	0.31 LB
220167	2" X 2-1/2'	0.31 LB
220471	2" X 5'	0.31 LB
220313	2-1/4" X 2-1/2'	0.32 LB
220297	2-1/2" X 2-1/2'	0.33 LB
220314	2-3/4" X 2-1/2'	0.33 LB
220474	2-3/4" X 5'	0.33 LB
126514	2-3/4" X 10'	0.33 LB
220296	3" X 2-1/2'	0.34 LB
220451	3" X 5'	0.34 LB
143437	3" X 10'	0.34 LB
220315	3-1/4" X 2-1/2'	0.35 LB
220475	3-1/4" X 5'	0.35 LB
220384	3-1/2" X 2-1/2'	0.41 LB
220476	3-1/2" X 5'	0.41 LB
220461	3-3/4" X 2-1/2'	0.42 LB
143440	3-3/4" X 10'	0.42 LB
220382	4" X 2-1/2'	0.44 LB
143441	4" X 10'	0.44 LB
220462	4-1/4" X 2-1/2'	0.47 LB
220479	4-1/4" X 5'	0.47 LB
143442	4-1/4" X 10'	0.47 LB
220385	4-1/2" X 2-1/2'	0.48 LB
220480	4-1/2" X 5'	0.48 LB
143443	4-1/2" X 10'	0.48 LB
220463	4-3/4" X 2-1/2'	0.48 LB
220481	4-3/4" X 5'	0.44 LB
143444	4-3/4" X 10'	0.44 LB
220386	5" X 2-1/2'	0.50 LB
220482	5" X 5'	0.50 LB
143445	5" X 10'	0.50 LB

MANUFACTURER

Dayton Superior Corporation
 1125 Byers Road
 Miamisburg, OH 45342
 Customer Service: 888-977-9600
 Technical Services: 877-266-7732
 Website: www.daytonsuperior.com

TECHNICAL DATA SHEET

WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.