

## Aztec® EZ Connect™ Heavy Duty - PSB

PATENTED



### APPLICATION:


Provides a continuous, strong and stable support for spacing rebar in a variety of applications.

### HEIGHT:

From 3/4" to 3"

### FEATURES:

- EZ Connect end design allows for a fast and secure connection
- Non-corrosive material
- Heights range from 3/4" to 3"
- Available in 2.5', 5' and 10' lengths
- Newly modeled support bed holds rebar in place



## PSB EZ Clip™

The EZ Clip allows for the Aztec® EZ Connect™ PSB to be used in **vertical applications**.



(For Slabs, Side-Form Spacers, Tilt-Wall and D.O.T. applications, refer to STRONG-BACK BOLSTER™)

## ReBoot™ Plastic Foundation Boot - PFB



### DESCRIPTION:

The PFB ReBoot Plastic Foundation Boot is a plastic, attachable boot used to position reinforcing steel. It consists of a fingered hole, structural base, and large bearing foot.

### FEATURES:

- Tight fitting rebar fingers
- I-beam constructed base
- Wide bearing foot

### APPLICATION:

The PFB ReBoot is used to maintain the concrete cover from the ends of vertical bars of a drilled shaft, rebar cage. It may also be used within a caisson ring for the same purpose.



## Aztec® StrongBack Slab/Beam Bolster™ - PSBB



### APPLICATION:

Elevated Slab, Tilt-Wall, Precast, Post-Tension, Parking Garage Decks, Side-Form Spacer

### HEIGHT:

From 3/4" to 3" (1/4" Increments)

### FEATURES:

- High load strength and impact resistant
- Qualifies for use as a Beam Bolster with 2-1/2" leg spacing
- Can be used individually or locked together to create any length
- Manufactured in 30" lengths in standard boxes
- Special packaging available in 5' or 10' sections, bundled and palletized



## Aztec® StrongBack SBU™ Slab Bolster Upper - PSBU



### APPLICATION:

Supports top layer in Double Mat application, Rebar or Wire Mesh, Slabs, Heavy Duty On-Grade, Corrugated Decking, Side-Form Spacer-below-grade applications only, Precast

### HEIGHT:

From 1" to 5" (1/4" increments)

### FEATURES:

- Designed for use with Epoxy-Coated/FRP/Stainless Steel/Galvanized rebar
- For use in corrosive environments
- Spans corrugations in elevated deck applications
- Suitable for use on Vapor Barriers or Insulating Foam
- No overlap required
- Manufactured in 30" lengths in standard boxes
- Special packaging available in 5' or 10' sections, bundled and palletized
- Strong as metal SBU

