

TECHNICAL DATA SHEET

DESCRIPTION

Citrus Cleaner J48 is a heavy duty concrete stripper that is used for the removal of curing compounds, curing and sealing compounds, sealers, oils, grease and rubber tire marks from concrete floors.

USE

Citrus Cleaner J48 is designed for stripping, degreasing and cleaning all types of concrete. It is ideal for concrete floor applications when it is necessary to remove dirt, tire marks, oil spills, grease and other contaminants. Citrus Cleaner J48 will also strip most curing compounds. It is an ideal application for warehouses, industrial plants, food processing plants, automotive plants, parking garages, plazas and service stations.

FEATURES

- Concrete Stripper
- Removes high solids sealers
- Has a citrus smell

PROPERTIES

Viscosity – 1.0 CPS Emulsifiable – Yes COLOR: Amber

VOC

774 g/l.

Estimating Guide

Stripping/Degreasing; Heavy Duty: 2.5-4.9 sq. M/L Normal: 9.8-12.3 sq. M/L

Packaging

PRODUCT CODE	PACKAGE	SIZE (Liters)
69298AU	Unit (4/case)	3.79
69297AU	Pail	18.93

STORAGE

Shelf Life - 2 Years

Placement:

Apply Citrus Cleaner J48 full strength for removing curing compounds, cure & seals, and sealers oils, grease and rubber tire marks from the concrete surface. Apply Citrus Cleaner J48 full strength to the floor, scrubbing with a stiff broom or floor buffer (swing scrubber).

Then allow the Citrus Cleaner J48 to dwell on the surface for 20 minutes or sufficient time to soften the contaminate so that it can be removed. Longer dwell times may be necessary for removal of multiple applications of curing compounds or cure and seals. Do not allow Citrus Cleaner J48 to dry during the dwell period. Once the contaminate is softened, rinse the entire floor thoroughly with water before the product dries. Re-application may be necessary for extremely dirty, stained floors, or hard-to-remove curing compounds.

CLEAN UP

Tools and equipment - use water

LIMITATIONS

FOR PROFESSIONAL USE ONLY

Use Citrus Cleaner J48 only on horizontal concrete or masonry surfaces. Do Not Use On Painted Walls. Always consult the Material Safety Data Sheet before use. Citrus Cleaner J48 will adversely affect vegetation. Citrus Cleaner J48 and the materials it removes may be hazardous and should be disposed of according to all local, state and federal regulations. Do not allow to flow into waterways.

PRECAUTIONS

READ SDS PRIOR TO USING PRODUCT

- Keep material and containers away from high heat, open flames, sparks or other sources of ignition
- Use with adequate ventilation
- Wear protective clothing, gloves and eye protection (goggles, safety glasses and/or face shield)
- Keep out of the reach of children
- Do not take internally
- In case of ingestion, seek medical help immediately
- May cause skin irritation upon contact, especially prolonged or repeated. If skin contact occurs, wash immediately with soap and water and seek medical help as needed.
- If eye contact occurs, flush immediately with clean water and seek medical help as needed
- Dispose of waste material in accordance with federal, state and local requirements

MANUFACTURER

Dayton Superior Corporation (Australia) PTY LTD Suite 2201 Level 22 Tower 2 Westfield Bondi Junction 101 Grafton Street Bondi Junction NSW 2022 Australia Phone: +61 (0)2 8095 6372 Fax: +61 (0)2 8095 6363

Website: www.daytonsuperior.com.au



TECHNICAL DATA SHEET

WARRANTY

Dayton Superior Corporation ("Dayton") warrants for 12 months from the date of manufacture or for the duration of the published product shelf life, whichever is less, that at the time of shipment by Dayton, the product is free of manufacturing defects and conforms to Dayton's product properties in force on the date of acceptance by Dayton of the order. Dayton shall only be liable under this warranty if the product has been applied, used, and stored in accordance with Dayton's instructions, especially surface preparation and installation, in force on the date of acceptance by Dayton of the order. The purchaser must examine the product when received and promptly notify Dayton in writing of any nonconformity before the product is used and no later than 30 days after such non-conformity is first discovered. If Dayton, in its sole discretion, determines that the product breached the above warranty, it will, in its sole discretion, replace the non-conforming product, refund the purchase price or issue a credit in the amount of the purchase price. This is the sole and exclusive remedy for breach of this warranty. Only a Dayton officer is authorized to modify this warranty. The information in this data sheet supersedes all other sales information received by the customer during the sales process. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM, TRADE OR OTHERWISE.

Dayton shall not be liable in contract or in tort (including, without limitation, negligence, strict liability or otherwise) for loss of sales, revenues or profits; cost of capital or funds; business interruption or cost of downtime, loss of use, damage to or loss of use of other property (real or personal); failure to realize expected savings; frustration of economic or business expectations; claims by third parties (other than for bodily injury), or economic losses of any kind; or for any special, incidental, indirect, consequential, punitive or exemplary damages arising in any way out of the performance of, or failure to perform, its obligations under any contract for sale of product, even if Dayton could foresee or has been advised of the possibility of such damages. The Parties expressly agree that these limitations on damages are allocations of risk constituting, in part, the consideration for this contract, and also that such limitations shall survive the determination of any court of competent jurisdiction that any remedy provided in these terms or available at law fails of its essential purpose.