

Clean Strip™ J1EF

DESCRIPTION

Clean Strip J1EF is a water-based, economical, V.O.C. compliant, concrete form release agent. Clean Strip J1EF works to ensure clean, positive release on plywood, fiberglass, aluminum, steel, urethane and other concrete forming materials and form liners.



FEATURES & BENEFITS

- Acts as a barrier to the adhesion of concrete while minimizing surface dusting
- Will not stain concrete or interfere with the adhesion of coatings
- Economical & V.O.C. compliant
- Clean, positive release
- Minimizes surface dusting
- Non-staining, water clean up
- Biodegradable
- Certified to conform to NSF/ANSI Standard 61 by WQA
- May contribute to LEED credits
- Contains 0 g/L. Compliant with all Canadian and U.S. VOC regulations for Concrete Form Release agents including Federal EPA, OTC, LADCO, SCAQMD & CARB

	Sq. Feet per gallon	Sq. Meters per liter
Steel	1000-1500	24.6-36.9
Aluminum	1000-1500	24.6-36.9
Medium Density Plywood	1000-1250	24.6-30.7
High Density Plywood	1000-1500	24.6-36.9
Rough Saw Lumber 1st coat	500-1000	12.3-24.6
2nd coat	500-1000	12.3-24.6

Texture and absorptions of forming matrecial will dictate final coverage rate. Prior to coating plywood forms, apply one or two heavy brush coats to edges to ensure ease of form removal.