Printing date 10.03.2017

Version number 114

Revision: 10.03.2017

Hazardous according to criteria of Australian Safety and Compensation Council.

1 Identification

· Product identifier

· Trade name: Epoxy Grout J55 - Part A

- · Article number: 145459AU-A
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Dayton Superior Corporation (Australia) PTY LTD 5A Connection Drive Campbellfield, VIC 3061 Australia Australia Phone: +61 1300 DAYTON (329866)

• Emergency telephone number:

Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

Australia in-country +(61)-290372994

2 Hazard(s) Identification

· Classification of the substance or mixture

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Muta. 2 H341 Suspected of causing genetic defects.

- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms



- · Signal word Warning
- *Hazard-determining components of labelling:* 2,3-epoxypropyl o-tolyl ether
- Hazard statements Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of causing genetic defects.
- **Precautionary statements** If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Avoid breathing dust/fume/gas/mist/vapours/spray.

(Contd. on page 2)

AU

Printing date 10.03.2017

Version number 114

Revision: 10.03.2017

(Contd. of page 1)

Trade name: Epoxy Grout J55 - Part A

Wear protective gloves/protective clothing/eye protection/face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

• Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

3 Composition and Information on Ingredients

· Chemical characterisation: Mixtures

 $\cdot \textit{Description: Mixture of substances listed below with nonhazardous additions.}$

· Dangerous components:		
- $ -$	75-100%	
♦ <i>Eye Irrit.</i> 2 <i>A</i> , <i>H</i> 319		
2210-79-9 2,3-epoxypropyl o-tolyl ether	<i>≤10%</i>	
Wuta. 2, H341; 🔶 Skin Irrit. 2, H315; Skin Sens. 1, H317		
• Additional information: For the wording of the listed hazard phrases refer to section 16.		

4 First Aid Measures

· Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Seek medical treatment.

· Information for doctor:

- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • Special hazards arising from the substance or mixture No further relevant information available.
 - (Contd. on page 3)

ontd. on page 3)

Printing date 10.03.2017

Version number 114

Revision: 10.03.2017

Trade name: Epoxy Grout J55 - Part A

· Advice for firefighters

• Protective equipment: No special measures required.

6 Accidental Release Measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.
- *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- · Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- · Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage: cool and dry
- Requirements to be met by storerooms and receptacles: Store in a cool dry location.
- · Information about storage in one common storage facility: Store away from incompatible materials.
- · Further information about storage conditions: Keep container tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

• Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

(Contd. on page 4)

(Contd. of page 2)

Printing date 10.03.2017

Version number 114

Revision: 10.03.2017

(Contd. of page 3)

Trade name: Epoxy Grout J55 - Part A

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use selfcontained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. • Eye protection: Wear appropriate eye protection to prevent eye contact.

9 Physical and Chemical Propertie	25
• Information on basic physical and cher • General Information	nical properties
· Appearance:	
Form:	Liquid
Colour: • Odour:	Grey Mild
• Odour: • Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	
	>94 °C
· Flash point:	
Flammability (solid, gas):	Not applicable.
· Ignition temperature:	
Decomposition temperature:	Not determined.
• Auto-ignition temperature:	Product is not selfigniting.
• Explosive properties:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density at 20 °C:	1.14 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
• Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic at 20 °C:	0 mPas
Kinematic:	Not determined.
	(Contd. on page 5)

Version number 114

Printing date 10.03.2017

Revision: 10.03.2017

Trade name: Epoxy Grout J55 - Part A

		(Contd. of page 4)
· Solvent content: Organic solvents:	0.0 %	
Solids content: • Other information	100.0 % No further relevant information available.	

10 Stability and Reactivity

· Reactivity No decomposition if stored and applied as directed.

· Chemical stability No decomposition if stored and applied as directed

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

• Conditions to avoid No further relevant information available.

• Incompatible materials: No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

· Information on toxicological effects

· Acute toxicity

· LD/LC50 values relevant for classification:

25085-99-8 Diglycidyl ether of bisphenol A homopolymer

Oral LD50 5000 mg/kg (rat) Dermal LD50 20000 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation May cause skin irritation.
- Serious eye damage/irritation Strong irritant with the danger of severe eye injury. Irritating effect.
- **Respiratory or skin sensitisation** Sensitisation possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

12 Ecological Information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

(Contd. on page 6)

AU

Printing date 10.03.2017

Version number 114

Revision: 10.03.2017

Trade name: Epoxy Grout J55 - Part A

(Contd. of page 5)

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

Non Regulated by DOT UN3082
Non Regulated by DOT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUII N.O.S. (2,3-epoxypropyl o-tolyl ether), MARINE POLLUTANT
Non Regulated by DOT
9 Miscellaneous dangerous substances and articles. 9
III
No Symbol (fish and tree)
Symbol (Jish and tree)
F-A,S-F

Version number 114

Revision: 10.03.2017

Trade name: Epoxy Grout J55 - Part A

Printing date 10.03.2017

	(Contd. of pag
Stowage Category	A
Transport in bulk according to Annex II og IBC Code	f Marpol and the Not applicable.
Transport/Additional information:	
IMDG	
Limited quantities (LQ)	5L
Excepted quantities $(\widetilde{E}Q)$	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	Non Regulated by DOT

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Chemical Substances

All ingredients are listed.

 \cdot Standard for the Uniform Scheduling of Medicines and Poisons

None of the ingredients is listed.

· GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms



· Signal word Warning

· Hazard-determining components of labelling: 2,3-epoxypropyl o-tolyl ether · Hazard statements Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of causing genetic defects. · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves/protective clothing/eye protection/face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see on this label). Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

(Contd. on page 8)

Printing date 10.03.2017

Version number 114


Revision: 10.03.2017

Trade name: Epoxy Grout J55 - Part A

(Contd. of page 7)

· National regulations:

• Technical instructions (air):



• Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environmental, Health & Safety Department

· Contact: Environmental, Health & Safety Manager

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1 Muta. 2: Germ cell mutagenicity – Category 2

AU -

Printing date 10.03.2017

Version number 114

Revision: 10.03.2017

Hazardous according to criteria of Australian Safety and Compensation Council.

1 Identification

· Product identifier

· Trade name: Epoxy Grout J55 - Part B

- · Article number: 145459AU-B
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Dayton Superior Corporation (Australia) PTY LTD 5A Connection Drive Campbellfield, VIC 3061 Australia Australia Phone: +61 1300 DAYTON (329866)

• Emergency telephone number:

Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

Australia in-country +(61)-290372994

2 Hazard(s) Identification

· Classification of the substance or mixture

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labelling:
- 3,6-diazaoctanethylenediamin
- 3,6,9-triazaundecamethylenediamine
- $2,4,6\-tris (dimethylaminomethyl) phenol$
- Hazard statements Causes severe skin burns and eye damage. May cause an allergic skin reaction.
- **Precautionary statements**
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children. Read label before use.
- Do not breathe dusts or mists.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

(Contd. on page 2)

AU

Printing date 10.03.2017

Version number 114

Revision: 10.03.2017

Trade name: Epoxy Grout J55 - Part B

(Contd. of page 1) IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

• Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition and Information on Ingredients

· Chemical characterisation: Mixtures

 \cdot **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:	
112-24-3 3,6-diazaoctanethylenediamin	10-25%
🚸 Skin Corr. 1B, H314; 🚸 Acute Tox. 4, H312; Skin Sens. 1, H317	
90-72-2 2,4,6-tris(dimethylaminomethyl)phenol	<i>≤10%</i>
() Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319	
112-57-2 3,6,9-triazaundecamethylenediamine	<i>≤10%</i>
Skin Corr. 1B, H314; 🚸 Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	
Additional information: For the wording of the listed hazard phrases refer to section 16.	<u>.</u>

4 First Aid Measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly. Immediately rinse with water.

If skin irritation continues, consult a doctor.

• After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

• After swallowing:

Drink plenty of water and provide fresh air. Call for a doctor immediately. Seek medical treatment.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

· Extinguishing media

• Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 3)

AU

Printing date 10.03.2017

Version number 114

Revision: 10.03.2017

(Contd. of page 2)

Trade name: Epoxy Grout J55 - Part B

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental Release Measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 Environmental precautions:
- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system. • Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent. Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

· Handling:

· Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- · Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool dry location.
- · Information about storage in one common storage facility: Store away from incompatible materials.
- Further information about storage conditions: Keep container tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

• Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

(Contd. on page 4)

Printing date 10.03.2017

Version number 114

Revision: 10.03.2017

Trade name: Epoxy Grout J55 - Part B

(Contd. of page 3)

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use selfcontained respiratory protective device.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. • Eye protection: Wear appropriate eye protection to prevent eye contact.

Information on basic physical and cher	nical properties	
General Information	nicui propernes	
Appearance:		
Form:	Liquid	
Colour:	Amber coloured	
Odour:	Distinctive	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range	2: 333 °C	
Flash point:	>94 °C	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	335 °C	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapour pressure:	Not determined.	
Density at 20 °C:	0.949 g/cm ³	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
Dynamic at 20 °C:	0 mPas	
Kinematic:	Not determined.	

Version number 114

Printing date 10.03.2017

Revision: 10.03.2017

Trade name: Epoxy Grout J55 - Part B

		(Contd. of page 4)
· Solvent content: Organic solvents:	0.0 %	
Solids content: • Other information	100.0 % No further relevant information available.	

10 Stability and Reactivity

· Reactivity No decomposition if stored and applied as directed.

· Chemical stability No decomposition if stored and applied as directed

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

• Conditions to avoid No further relevant information available.

· Incompatible materials: No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

· Information on toxicological effects

· Acute toxicity

· LD/LC50 values relevant for classification:

112-24-3 3,6-diazaoctanethylenediamin

Oral LD50 2500 mg/kg (rat)

Dermal LD50 805 mg/kg (rabbit)

112-57-2 3,6,9-triazaundecamethylenediamine

Dermal LD50 660 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation May cause skin irritation.
- · Serious eye damage/irritation Strong caustic effect.
- · Respiratory or skin sensitisation Sensitisation possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

12 Ecological Information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- $\cdot \textit{Persistence and degradability} \textit{ No further relevant information available}.$
- \cdot Behaviour in environmental systems:
- $\cdot \textit{Bioaccumulative potential No further relevant information available}.$
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish

Printing date 10.03.2017

Version number 114

Revision: 10.03.2017

Trade name: Epoxy Grout J55 - Part B

· Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

UN-Number ADG, IMDG, IATA	UN2735
UN proper shipping name	
ADG	2735 AMINES, LIQUID, CORROSIVE, N.O.S (TETRAETHYLENEPENTAMINE)
IMDG	A M I N E S, L I Q U I D, C O R R O S I V E, N.O.S (TETRAETHYLENEPENTAMINE), MARINE POLLUTANT
IATA	AMINES, LIQUID, CORROSIVE, N.O.S (TETRAETHYLENEPENTAMINE)
Transport hazard class(es)	
ADG, IATA	
Class	8 Corrosive substances.
Label	8

(Contd. of page 5)

Printing date 10.03.2017

Version number 114

Revision: 10.03.2017

Trade name: Epoxy Grout J55 - Part B

	(Contd. of page
IMDG	
Class	8 Corrosive substances.
Label	8
Packing group ADG, IMDG, IATA	111
Environmental hazards: Marine pollutant:	No Symbol (fish and tree)
Special precautions for user	Warning: Corrosive substances.
Danger code (Kemler):	80 E A S B
EMS Number:	F-A,S-B Alkalis
Segregation groups Stowage Category	Alkans A
Segregation Code	SG35 Stow "separated from" acids.
Transport in bulk according to Annex II of M	
IBC Code	Not applicable.
Transport/Additional information:	
ADG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
Transport category	Maximum net quantity per outer packaging: 1000 ml 3
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities $(\widetilde{E}Q)$	Code: El
-	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O., (TETRAETHYLENEPENTAMINE), 8, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Chemical Substances

All ingredients are listed.

· Standard for the Uniform Scheduling of Medicines and Poisons

None of the ingredients is listed.

• *GHS label elements* The product is classified and labelled according to the Globally Harmonised System (GHS).


(Contd. on page 8)

Printing date 10.03.2017

Version number 114

Revision: 10.03.2017

Trade name: Epoxy Grout J55 - Part B



· National regulations:

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environmental, Health & Safety Department
- · Contact: Environmental, Health & Safety Manager

· Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Skin Sens. 1: Skin sensitisation – Category 1

Printing date 10.03.2017

Version number 86

Revision: 10.03.2017

Hazardous according to criteria of Australian Safety and Compensation Council.

1 Identification

· Product identifier

• Trade name: Epoxy Grout J55 - Part C

- · Article number: 145459AU-C
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Dayton Superior Corporation (Australia) PTY LTD 5A Connection Drive Campbellfield, VIC 3061 Australia Australia Phone: +61 1300 DAYTON (329866)

• Emergency telephone number:

Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

Australia in-country +(61)-290372994

2 Hazard(s) Identification

· Classification of the substance or mixture

Eye Irrit. 2A H319 Causes serious eye irritation.

Carc. 1A H350 May cause cancer.

· Label elements

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms



· Signal word Danger

- Hazard-determining components of labelling: Quartz (SiO2)
- Hazard statements Causes serious eye irritation. May cause cancer.

Precautionary statements
If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read label before use.
Wear protective gloves/protective clothing/eye protection/face protection.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Store locked up.

Printing date 10.03.2017

Version number 86

Revision: 10.03.2017

(Contd. of page 1)

Trade name: Epoxy Grout J55 - Part C

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

3 Composition and Information on Ingredients

· Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

Dungerous	components.	
14808-60-7	Quartz (SiO2) 🚯 Carc. 1A, H350; 🚯 Eye Irrit. 2A, H319 50-7	'5%
7727-43-7	barium sulphate, natural 25-5	0%
4 7 7 7		

• Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: If skin irritation continues, consult a doctor.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Seek medical treatment.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

· Extinguishing media

- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
Environmental precautions: Do not allow product to reach sewage system or any water course. No special measures required. Do not allow to enter sewers/ surface or ground water.
Methods and material for containment and cleaning up: Pick up mechanically.
Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

(Contd. on page 3)

Printing date 10.03.2017

Version number 86

Revision: 10.03.2017

(Contd. of page 2)

Trade name: Epoxy Grout J55 - Part C

7 Handling and Storage

- · Handling:
- · Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

14808-60-7 Quartz (SiO2)

WES (Australia) Long-term value: 0.1 mg/m³

respirable dust

7727-43-7 barium sulphate, natural

WES (Australia) Long-term value: 10 mg/m³

· Additional information: The lists valid during the making were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Wear appropriate eye protection to prevent eye contact.

9 Physical and Chemical Properties • Information on basic physical and chemical properties • General Information • Appearance: Form: Solid Colour: White • Odour: Odourless

Printing date 10.03.2017

Version number 86

Revision: 10.03.2017

Trade name: Epoxy Grout J55 - Part C

	(Contd. of page 2
Odour threshold:	Not determined.
pH-value:	Not applicable.
Change in condition Melting point/freezing point: Initial boiling point and boiling range:	Undetermined. Undetermined.
Flash point:	Not applicable.
Flammability (solid, gas):	Not determined.
Ignition temperature:	
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits: Lower: Upper:	Not determined. Not determined.
Vapour pressure:	Not applicable.
Density at 20 °C: Relative density Vapour density Evaporation rate	3.2 g/cm ³ Not determined. Not applicable. Not applicable.
Solubility in / Miscibility with water:	Insoluble.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic at 20 °C: Kinematic:	0 mPas Not applicable.
Solvent content: Organic solvents:	0.0 %
Solids content: • Other information	100.0 % No further relevant information available.

10 Stability and Reactivity

· Reactivity No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid No further relevant information available.

• *Incompatible materials:* No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 5)

Printing date 10.03.2017

Version number 86

Revision: 10.03.2017

Trade name: Epoxy Grout J55 - Part C

(Contd. of page 4)

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity
- · Primary irritant effect:
- \cdot Skin corrosion/irritation May cause skin irritation.
- \cdot Serious eye damage/irritation Strong irritant with the danger of severe eye injury.
- \cdot **Respiratory or skin sensitisation** No sensitising effects known.

12 Ecological Information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:
- · General notes:
- Generally not hazardous for water
- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Danger to drinking water if even extremely small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

- · Recommendation
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number		
ADG, ADN, IMDG, IATA	Non Regulated by DOT	
UN proper shipping name		
ADG, ADN, IMDG, IATA	Non Regulated by DOT	
Transport hazard class(es)		
ADG, ADN, IMDG, IATA		
Class	Non Regulated by DOT	

Printing date 10.03.2017	Version number 86	Revision: 10.03.2017	
Trade name: Epoxy Grout J55 - Part C			
		(Contd. of page 5)	
· Packing group · ADG, IMDG, IATA	Non Regulated by DOT		
• Environmental hazards: • Marine pollutant:	No		
• Transport in bulk according to Annex II o IBC Code	f Marpol and the Not applicable.		
· UN "Model Regulation":	Non Regulated by DOT		

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Chemical Substances

All ingredients are listed.

· Standard for the Uniform Scheduling of Medicines and Poisons

None of the ingredients is listed.

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms



· Signal word Danger

- Hazard-determining components of labelling: Quartz (SiO2)
 Hazard statements
- Causes serious eye irritation. May cause cancer.
- Precautionary statements
 If medical advice is needed, have product container or label at hand.
 Keep out of reach of children.
 Read label before use.
 Wear protective gloves/protective clothing/eye protection/face protection.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF exposed or concerned: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

 Directive 2012/18/EU
 Named dangerous substances ANNEX I None of the ingredients is listed.
- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 7)

Printing date 10.03.2017

Version number 86

Revision: 10.03.2017

Trade name: Epoxy Grout J55 - Part C

(Contd. of page 6)

AU

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environmental, Health & Safety Department

· Contact: Environmental, Health & Safety Manager

• Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Carc. 1A: Carcinogenicity – Category 1A Carc. 1A: Carcinogenicity – Category 1A