

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/22/2025

Reviewed on 04/22/2025

1 Identification

- **Product identifier**
- **Trade name:** Hydraulic Cement
- **Article number:** 307979
- **Application of the substance / the mixture**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Dayton® Superior
4226 Kansas Avenue
Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

2 Hazard(s) identification

- **Classification of the substance or mixture**
Acute Tox. 4 H302 Harmful if swallowed.
Eye Dam. 1 H318 Causes serious eye damage.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Carc. 1A H350 May cause cancer.
Repr. 1A H360 May damage fertility or the unborn child.
STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



- **Signal word** Danger
- **Hazard-determining components of labeling:**
Cement, portland, chemicals
lithium carbonate
Quartz (SiO₂)
calcium dihydroxide
- **Hazard statements**
Harmful if swallowed.
Causes serious eye damage.
May cause an allergic skin reaction.
May cause cancer.
May damage fertility or the unborn child.
Causes damage to organs through prolonged or repeated exposure.
- **Precautionary statements**
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center/doctor.
Specific treatment (see on this label).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/22/2025

Reviewed on 04/22/2025

Trade name: Hydraulic Cement

(Contd. of page 1)

Rinse mouth.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**· **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = 1
FIRE	0	Fire = 0
PHYSICAL HAZARD	0	Reactivity = 0

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**· **Description:** Mixture of the substances listed below with nonhazardous additions.· **Dangerous components:**

65997-15-1	Cement, portland, chemicals	≥30-≤60%
14808-60-7	Quartz (SiO ₂)	≥15-≤40%
1309-48-4	magnesium oxide	≥0-≤5%
1305-62-0	calcium dihydroxide	5%
554-13-2	lithium carbonate	≥0-≤1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· **Description of first aid measures**· **General information:**

Immediately remove any clothing soiled by the product.

In the event of persistent symptoms receive medical treatment.

· **After inhalation:**

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.· **After swallowing:** Seek medical treatment.· **Information for doctor:**· **Most important symptoms and effects, both acute and delayed** No further relevant information available.· **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/22/2025

Reviewed on 04/22/2025

Trade name: Hydraulic Cement

(Contd. of page 2)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:**
Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
No special measures required.
- **Methods and material for containment and cleaning up:** Pick up mechanically.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:** cool and dry
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

65997-15-1 Cement, portland, chemicals

PEL	Long-term value: 50 mppcf or 15* 5** mg/m ³ *total dust **respirable fraction
-----	---

(Contd. on page 4)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/22/2025

Reviewed on 04/22/2025

Trade name: Hydraulic Cement

(Contd. of page 3)

REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	Long-term value: 1* mg/m ³ E; *as respirable fraction
14808-60-7 Quartz (SiO₂)	
PEL	Long-term value: 0.05* mg/m ³ *resp. dust; 30mg/m ³ /%SiO ₂ +2
REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m ³ *as respirable fraction
1309-48-4 magnesium oxide	
PEL	Long-term value: 15* mg/m ³ fume; *total particulate
TLV	Long-term value: 10* mg/m ³ *as inhalable fraction
1305-62-0 calcium dihydroxide	
PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 5 mg/m ³
TLV	Long-term value: 5 mg/m ³

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Wear appropriate eye protection to prevent eye contact.

US

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/22/2025

Reviewed on 04/22/2025

Trade name: Hydraulic Cement

(Contd. of page 4)

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Solid

Color: According to product specification

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not applicable.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: >999 °C (>1,830.2 °F)

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not determined.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.

Upper: Not determined.

· **Vapor pressure:** Not applicable.

· **Density at 20 °C (68 °F):** 2.96 g/cm³ (24.7012 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not applicable.

· **Evaporation rate** Not applicable.

· Solubility in / Miscibility with

Water: Soluble.

· **Partition coefficient (n-octanol/water):** Not determined.

· Viscosity:

Dynamic: Not applicable.

Kinematic: Not applicable.

· Solvent content:

Solids content: 100.0 %

· **Other information** No further relevant information available.

10 Stability and reactivity

· **Reactivity** No decomposition if stored and applied as directed.

· **Chemical stability** No decomposition if stored and applied as directed

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Possibility of hazardous reactions** No dangerous reactions known.

· **Conditions to avoid** Keep away from heat and sources of ignition.

· **Incompatible materials:** No further relevant information available.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/22/2025

Reviewed on 04/22/2025

Trade name: Hydraulic Cement

(Contd. of page 5)

· **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**· **Acute toxicity:**· **Primary irritant effect:**· **on the skin:** May cause skin irritation.· **on the eye:** Irritating effect.· **Sensitization:** No sensitizing effects known.· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**14808-60-7 Quartz (SiO₂)

I

· **NTP (National Toxicology Program)**14808-60-7 Quartz (SiO₂)

K

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**· **Aquatic toxicity:** No further relevant information available.· **Persistence and degradability** No further relevant information available.· **Behavior in environmental systems:**· **Bioaccumulative potential** No further relevant information available.· **Mobility in soil** No further relevant information available.· **Additional ecological information:**· **General notes:** Water hazard class 1 (Self-assessment): slightly hazardous for water· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**· **Recommendation:**

Must not be disposed of as normal garbage. Do not allow product to reach sewage system.

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

· **Uncleaned packagings:**· **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/22/2025

Reviewed on 04/22/2025

Trade name: Hydraulic Cement

(Contd. of page 6)

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· UN-Number · DOT, ADR, ADN, IMDG, IATA	Not Regulated
· UN proper shipping name · DOT, ADR, ADN, IMDG, IATA	Not Regulated
· Transport hazard class(es) · DOT, ADR, ADN, IMDG, IATA · Class	Not Regulated
· Packing group · DOT, ADR, IMDG, IATA	Not Regulated
· Environmental hazards: · Marine pollutant:	No
· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · U.S. Domestic Ground Shipments: · U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments: · Emergency Response Guide (ERG) Number: · UN "Model Regulation":	Same as listed for Standard Shipments above. Same as listed for Standard Shipments above. Not determine Not Regulated

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

554-13-2	lithium carbonate	≥0-≤1%
----------	-------------------	--------

· **TSCA (Toxic Substances Control Act):**

65997-16-2	Cement, alumina, chemicals	ACTIVE
65997-15-1	Cement, portland, chemicals	ACTIVE
14808-60-7	Quartz (SiO ₂)	ACTIVE
1309-48-4	magnesium oxide	ACTIVE
1305-62-0	calcium dihydroxide	ACTIVE
554-13-2	lithium carbonate	ACTIVE

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/22/2025

Reviewed on 04/22/2025

Trade name: Hydraulic Cement

(Contd. of page 7)

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65**· Chemicals known to the State of California (Prop. 65) to cause cancer:**14808-60-7 Quartz (SiO₂)**· Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

554-13-2 lithium carbonate

· Cancerogenity categories**· EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)14808-60-7 Quartz (SiO₂)

A2

1309-48-4 magnesium oxide

A4

· MAK (German Maximum Workplace Concentration)14808-60-7 Quartz (SiO₂)

1

· NIOSH-Ca (National Institute for Occupational Safety and Health)14808-60-7 Quartz (SiO₂)**· GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).**· Hazard pictograms**

GHS05 GHS07 GHS08

· Signal word Danger**· Hazard-determining components of labeling:**

Cement, portland, chemicals

lithium carbonate

Quartz (SiO₂)

calcium dihydroxide

· Hazard statements

Harmful if swallowed.

Causes serious eye damage.

May cause an allergic skin reaction.

May cause cancer.

May damage fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure.

· Precautionary statements

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Rinse mouth.

Store locked up.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/22/2025

Reviewed on 04/22/2025

Trade name: Hydraulic Cement

(Contd. of page 8)

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

The provided information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environmental, Health & Safety Department

· **Contact:** Environmental, Health & Safety Manager

· **Date of preparation / last revision** 04/22/2025 / 111

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity – Category 4

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 1A: Carcinogenicity – Category 1A

Repr. 1A: Reproductive toxicity – Category 1A

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1