Printing date 03/14/2016

Reviewed on 03/14/2016

1 Identification

- · Product identifier
- Trade name: Seal Coat 1000
- · Article number: 83-67390
- Application of the substance / the mixture
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Dayton® Superior 4226 Kansas Avenue Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

· Information department: Environmental, Health, and Safety department.

2 Hazard(s) identification

· Classification of the substance or mixture

Skin Corr. 1C H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 1A H350 May cause cancer.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Danger

• Hazard-determining components of labeling: Cement, portland, chemicals Quartz (SiO2) calcium dihydroxide

• Hazard statements Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May cause cancer.

May cause respiratory irritation.

· Precautionary statements

Do not breathe dusts or mists.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Printing date 03/14/2016

Trade name: Seal Coat 1000

Reviewed on 03/14/2016

(Contd. of page 1)

• Classification system: • NFPA ratings (scale 0 - 4)

> Health = 1 Fire = 0 Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH1Health = 1FIRE0Fire = 0PHYSICAL HAZARD0Reactivity = 0

 \cdot Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

 $\cdot \textit{Description: Mixture of the substances listed below with nonhazardous additions.}$

· Dangerous components:				
65997-15-1	Cement, portland, chemicals	25-50%		
14808-60-7	Quartz (SiO2)	25-50%		
1305-62-0	calcium dihydroxide	<i>≤</i> 5%		
13397-24-5	Gypsum (Calcium sulfate)	<i>≤</i> 2.5%		
Additional i	nformation: For the wording of the listed hazard phrases refer to section 16	·		

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

In the event of persistent symptoms recieve medical treatment.

- After inhalation:
- Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

• After skin contact:

- Immediately wash with water and soap and rinse thoroughly.
- If skin irritation continues, consult a doctor.

• After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

- · After swallowing: Seek medical treatment.
- · Information for doctor:

• Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. on page 3)

Printing date 03/14/2016

Trade name: Seal Coat 1000

Reviewed on 03/14/2016

(Contd. of page 2)

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. No special measures required.
- Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage: cool and dry
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- *Specific end use(s) No further relevant information available.*

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

65997-15-1 Cement, portland, chemicals

PEL Long-term value: 50 mppcf or 15* 5** mg/m³ *total dust **respirable fraction

(Contd. on page 4)

US -

Printing date 03/14/2016

Reviewed on 03/14/2016

Trade name: Seal Coat 1000

	(Contd. of page 3)
REL	Long-term value: 10* 5** mg/m ³
	*total dust **respirable fraction
ILV	Long-term value: 1* mg/m ³ E; *as respirable fraction
1480	28-60-7 Quartz (SiO2)
	see Quartz listing
	Long-term value: 0.05* mg/m ³
	*respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m ³
	*as respirable fraction
	5-62-0 calcium dihydroxide
PEL	Long-term value: 15* 5** mg/m ³
	*total dust **respirable fraction
	Long-term value: 5 mg/m ³
	Long-term value: 5 mg/m ³
	07-24-5 Gypsum (Calcium sulfate)
REL	Long-term value: 10* 5** mg/m ³
777.17	*Total dust; **Respirable fraction
ILV	Long-term value: 10* mg/m ³ *as inhalable fraction
. Addi	itional information: The lists that were valid during the creation were used as basis.
	osure controls onal protective equipment:
	eral protective equipment. eral protective and hygienic measures:
	a way from foodstuffs, beverages and feed.
	ediately remove all soiled and contaminated clothing.
	h hands before breaks and at the end of work.
	d contact with the eyes and skin.
	athing equipment: Suitable respiratory protective device recommended. ection of hands:
1100	ccuon of numus.
	Protective gloves
	glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
	erial of gloves
ine	selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from

manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Wear appropriate eye protection to prevent eye contact.

(Contd. on page 5)

Printing date 03/14/2016

Trade name: Seal Coat 1000

Reviewed on 03/14/2016

(Contd. of page 4)

9 Physical and chemical properties					
• Information on basic physical and • General Information	chemical properties				
· Appearance:					
Form:	Solid				
Color:	According to product specification				
· Odor:	Characteristic				
· Odor threshold:	Not determined.				
· pH-value:	Not applicable.				
· Change in condition					
Melting point/Melting range:	Undetermined.				
Boiling point/Boiling range:	>999 °C (>1830 °F)				
· Flash point:	Not applicable.				
· Flammability (solid, gaseous):	Not determined.				
· Ignition temperature:					
Decomposition temperature:	Not determined.				
· Auto igniting:	Product is not selfigniting.				
• Danger of explosion:	Product does not present an explosion hazard.				
· Explosion limits:					
Lower:	Not determined.				
Upper:	Not determined.				
· Vapor pressure:	Not applicable.				
· Density at 20 °C (68 °F):	2.83831 g/cm ³ (23.686 lbs/gal)				
· Relative density	Not determined.				
· Vapor density	Not applicable.				
· Evaporation rate	Not applicable.				
· Solubility in / Miscibility with					
Water:	Soluble.				
· Partition coefficient (n-octanol/wat	· Partition coefficient (n-octanol/water): Not determined.				
· Viscosity:					
Dynamic:	Not applicable.				
Kinematic:	Not applicable.				
· Solvent content:					
Organic solvents:	0.0 %				
Solids content:	100.0 %				
· Other information	No further relevant information available.				
· Volatile Organic Compounds:	Not determined				

10 Stability and reactivity

• Reactivity No decomposition if stored and applied as directed.

- · Chemical stability No decomposition if stored and applied as directed
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 6)

(Contd. of page 5)

1

2B

3

K

Safety Data Sheet acc. to OSHA HCS

Printing date 03/14/2016

Reviewed on 03/14/2016

Trade name: Seal Coat 1000

- \cdot Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid Keep away from heat and sources of ignition.
- Incompatible materials: No further relevant information available.
- $\cdot \textit{Hazardous decomposition products: No dangerous decomposition products known.}$

11 Toxicological information

- \cdot Information on toxicological effects
- Acute toxicity:
- Primary irritant effect:
- on the skin: May cause skin irritation.
- on the eye: Irritating effect.
- \cdot Sensitization: Sensitization possible through skin contact.
- \cdot Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

14808-60-7 Quartz (SiO2)

13463-67-7 titanium dioxide

1309-37-1 diiron trioxide

· NTP (National Toxicology Program)

14808-60-7 Quartz (SiO2)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water Harmful to aquatic organisms

- \cdot Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

(Contd. on page 7)

(Contd. of page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/14/2016

Reviewed on 03/14/2016

Trade name: Seal Coat 1000

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as normal garbage. Do not allow product to reach sewage system. It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to Federal, State, and Local regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

Transport information	
UN-Number DOT, ADR, ADN, IMDG, IATA	Not Regulated
UN proper shipping name DOT, ADR, ADN, IMDG, IATA	Not Regulated
Transport hazard class(es)	
DOT, ADR, ADN, IMDG, IATA Class	Not Regulated
Packing group DOT, ADR, IMDG, IATA	Not Regulated
Environmental hazards: Marine pollutant:	No
Transport in bulk according to Annex II of MARPOL73/ and the IBC Code	78 Not applicable.
Transport/Additional information:	
ADR U.S. Domestic Ground Shipments: U.S. Domestic Ground Non-Bulk (119 gal or less per	Same as listed for Standard Shipments above.
container) Shipments:	Same as listed for Standard Shipments above.
Emergency Response Guide (ERG) Number:	Not determine

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
Sara
Section 355 (extremely hazardous substances):
None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

(Contd. on page 8)

Printing date 03/14/2016

Reviewed on 03/14/2016

Trade name: Seal Coat 1000

1244 20 1 1		(Contd. of pag
1344-28-1 aluminium oxide		<u>≤1</u>
TSCA (Toxic Substances Control Ac		
65997-15-1 Cement, portland, chem	icals	
14808-60-7 Quartz (SiO2)		
1305-62-0 calcium dihydroxide		
7647-14-5 sodium chloride		
1592-23-0 calcium distearate, pure		
1344-28-1 aluminium oxide		
1309-42-8 magnesium hydroxide		
1309-48-4 magnesium oxide		
1317-65-3 Limestone		
13463-67-7 titanium dioxide		
1309-37-1 diiron trioxide		
Proposition 65		
Chemicals known to the State of Ca	lifornia (Prop. 65) to cause cancer:	
14808-60-7 Quartz (SiO2)		
13463-67-7 titanium dioxide		
Chemicals known to cause reproduc	tive toxicity for females:	
None of the ingredients is listed.		
Chemicals known to cause reproduc	tive toxicity for males:	
None of the ingredients is listed.		
Chemicals known to cause developn	nental toxicity:	
None of the ingredients is listed.	-	
Cancerogenity categories		
EPA (Environmental Protection Age	ency)	
None of the ingredients is listed.		
TLV (Threshold Limit Value establi	shed by ACGIH)	
14808-60-7 Quartz (SiO2)	······································	1
1344-28-1 aluminium oxide		1
1309-48-4 magnesium oxide		1
13463-67-7 titanium dioxide		1
1309-37-1 diiron trioxide		
MAK (German Maximum Workplac	e Concentration)	
14808-60-7 Quartz (SiO2)		
1344-28-1 aluminium oxide		
13463-67-7 titanium dioxide		
	ccupational Safety and Health)	
NIOSH-Ca (National Institute for O 14808-60-7 Quartz (SiO2)	ccupational Safety and Health)	

(Contd. on page 9) US

Printing date 03/14/2016

Reviewed on 03/14/2016

Trade name: Seal Coat 1000

(Contd. of page 8)

· Hazard pictograms



· Signal word Danger

• Hazard-determining components of labeling: Cement, portland, chemicals Quartz (SiO2) calcium dihydroxide

• Hazard statements Causes severe skin h

Causes severe skin burns and eye damage. May cause an allergic skin reaction.

May cause an aller May cause cancer.

May cause respiratory irritation.

· Precautionary statements

Do not breathe dusts or mists.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

- Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The provided information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environmental, Health & Safety Department

- · Contact: Environmental, Health & Safety Manager
- Date of preparation / last revision 03/14/2016/15
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

(Contd. on page 10)

Printing date 03/14/2016

Trade name: Seal Coat 1000

REL: Recommended Exposure Limit Skin Corr. 1C: Skin corrosion/irritation, Hazard Category 1C Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 Carc. 1A: Carcinogenicity, Hazard Category 1A STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 Reviewed on 03/14/2016

(Contd. of page 9)