

# Sure Lift™ J6LVOC

## DESCRIPTION

A reactive and membrane forming low VOC, solvent based bond breaker for use in tilt wall construction, Sure Lift J6LVOC is a special formula of polymers and propriety ingredients designed to provide clean, easy lifting of tilt panels.

## FEATURES & BENEFITS

Sure Lift J6LVOC is designed to allow for easy lifting of tilt wall panels from properly designed, finished and cured concrete casting beds:

- Chemically reactive
- Good resistance to rain and weather
- Panels lift cleanly
- Minimal panel residue
- Resists construction foot traffic
- Meets ASTM C309 for water loss



*"We used the J6LVOC through one of the more severe winters we've had in over 20 years, and it outperformed all other bond breakers we've used. It was excellent in harsh winter conditions. There was a noticeable difference on the exterior of the panel."*

Guy Abrahamson, Owner of Monson Construction.

## PRODUCT DATA

J6LVOC can be used as a concrete cure, thus eliminating the need for multiple products on the jobsite.

With a VOC content of less than 350 g/L, Sure Lift J6LVOC is compliant with:

- U.S. Federal EPA
- OTC
- LADCO
- CARB
- UTAH ADMINISTRATIVE CODE- Rule R307361
- All Canadian V.O.C. regulations

### Estimating Guide

- Cure Coat: 200 sq. ft./gal (4.9 sq. M/L)
  - First Bond Breaker Coat: 400 sq. ft./gal. (9.8 sq. M/L)
  - Second Bond Breaker Coat: 550-700 sq. ft./gal (13.5-17.2 sq. M/L)
- Coverage rates are averages based on average site and concrete conditions.*

