

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/19/2023

Reviewed on 04/19/2023

1 Identification

- **Product identifier**

- **Trade name:** Sure Lift™ with Dye J6D

- **Article number:** 69231

- **Application of the substance / the mixture**

- **Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

Dayton® Superior
4226 Kansas Avenue
Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

2 Hazard(s) identification

- **Classification of the substance or mixture**

Flam. Liq. 3	H226	Flammable liquid and vapor.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2B	H320	Causes eye irritation.
Carc. 1B	H350	May cause cancer.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
STOT RE 1	H372	Causes damage to the central nervous system through prolonged or repeated exposure.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Stoddard solvent
butanol
1,2,4-trimethylbenzene
Naphtha (petroleum), hydrodesulfurized heavy

- **Hazard statements**

Flammable liquid and vapor.
Causes skin and eye irritation.
May cause cancer.
May cause respiratory irritation. May cause drowsiness or dizziness.
Causes damage to the central nervous system through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.
Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/19/2023

Reviewed on 04/19/2023

Trade name: Sure Lift™ with Dye J6D

(Contd. of page 1)

- **Precautionary statements**

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	2	Fire = 2
PHYSICAL HAZARD	0	Reactivity = 0

- **Other hazards**

- **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

8052-41-3	Stoddard solvent	≥20-<35%
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	≥20-<35%
64742-95-6	Solvent naphtha (petroleum), light arom.	>8-≤14%
95-63-6	1,2,4-trimethylbenzene	>5.5-≤9.5%
9003-29-6	Butene, homopolymer	≥1-≤5%
78-83-1	butanol	≥3-≤5%
64742-47-8	Distillates (petroleum), hydrotreated light	≥0.4-≤2%
98-82-8	cumene	≥1-<1.7%
64742-48-9	Naphtha (petroleum), hydrotreated heavy	<1.0%
103-65-1	propylbenzene	≥0.5-≤0.8%
91-20-3	naphthalene	≥0.1-<0.2%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/19/2023

Reviewed on 04/19/2023

Trade name: Sure Lift™ with Dye J6D

(Contd. of page 2)

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
In the event of persistent symptoms receive medical treatment.
- **After inhalation:**
Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Seek medical treatment.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Foam
- **For safety reasons unsuitable extinguishing agents:** Water
- **Special hazards arising from the substance or mixture** Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:**
Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/19/2023

Reviewed on 04/19/2023

Trade name: Sure Lift™ with Dye J6D

(Contd. of page 3)

- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:** cool and dry
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

8052-41-3 Stoddard solvent

PEL	Long-term value: 2900 mg/m ³ , 500 ppm
REL	Long-term value: 350 mg/m ³ Ceiling limit value: 1800* mg/m ³ *15-min
TLV	Long-term value: 525 mg/m ³ , 100 ppm

95-63-6 1,2,4-trimethylbenzene

REL	Long-term value: 125 mg/m ³ , 25 ppm
TLV	Long-term value: 123 mg/m ³ , 25 ppm

78-83-1 butanol

PEL	Long-term value: 300 mg/m ³ , 100 ppm
REL	Long-term value: 150 mg/m ³ , 50 ppm
TLV	Long-term value: 152 mg/m ³ , 50 ppm

98-82-8 cumene

PEL	Long-term value: 245 mg/m ³ , 50 ppm Skin
REL	Long-term value: 245 mg/m ³ , 50 ppm Skin
TLV	Long-term value: (246) NIC-0.5 mg/m ³ , (50) NIC-0.1 ppm NIC-A3

91-20-3 naphthalene

PEL	Long-term value: 50 mg/m ³ , 10 ppm
REL	Short-term value: 75 mg/m ³ , 15 ppm Long-term value: 50 mg/m ³ , 10 ppm
TLV	Long-term value: 52 mg/m ³ , 10 ppm Skin; BEI

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/19/2023

Reviewed on 04/19/2023

Trade name: Sure Lift™ with Dye J6D

(Contd. of page 4)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Eye protection:** Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: According to product specification

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 162 °C (323.6 °F)

· **Flash point:** 40 °C (104 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 230 °C (446 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower: 1.1 Vol %

Upper: 6 Vol %

· **Vapor pressure at 20 °C (68 °F):** 1 hPa (0.8 mm Hg)

· **Density at 20 °C (68 °F):** 0.81122 g/cm³ (6.76963 lbs/gal)

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/19/2023

Reviewed on 04/19/2023

Trade name: Sure Lift™ with Dye J6D

(Contd. of page 5)

· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	17.9-32.9 %
· Other information	No further relevant information available.
· Volatile Organic Compounds:	Contains less than 750 g/L.

10 Stability and reactivity

- **Reactivity** No decomposition if stored and applied as directed.
- **Chemical stability** No decomposition if stored and applied as directed
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Keep away from heat and sources of ignition.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

95-63-6 1,2,4-trimethylbenzene

Oral	LD50	5,000 mg/kg (rat)
------	------	-------------------

98-82-8 cumene

Oral	LD50	1,400 mg/kg (rat)
Dermal	LD50	12,300 mg/kg (rabbit)
Inhalative	LC50/4 h	24.7 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** May cause skin irritation.
- **on the eye:**
Strong irritant with the danger of severe eye injury.
Irritating effect.
- **Sensitization:** No sensitizing effects known.

(Contd. on page 7)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/19/2023

Reviewed on 04/19/2023

Trade name: Sure Lift™ with Dye J6D

(Contd. of page 6)

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

Carcinogenic.

The product can cause inheritable damage.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

98-82-8	cumene	2B
1330-20-7	xylene	3
91-20-3	naphthalene	2B
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

98-82-8	cumene	R
91-20-3	naphthalene	R

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Harmful to fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Water hazard class 1 (Self-assessment): slightly hazardous for water

Harmful to aquatic organisms

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of as normal garbage. Do not allow product to reach sewage system.

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/19/2023



Reviewed on 04/19/2023

Trade name: Sure Lift™ with Dye J6D

(Contd. of page 7)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT, ADR, IMDG, IATA 	<p style="margin-left: 20px;">UN1268</p>
<ul style="list-style-type: none"> · UN proper shipping name · DOT · ADR · IMDG, IATA 	<p style="margin-left: 20px;">Petroleum distillates, n.o.s. 1268 PETROLEUM DISTILLATES, N.O.S., ENVIRONMENTALLY HAZARDOUS PETROLEUM DISTILLATES, N.O.S.</p>
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT 	<p style="margin-left: 20px;">3 Flammable liquids</p>
<div style="text-align: center;">  </div> <ul style="list-style-type: none"> · Class · Label 	<p style="margin-left: 20px;">3</p>
<ul style="list-style-type: none"> · ADR, IMDG, IATA 	<div style="text-align: center;">  </div> <ul style="list-style-type: none"> · Class · Label
<ul style="list-style-type: none"> · Packing group · DOT, ADR, IMDG, IATA 	<p style="margin-left: 20px;">III</p>
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: 	<p style="margin-left: 20px;">No</p>
<ul style="list-style-type: none"> · Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category 	<p style="margin-left: 20px;">Warning: Flammable liquids 30 F-E,S-E A</p>
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code 	<p style="margin-left: 20px;">Not applicable.</p>
<ul style="list-style-type: none"> · Transport/Additional information: 	<p style="margin-left: 20px;">Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml Same as listed for Standard Shipments above.</p>
<ul style="list-style-type: none"> · ADR · Excepted quantities (EQ) · U.S. Domestic Ground Shipments: · U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments: 	<p style="margin-left: 20px;">DOT: Not regulated (Reclassified as per 49CFR 173.150).</p>

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/19/2023

Reviewed on 04/19/2023

Trade name: Sure Lift™ with Dye J6D

(Contd. of page 8)

· Emergency Response Guide (ERG) Number:	Not determine
· IMDG	5L
· Limited quantities (LQ)	Code: E1
· Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, III, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

95-63-6	1,2,4-trimethylbenzene	>5.5-≤9.5%
98-82-8	cumene	≥1-<1.7%
1330-20-7	xylene	>0.5-<1%
91-20-3	naphthalene	≥0.1-<0.2%
100-41-4	ethylbenzene	>0-<0.1%

· **TSCA (Toxic Substances Control Act):**

8052-41-3	Stoddard solvent	ACTIVE
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	ACTIVE
64742-95-6	Solvent naphtha (petroleum), light arom.	ACTIVE
95-63-6	1,2,4-trimethylbenzene	ACTIVE
9003-29-6	Butene, homopolymer	ACTIVE
112-62-9	Methyl 9-octadecenoate	ACTIVE
78-83-1	butanol	ACTIVE
112-80-1	oleic acid, pure	ACTIVE
25551-13-7	Trimethylbenzene	ACTIVE
64742-47-8	Distillates (petroleum), hydrotreated light	ACTIVE
98-82-8	cumene	ACTIVE
64742-48-9	Naphtha (petroleum), hydrotreated heavy	ACTIVE
1330-20-7	xylene	ACTIVE
103-65-1	propylbenzene	ACTIVE
526-73-8	1,2,3-trimethylbenzene	ACTIVE
108-67-8	mesitylene	ACTIVE
91-20-3	naphthalene	ACTIVE
4477-79-6	2-naphthalenol	ACTIVE
100-41-4	ethylbenzene	ACTIVE

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/19/2023

Reviewed on 04/19/2023

Trade name: Sure Lift™ with Dye J6D

(Contd. of page 9)

· **Hazardous Air Pollutants**

98-82-8	cumene
1330-20-7	xylene
91-20-3	naphthalene
100-41-4	ethylbenzene

· **Proposition 65**· **Chemicals known to the State of California (Prop. 65) to cause cancer:**

64742-95-6	Solvent naphtha (petroleum), light arom.
98-82-8	cumene
91-20-3	naphthalene
100-41-4	ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Cancerogenity categories**· **EPA (Environmental Protection Agency)**

95-63-6	1,2,4-trimethylbenzene	II
98-82-8	cumene	D, CBD
1330-20-7	xylene	I
526-73-8	1,2,3-trimethylbenzene	II
108-67-8	mesitylene	II
91-20-3	naphthalene	C, CBD
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene	A4
91-20-3	naphthalene	A4
100-41-4	ethylbenzene	A3

· **MAK (German Maximum Workplace Concentration)**

112-80-1	oleic acid, pure	3A
91-20-3	naphthalene	2
100-41-4	ethylbenzene	3A

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).· **Hazard pictograms**

GHS02

GHS07

GHS08

(Contd. on page 11)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/19/2023

Reviewed on 04/19/2023

Trade name: **Sure Lift™ with Dye J6D**

(Contd. of page 10)

· **Signal word** *Danger*· **Hazard-determining components of labeling:***Stoddard solvent**butanol**1,2,4-trimethylbenzene**Naphtha (petroleum), hydrodesulfurized heavy*· **Hazard statements***Flammable liquid and vapor.**Causes skin and eye irritation.**May cause cancer.**May cause respiratory irritation. May cause drowsiness or dizziness.**Causes damage to the central nervous system through prolonged or repeated exposure.**May be fatal if swallowed and enters airways.**Harmful to aquatic life with long lasting effects.*· **Precautionary statements***If swallowed: Immediately call a poison center/doctor.**Specific treatment (see on this label).**Do NOT induce vomiting.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**Take off contaminated clothing and wash it before reuse.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.*· **National regulations:**· **Information about limitation of use:***Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.*· **Water hazard class:** *Water hazard class 3 (Self-assessment): extremely hazardous for water.*· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

*The provided information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.**This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*· **Department issuing SDS:** *Environmental, Health & Safety Department*· **Contact:** *Environmental, Health & Safety Manager*· **Date of preparation / last revision** *04/19/2023 / 178*· **Abbreviations and acronyms:***ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**DOT: US Department of Transportation**IATA: International Air Transport Association**ACGIH: American Conference of Governmental Industrial Hygienists**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic*

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS

Printing date 04/19/2023

Reviewed on 04/19/2023

Trade name: Sure Lift™ with Dye J6D

(Contd. of page 11)

*vPvB: very Persistent and very Bioaccumulative**NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**Flam. Liq. 3: Flammable liquids – Category 3**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B**Carc. 1B: Carcinogenicity – Category 1B**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1**Asp. Tox. 1: Aspiration hazard – Category 1**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

US