

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 04/22/2025

Reviewed on 04/22/2025

### 1 Identification

· **Product identifier**

· **Trade name:** Tuf Seal™ J35

· **Article number:** 69076

· **Application of the substance / the mixture**

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Dayton® Superior  
4226 Kansas Avenue  
Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

· **Information department:** Environmental, Health, and Safety department.

### 2 Hazard(s) identification

· **Classification of the substance or mixture**

Flam. Liq. 3	H226 Flammable liquid and vapor.
Acute Tox. 4	H302 Harmful if swallowed.
Acute Tox. 4	H312 Harmful in contact with skin.
Acute Tox. 4	H332 Harmful if inhaled.
Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2A	H319 Causes serious eye irritation.
Carc. 2	H351 Suspected of causing cancer.
Repr. 1B	H360 May damage fertility or the unborn child.
STOT SE 3	H335 May cause respiratory irritation.
STOT RE 2	H373 May cause damage to the hearing organs through prolonged or repeated exposure.
Asp. Tox. 1	H304 May be fatal if swallowed and enters airways.
Aquatic Acute 2	H401 Toxic to aquatic life.
Aquatic Chronic 2	H411 Toxic to aquatic life with long lasting effects.

· **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02   GHS07   GHS08   GHS09

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

xylene  
dibutyl phthalate  
ethylbenzene

· **Hazard statements**

Flammable liquid and vapor.  
Harmful if swallowed, in contact with skin or if inhaled.

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/22/2025

Reviewed on 04/22/2025

**Trade name: Tuf Seal™ J35**

(Contd. of page 1)

*Causes skin irritation.**Causes serious eye irritation.**Suspected of causing cancer.**May damage fertility or the unborn child.**May cause respiratory irritation.**May cause damage to the hearing organs through prolonged or repeated exposure.**May be fatal if swallowed and enters airways.**Toxic to aquatic life.**Toxic to aquatic life with long lasting effects.***· Precautionary statements***If swallowed: Immediately call a poison center/doctor.**Specific treatment (see on this label).**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**Rinse mouth.**Take off contaminated clothing and wash it before reuse.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.***· Classification system:****· NFPA ratings (scale 0 - 4)**

Health = 2

Fire = 3

Reactivity = 0

**· HMIS-ratings (scale 0 - 4)**

HEALTH	2
FIRE	3
PHYSICAL HAZARD	0

Health = \*2

Fire = 3

Reactivity = 0

**· Other hazards****· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.

## 3 Composition/information on ingredients

**· Chemical characterization: Mixtures****· Description:** Mixture of the substances listed below with nonhazardous additions.**· Dangerous components:**

1330-20-7	xylene	>50-≤90%
100-41-4	ethylbenzene	≥1-≤5%
84-74-2	dibutyl phthalate	≥2.5-≤5%

**· Additional information:** For the wording of the listed hazard phrases refer to section 16.

(Contd. on page 3)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 04/22/2025

Reviewed on 04/22/2025

Trade name: Tuf Seal™ J35

(Contd. of page 2)

### 4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

In the event of persistent symptoms receive medical treatment.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

If skin irritation continues, consult a doctor.

- **After eye contact:** Rinse opened eye for several minutes under running water.

- **After swallowing:** Seek medical treatment.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:**

CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

Foam

- **For safety reasons unsuitable extinguishing agents:** Water

- **Special hazards arising from the substance or mixture** Formation of toxic gases is possible during heating or in case of fire.

- **Advice for firefighters**

- **Protective equipment:**

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

Mouth respiratory protective device.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 04/22/2025

Reviewed on 04/22/2025

Trade name: Tuf Seal™ J35

(Contd. of page 3)

See Section 13 for disposal information.

## 7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:** cool and dry

- **Requirements to be met by storerooms and receptacles:** No special requirements.

- **Information about storage in one common storage facility:** Store away from foodstuffs.

- **Further information about storage conditions:** Keep receptacle tightly sealed.

- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

### 1330-20-7 xylene

PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

REL Short-term value: 655 mg/m<sup>3</sup>, 150 ppm

Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

TLV Short-term value: 651 mg/m<sup>3</sup>, 150 ppm

Long-term value: 434 mg/m<sup>3</sup>, 100 ppm

BEI

### 100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

REL Short-term value: 545 mg/m<sup>3</sup>, 125 ppm

Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

TLV Long-term value: 87 mg/m<sup>3</sup>, 20 ppm

BEI

### 84-74-2 dibutyl phthalate

PEL Long-term value: 5 mg/m<sup>3</sup>

REL Long-term value: 5 mg/m<sup>3</sup>

TLV Long-term value: 5 mg/m<sup>3</sup>

- **Ingredients with biological limit values:**

### 1330-20-7 xylene

BEI 1.5 g/g creatinine

Medium: urine

Time: end of shift

Parameter: Methylhippuric acids

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/22/2025

Reviewed on 04/22/2025

Trade name: Tuf Seal™ J35

(Contd. of page 4)

**100-41-4 ethylbenzene**

BEI	0.7 g/g creatinine
	Medium: urine
	Time: end of shift at end of workweek
	Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	
	Medium: end-exhaled air
	Time: not critical
	Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Wear appropriate eye protection to prevent eye contact.

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

**Form:** Liquid

**Color:** According to product specification

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

**Melting point/Melting range:** Undetermined.

(Contd. on page 6)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 04/22/2025

Reviewed on 04/22/2025

Trade name: Tuf Seal™ J35

(Contd. of page 5)

<b>Boiling point/Boiling range:</b>	137 °C (278.6 °F)
· <b>Flash point:</b>	27 °C (80.6 °F)
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Ignition temperature:</b>	430 °C (806 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits:</b>	
Lower:	1 Vol %
Upper:	7.8 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	9.5 hPa (7.1 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	0.8987 g/cm <sup>3</sup> (7.49965 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
Dynamic:	Not determined.
Kinematic:	Not determined.
· <b>Solvent content:</b>	
Organic solvents:	56-95 %
Solids content:	15.0 %
· <b>Other information</b>	No further relevant information available.
· <b>Volatile Organic Compounds:</b>	Contains less than 800 g/L.

## 10 Stability and reactivity

- **Reactivity** No decomposition if stored and applied as directed.
- **Chemical stability** No decomposition if stored and applied as directed
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Keep away from heat and sources of ignition.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/22/2025

Reviewed on 04/22/2025

Trade name: Tuf Seal™ J35

(Contd. of page 6)

## 11 Toxicological information

### · Information on toxicological effects

#### · Acute toxicity:

#### · LD/LC50 values that are relevant for classification:

##### 1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

##### 100-41-4 ethylbenzene

Oral LD50 3,500 mg/kg (rat)

Dermal LD50 17,800 mg/kg (rabbit)

##### 84-74-2 dibutyl phthalate

Oral LD50 8,000 mg/kg (rat)

Dermal LD50 20,000 mg/kg (rabbit)

#### · Primary irritant effect:

· **on the skin:** May cause skin irritation.· **on the eye:** Strong irritant with the danger of severe eye injury.· **Sensitization:** No sensitizing effects known.

#### · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

#### · Carcinogenic categories

#### · IARC (International Agency for Research on Cancer)

1330-20-7 xylene

3

100-41-4 ethylbenzene

2B

#### · NTP (National Toxicology Program)

None of the ingredients is listed.

#### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

### · Toxicity

· **Aquatic toxicity:** No further relevant information available.· **Persistence and degradability** No further relevant information available.

#### · Behavior in environmental systems:

· **Bioaccumulative potential** No further relevant information available.· **Mobility in soil** No further relevant information available.

#### · Additional ecological information:

#### · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

#### · Results of PBT and vPvB assessment

· **PBT:** Not applicable.· **vPvB:** Not applicable.

(Contd. on page 8)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 04/22/2025

Reviewed on 04/22/2025

Trade name: Tuf Seal™ J35

(Contd. of page 7)

· **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

· **Waste treatment methods**· **Recommendation:**

Must not be disposed of as normal garbage. Do not allow product to reach sewage system.

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

· **Uncleaned packagings:**· **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

### 14 Transport information

· **UN-Number**· **DOT, ADR, IMDG, IATA**

UN1993

· **UN proper shipping name**· **DOT**

Flammable liquids, n.o.s. (Xylenes)

· **ADR**1993 FLAMMABLE LIQUID, N.O.S. (XYLENES),  
ENVIRONMENTALLY HAZARDOUS· **IMDG, IATA**

FLAMMABLE LIQUID, N.O.S. (XYLENES)

· **Transport hazard class(es)**· **DOT**· **Class**

3 Flammable liquids

· **Label**

3

· **ADR**· **Class**

3 Flammable liquids

· **Label**

3

· **IMDG, IATA**· **Class**

3 Flammable liquids

· **Label**

3

· **Packing group**· **DOT, ADR, IMDG, IATA**

III

(Contd. on page 9)

US



# Safety Data Sheet

## acc. to OSHA HCS

Printing date 04/22/2025

Reviewed on 04/22/2025

**Trade name: Tuf Seal™ J35**

(Contd. of page 8)

· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special marking (ADR):</b>	Symbol (fish and tree)
· <b>Special precautions for user</b>	Warning: Flammable liquids
· <b>Danger code (Kemler):</b>	30
· <b>EMS Number:</b>	F-E,S-E
· <b>Stowage Category</b>	A
· <b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml Same as listed for Standard Shipments above.
· <b>U.S. Domestic Ground Shipments:</b>	
· <b>U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:</b>	Same as listed for Standard Shipments above.
· <b>Emergency Response Guide (ERG) Number:</b>	Not determine
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1993 FLAMMABLE LIQUID, N.O.S. (XYLENES), 3, III, ENVIRONMENTALLY HAZARDOUS

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

#### · **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

#### · **Section 313 (Specific toxic chemical listings):**

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

1330-20-7	xylene	>50-≤90%
100-41-4	ethylbenzene	≥1-≤5%
84-74-2	dibutyl phthalate	≥2.5-≤5%

#### · **TSCA (Toxic Substances Control Act):**

1330-20-7	xylene	ACTIVE
28262-63-7	Butyl methacrylate, methacrylic acid polymer	ACTIVE
100-41-4	ethylbenzene	ACTIVE
84-74-2	dibutyl phthalate	ACTIVE

#### · **Hazardous Air Pollutants**

1330-20-7	xylene
-----------	--------

(Contd. on page 10)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/22/2025

Reviewed on 04/22/2025

**Trade name: Tuf Seal™ J35**

(Contd. of page 9)

100-41-4	ethylbenzene
84-74-2	dibutyl phthalate

· **Proposition 65**· **Chemicals known to the State of California (Prop. 65) to cause cancer:**

100-41-4	ethylbenzene
----------	--------------

· **Chemicals known to cause reproductive toxicity for females:**

84-74-2	dibutyl phthalate
---------	-------------------

· **Chemicals known to cause reproductive toxicity for males:**

84-74-2	dibutyl phthalate
---------	-------------------

· **Chemicals known to cause developmental toxicity:**

84-74-2	dibutyl phthalate
---------	-------------------

· **Carcinogenicity categories**· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
100-41-4	ethylbenzene	D
84-74-2	dibutyl phthalate	D

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3

· **MAK (German Maximum Workplace Concentration)**

100-41-4	ethylbenzene	3A
----------	--------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).· **Hazard pictograms**

GHS02   GHS07   GHS08   GHS09

· **Signal word** Danger· **Hazard-determining components of labeling:**

xylene

dibutyl phthalate

ethylbenzene

· **Hazard statements**

Flammable liquid and vapor.

Harmful if swallowed, in contact with skin or if inhaled.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

May damage fertility or the unborn child.

May cause respiratory irritation.

May cause damage to the hearing organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Toxic to aquatic life.

(Contd. on page 11)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 04/22/2025

Reviewed on 04/22/2025

**Trade name: Tuf Seal™ J35**

(Contd. of page 10)

*Toxic to aquatic life with long lasting effects.***· Precautionary statements***If swallowed: Immediately call a poison center/doctor.**Specific treatment (see on this label).**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Rinse mouth.**Take off contaminated clothing and wash it before reuse.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.***· National regulations:****· Water hazard class:** *Water hazard class 2 (Self-assessment): hazardous for water.***· Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

## 16 Other information

*The provided information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.**This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.***· Department issuing SDS:** *Environmental, Health & Safety Department***· Contact:** *Environmental, Health & Safety Manager***· Date of preparation / last revision** *04/22/2025 / 117***· Abbreviations and acronyms:***ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**DOT: US Department of Transportation**IATA: International Air Transport Association**ACGIH: American Conference of Governmental Industrial Hygienists**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**BEI: Biological Exposure Limit**Flam. Liq. 3: Flammable liquids – Category 3**Acute Tox. 4: Acute toxicity – Category 4**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A**Carc. 2: Carcinogenicity – Category 2**Repr. 1B: Reproductive toxicity – Category 1B**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2**Asp. Tox. 1: Aspiration hazard – Category 1**Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*