Tel.: (866) 329-8724

Safety Data Sheet acc. to OSHA HCS

Printing date 01/17/2015 Reviewed on 01/17/2015

1 Identification

- · Product identifier
- · Trade name: Turbo Grout LT12
- · Article number: 83-309013
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Dayton® Superior

4226 Kansas Avenue

Kansas City, KS 66106

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

· Information department: Environmental, Health, and Safety department.

2 Hazard(s) identification

· Classification of the substance or mixture

Carc. 1A H350 May cause cancer.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

May cause eye and skin irritation. Prolonged contact may cause sensitization.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to internationally acknowledged calculation procedures using the latest valid versions.

· Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labeling:

Quartz (SiO2)

· Hazard statements

May cause cancer.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Use personal protective equipment as required.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF exposed or concerned: Get medical advice/attention.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS

Printing date 01/17/2015 Reviewed on 01/17/2015

Trade name: Turbo Grout LT12

· Classification system:

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
14808-60-7	Quartz (SiO2)	25-50%
65997-15-1	Cement, portland, chemicals	25-50%
7778-18-9	calcium sulphate, natural	≤10%

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: If skin irritation continues, consult a doctor.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Seek medical treatment.
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 01/17/2015 Reviewed on 01/17/2015

Trade name: Turbo Grout LT12

(Contd. of page 2)

- · Advice for firefighters
- · Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: No special measures required.
- · Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

14808-60-7 Quartz (SiO2)

PEL see Quartz listing

REL Long-term value: 0.05* mg/m³

*respirable dust; See Pocket Guide App. A

TLV Long-term value: 0.025* mg/m³

*as respirable fraction

65997-15-1 Cement, portland, chemicals

PEL Long-term value: 50 mppcf or 15*5** mg/m³

*total dust **respirable fraction

REL Long-term value: 10*5** mg/m³

*total dust **respirable fraction

TLV Long-term value: 1* mg/m³ E; *as respirable fraction

(Contd. on page 4)

Printing date 01/17/2015 Reviewed on 01/17/2015

Trade name: Turbo Grout LT12

(Contd. of page 3)

69012-64-2 Silica-Amorphous Silica fume

TLV TLV withdrawn

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Breathing equipment: Suitable respiratory protective device recommended.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection: Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical properties

· Density at 20 °C (68 °F):

· Relative density

· Vapour density

9 Physical and chemical properties		
· Information on basic physical and chemical properties · General Information		
· Appearance: Form:	Solid	
Color:	According to product specification	
· Odor:	Characteristic	
· Odour threshold:	Not determined.	
· pH-value:	Not applicable.	
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. Undetermined.	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not determined.	
· Ignition temperature:		
Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits: Lower: Upper:	Not determined. Not determined.	
· Vapor pressure:	Not applicable.	

2.866 g/cm³ (23.917 lbs/gal)

Not determined.

Not applicable.

(Contd. on page 5)

Printing date 01/17/2015 Reviewed on 01/17/2015

Trade name: Turbo Grout LT12

		(Contd. of page
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
Water:	Insoluble.	
· Partition coefficient (n-octanol/water): Not determined.		
· Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
· Solvent content:		
Organic solvents:	0.0 %	
Solids content:	100.0 %	
· Other information	No further relevant information available.	
· Volatile Organic Compounds:	Not determined	

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: May cause skin irritation.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

eur eurogen	ic cureyories		
· IARC (Inter	· IARC (International Agency for Research on Cancer)		
14808-60-7	Quartz (SiO2)	1	
69012-64-2	Silica-Amorphous Silica fume	3	
1309-37-1	diiron trioxide	3	
13463-67-7	titanium dioxide	2 <i>B</i>	
· NTP (Natio	nal Toxicology Program)	<u> </u>	
14808-60-7	Quartz (SiO2)	K	
		(C . 1 .	

(Contd. on page 6)

Printing date 01/17/2015 Reviewed on 01/17/2015

Trade name: Turbo Grout LT12

(Contd. of page 5)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Water hazard class 1 (Self-assessment): slightly hazardous for water
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to Federal, State, and Local regulations.

14 Transport information	
· UN-Number · DOT, ADR, ADN, IMDG, IATA	Not Regulated
· UN proper shipping name · DOT, ADR, ADN, IMDG, IATA	Not Regulated
· Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
· Class	Not Regulated
· Packing group · DOT, ADR, IMDG, IATA	Not Regulated
· Environmental hazards: · Marine pollutant:	No
· Transport in bulk according to Annex II of MARPOL73/76 and the IBC Code	8 Not applicable.

(Contd. on page 7)

Printing date 01/17/2015 Reviewed on 01/17/2015

Trade name: Turbo Grout LT12

· Transport/Additional information:

· ADR
· U.S. Domestic Ground Shipments:
· U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:
· Emergency Response Guide (ERG) Number:

· UN "Model Regulation":

- (Contd. of page 6)

Same as listed for Standard Shipments above.

Not determine

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

554-13-2	lithium carbonate	≤1%
1344-28-1	aluminium oxide	≤1%
7429-90-5	aluminium powder (pyrophoric)	≤0.01%

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to the State of California (Prop. 65) to cause cancer:

14808-60-7 Quartz (SiO2)

13463-67-7 titanium dioxide

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

554-13-2 lithium carbonate

- · Cancerogenity categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Thres	shold Limit Value established by ACGIH)	
14808-60-7	Quartz (SiO2)	A2
1344-28-1	aluminium oxide	A4
1309-37-1	diiron trioxide	A4
1309-48-4	magnesium oxide	A4
13463-67-7	titanium dioxide	A4
7429-90-5	aluminium powder (pyrophoric)	A4
		(C (1 0)

(Contd. on page 8)

Printing date 01/17/2015 Reviewed on 01/17/2015

Trade name: Turbo Grout LT12

 (Contd. of page 7)

 • MAK (German Maximum Workplace Concentration)

 14808-60-7 Quartz (SiO2)
 1

 1344-28-1 aluminium oxide
 2

 13463-67-7 titanium dioxide
 3A

 112-80-1 oleic acid, pure
 3A

 • NIOSH-Ca (National Institute for Occupational Safety and Health)
 14808-60-7 Quartz (SiO2)

 13463-67-7 titanium dioxide
 Itanium dioxide

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labeling:

Quartz (SiO2)

· Hazard statements

May cause cancer.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Use personal protective equipment as required.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF exposed or concerned: Get medical advice/attention.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Environmental, Health & Safety Department
- · Contact: Environmental, Health & Safety Manager
- · Date of preparation / last revision 01/17/2015 / 31
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 9)

Printing date 01/17/2015 Reviewed on 01/17/2015

Trade name: Turbo Grout LT12

 ${\it CAS: Chemical Abstracts Service (division of the American Chemical Society)}$

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) Carc. 1A: Carcinogenicity, Hazard Category 1A

(Contd. of page 8)