Printing date 08/31/2022

Reviewed on 08/31/2022

1 Identification

- · Product identifier
- Trade name: Underwater Grout
- · Article number: 83-309351
- Application of the substance / the mixture
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Dayton® Superior 4226 Kansas Avenue Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

· Information department: Environmental, Health, and Safety department.

2 Hazard(s) identification

· Classification of the substance or mixture

Skin Corr. 1C H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 1A H350 May cause cancer.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Danger

- *Hazard-determining components of labeling:* Cement, portland, chemicals Quartz (SiO2)
- Hazard statements Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause cancer.

May cause respiratory irritation.

· Precautionary statements

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/31/2022

Reviewed on 08/31/2022

Trade name: Underwater Grout

·	Classification	system:

· NFPA ratings (scale 0 - 4)

 $\begin{array}{c} \textbf{Health} = 1\\ Fire = 0\\ Reactivity = 0 \end{array}$

· HMIS-ratings (scale 0 - 4)

HEALTH1Health = 1FIRE0Fire = 0PHYSICAL HAZARDReactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
14808-60-7	Quartz (SiO2)	<i>≥</i> 10-<50%
65997-15-1	Cement, portland, chemicals	<i>≥</i> 20-<50%
7778-18-9	calcium sulphate, natural	<3.25%
• Additional information: For the wording of the listed hazard phrases refer to section 16.		

4 First-aid measures

· Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

In the event of persistent symptoms recieve medical treatment.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention. • After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

• After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

- · After swallowing: Seek medical treatment.
- Information for doctor:

• Most important symptoms and effects, both acute and delayed No further relevant information available.

• Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

• Suitable extinguishing agents: Use fire fighting measures that suit the environment.

(Contd. on page 3)

US

(Contd. of page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/31/2022

Reviewed on 08/31/2022

Trade name: Underwater Grout

- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions: Do not allow product to reach sewage system or any water course. No special measures required.
- Methods and material for containment and cleaning up: Ensure adequate ventilation.
- **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage: cool and dry
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:	
14808-60-7 Quartz (SiO2)	
	Long-term value: 0.05* mg/m ³ *resp. dust; 30mg/m3/%SiO2+2
	Long-term value: 0.05* mg/m³ *respirable dust; See Pocket Guide App. A
	Long-term value: 0.025* mg/m ³ *as respirable fraction
	(Contd. on page 4)

Printing date 08/31/2022

Reviewed on 08/31/2022

Trade name: Underwater Grout

	(Contd. of page 3)
6599	7-15-1 Cement, portland, chemicals
PEL	Long-term value: 50 mppcf or 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	Long-term value: 1* mg/m ³ E; *as respirable fraction
7778	-18-9 calcium sulphate, natural
PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	Long-term value: 10* mg/m ³ *as inhalable fraction
· Addi	tional information: The lists that were valid during the creation were used as basis.
· Perso · Gene Keep Immo Wash Avoid · Brea	onal protective equipment: eral protective and hygienic measures: a way from foodstuffs, beverages and feed. ediately remove all soiled and contaminated clothing. a hands before breaks and at the end of work. d contact with the eyes and skin. thing equipment: Suitable respiratory protective device recommended. ection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- · Penetration time of glove material
- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection: Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical properties

• Information on basic physical and chemical properties • General Information		
· Appearance:		
Form:	Solid According to product specification Characteristic	
Color:		
· Odor:		
• Odor threshold:	Not determined.	
· pH-value:	Not applicable.	

(Contd. on page 5)

US

Printing date 08/31/2022

Reviewed on 08/31/2022

Trade name: Underwater Grout

		(Contd. of page
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. >999 °C (>1,830.2 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not determined.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure:	Not applicable.	
Density at 20 °C (68 °F):	2.9134 g/cm³ (24.31232 lbs/gal)	
Relative density	Not determined.	
· Vapor density	Not applicable.	
· Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
Water:	Soluble.	
Partition coefficient (n-octanol/wa	ter): Not determined.	
· Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
Solvent content:		
Solids content:	100.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No decomposition if stored and applied as directed.

- · Chemical stability No decomposition if stored and applied as directed
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid Keep away from heat and sources of ignition.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- \cdot on the skin: May cause skin irritation.
- on the eye: Irritating effect.
- Sensitization: Sensitization possible through skin contact.

(Contd. on page 6)

(Contd. of page 5)

1

3

2B

K

Safety Data Sheet acc. to OSHA HCS

Printing date 08/31/2022

Reviewed on 08/31/2022

Trade name: Underwater Grout

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

14808-60-7 Quartz (SiO2)

1309-37-1 diiron trioxide

13463-67-7 titanium dioxide

· NTP (National Toxicology Program)

14808-60-7 Quartz (SiO2)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:
- · General notes: Water hazard class 1 (Self-assessment): slightly hazardous for water
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as normal garbage. Do not allow product to reach sewage system.

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

· Uncleaned packagings:

- *Recommendation:* Disposal must be made according to Federal, State, and Local regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information		
· UN-Number · IMDG, IATA	Not Regulated	
· UN proper shipping name · IMDG, IATA	Not Regulated	
		(Contd. on page 7)

<0.4%

Safety Data Sheet acc. to OSHA HCS

Printing date 08/31/2022

Reviewed on 08/31/2022

Trade name: Underwater Grout

	(Contd. of page
· Transport hazard class(es)	
·DOT	
· Class	N/A
· Label	Ν/Α
· ADR	
· Class	N/A
· IMDG, IATA	
· Class	Not Regulated
· Packing group	
· IMDG, IATA	Not Regulated
· Environmental hazards:	
• Marine pollutant:	No
• Transport in bulk according to Annex II of MARPOL73/78	
and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· U.S. Domestic Ground Shipments:	Same as listed for Standard Shipments above.
· U.S. Domestic Ground Non-Bulk (119 gal or less per	
container) Shipments:	Same as listed for Standard Shipments above.
· Emergency Response Guide (ERG) Number:	Not determine
· UN "Model Regulation":	Not Regulated

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

1344-28-1 aluminium oxide

· TSCA (Toxic Substances Control Act):		
	Quartz (SiO2)	ACTIVE
65997-15-1	Cement, portland, chemicals	ACTIVE
7778-18-9	calcium sulphate, natural	ACTIVE
1344-28-1	aluminium oxide	ACTIVE
1309-37-1	diiron trioxide	ACTIVE
13463-67-7	titanium dioxide	ACTIVE
· Hazardous Air Pollutants		
None of the ingredients is listed.		
(Contd. on page 8)		

Printing date 08/31/2022

Reviewed on 08/31/2022

Trade name: Underwater Grout

· Proposition	n 65	(Contd. of page 7)
-	h os h known to the State of California (Prop. 65) to cause cancer:	
	7 Quartz (SiO2)	
13463-67-2	7 titanium dioxide	
· Chemicals	known to cause reproductive toxicity for females:	
	e ingredients is listed.	
· Chemicals	known to cause reproductive toxicity for males:	
	e ingredients is listed.	
· Chemicals	known to cause developmental toxicity:	
	e ingredients is listed.	
Cancaroaa	enity categories	
-	ironmental Protection Agency)	
	e ingredients is listed.	
• TLV (Thre	eshold Limit Value established by ACGIH)	
	7 Quartz (SiO2)	A2
	1 aluminium oxide	A4
1309-37-	1 diiron trioxide	A4
13463-67-2	7 titanium dioxide	A4
· MAK (Ger	man Maximum Workplace Concentration)	
14808-60-2	7 Quartz (SiO2)	1
1344-28	1 aluminium oxide	2
13463-67-2	7 titanium dioxide	3A
· NIOSH-Ca	a (National Institute for Occupational Safety and Health)	
14808-60-2	7 Quartz (SiO2)	
13463-67-2	7 titanium dioxide	

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

 Hazard-determining components of labeling: Cement, portland, chemicals Quartz (SiO2)
Hazard statements

Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause cancer. May cause respiratory irritation.

· Precautionary statements

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see on this label).

(Contd. on page 9)

Printing date 08/31/2022

Reviewed on 08/31/2022

Trade name: Underwater Grout

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

- Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The provided information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environmental, Health & Safety Department

· Contact: Environmental, Health & Safety Manager

- · Date of preparation / last revision 08/31/2022 / 94
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 1A: Carcinogenicity – Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

US