Printing date 05/07/2020 Reviewed on 05/07/2020

1 Identification

- · Product identifier
- · Trade name: WaterstopTM
- · Article number: 83-67375
- · Application of the substance / the mixture
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Dayton® Superior

4226 Kansas Avenue

Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

· Information department: Environmental, Health, and Safety department.

2 Hazard(s) identification

· Classification of the substance or mixture

Skin Corr. 1C H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- GHS label dements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

Cement, portland, chemicals

· Hazard statements

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

· Precautionary statements

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Printing date 05/07/2020 Reviewed on 05/07/2020

Trade name: WaterstopTM

(Contd. of page 1)

- · Classification system:
- · NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)



- Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
14808-60-7	Quartz (SiO2)	≥10-<45%
65997-15-1	Cement, portland, chemicals	≥5-<11%
26499-65-0	Calcium sulfate	<3.5%
7778-18-9	calcium sulphate, natural	<3.0%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

In the event of persistent symptoms recieve medical treatment.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Seek medical treatment.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

Printing date 05/07/2020 Reviewed on 05/07/2020

Trade name: WaterstopTM

(Contd. of page 2)

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

No special measures required.

- · Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage: cool and dry
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

Printing date 05/07/2020 Reviewed on 05/07/2020

Trade name: WaterstopTM

(Contd. of page 3)

· Control parameters

· Components with limit values that require monitoring at the workplace:

14808-60-7 Quartz (SiO2)

- PEL Long-term value: 0.05* mg/m³
 - *resp. dust; 30mg/m3/% SiO2+2
- REL Long-term value: 0.05* mg/m³
 - *respirable dust; See Pocket Guide App. A
- TLV Long-term value: 0.025* mg/m³
 *as respirable fraction

65997-15-1 Cement, portland, chemicals

- PEL Long-term value: 50 mppcf or 15* 5** mg/m³
 - *total dust **respirable fraction
- REL Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
- TLV Long-term value: 1* mg/m³ E; *as respirable fraction

26499-65-0 Calcium sulfate

- PEL Long-term value: 15* 5** mg/m³
 - *total dust **respirable fraction
- REL Long-term value: 10* 5** mg/m³
 *total dust **respirable fraction

7778-18-9 calcium sulphate, natural

- PEL Long-term value: 15* 5** mg/m³
 - *total dust **respirable fraction
- REL Long-term value: 10* 5** mg/m³
 *total dust **respirable fraction
- TLV Long-term value: 10* mg/m³
 - *as inhalable fraction
- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Breathing equipment: Suitable respiratory protective device recommended.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

Printing date 05/07/2020 Reviewed on 05/07/2020

Trade name: WaterstopTM

(Contd. of page 4)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical propert	ies
· Information on basic physical and	chemical properties
· General Information	• •
· Appearance:	
Form:	Solid
Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not applicable.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	>999 °C (>1,830.2 °F)
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not determined.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not applicable.
· Density at 20 °C (68 °F):	2.90949 g/cm³ (24.27969 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
Water:	Soluble.
· Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· Solvent content:	
Solids content:	100.0 %

(Contd. on page 6)

Printing date 05/07/2020 Reviewed on 05/07/2020

Trade name: WaterstopTM

(Contd. of page 5)

- Other information No further relevant information available.
- · Volatile Organic Compounds: Contains less than 10 g/L

10 Stability and reactivity

- · Reactivity No decomposition if stored and applied as directed.
- · Chemical stability No decomposition if stored and applied as directed
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Keep away from heat and sources of ignition.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: May cause skin irritation.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (Internationa	l Agency for	r Research on	Cancer)
----------------------	--------------	---------------	---------

14808-60-7 Quartz (SiO2)

1

· NTP (National Toxicology Program)

14808-60-7 Quartz (SiO2)

K

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Water hazard class 1 (Self-assessment): slightly hazardous for water
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 7)

Printing date 05/07/2020 Reviewed on 05/07/2020

Trade name: WaterstopTM

· Other adverse effects No further relevant information available.

(Contd. of page 6)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as normal garbage. Do not allow product to reach sewage system.

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to Federal, State, and Local regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information		
· UN-Number · DOT, ADR, ADN, IMDG, IATA	Not Regulated	
· UN proper shipping name · DOT, ADR, ADN, IMDG, IATA	Not Regulated	
· Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA · Class	Not Regulated	
· Packing group · DOT, ADR, IMDG, IATA	Not Regulated	
· Environmental hazards: · Marine pollutant:	No	
Transport in bulk according to Annex II of MARPOL73 and the IBC Code	3/78 Not applicable.	
· Transport/Additional information:		
· ADR · U.S. Domestic Ground Shipments:	Same as listed for Standard Shipments above.	
 U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments: 	Same as listed for Standard Shipments above.	
Emergency Response Guide (ERG) Number:	Not determine	
· UN "Model Regulation":	Not Regulated	

US -

Printing date 05/07/2020 Reviewed on 05/07/2020

Trade name: WaterstopTM

(Contd. of page 7)

Cafety, bookly and anning montal negative distribution and of a few them.	~~ ~~ ~~ ~~ ~~ ~~ ~~ ~~ ~~ ~~ ~~ ~~ ~~
Safety, health and environmental regulations/legislation specific for the substa Sara	ance or mixture
Section 355 (extremely hazardous substances):	
None of the ingredient is listed.	
Section 313 (Specific toxic chemical listings):	
This product may contain 1 or more toxic chemicals subject to the reporting re Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR pa	
554-13-2 lithium carbonate	<0.
TSCA (Toxic Substances Control Act):	
14808-60-7 Quartz (SiO2)	ACT
65997-16-2 Cement, alumina, chemicals	ACT
65997-15-1 Cement, portland, chemicals	ACT
7778-18-9 calcium sulphate, natural	ACT
1305-62-0 calcium dihydroxide	ACT
1317-65-3 Limestone	ACT
554-13-2 lithium carbonate	ACT
Hazardous Air Pollutants	
None of the ingredients is listed.	
Proposition 65	
Chemicals known to the State of California (Prop. 65) to cause cancer:	
14808-60-7 Quartz (SiO2)	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
554-13-2 lithium carbonate	
Cancerogenity categories	
EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
TLV (Threshold Limit Value established by ACGIH)	
14808-60-7 Quartz (SiO2)	
MAK (German Maximum Workplace Concentration)	
14808-60-7 Quartz (SiO2)	

· GHS label dements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

Printing date 05/07/2020 Reviewed on 05/07/2020

Trade name: WaterstopTM

· Hazard pictograms

(Contd. of page 8)





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

Cement, portland, chemicals

· Hazard statements

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

· Precautionary statements

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The provided information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environmental, Health & Safety Department
- · Contact: Environmental, Health & Safety Manager
- · Date of preparation / last revision 05/07/2020 / 105
- · Abbreviations and acronyms:

ADR: Accord europé en sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

 ${\it IATA: International Air Transport Association}$

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

(Contd. on page 10)

Printing date 05/07/2020 Reviewed on 05/07/2020

Trade name: WaterstopTM

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Skin Sens. 1: Skin sensitisation – Category 1

(Contd. of page 9)