

DEWALT

100
YEARS

ANCHORS & FASTENERS



SINCE
1924

BUYERS GUIDE

MECHANICAL ANCHORS • ADHESIVE ANCHORS
DIRECT FASTENING • SCREW FASTENERS • INSTALLATION TOOLS
DUST MANAGEMENT • DESIGN SOFTWARE OPTIONS



DESIGN




COMPARE



DOCUMENT



ANCHOR



Mechanical



Adhesives



Cast-in-Place

STATE-OF-THE-ART STRUCTURAL DESIGN SOFTWARE

FOR MORE INFORMATION OR TO DOWNLOAD NOW

log on to ANCHORS.DEWALT.COM/DDA

www.DEWALT.com | (800) 524-3244 | anchors@DEWALT.com



TABLE OF CONTENTS

MECHANICAL ANCHORS

WEDGE EXPANSION ANCHORS	12
UNDERCUT ANCHORS	20
SLEEVE ANCHORS.....	23
SCREW ANCHORS.....	28
ROD HANGING SYSTEMS	41
BOLT & SHIELD ANCHORS.....	45
RAPIDSET TOOLS.....	54
CAST-IN ANCHOR INSERTS	56
IMPACT, NAIL & PIN ANCHORS	64
LIGHT DUTY ANCHORS.....	71

ADHESIVES

CHEMICAL ANCHORING.....	79
GLASS CAPSULE ANCHORS.....	85
EXPANSION FOAMS.....	86
ADHESIVE SEALANTS.....	86
ADHESIVE ACCESSORIES	88

DIRECT FASTENING

CORDLESS TOOLS	95
GAS FASTENING.....	100
POWDER-ACTUATED	103
HAMMER-DRIVE.....	118

SCREW FASTENERS

SELF-DRILLING METAL SCREWS.....	119
SELF-TAPPING METAL SCREWS	137
PANEL RIVETS.....	139
BUILDING PROTECTION SYSTEMS.....	140

INSTALLATION TOOLS & ACCESSORIES

DRILL BITS	142
INSTALLATION TOOLS	146
SDS+ ROTARY HAMMERS.....	149
DUST EXTRACTION	152
CORDLESS IMPACT DRIVERS/WRENCHES	157



ANCHORS & FASTENERS

DISCLAIMER

DISCLAIMER FOR RECOMMENDATIONS, INFORMATION AND USE OF DATA

OUR PRODUCTS: The recommendations, information and data contained in this buyers guide and on the Site are put together with the greatest care and accuracy possible. They are based on principles, equations and safety factors set out in the technical documentation of DEWALT, that are believed to be true and correct at the time of publication on April 1, 2024. The information and data is subject to change after such date as DEWALT reserves the right to change the designs, materials and specifications of the products on the Site without notice.

It is the responsibility of the design professional to ensure that suitable product is selected, properly designed and used in the intended application. This includes that the selected product and its use is compliant with applicable building codes and other legal requirements and will satisfy durability and performance criteria and margins of safety which the design professional determine are applicable. The products must be used, handled, applied and installed strictly in accordance with all current instructions for use published by DEWALT.

The performance data in the buyers guide and on the Site are the result of the evaluation of tests conducted under laboratory conditions. It is the responsibility of the designer and installer in charge to consider the project conditions and to ensure the performance data set forth on the Site is applicable to the actual conditions. In particular the base materials and environmental conditions must be checked prior to installation. In case of doubt, contact the technical support of DEWALT.

DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: OUR EXPRESS WARRANTIES ARE LIMITED TO THOSE SPECIFIED WITH EACH PRODUCT. TO THE FULL EXTENT PERMISSIBLE BY APPLICABLE LAW, WE DISCLAIM ALL IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT WILL WE BE LIABLE TO ANY PARTY FOR ANY DAMAGES OF ANY KIND ARISING FROM THE USE OF THIS SITE OR FROM ANY INFORMATION, CONTENT, MATERIALS (INCLUDING SOFTWARE) OR SERVICES INCLUDED ON OR OTHERWISE MADE AVAILABLE TO YOU, INCLUDING, BUT NOT LIMITED TO, DIRECT, INDIRECT, INCIDENTAL, PUNITIVE, AND CONSEQUENTIAL DAMAGES, LOST PROFITS OR REVENUES, COSTS OF REPLACEMENT, BUSINESS INTERRUPTIONS, LOSS OF DATA OR DAMAGES RESULTING FROM USE OF OR RELIANCE ON THE INFORMATION PRESENT, EVEN IF STANLEY BLACK & DECKER IS EXPRESSLY ADVISED ABOUT THE POSSIBILITY OF SUCH DAMAGES, UNLESS OTHERWISE SPECIFIED IN WRITING. CERTAIN STATE LAWS DO NOT ALLOW LIMITATIONS ON IMPLIED WARRANTIES OR THE EXCLUSION OR LIMITATION OF CERTAIN DAMAGES. IF THESE LAWS APPLY TO YOU, SOME OR ALL OF THE ABOVE DISCLAIMERS, EXCLUSIONS, OR LIMITATIONS MAY NOT APPLY TO YOU, AND YOU MIGHT HAVE ADDITIONAL RIGHTS. FURTHER, STANLEY BLACK & DECKER SHALL HAVE NO LIABILITY WITH RESPECT TO CHANGES IN THE DESIGN, MATERIALS AND SPECIFICATIONS IN THE PRODUCTS, NOR WITH RESPECT TO ANY PRODUCT WHICH HAS BEEN MODIFIED OR INSTALLED IMPROPERLY, REGARDLESS OF ANY SPECIFIC INSTRUCTIONS TO THE INSTALLER. THE RESPONSIBLE DESIGNER AND INSTALLER SHALL HOLD STANLEY BLACK & DECKER HARMLESS FROM AND AGAINST ANY AND ALL CLAIMED LOSS OR DAMAGE OCCASIONED, IN WHOLE OR IN PART, BY ANY MODIFIED PRODUCTS OR DEVIATIONS IN PRODUCT INSTALLATION PROCEDURES.










LEGAL NOTICE FOR NEW JERSEY RESIDENTS: Under the New Jersey Truth-in-Consumer Contract, Warranty and Notice ACT ("TCCWNA"), N.J.S.A. 56:12-14 et seq., consumers may not be offered any written contract which includes any provision that violates any clearly established legal right of a consumer, or responsibility of a seller, as established by state or federal law. In addition, under the TCCWNA, no consumer contract may state that any of its provisions are or may be void, unenforceable or inapplicable in some jurisdictions without specifying which provisions are or are not void, unenforceable or inapplicable in New Jersey. Therefore, the following provisions of these Terms shall not be applicable to New Jersey residents: (1) in the Disclaimer of Warranties and Limitation of Liability section, (a) the provision concerning limiting our liability for any loss or damage is not applicable to New Jersey residents to the extent we were negligent or have breached our obligation to you, and (b) the provision concerning the exclusion or limitation of certain damages is not applicable to New Jersey residents with respect to punitive damages, loss of data, and loss of or damage to property; and (c) the provision concerning the indemnification by you is not applicable to New Jersey residents unless you were negligent or have breached these requirements.

For technical support for **DEWALT USA** please contact a **DEWALT Product & Code expert at 800-524-3244**, for **DEWALT Canada** call **905-673-7295** or visit our website at **DEWALT.com**. Verify scope of approval relative to intended application. The information and data contained within this document is current as of **NOV 01, 2023** and is subject to change after such date. **DEWALT** reserves the right to change the designs, materials, and specifications of the products in this document without notice and shall have no liability with respect to such changes. Please contact **DEWALT** for the most current and up to date information and data or refer to our website at **www.DEWALT.com**

© 2024 DEWALT. The following are trademarks for one or more DEWALT power tools, accessories, anchors and concrete adhesives: The yellow and black color scheme; the "D"-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool.

DEWALT Tech Bulletin, **Hilti is registered trademark of Hilti Corporation,
***Simpson is registered trademark of Simpson Strong-Tie Company, Inc.,
****TW Red Head is registered trademark of Illinois Tool Works, Inc.

MECHANICAL ANCHORS

















MECHANICAL ANCHORS					Similar Anchoring Products							
Power-Stud® + SD1 	Page 12	 ESR	ESR-2818, ESR-2966	Concrete	Wood	Anchor Diameter 1/4 in. – 1-1/4 in.	Under 500 lbs.	Over 500 lbs.	Over 5000 lbs.	Hiti Kwik Bolt 3 (KB3) Hiti KB1 Simpson Strong Bolt 2		
	Page 13	 ESR	ESR-2502	Concrete	Drywall		3/8 in. – 3/4 in.	Under 500 lbs.	Over 500 lbs.		Over 5000 lbs.	Hiti Kwik Bolt TZ/TZ2 Simpson Strong Bolt 2
	Page 14	 ESR	ESR-2502	Concrete	Unreinforced Masonry		1/4 in. – 3/4 in.	Under 500 lbs.	Over 500 lbs.		Over 5000 lbs.	Hiti Kwik Bolt 3 (KB3) / KB TZ/TZ2 SS – Simpson Strong Bolt 2
	Page 15	 ESR	ESR-2502	Concrete	Hollow Brick		1/4 in. – 3/4 in.	Under 500 lbs.	Over 500 lbs.		Over 5000 lbs.	Hiti Kwik Bolt 3 (KB3) / KB TZ/TZ2 SS Simpson Strong Bolt 2
	Page 16		–	Concrete	Solid Brick		3/8 in. – 3/4 in.	Under 500 lbs.	Over 500 lbs.		Over 5000 lbs.	Hiti Kwik Bolt 3 (KB3)
	Page 20		–	Concrete	Hollow Masonry		3/8 in. – 3/4 in. Anchor Rod Carbon Steel & Stainless Steel	Under 500 lbs.	Over 500 lbs.		Over 5000 lbs.	Hiti HDA Undercut Simpson TCA
	Page 28	 ESR	ESR-3889, ESR-4042	Concrete			1/4 in. – 3/4 in. (Zinc Plated & Mech Galv)	Under 500 lbs.	Over 500 lbs.		Over 5000 lbs.	Hiti KH-EZ / KWIK Simpson Titen HD
	Page 29	 ESR	ESR-3889, ESR-4042	Concrete			1/4 in. – 1/2 in. (Zinc Plated & Mech Galv)	Under 500 lbs.	Over 500 lbs.		Over 5000 lbs.	Hiti KH-EZ / KWIK Simpson Titen HD Hiti KH-EZ / SS3316
	Page 30		–	Concrete			1/4 in. – 1/2 in.	Under 500 lbs.	Over 500 lbs.		Over 5000 lbs.	Simpson Stainless Steel Simpson Titen HD
	Page 31	 ESR	ESR-3088, ESR-3196, ESR-3042, ESR-3213	Concrete			3/16 in. – 1/4 in.	Under 500 lbs.	Over 500 lbs.		Over 5000 lbs.	Simpson Titen Turbo ***ITW Tapcon
Page 23	 ESR	ESR-3260	Concrete		1/4 in. – 3/4 in. Carbon Steel	Under 500 lbs.	Over 500 lbs.	Over 5000 lbs.	Hiti HSL-3/ HSL-4			

















MEDIUM/LIGHT DUTY ANCHORS

6 SELECTION GUIDE

DEWALT Tech Bulletin, **Hilti is registered trademark of Hilti Corporation,
*****Simpson is registered trademark of Simpson Strong-Tie Company, Inc.,
*****ITW Red Head is registered trademark of Illinois Tool Works, Inc.

ROD HANGING ANCHORS

ROD HANGING ANCHORS				Similar Anchoring Products	
	Page 56		ESR-3657	Concrete	Concrete
	Page 57		ESR-3657	Concrete	Concrete
	Page 60		ESR-3657	Concrete	Concrete
	Page 45		ESR-2272	Concrete	Concrete
	Page 46		-	Concrete	Concrete
	Page 50		ESR-3912	Concrete	Concrete
	Page 41		ESR-3889	Concrete	Concrete
	Page 42		-	Concrete	Concrete

ADHESIVES	Image	Page	ES	ESR	Concrete	Lightweight Concrete	Concrete Masonry (Grout-Filled)	Hollow Core Pre-Cast	Hollow Masonry	Solid Brick	Hollow Brick	Unreinforced Masonry	Stone	Structural Clay/Tile	Anchor Diameter	Under 500 lbs.	Over 500 lbs.	Over 5000 lbs.	Similar Anchoring Products
AC200+™		Page 79		ESR-4027	■	■	□			□					3/8 in. – 1-1/4 in. #3 – #10 Rebar	■	■	■	Hilti HY 200 Simpson AT-3G
AC100+ Gold®		Page 80		ESR-2582, ESR-3200, ESR-4105	■	■	■	□	■	■	■	■	□		3/8 in. – 1-1/4 in. #3 – #10 Rebar	■	■	■	Hilti HY 100 Hilti HY 270
AC50™		Page 81		–	■								□		3/8 in. – 1 in. #3 – #8 Rebar				–
Pure220+™		Page 82		ESR-5144	■	■	■		■	■	□		□		3/8 in. – 1-1/4 in. #3 – #11 Rebar	■	■	■	**Hilti RE 500 V3 ***Simpson Set 3G
Pure110+®		Page 83		ESR-3298	■	■	■		■	■	□		□		3/8 in. – 1-1/4 in. #3 – #11 Rebar	■	■	■	Hilti RE 500 V3 Hilti RE 100 Simpson Set 3G
Pure50+™		Page 84		ESR-3576	■	■	□		□	□			□		3/8 in. – 1-1/4 in. #3 – #10 Rebar	■	■	■	Hilti RE 100 Simpson ET-3G
Hammer-Capsule®		Page 85		–	■	□	□			□			□		3/8 in. – 1 in. #3 – #8 Rebar				–
PowerStick™		Page 86		–	■	■	■		■	■	■		■		–				–
PowerFoam™		Page 86		ESR-3263	■	■	■		■	■	■		■		–				–
TriggerFoam™ Pro		Page 87		–	■	■	■		■	■	■		■		–				–

■ SUITABLE □ MAY BE SUITABLE
 *DEWALT Tech Bulletin, **Hilti is registered trademark of Hilti Corporation,
 ***Simpson is registered trademark of Simpson Strong-Tie Company, Inc.,
 ****TJW Red Head is registered trademark of Illinois Tool Works, Inc.

■ SUITABLE □ MAY BE SUITABLE

CCN & TRAK-IT® C5 PINS		ICC-ES Code Recognition						
CCN Straight Pins	Page 96	Stick-E Accessories	■	ESR-4076				
CCN Steel Fasteners	Page 96	Wood to Steel		ESR-4076				■
CCN Specialty Fasteners	Page 96	A36/A572 Steel		ESR-4076	□	■		■
Trak-It® Concrete & Masonry Pins	Page 101	Plywood to Light Gauge Steel						■
Trak-It® Steel Pins	Page 101	Brick Masonry	□					■
Trak-It® Specialty Pins	Page 101	Hollow Concrete Masonry	□		□		□	■
STICK-E™ Assemblies	Page 97	Grouted Concrete Masonry	□		□		□	■
		Wood Sill Plate to Concrete						■
		Lightweight Concrete On Metal Deck	■		■			■
		Lightweight Concrete	■		■			■
		High Strength / Concrete Precast Concrete			□		■	■
		Concrete	■		■		■	■
		Length	3/4" – 2-1/4"	1/2"	.78" – 1-3/8"	3/4" – 1-1/2"	1/2" – 1-1/4"	0.68" – 1-3/8"
		Diameter	0.102" – 0.145"	0.120"	0.102" – 0.120"	0.102" – 0.145"	0.120 – 0.145"	0.102" – 0.120"

■ SUITABLE □ MAY BE SUITABLE

POWDER-ACTUATED
DIRECT FASTENING
SYSTEMS PINS

POWDER-ACTUATED DIRECT FASTENING SYSTEMS PINS		DIMENSIONS	BASE				DEWALT TOOLS						OTHER TOOLS						ICC-ES Approvals		
			Concrete	Lightweight Concrete	Steel	Shank Length	DFD270	P1000	T1000	P2201	P3500/PA3500	P3600	Sniper	SA270	Cobra	Viper / Viper 4	XT540	RA27		DX351	DX2
Spiral CSI Drive Pins		Page 108	■	■	■	1/2" – 2-7/8"	■	■	■	■	■	■	■	■	■	■	■	■	■	■	ESR-2024
Spiral CSI Drive Pins Collated		Page 109	■	■	■	1/2" – 2-1/2"	■	■	■	■	■	■	■	■	■	■	■	■	■	■	ESR-2024
Spiral CSI Drive Pins with Washer		Page 108	■	■	■	3/4" – 2-7/8"	■	■	■	■	■	■	■	■	■	■	■	■	■	■	ESR-2024
0.300" Head Drive Pins		Page 110	■	■	■	1/2" – 3"	■	■	■	■	■	■	■	■	■	■	■	■	■	■	ESR-2024
0.300" Head Drive Pins with Top Hat		Page 110	■	■	■	1/2" – 1"	■	■	■	■	■	■	■	■	■	■	■	■	□	■	ESR-2024
0.300" Head Drive Pins with Washer		Page 111	■	■	■	3/4" – 3"	■	■	■	■	■	■	■	■	■	■	■	■	■	■	ESR-2024
8mm Head Drive Pins with Top Hat		Page 112	■	■	■	5/8" – 1"	■	■	■	■	■	■	■	■	■	■	■	■	■	■	ESR-2024
1/4"-20 Threaded Studs		Page 114	■	■	■	1/2" – 1-1/4"	■	■	■	■	■	■	■	■	■	■	■	■	■	■	ESR-2024
3/8"-16 Threaded Studs		Page 114	■	■	■	3/4" – 1-1/4"	■	■	■	■	■	■	■	■	■	■	■	■	■	■	ESR-2024
Rod Hangers and Post Nut Hangers		Page 116	■	■	■	1" – 1-1/4"	■	■	■	■	■	■	■	■	■	■	■	■	■	■	ESR-2024
Drive Pins with Ceiling Clip		Page 114	■	■	■	1" – 1-1/4"	■	■	■	■	■	■	■	■	■	■	■	■	■	■	ESR-2024
Drive Pins with BX-EMT Conduit Clip		Page 115	■	■	■	1" – 1-1/4"	■	■	■	■	■	■	■	■	■	■	■	■	■	■	ESR-2024
Drive Pins with Rebar Basket Clip		Page 116	■	■	■	1-1/2" – 2-1/2"	■	■	■	■	■	■	■	■	■	■	■	■	■	■	ESR-2024

■ SUITABLE □ MAY BE SUITABLE

SCREW FASTENER
DESCRIPTION/TYPE

SCREW FASTENER DESCRIPTION/TYPE	AVAILABLE FEATURES	PLATING/ COATING	MATERIAL	HEAD STYLE	FASTENER DIAMETER	CONNECTION TYPE	Pilot Point® for Wood-to-Metal Applications																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																	
------------------------------------	-----------------------	---------------------	----------	------------	-------------------	-----------------	---	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

WEDGE EXPANSION ANCHORS

Power-Stud®+ SD1

Description



The Power-Stud®+ SD1 anchor is a fully threaded, torque-controlled, zinc plated wedge expansion anchor designed for consistent performance in cracked and uncracked concrete and grouted concrete masonry.

Approvals



ICC-ES ESR-2818

(Concrete)

ESR-2966 (Masonry)

IBC & IRC 2021, 2018, 2015, 2012

Recognition in cracked & uncracked concrete including seismic and wind loading (Category 1 Anchors)

Full FM & UL listings in product brochure or at www.DEWALT.com

Base Materials

Normal-weight concrete, Sand-lightweight concrete, Concrete over metal deck, Grouted concrete masonry (CMU)

Anchor Material

Zinc plated carbon steel body with expansion clip, nut and washer

*For Power-Stud+ SD1: Less than the minimum standard anchor length for strength design. Published length is the overall length of the anchor. Allow for fixture thickness plus one anchor diameter for the nut and washer thickness when selecting a length. Packaged with nuts and washers.

1/4" diameter Power-Stud+ SD1 and Tie-Wire Power-Stud for uncracked concrete only.



POWER-STUD+ SD1 CARBON STEEL BODY & EXPANSION CLIP

CAT #	SIZE	THREAD LENGTH	PACK	CTN
7400SD1-PWR*	1/4" x 1-3/4"	3/4"	100	600
7402SD1-PWR	1/4" x 2-1/4"	1-1/4"	100	600
7404SD1-PWR	1/4" x 3-1/4"	2-1/4"	100	600
7410SD1-PWR*	3/8" x 2-1/4"	7/8"	50	300
7412SD1-PWR*	3/8" x 2-3/4"	1-3/8"	50	300
7413SD1-PWR	3/8" x 3"	1-5/8"	50	300
7414SD1-PWR	3/8" x 3-1/2"	2-1/8"	50	300
7415SD1-PWR	3/8" x 3-3/4"	2-3/8"	50	300
7416SD1-PWR	3/8" x 5"	3-5/8"	50	300
7417SD1-PWR	3/8" x 7"	5-5/8"	50	200
7420SD1-PWR*	1/2" x 2-3/4"	1"	50	200
7422SD1-PWR	1/2" x 3-3/4"	2"	50	200
7423SD1-PWR	1/2" x 4-1/2"	2-3/4"	50	200
7424SD1-PWR	1/2" x 5-1/2"	3-3/4"	50	150
7426SD1-PWR	1/2" x 7"	5-1/4"	25	100
7427SD1-PWR	1/2" x 8-1/2"	6-3/4"	25	100
7428SD1-PWR	1/2" x 10"	8-1/4"	25	100
7430SD1-PWR*	5/8" x 3-1/2"	1-1/2"	25	100
7432SD1-PWR	5/8" x 4-1/2"	2-1/2"	25	100
7433SD1-PWR	5/8" x 5"	3"	25	100
7434SD1-PWR	5/8" x 6"	4"	25	75
7436SD1-PWR	5/8" x 7"	5"	25	75
7438SD1-PWR	5/8" x 8-1/2"	6-1/2"	25	50
7439SD1-PWR	5/8" x 10"	8"	25	50
7440SD1-PWR*	3/4" x 4-1/4"	1-3/4"	20	60
7441SD1-PWR*	3/4" x 4-3/4"	2-1/4"	20	60
7442SD1-PWR	3/4" x 5-1/2"	3"	20	60
7444SD1-PWR	3/4" x 6-1/4"	3-3/4"	20	60
7446SD1-PWR	3/4" x 7"	4-1/2"	20	60
7448SD1-PWR	3/4" x 8-1/2"	6"	10	40
7449SD1-PWR	3/4" x 10"	7-1/2"	10	40
7451SD1-PWR	3/4" x 12"	9-1/2"	10	20
7450SD1-PWR*	7/8" x 6"	2-3/4"	10	40
7452SD1-PWR	7/8" x 8"	4-3/4"	10	40
7454SD1-PWR	7/8" x 10"	6-3/4"	10	20
7461SD1-PWR*	1" x 6"	2-3/8"	10	30
7463SD1-PWR	1" x 9"	5-3/8"	10	20
7465SD1-PWR	1" x 12"	8-3/8"	5	10
7473SD1-PWR	1-1/4" x 9"	4-3/4"	5	10
7475SD1-PWR	1-1/4" x 12"	7-3/4"	5	10



TIE-WIRE POWER-STUD

CAT #	SIZE	WIRE HOLE	MIN EMBED	PACK	CTN
7409SD1-PWR*	1/4" x 2"	9/32"	1-1/8"	100	600

WEDGE EXPANSION ANCHORS

Power-Stud®+ SD2

Description



The Power-Stud®+ SD2 anchor is a fully threaded, torque-controlled, zinc plated wedge expansion anchor with stainless steel expansion clip designed for premium performance in cracked and uncracked concrete and grouted concrete masonry.

Approvals



ICC-ES ESR-2502
(Concrete)

IBC & IRC 2018, 2015,
2012, 2009

Recognition in cracked
& uncracked concrete
including seismic and
wind loading
(Category 1 Anchors)

Full FM & UL listings in
product brochure or at www.DEWALT.com

Base Materials

Normal-weight concrete,
Sand-lightweight concrete,
Concrete over metal deck,
Grouted concrete masonry
(CMU)

Anchor Material

Zinc Plated Carbon Steel
Body hex nut and washer
with 316 SS Expansion Clip



POWER-STUD+ SD2 CARBON STEEL BODY & SS EXPANSION CLIP

CAT #	SIZE	THREAD LENGTH	PACK	CTN
7413SD2-PWR	3/8" x 3"	1-5/8"	50	300
7414SD2-PWR	3/8" x 3-1/2"	2-1/4"	50	300
7415SD2-PWR	3/8" x 3-3/4"	2-1/2"	50	300
7416SD2-PWR	3/8" x 5"	3-3/4"	50	300
7422SD2-PWR	1/2" x 3-3/4"	2-1/8"	50	200
7423SD2-PWR	1/2" x 4-1/2"	2-7/8"	50	200
7424SD2-PWR	1/2" x 5-1/2"	3-7/8"	50	150
7426SD2-PWR	1/2" x 7"	5-3/8"	25	100
7427SD2-PWR	1/2" x 8-1/2"	6-7/8"	25	100
7435SD2-PWR	5/8" x 4-3/4"	2-7/8"	25	100
7433SD2-PWR	5/8" x 5"	3-1/8"	25	100
7434SD2-PWR	5/8" x 6"	4-1/8"	25	75
7436SD2-PWR	5/8" x 7"	5-1/8"	25	75
7438SD2-PWR	5/8" x 8-1/2"	6-5/8"	25	50
7442SD2-PWR	3/4" x 5-1/2"	3-1/4"	20	60
7444SD2-PWR	3/4" x 6-1/4"	4"	20	60
7446SD2-PWR	3/4" x 7"	4-3/4"	20	60
7448SD2-PWR	3/4" x 8-1/2"	6-1/4"	10	40



WEDGE EXPANSION ANCHORS

Power-Stud®+ SD4

Description



The Power-Stud®+ SD4 is a fully threaded, torque-controlled, 304 stainless steel wedge expansion anchor designed for consistent performance in cracked and uncracked concrete and grouted concrete masonry.

Approvals



ICC-ES ESR-2502
(Concrete)

IBC & IRC 2021, 2018,
2015, 2012

Recognition in cracked
& uncracked concrete
including seismic and wind
loading
(Category 1 Anchors)

Base Materials

Normal-weight concrete,
Sand-lightweight concrete,
Grouted concrete masonry
(CMU)

Anchor Material

SD4: Type 304
stainless steel body with
300 series washer and
Type 316 stainless steel
expansion clip and nut

*For Power-Stud+ SD4:
Less than the minimum stan-
dard anchor length for strength
design. Published length is the
overall length of the anchor.
Allow for fixture thickness plus
one anchor diameter for the
nut and washer thickness when
selecting a length. Packaged
with nuts and washers.

¹Domestically manufactured
anchors include "USA" in the
catalog number.

1/4" diameter Power-Stud+
SD4 for uncracked concrete
only.



POWER-STUD+ SD4 (304 SS)

CAT # STANDARD	CAT # DOMESTIC ¹	SIZE	THREAD LENGTH	PACK	CTN
7300SD4-PWR*	—	1/4" x 1-3/4"	3/4"	100	600
7302SD4-PWR	—	1/4" x 2-1/4"	1-1/4"	100	600
7304SD4-PWR	7304SD4USA-PWR	1/4" x 3-1/4"	2-1/4"	100	600
—	7310SD4USA-PWR*	3/8" x 2-1/4"	7/8"	50	300
7313SD4-PWR	7313SD4USA-PWR	3/8" x 3"	1-5/8"	50	300
7315SD4-PWR	7315SD4USA-PWR	3/8" x 3-3/4"	2-3/8"	50	300
7316SD4-PWR	7316SD4USA-PWR	3/8" x 5"	3-5/8"	50	300
—	7317SD4USA-PWR	3/8" x 7"	3/8" x 7"	50	200
—	7320SD4USA-PWR*	1/2" x 2-3/4"	1"	50	200
7322SD4-PWR	7322SD4USA-PWR	1/2" x 3-3/4"	2"	50	200
7323SD4-PWR	7323SD4USA-PWR	1/2" x 4-1/2"	2-3/4"	50	200
7324SD4-PWR	7324SD4USA-PWR	1/2" x 5-1/2"	3-3/4"	50	150
7326SD4-PWR	7326SD4USA-PWR	1/2" x 7"	5-1/4"	25	100
—	7330SD4USA-PWR*	5/8" x 3-1/2"	1-1/2"	25	100
—	7332SD4USA-PWR	5/8" x 4-1/2"	2-1/2"	25	100
7333SD4-PWR	7333SD4USA-PWR	5/8" x 5"	3"	25	100
7334SD4-PWR	7334SD4USA-PWR	5/8" x 6"	4"	25	75
—	7336SD4USA-PWR	5/8" x 7"	4"	25	75
7338SD4-PWR	7338SD4USA-PWR	5/8" x 8-1/2"	6-1/2"	25	50
—	7340SD4USA-PWR*	3/4" x 4-1/4"	1-7/8"	20	60
—	7341SD4USA-PWR*	3/4" x 4-3/4"	2-3/8"	20	60
7342SD4-PWR	7342SD4USA-PWR	3/4" x 5-1/2"	3-1/8"	20	60
—	7344SD4USA-PWR	3/4" x 6-1/4"	3-7/8"	20	60
—	7346SD4USA-PWR	3/4" x 7"	4-5/8"	20	60
7348SD4-PWR	7348SD4USA-PWR	3/4" x 8-1/2"	6-1/8"	10	40
7349SD4-PWR	7349SD4USA-PWR	3/4" x 10"	7-5/8"	10	40



WEDGE EXPANSION ANCHORS

Power-Stud®+ SD6

Description



The Power-Stud®+ SD6 anchor is a fully threaded, torque-controlled, 316 stainless steel wedge expansion anchor designed for consistent performance in cracked and uncracked concrete and grouted concrete masonry.

Approvals



ICC-ES ESR-2502
(Concrete)

IBC & IRC 2021, 2018,
2015, 2012

Recognition in cracked
& uncracked concrete
including seismic and wind
loading
(Category 1 Anchors)

Base Materials

Normal-weight concrete,
Sand-lightweight concrete,
Grouted concrete masonry
(CMU)

Anchor Material

SD6: Type 316
stainless steel anchor body
expansion clip washer
and nut

*For Power-Stud+ SD6:
Less than the minimum stan-
dard anchor length for strength
design. Published length is the
overall length of the anchor.
Allow for fixture thickness plus
one anchor diameter for the
nut and washer thickness when
selecting a length. Packaged
with nuts and washers.

*Domestically manufactured
anchors include "USA" in the
catalog number.

1/4" diameter Power-Stud+
SD6 for uncracked concrete
only.



POWER-STUD+ SD6 (316SS)

CAT # STANDARD	CAT # DOMESTIC¹	SIZE	THREAD LENGTH	PACK	CTN
7602SD6-PWR	—	1/4" x 2-1/4"	1-1/4"	100	600
7604SD6-PWR	7604SD6USA-PWR	1/4" x 3-1/4"	2-1/4"	100	600
7610SD6-PWR*	7610SD6USA-PWR*	3/8" x 2-1/4"	7/8"	50	300
7612SD6-PWR	7612SD6USA-PWR	3/8" x 2-3/4"	1-3/8"	50	300
7613SD6-PWR	7613SD6USA-PWR	3/8" x 3"	1-5/8"	50	300
7614SD6-PWR	7613SD6USA-PWR	3/8" x 3-1/2"	2-1/8"	50	300
7615SD6-PWR	7615SD6USA-PWR	3/8" x 3-3/4"	2-3/8"	50	300
7616SD6-PWR	7616SD6USA-PWR	3/8" x 5"	3-5/8"	50	300
7617SD6-PWR	7617SD6USA-PWR	3/8" x 7"	5-5/8"	50	200
7620SD6-PWR*	7620SD6USA-PWR*	1/2" x 2-3/4"	1"	50	200
7622SD6-PWR	7622SD6USA-PWR	1/2" x 3-3/4"	2"	50	200
7623SD6-PWR	7623SD6USA-PWR	1/2" x 4-1/2"	2-3/4"	50	200
7624SD6-PWR	7624SD6USA-PWR	1/2" x 5-1/2"	3-3/4"	50	150
7626SD6-PWR	7626SD6USA-PWR	1/2" x 7"	5-1/4"	25	100
7630SD6-PWR*	7630SD6USA-PWR*	5/8" x 3-1/2"	1-1/2"	25	100
7632SD6-PWR	7632SD6USA-PWR	5/8" x 4-1/2"	2-1/2"	25	100
7633SD6-PWR	7633SD6USA-PWR	5/8" x 5"	3"	25	100
7634SD6-PWR	7634SD6USA-PWR	5/8" x 6"	4"	25	75
7636SD6-PWR	7636SD6USA-PWR	5/8" x 7"	5"	25	75
7638SD6-PWR	7638SD6USA-PWR	5/8" x 8-1/2"	6-1/2"	25	50
7640SD6-PWR*	7640SD6USA-PWR*	3/4" x 4-1/4"	1-7/8"	20	60
7641SD6-PWR*	7641SD6USA-PWR*	3/4" x 4-3/4"	2-3/8"	20	60
7642SD6-PWR	7642SD6USA-PWR	3/4" x 5-1/2"	3-1/8"	20	60
7644SD6-PWR	7644SD6USA-PWR	3/4" x 6-1/4"	3-7/8"	20	60
7646SD6-PWR	7646SD6USA-PWR	3/4" x 7"	4-5/8"	20	60
7648SD6-PWR	7648SD6USA-PWR	3/4" x 8-1/2"	6-1/8"	10	40
7649SD6-PWR	—	3/4" x 10"	7-5/8"	10	40



DCH416X2
60V MAX* 1-1/4 in.
Brushless Cordless SDS PLUS
Rotary Hammer Kit

WEDGE EXPANSION ANCHORS

Power-Stud®+ HD5

Description



The Power-Stud® HD5 anchor is a fully threaded, torque-controlled, hot-dipped galvanized wedge expansion anchor designed for use in concrete and grouted concrete masonry.

Base Materials

Normal-weight concrete,
Grouted concrete masonry (CMU)

Anchor Material

Hot-dip galvanized carbon steel body nut and washer
Type 304 stainless steel expansion clip

Zinc galvanized according to ASTM A 153 Class C or D



HOT-DIP GALVANIZED POWER-STUD

CAT #	SIZE	THREAD LENGTH	PACK	CTN
7713HD5-PWR	3/8" x 3"	1-1/2"	50	300
7715HD5-PWR	3/8" x 3-3/4"	2-3/8"	50	300
7716HD5-PWR	3/8" x 5"	3-1/2"	50	300
7717HD5-PWR	3/8" x 7"	5-1/2"	50	200
7720HD5-PWR	1/2" x 2-3/4"	1"	50	200
7722HD5-PWR	1/2" x 3-3/4"	2"	50	200
7723HD5-PWR	1/2" x 4-1/2"	2-3/4"	50	200
7724HD5-PWR	1/2" x 5-1/2"	3-3/4"	50	150
7726HD5-PWR	1/2" x 7"	5-1/4"	25	100
7730HD5-PWR	5/8" x 3-1/2"	1-1/2"	25	100
7733HD5-PWR	5/8" x 5"	3"	25	100
7734HD5-PWR	5/8" x 6"	4"	25	75
7738HD5-PWR	5/8" x 8-1/2"	6-1/2"	25	50
7741HD5-PWR	3/4" x 4-3/4"	2-1/4"	20	60
7742HD5-PWR	3/4" x 5-1/2"	3"	20	60
7746HD5-PWR	3/4" x 7"	4-1/2"	20	60
7748HD5-PWR	3/4" x 8-1/2"	6"	10	40

DEWALT

PERFORM PROTECT

DEWALT'S PERFORM & PROTECT™ line of tools is designed to provide a high level of one or more of the following: control dust containment or low vibration without sacrificing performance.

YOUR FIRST LINE OF DEFENSE.

DUST

CONTROL

VIBRATION

DEWALT.com/PERFORMANDPROTECT

WEDGE EXPANSION ANCHORS

Power-Stud® - 304 Stainless

Description



The Power-Stud® anchor is a fully threaded, torque-controlled, 304 stainless steel wedge expansion anchor designed for use in concrete and grouted concrete masonry.

Approvals



Full UL listings in product brochure or at www.DEWALT.com

If your job site requires ICC-ESR compliance reference page 14 and 15 for Power-Stud+ SD4/SD6 anchor options.

Base Materials

Normal-weight concrete, Lightweight concrete, Grouted concrete masonry (CMU)

Anchor Material

304 stainless steel body with 300 series expansion clip hex nut and washer

The published length is the overall length of the anchor. Allow for fixture thickness plus one anchor diameter for the nut and washer thickness when selecting a length.



TYPE 304 STAINLESS STEEL POWER-STUD

CAT #	SIZE	THREAD LENGTH	PACK	CTN
07300-PWR	1/4" x 1-3/4"	3/4"	100	500
07302-PWR	1/4" x 2-1/4"	1-1/4"	100	500
07304-PWR	1/4" x 3-1/4"	2-1/4"	100	500
07310-PWR	3/8" x 2-1/4"	1-1/4"	50	250
07312-PWR	3/8" x 2-3/4"	1-5/8"	50	250
07313-PWR	3/8" x 3"	1-7/8"	50	250
07314-PWR	3/8" x 3-1/2"	2-3/8"	50	250
07315-PWR	3/8" x 3-3/4"	2-5/8"	50	250
07316-PWR	3/8" x 5"	3-1/8"	50	250
07320-PWR	1/2" x 2-3/4"	1-3/8"	50	200
07322-PWR	1/2" x 3-3/4"	2-3/8"	50	200
07323-PWR	1/2" x 4-1/2"	3-1/8"	50	200
07324-PWR	1/2" x 5-1/2"	4-1/8"	50	150
07326-PWR	1/2" x 7"	5-5/8"	25	100
07330-PWR	5/8" x 3-1/2"	2"	25	100
07332-PWR	5/8" x 4-1/2"	3"	25	100
07333-PWR	5/8" x 5"	3-1/2"	25	100
07334-PWR	5/8" x 6"	4-1/2"	25	75
07336-PWR	5/8" x 7"	5-1/2"	25	75
07338-PWR	5/8" x 8-1/2"	7"	25	75
07340-PWR	3/4" x 4-1/4"	2-3/8"	20	60
07341-PWR	3/4" x 4-3/4"	2-7/8"	20	60
07342-PWR	3/4" x 5-1/2"	3-5/8"	20	60
07344-PWR	3/4" x 6-1/4"	4-3/8"	20	60
07346-PWR	3/4" x 7"	5-1/8"	20	60
07348-PWR	3/4" x 8-1/2"	6-5/8"	10	40
07349-PWR	3/4" x 10"	8-1/8"	10	30
07352-PWR	7/8" x 8"	4-3/4"	10	40
07361-PWR	1" x 6"	2-3/8"	10	30
07363-PWR	1" x 9"	5-3/8"	10	30
07365-PWR	1" x 12"	8-3/8"	5	15



WEDGE EXPANSION ANCHORS

Power-Stud® - 316 Stainless

Description



The Power-Stud® anchor is a fully threaded, torque-controlled, 316 Stainless Steel wedge expansion anchor designed for use in concrete and grouted concrete masonry.

Approvals



Full UL listings in product brochure or at www.DEWALT.com

If your job site requires ICC-ESR compliance reference page 14 and 15 for Power-Stud+ SD4/SD6 anchor options.

Base Materials

Normal-weight concrete, Lightweight concrete, Grouted concrete masonry (CMU)

Anchor Material

316 stainless steel body expansion clip hex nut and washer

The published length is the overall length of the anchor. Allow for fixture thickness plus one anchor diameter for the nut and washer thickness when selecting a length.



TYPE 316 STAINLESS STEEL POWER-STUD

CAT #	SIZE	THREAD LENGTH	PACK	CTN
07600-PWR	1/4" x 1-3/4"	3/4"	100	500
07602-PWR	1/4" x 2-1/4"	1-1/4"	100	500
07604-PWR	1/4" x 3-1/4"	2-1/4"	100	500
07610-PWR	3/8" x 2-1/4"	1-1/4"	50	250
07612-PWR	3/8" x 2-3/4"	1-5/8"	50	250
07613-PWR	3/8" x 3"	1-7/8"	50	250
07614-PWR	3/8" x 3-1/2"	2-3/8"	50	250
07615-PWR	3/8" x 3-3/4"	2-5/8"	50	250
07616-PWR	3/8" x 5"	3-1/8"	50	250
07620-PWR	1/2" x 2-3/4"	1-3/8"	50	200
07622-PWR	1/2" x 3-3/4"	2-3/8"	50	200
07623-PWR	1/2" x 4-1/2"	3-1/8"	50	200
07624-PWR	1/2" x 5-1/2"	4-1/8"	50	150
07626-PWR	1/2" x 7"	5-5/8"	25	100
07630-PWR	5/8" x 3-1/2"	2"	25	100
07332-PWR	5/8" x 4-1/2"	3"	25	100
07633-PWR	5/8" x 5"	3-1/2"	25	100
07634-PWR	5/8" x 6"	4-1/2"	25	75
07636-PWR	5/8" x 7"	5-1/2"	25	75
07638-PWR	5/8" x 8-1/2"	7"	25	75
07641-PWR	3/4" x 4-3/4"	2-7/8"	20	60
07642-PWR	3/4" x 5-1/2"	3-5/8"	20	60
07644-PWR	3/4" x 6-1/4"	4-3/8"	20	60
07646-PWR	3/4" x 7"	5-1/8"	20	60
07648-PWR	3/4" x 8-1/2"	6-5/8"	10	40



HEAVY DUTY UNDERCUT ANCHORS



CCU+™ CRITICAL CONNECTION UNDERCUT

When critical mechanical anchor connections are required consider the DEWALT® Critical Connection Undercut Anchor (CCU+™). The CCU+™ anchor range combined with Hollow Stop Bits, Hollow Undercutting Bits, 60V MAX* rotary hammers and dust extractors, meet OSHA Table 1 compliance in a fully cordless system. Available in 3 steel grades and Made in the USA** for Buy America Act construction projects.

*System is compliant to the Exposure Control Methods described in Table 1 of 29 CFR 1926.1153 when outlined components are operating and maintained in accordance to manufacturer's instructions.

**CCU+ Anchors are 100% domestically produced and qualify under FHWA as Made In the USA.



UNDERCUT ANCHORS

CCU+™

Description



The CCU+™ is a post-installed bottom-bearing structural anchor designed for static, dynamic and seismic loading in the tension zone of both cracked and uncracked concrete. The CCU+™ keys into the base material with minimal expansive forces allowing for close edge distance and anchor spacing, similar to a cast-in-place headed stud.

Approvals



ICC-ES ESR-4810
(Concrete)

IBC & IRC 2021, 2018
2015, 2012

Recognition in cracked
& uncracked concrete
including seismic and
wind loading
(Category 1 Anchors)

Base Materials

Normal-weight concrete,
Lightweight concrete

Anchor Material

Zinc plated A36 carbon
steel zinc plated high
strength A193 Grade B7
steel type 316 stainless
steel



A36 CARBON STEEL, B7 CARBON STEEL, 316 STAINLESS EXTERNALLY THREADED CLASS 2

A36 CARBON STEEL CAT #	B7 CARBON STEEL CAT #	316 STAINLESS STEEL CAT #	ANCHOR TYPE	SIZE	DRILL HOLE DIA.	PACK
DFM1311050	DFM1371050	DFM1361050	PS	3/8" x 6"	11/16"	20
DFM1311550	DFM1371550	DFM1361550	TB	3/8" x 6"	11/16"	20
DFM1311100	DFM1371100	DFM1361100	PS	1/2" x 7-1/2"	13/16"	12
DFM1311600	DFM1371600	DFM1361600	TB	1/2" x 7-1/2"	13/16"	12
DFM1311150	DFM1371150	DFM1361150	PS	1/2" x 8-1/4"	13/16"	12
DFM1311650	DFM1371650	DFM1361650	TB	1/2" x 8-1/4"	13/16"	12
DFM1311200	DFM1371200	DFM1361200	PS	5/8" x 10-3/4"	1"	10
DFM1311700	DFM1371700	DFM1361700	PS	5/8" x 10-3/4"	1"	10
DFM1311250	DFM1371250	DFM1361250	TB	5/8" x 11-1/2"	1"	10
DFM1311750	DFM1371750	DFM1361750	TB	5/8" x 11-1/2"	1"	10
DFM1311300	DFM1371300	DFM1361300	PS	3/4" x 14"	1-1/4"	6
DFM1311800	DFM1371800	DFM1361800	TB	3/4" x 14"	1-1/4"	6
DFM1311350	DFM1371350	DFM1361350	PS	3/4" x 16"	1-1/4"	6
DFM1311850	DFM1371850	DFM1361850	TB	3/4" x 16"	1-1/4"	6

PS = Preset Version TB = Thrubolt Version

*For rotary hammer drill connector options designated drill bits can be considered for use with a DW5891 SDS-Max to SDS-Plus adapter (e.g. HUCB and UCB for 5/8-inch nominal anchor size).

CCU+ anchors are 100% domestically produced and qualify under FHWA as Made In the USA.



UNDERCUT ANCHORS

CCU+™ Accessories

Description



CCU+™ Accessories are tools used to properly install and set CCU+™ anchors.



SETTING SLEEVES (MANUAL)

CAT #	FITS ANCHOR SIZE	USABLE LENGTH	PACK
DFX313805	3/8"	5"	1
DFX311210	1/2"	5"	1
DFX315815	5/8"	5-1/4"	1
DFX313420	3/4"	7"	1



SETTING SLEEVES (POWERED)

CAT #	FITS ANCHOR SIZE	USABLE LENGTH	SHANK TYPE	PACK
DFX313825	3/8"	2-3/4"	SDS-PLUS	1
DFX311230	1/2"	3-3/4"	SDS-PLUS	1
DFX315835	5/8"	4-3/4"	SDS-MAX	1
DFX313440	3/4"	6-1/2"	SDS-MAX	1



HOLLOW STOP BITS (HSB)


CAT #	FITS ANCHOR SIZE	DRILL DEPTH	SHANK TYPE	PACK
DFX11380	11/16"	4-1/4"	SDS-PLUS	1
DFX11120	13/16"	5-3/8"	SDS-PLUS	1
DFX11580	1"	8"	SDS-MAX	1
DFX11340	1-1/4"	10-5/8"	SDS-MAX	1

*For rotary hammer drill connector options designated drill bits can be considered for use with a DW5891 SDS-Max to SDS-Plus adapter (e.g. HUCB and UCB for 5/8-inch nominal anchor size).

UNDERCUT ANCHORS

CCU+™ Accessories

Description



CCU+™ Accessories are tools used to properly install and set CCU+™ anchors.



UNDERCUT BITS (UCB)

CAT #	NOMINAL DRILL BIT DIAMETER	MAX HOLE DEPTH	SHANK TYPE	PACK
DFX21381	11/16"	6"	SDS-PLUS	1
DFX21121	13/16"	8"	SDS-PLUS	1
DFX21581*	1"	11"	SDS-PLUS	1
DFX21341	1-1/4"	15-1/4"	SDS-MAX	1



HOLLOW UNDERCUT BITS (HUCB)

CAT #	NOMINAL DRILL BIT DIAMETER	MAX HOLE DEPTH	SHANK TYPE	PACK
DFX21380	11/16"	6"	SDS-PLUS	1
DFX21120	13/16"	8"	SDS-PLUS	1
DFX21580*	1"	11"	SDS-PLUS	1
DFX21340	1-1/4"	15-1/4"	SDS-MAX	1



REPLACEMENT BOW JAWS FOR UNDERCUT BITS

CAT #	NOMINAL STOP BIT DIAMETER	COMPATIBLE WITH		PACK
		HUCB	UCB	
DFX213807	11/16"	DFX21380	—	1
DFX213805	11/16"	—	DFX21381	1
DFX211212	13/16"	DFX21120	—	1
DFX211210	13/16"	—	DFX21121	1
DFX215817	1"	DFX21580	—	1
DFX215815	1"	—	DFX21581	1
DFX213422	1-1/4"	DFX21340	—	1
DFX213420	1-1/4"	—	DFX21341	1

*For rotary hammer drill connector options designated drill bits can be considered for use with a DW5891 SDS-Max to SDS-Plus adapter (e.g. HUCB and UCB for 5/8-inch nominal anchor size).

SLEEVE ANCHORS

Power-Bolt® +

Description



The Power-Bolt+ is a torque controlled heavy duty sleeve style anchor designed for consistent performance in cracked and uncracked concrete.

Approvals



ICC-ES ESR-3260 (Concrete); 1/2", 5/8" & 3/4" IBC & IRC 2021, 2018 2015, 2012

Recognition in cracked & uncracked concrete including seismic and wind loading (Category 1 Anchors)

Base Materials

Normal-weight concrete, Lightweight concrete

Anchor Material

Carbon steel Grade 8 bolt (equivalent)

*Less than the minimum standard anchor length for strength design or not included in ESR-3260. The published size includes the diameter and the length which is measured from below the washer to the end of the anchor. Allow for fixture thickness when selecting a length.



CARBON STEEL HEX HEAD POWER-BOLT+

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
6902SD-PWR	1/4" x 1-3/4"	1/4"	100	600
6906SD-PWR	1/4" x 3"	1/4"	100	600
6911SD-PWR	3/8" x 1-7/8"	3/8"	50	300
6910SD-PWR	3/8" x 2-1/4"	3/8"	50	300
6913SD-PWR	3/8" x 3"	3/8"	50	300
6914SD-PWR	3/8" x 3-1/2"	3/8"	50	300
6916SD-PWR	3/8" x 4"	3/8"	50	300
6930SD-PWR*	1/2" x 2-3/4"	1/2"	50	200
6932SD-PWR	1/2" x 3-1/2"	1/2"	50	200
6934SD-PWR	1/2" x 4-3/4"	1/2"	25	150
6936SD-PWR	1/2" x 5-3/4"	1/2"	25	150
6940SD-PWR*	5/8" x 3"	5/8"	20	120
6942SD-PWR	5/8" x 4"	5/8"	15	90
6944SD-PWR	5/8" x 5"	5/8"	15	90
6945SD-PWR	5/8" x 6"	5/8"	15	60
6947SD-PWR	5/8" x 8-1/2"	5/8"	10	40

CARBON STEEL HEX HEAD POWER-BOLT+

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
6950SD-PWR	3/4" x 3-1/4"	1/4"	15	90
6952SD-PWR	3/4" x 4-1/2"	3/4"	10	60
6954SD-PWR	3/4" x 5-1/4"	3/4"	10	50
6956SD-PWR	3/4" x 7-1/4"	3/4"	10	40
6957SD-PWR	3/4" x 8-1/4"	3/4"	10	40

DCH614X2
60V MAX* 1-3/4 In.
Brushless Cordless SDS MAX
Rotary Hammer Kit



SLEEVE ANCHORS

Lok-Bolt AS®

Description



The Lok-Bolt AS® is a sleeve anchor designed for use in concrete or masonry base materials. They are available in multiple head styles for numerous applications.

Base Materials

Normal-weight concrete, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Brick masonry, Stone

Anchor Material

Carbon steel and stainless steel

Hex Nut Lok-Bolt: Published length measured from below the washer to the end of the anchor.

Acorn Nut Lok-Bolt: The published length is measured from below the washer to the end of the anchor.



HEX NUT LOK-BOLT AS CARBON STEEL

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
05005S-PWR	5/16" x 1-1/2"	5/16"	100	600
05010S-PWR	5/16" x 2-3/8"	5/16"	100	500
05015S-PWR	3/8" x 1-7/8"	3/8"	50	300
05020S-PWR	3/8" x 3"	3/8"	50	250
05022S-PWR	3/8" x 4"	3/8"	50	250
05025S-PWR	1/2" x 2-1/2"	1/2"	25	150
05030S-PWR	1/2" x 3"	1/2"	25	150
05034S-PWR	1/2" x 3-3/4"	1/2"	25	150
05033S-PWR	1/2" x 5-1/4"	1/2"	25	125
05032S-PWR	1/2" x 6"	1/2"	10	50
05035S-PWR	5/8" x 2-1/2"	5/8"	25	125
05038S-PWR	5/8" x 3"	5/8"	25	100
05040S-PWR	5/8" x 4-1/4"	5/8"	10	60
05045S-PWR	5/8" x 5-3/4"	5/8"	10	50
05050S-PWR	3/4" x 2-3/4"	3/4"	10	60
05055S-PWR	3/4" x 4-1/4"	3/4"	10	40
05060S-PWR	3/4" x 6-1/4"	3/4"	10	30

HEX NUT LOK-BOLT AS 304 STAINLESS STEEL

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
06152S-PWR	3/8" x 1-7/8"	3/8"	50	300
06153S-PWR	3/8" x 3"	3/8"	50	250
06157S-PWR	1/2" x 3"	1/2"	25	150
06160S-PWR	1/2" x 3-3/4"	1/2"	25	150
06164S-PWR	5/8" x 4-1/4"	5/8"	10	60
06168S-PWR	3/4" x 4-1/4"	3/4"	10	40



ACORN NUT LOK-BOLT AS CARBON STEEL

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
05125S-PWR	1/4" x 5/8"	1/4"	100	1000
05150S-PWR	1/4" x 1-3/8"	1/4"	100	600
05175S-PWR	1/4" x 2-1/4"	1/4"	100	600

ACORN NUT LOK-BOLT AS 304 STAINLESS STEEL

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
06150S-PWR	1/4" x 1-3/8"	1/4"	100	600

The published length is measured from below the washer to the end of the anchor.



ROUND HEAD LOK-BOLT AS CARBON STEEL

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
05205S-PWR	1/4" x 1-3/8"	1/4"	100	1000
05215S-PWR	1/4" x 3"	1/4"	100	600
05240S-PWR	3/8" x 3-3/4"	3/8"	50	250

ROUND HEAD LOK-BOLT AS 304 STAINLESS STEEL

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
06180S-PWR	1/4" x 2-1/4"	1/4"	100	600

SLEEVE ANCHORS

Lok-Bolt AS®

Description



The Lok-Bolt AS® is a sleeve anchor designed for use in concrete or masonry base materials. They are available in multiple head styles for numerous applications.

Base Materials

Normal-weight concrete, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Brick masonry, Stone

Anchor Material

Carbon steel and stainless steel

Combo and Threshold Flat Head Lok-Bolt: These parts do not have a compression ring.



COMBO FLAT HEAD LOK-BOLT AS CARBON STEEL

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
05310S-PWR	1/4" x 2-1/4"	1/4"	100	600
05315S-PWR	1/4" x 3"	1/4"	100	600
05320S-PWR	1/4" x 4"	1/4"	100	600
05325S-PWR	1/4" x 5-1/4"	1/4"	100	600
05330S-PWR	5/16" x 2-1/4"	5/16"	100	600
05340S-PWR	3/8" x 2-3/4"	3/8"	50	300
05345S-PWR	3/8" x 4"	3/8"	50	250
05350S-PWR	3/8" x 5"	3/8"	50	250
05360S-PWR	3/8" x 6"	3/8"	50	250

COMBO FLAT HEAD LOK-BOLT AS 304 STAINLESS STEEL

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
06170S-PWR	1/4" x 2-1/4"	1/4"	100	600
06172S-PWR	1/4" x 3"	1/4"	100	600
06174S-PWR	3/8" x 4"	3/8"	50	250
06175S-PWR	3/8" x 5"	3/8"	50	250
06176S-PWR	3/8" x 6"	3/8"	50	250



THRESHOLD FLAT HEAD LOK-BOLT AS

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
05500S-PWR	1/4" x 2"	1/4"	100	600



ROD HANGER LOK-BOLT AS CARBON STEEL

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
05810S-PWR	1/4" x 1-1/2"	5/16"	50	300
05815S-PWR	3/8" x 1-7/8"	3/8"	50	300
05825S-PWR	1/2" x 2-1/4"	1/2"	25	150



TIE-WIRE LOK-BOLT AS

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
05700S-PWR	5/16" x 1-1/2"	5/16"	100	600



LOK-BOLT AS EXTENDERS CARBON STEEL

CAT #	SIZE	PACK	CTN
05684-PWR	3/8" x 1-1/4"	50	500

SLEEVE ANCHORS

Power-Bolt®

Description

The Power-Bolt® is a heavy duty sleeve style, self-locking anchor which is vibration resistant and removable. It is available with a finished hex head or flat head with a hex key insert and can be considered for use in concrete, block, brick, or stone.

Approvals



Full UL listings in product brochure or at www.DEWALT.com

Base Materials

Normal-weight concrete, Lightweight concrete, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Brick masonry, Stone

Anchor Material

Type 304 stainless steel & carbon steel (flat head)

Published length is measured from under the washer to the end of the anchor.



304 STAINLESS STEEL HEX HEAD POWER-BOLT

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
05902-PWR	1/4" x 1-3/4"	1/4"	100	600
05906-PWR	1/4" x 3"	1/4"	100	600
05910-PWR	3/8" x 2-1/4"	3/8"	50	300
05914-PWR	3/8" x 3-1/2"	3/8"	50	300
05916-PWR	3/8" x 4"	3/8"	50	300
05930-PWR	1/2" x 2-3/4"	1/2"	50	200
05934-PWR	1/2" x 4-3/4"	1/2"	25	150



CARBON STEEL FLAT HEAD POWER-BOLT

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
06981-PWR	3/8" x 3-3/4"	3/8"	50	300
06982-PWR	3/8" x 5"	3/8"	50	250

CARBON STEEL FLAT HEAD POWER-BOLT

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
06983-PWR	3/8" x 6"	3/8"	50	250
06984-PWR	1/2" x 5"	1/2"	25	125
06987-PWR	5/8" x 5-1/2"	5/8"	15	90



DCH263R2
20V MAX 1-1/8 in.
Brushless Cordless SDS PLUS
D-Handle Rotary Hammer Kit

DUST X+™
ANCHOR INSTALLATION SYSTEM



EXTRACTOR



+



ROTARY HAMMER

+



HOLLOW BIT

+



ANCHORS



**DESIGNED TO FAST-TRACK
ANCHOR INSTALLATION AND
REDUCE DUST EXPOSURE.**

Using the DeWALT Hollow Bit™ and dust extractor with SDS rotary hammers creates an OSHA-compliant (1926.1153) solution for dust control. The Hollow Bit™ simultaneously extracts dust to clean holes while drilling. For agility on the job site go cordless with DeWALT's offering of battery-powered hammer drills dust extractors and Portable Power Stations.™



DUST EXTRACTORS



**DWV010 8 Gallon
HEPA/RRP Dust
Extractor**



**DWV015 10 Gallon
Wet/Dry HEPA/RRP
Dust Extractor**



**DCV585
60V MAX* Dust
Extractor**

SDS MAX ROTARY HAMMERS



**DCH416 60V MAX*
Brushless 1-1/4" SDS PLUS Rotary
Hammer**



**DCH614 60V MAX*
Brushless 1-3/4" SDS
MAX Combination Rotary
Hammer**

With respect to 60V MAX Maximum initial battery voltage (measured without a workload) is 60 volts. Nominal voltage is 54.

SCREW ANCHORS

Screw-Bolt™ +

Description



The Screw-Bolt™+ anchor is a one piece, heavy duty screw anchor. It is simple to install, easy to identify, and fully removable. Anchor diameter equals drill bit diameter using standard ANSI drill bits.

Approvals



ICC-ES ESR-3889
(Concrete) ESR-4042
(Masonry)



IBC & IRC 2021, 2018,
2015, 2012



Recognition in cracked
& uncracked concrete
including seismic and
wind loading
(Category 1 Anchors)

Base Materials

Normal-weight concrete,
Lightweight concrete,
Concrete over steel deck,
Grouted concrete masonry
(CMU), Brick masonry

Anchor Material

Carbon steel



CARBON STEEL HEX HEAD

CAT #	SIZE	SOCKET SIZE	PACK	CTN
PFM1411000	1/4" x 1-1/4"	7/16"	100	600
PFM1411020	1/4" x 1-3/4"	7/16"	100	600
PFM1411060	1/4" x 2-1/4"	7/16"	100	600
PFM1411080	1/4" x 2-5/8"	7/16"	100	500
PFM1411100	1/4" x 3"	7/16"	100	500
PFM1411160	3/8" x 1-3/4"	9/16"	50	300
PFM1411220	3/8" x 2-1/2"	9/16"	50	300
PFM1411240	3/8" x 3"	9/16"	50	250
PFM1411280	3/8" x 4"	9/16"	50	250
PFM1411300	3/8" x 5"	9/16"	50	250
PFM1411320	3/8" x 6"	9/16"	50	150
PFM1411340	1/2" x 2"	3/4"	50	200
PFM1411360	1/2" x 2-1/2"	3/4"	50	200
PFM1411380	1/2" x 3"	3/4"	50	150
PFM1411420	1/2" x 4"	3/4"	50	150
PFM1411460	1/2" x 5"	3/4"	25	100
PFM1411480	1/2" x 6"	3/4"	25	75
PFM1411520	1/2" x 8"	3/4"	25	100
PFM1411540	5/8" x 3"	15/16"	25	100
PFM1411580	5/8" x 4"	15/16"	25	100
PFM1411600	5/8" x 5"	15/16"	25	75
PFM1411640	5/8" x 6"	15/16"	25	75
PFM1411680	5/8" x 8"	15/16"	25	50
PFM1411700	3/4" x 3"	1-1/8"	20	60
PFM1411720	3/4" x 4"	1-1/8"	20	60
PFM1411760	3/4" x 5"	1-1/8"	20	60
PFM1411800	3/4" x 6"	1-1/8"	20	60
PFM1411840	3/4" x 8"	1-1/8"	10	40
PFM1411880	3/4" x 10"	1-1/8"	10	20



SCREW ANCHORS

Screw-Bolt™+

Description



The Screw-Bolt™+ anchor is a one piece, heavy duty screw anchor. It is simple to install, easy to identify, and fully removable. Anchor diameter equals drill bit diameter using standard ANSI drill bits.

Approvals



ICC-ES ESR-3889
(Concrete) ESR-4042
(Masonry)

IBC & IRC 2021, 2018,
2015, 2012

Recognition in cracked
& uncracked concrete
including seismic and
wind loading
(Category 1 Anchors)

Base Materials

Normal-weight concrete,
Lightweight concrete,
Concrete over steel deck,
Grouted concrete masonry
(CMU), Brick masonry

Anchor Material

Carbon steel



CARBON STEEL FLAT HEAD

CAT #	SIZE	DRIVER BIT	BIT SIZE	PACK	CTN
PFM1411105	1/4" x 3"	DWATX30IR2-Z	T30	100	500
PFM1411225	3/8" x 2-1/2"	PFM1411SKT50	T50	50	300
PFM1411245	3/8" x 3"	PFM1411SKT50	T50	50	250
PFM1411285	3/8" x 4"	PFM1411SKT50	T50	50	250
PFM1411385	1/2" x 3"	PFM1411SKT55	T55	50	150
PFM1411425	1/2" x 4"	PFM1411SKT55	T55	50	150
PFM1411465	1/2" x 5"	PFM1411SKT55	T55	25	100



CARBON STEEL HEX HEAD MECHANICALLY GALVANIZED

CAT #	SIZE	SOCKET SIZE	PACK	CTN
PFM1461240	3/8" x 3"	9/16"	50	250
PFM1461280	3/8" x 4"	9/16"	50	250
PFM1461300	3/8" x 5"	9/16"	50	250
PFM1461320	3/8" x 6"	9/16"	50	150
PFM1461420	1/2" x 4"	3/4"	50	150
PFM1461460	1/2" x 5"	3/4"	25	100
PFM1461480	1/2" x 6"	3/4"	25	75
PFM1461520	1/2" x 8"	3/4"	25	100
PFM1461600	5/8" x 5"	15/16"	25	75
PFM1461640	5/8" x 6"	15/16"	25	75
PFM1461680	5/8" x 8"	15/16"	25	50
PFM1461800	3/4" x 6"	1-1/8"	20	60
PFM1461850	3/4" x 8"	1-1/8"	10	40



SCREW ANCHORS

316 Stainless Steel Wedge-Bolt™

Description

The 316 Stainless Steel Wedge-Bolt™ is a one piece, heavy duty screw anchor designed for use in concrete and CMU where a higher level of corrosion resistance is desired.



Approvals

Tested in accordance with ASTM E488 AC106 criteria and AC193 criteria

Base Materials

Normal-weight concrete, Lightweight concrete, Grouted concrete masonry (CMU), Brick masonry

Anchor Material

316 Stainless steel

			
316 STAINLESS STEEL FINISHED HEX WASHER HEAD			
CAT #	ANCHOR SIZE	PACK	CTN
07870-PWR	1/4" x 2"	100	600
07872-PWR	1/4" x 3"	100	500
07876-PWR	1/4" x 4"	100	500
07878-PWR	1/4" x 5"	100	500
07880-PWR	3/8" x 2-1/2"	50	300
07882-PWR	3/8" x 3"	50	250
07884-PWR	3/8" x 4"	50	250
07886-PWR	3/8" x 5"	50	250
07888-PWR	1/2" x 3"	50	150
07890-PWR	1/2" x 4"	50	150
07892-PWR	1/2" x 5"	25	100
07894-PWR	1/2" x 6"	25	75

CAT #	ANCHOR SIZE	SUGGESTED WEDGE-BIT		
		SDS-PLUS	SDS-MAX	STRAIGHT SHANK
07870-PWR	1/4" x 2"	01312-PWR	—	01370-PWR
07872-PWR	1/4" x 3"	01314-PWR	—	01372-PWR
07876-PWR	1/4" x 4"	01314-PWR	—	01372-PWR
07878-PWR	1/4" x 5"	01315-PWR	—	—
07880-PWR	3/8" x 2-1/2"	01316-PWR	—	01380-PWR
07882-PWR	3/8" x 3"	01316-PWR	—	01380-PWR
07884-PWR	3/8" x 4"	01316-PWR	—	01380-PWR
07886-PWR	3/8" x 5"	01318-PWR	01354-PWR	—
07888-PWR	1/2" x 3"	01320-PWR	01354-PWR	01390-PWR
07890-PWR	1/2" x 4"	01320-PWR	01354-PWR	01390-PWR
07892-PWR	1/2" x 5"	01322-PWR	01354-PWR	01394-PWR
07894-PWR	1/2" x 6"	01322-PWR	01354-PWR	01394-PWR



SCREW ANCHORS

UltraCon+®

Description



The UltraCon+® is a complete family of screw anchors for light to medium duty applications in concrete, masonry block, brick, and wood base materials.

Approvals



ICC-ES ESR-3068
(Concrete)

ICC-ES ESR-3196
(Masonry-CMU)

ICC-ES ESR-3042
(Wood-to-Wood)

ICC-ES ESR-3213
(Chemically Treated Lumber)

Miami-Dade NOA
Florida Building Code

Base Materials

Normal-weight concrete, Lightweight concrete, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Solid brick masonry, Wood

Anchor Material

Carbon Steel

*Sizes which are less than the minimum standard anchor length for strength design.



CARBON STEEL FINISHED BLUE HEX WASHER HEAD

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM12700*	3/16" x 1-1/4"	5/32"	100
DFM12700B	3/16" x 1-1/4"	5/32"	5,000
DFM12702*	3/16" x 1-3/4"	5/32"	100
DFM12702B*	3/16" x 1-3/4"	5/32"	3,000
DFM12704	3/16" x 2-1/4"	5/32"	100
DFM12704B	3/16" x 2-1/4"	5/32"	2,000
DFM12706	3/16" x 2-3/4"	5/32"	100
DFM12706B	3/16" x 2-3/4"	5/32"	1,500
DFM12708	3/16" x 3-1/4"	5/32"	100
DFM12708B	3/16" x 3-1/4"	5/32"	1,000
DFM12710	3/16" x 3-3/4"	5/32"	100
DFM12710B	3/16" x 3-3/4"	5/32"	1,000
DFM12712	3/16" x 4"	5/32"	100
DFM12712B	3/16" x 4"	5/32"	1,000
DFM12715*	1/4" x 1"	3/16"	100
DFM12720*	1/4" x 1-1/4"	3/16"	100
DFM12720B*	1/4" x 1-1/4"	3/16"	2,000
DFM12722*	1/4" x 1-3/4"	3/16"	100
DFM12722B*	1/4" x 1-3/4"	3/16"	2,000
DFM12724	1/4" x 2-1/4"	3/16"	100
DFM12724B	1/4" x 2-1/4"	3/16"	1,500
DFM12726	1/4" x 2-3/4"	3/16"	100
DFM12726B	1/4" x 2-3/4"	3/16"	1,000
DFM12728	1/4" x 3-1/4"	3/16"	100
DFM12728B	1/4" x 3-1/4"	3/16"	1,000
DFM12730	1/4" x 3-3/4"	3/16"	100
DFM12730B	1/4" x 3-3/4"	3/16"	500
DFM12732	1/4" x 4"	3/16"	100
DFM12732B	1/4" x 4"	3/16"	500
DFM12734	1/4" x 5"	3/16"	100
DFM12734B	1/4" x 5"	3/16"	500

SCREW ANCHORS

UltraCon+®

Description



The UltraCon+® is a complete family of screw anchors for light to medium duty applications in concrete, masonry block, brick, and wood base materials.

Approvals



ICC-ES ESR-3068
(Concrete)

ICC-ES ESR-3196
(Masonry-CMU)

ICC-ES ESR-3042
(Wood-to-Wood)

ICC-ES ESR-3213
(Chemically Treated Lumber)

Miami-Dade NOA

Florida Building Code

Base Materials

Normal-weight concrete, Lightweight concrete, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Solid brick masonry, Wood

Anchor Material

Carbon Steel

*Sizes which are less than the minimum standard anchor length for strength design.



CARBON STEEL FINISHED BLUE T25 STAR DRIVE FLAT HEAD

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM12740S	3/16" x 1-1/4"	5/32"	100
DFM12740SB	3/16" x 1-1/4"	5/32"	5,000
DFM12742S	3/16" x 1-3/4"	5/32"	100
DFM12742SB	3/16" x 1-3/4"	5/32"	3,000
DFM12744S	3/16" x 2-1/4"	5/32"	100
DFM12744SB	3/16" x 2-1/4"	5/32"	2,500
DFM12746S	3/16" x 2-3/4"	5/32"	100
DFM12746SB	3/16" x 2-3/4"	5/32"	1,500
DFM12748S	3/16" x 3-1/4"	5/32"	100
DFM12748SB	3/16" x 3-1/4"	5/32"	1,000
DFM12750S	3/16" x 3-3/4"	5/32"	100
DFM12750SB	3/16" x 3-3/4"	5/32"	1,000
DFM12752S	3/16" x 4"	5/32"	100
DFM12752SB	3/16" x 4"	5/32"	1,000
DFM12760S	1/4" x 1-1/4"	3/16"	100
DFM12760SB	1/4" x 1-1/4"	3/16"	2,500
DFM12762S	1/4" x 1-3/4"	3/16"	100
DFM12762SB	1/4" x 1-3/4"	3/16"	2,500
DFM12764S	1/4" x 2-1/4"	3/16"	100
DFM12764SB	1/4" x 2-1/4"	3/16"	1,500
DFM12766S	1/4" x 2-3/4"	3/16"	100
DFM12766SB	1/4" x 2-3/4"	3/16"	1,000
DFM12768S	1/4" x 3-1/4"	3/16"	100
DFM12768SB	1/4" x 3-1/4"	3/16"	1,000
DFM12770S	1/4" x 3-3/4"	3/16"	100
DFM12770SB	1/4" x 3-3/4"	3/16"	500
DFM12772S	1/4" x 4"	3/16"	100
DFM12772SB	1/4" x 4"	3/16"	500
DFM12774S	1/4" x 5"	3/16"	100
DFM12776S	1/4" x 6"	3/16"	100



SCREW ANCHORS

UltraCon+®

Description



The UltraCon+® is a complete family of screw anchors for light to medium duty applications in concrete, masonry block, brick, and wood base materials.

Approvals



ICC-ES ESR-3068
(Concrete)

ICC-ES ESR-3196
(Masonry-CMU)

ICC-ES ESR-3042
(Wood-to-Wood)

ICC-ES ESR-3213
(Chemically Treated Lumber)

Miami-Dade NOA
Florida Building Code


Base Materials

Normal-weight concrete, Lightweight concrete, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Solid brick masonry, Wood

Anchor Material

Carbon Steel

*Sizes which are less than the minimum standard anchor length for strength design.



CARBON STEEL FINISHED WHITE HEX WASHER HEAD

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM2ELD200*	3/16" x 1-1/4"	5/32"	5,000
DFM2ELD210*	3/16" x 1-3/4"	5/32"	3,000
DFM2ELD220	3/16" x 2-1/4"	5/32"	2,500
DFM2ELD230	3/16" x 2-3/4"	5/32"	1,500
DFM2ELD250*	1/4" x 1-1/4"	3/16"	2,500
DFM2ELD195*	1/4" x 1-3/4"	3/16"	2,000
DFM2ELD205	1/4" x 2-1/4"	3/16"	1,500
DFM2ELD215	1/4" x 2-3/4"	3/16"	1,000
DFM2ELD225	1/4" x 3-1/4"	3/16"	1,000
DFM2ELD235	1/4" x 3-3/4"	3/16"	500
DFM2ELD245	1/4" x 4"	3/16"	500
DFM2ELD255	1/4" x 5"	3/16"	500
DFM2ELD265	1/4" x 6"	3/16"	500



CARBON STEEL FINISHED WHITE T25 STAR DRIVE FLAT HEAD

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM2ELD320S	3/16" x 1-1/4"	5/32"	5,000
DFM2ELD330S	3/16" x 1-3/4"	5/32"	3,000
DFM2ELD340S	3/16" x 2-1/4"	5/32"	2,500
DFM2ELD350S	3/16" x 2-3/4"	5/32"	1,500
DFM2ELD360S	3/16" x 3-1/4"	5/32"	1,000
DFM2ELD370S	3/16" x 3-3/4"	5/32"	1,000
DFM2ELD385S	1/4" x 1-1/4"	3/16"	2,500
DFM2ELD386S	1/4" x 1-3/4"	3/16"	2,000
DFM2ELD387S	1/4" x 2-1/4"	3/16"	1,500
DFM2ELD388S	1/4" x 2-3/4"	3/16"	1,000
DFM2ELD389S	1/4" x 3-1/4"	3/16"	1,000



CARBON STEEL FINISHED WHITE HEX WASHER FLANGE HEAD

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM2ELD270*	1/4" x 1-3/4"	3/16"	2,000
DFM2ELD275*	1/4" x 1-3/4"	3/16"	1,500
DFM2ELD285	1/4" x 2-1/4"	3/16"	1,000
DFM2ELD295	1/4" x 2-3/4"	3/16"	1,000
DFM2ELD305	1/4" x 3-1/4"	3/16"	500

SCREW ANCHORS

UltraCon+®

Description



The UltraCon+® is a complete family of screw anchors for light to medium duty applications in concrete, masonry block, brick, and wood base materials.

Approvals



ICC-ES ESR-3068
(Concrete)

ICC-ES ESR-3196
(Masonry-CMU)

ICC-ES ESR-3042
(Wood-to-Wood)

ICC-ES ESR-3213
(Chemically Treated Lumber)

Miami-Dade NOA
Florida Building Code

Base Materials

Normal-weight concrete,
Lightweight concrete,
Grouted concrete masonry
(CMU), Hollow concrete
masonry (CMU), Solid brick
masonry, Wood

Anchor Material

Carbon Steel

*Sizes which are less than the
minimum standard anchor
length for strength design.



CARBON STEEL FINISHED WHITE T25 STAR DRIVE FLAT TRIM HEAD

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM2ELD400S	1/4" x 1-3/4"	3/16"	2,000
DFM2ELD410S	1/4" x 2-1/4"	3/16"	1,500
DFM2ELD420S	1/4" x 2-3/4"	3/16"	1,000
DFM2ELD430S	1/4" x 3-1/4"	3/16"	1,000
DFM2ELD440S	1/4" x 3-3/4"	3/16"	500
DFM2ELD450S	1/4" x 4"	3/16"	500



CARBON STEEL FINISHED SILVER HEX WASHER HEAD

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM2ELG340*	1/4" x 1-1/4"	3/16"	2,500
DFM2ELG341*	1/4" x 1-3/4"	3/16"	2,000
DFM2ELG371	1/4" x 2-1/4"	3/16"	1,500
DFM2ELG401	1/4" x 2-3/4"	3/16"	1,000
DFM2ELG431	1/4" x 3-1/4"	3/16"	1,000



CARBON STEEL FINISHED SILVER T25 STAR DRIVE FLAT HEAD

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM2ELG521S	3/16" x 1-1/4"	5/32"	5,000
DFM2ELG551S	3/16" x 1-3/4"	5/32"	3,000
DFM2ELG581S	3/16" x 2-1/4"	5/32"	2,500
DFM2ELG611S	3/16" x 2-3/4"	5/32"	1,500
DFM2ELG612S	3/16" x 2-3/4"	5/32"	1,500
DFM2ELG641S	3/16" x 3-3/4"	5/32"	1,000
DFM2ELG671S	3/16" x 3-3/4"	5/32"	1,000



CARBON STEEL FINISHED SILVER T25 STAR DRIVE FLAT TRIM HEAD

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM2ELG770S	1/4" x 1-1/4"	3/16"	2,500
DFM2ELG771S	1/4" x 1-3/4"	3/16"	2,000
DFM2ELG801S	1/4" x 2-1/4"	3/16"	1,500
DFM2ELG831S	1/4" x 2-3/4"	3/16"	1,000
DFM2ELG861S	1/4" x 3-1/4"	3/16"	1,000
DFM2ELG891S	1/4" x 3-3/4"	3/16"	500
DFM2ELG921S	1/4" x 4"	3/16"	500

SCREW ANCHORS

UltraCon+®

Description



The UltraCon+® is a complete family of screw anchors for light to medium duty applications in concrete, masonry block, brick, and wood base materials.

Approvals



ICC-ES ESR-3068
(Concrete)

ICC-ES ESR-3196
(Masonry-CMU)

ICC-ES ESR-3042
(Wood-to-Wood)

ICC-ES ESR-3213
(Chemically Treated Lumber)

Miami-Dade NOA
Florida Building Code

Base Materials

Normal-weight concrete, Lightweight concrete, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Solid brick masonry, Wood

Anchor Material

Carbon Steel

*Sizes which are less than the minimum standard anchor length for strength design.

ULTRACon+® INSTALLATION KIT

	CAT #	DESCRIPTION
	DW5366	5/32" and 3/16" SDS+ Drill Bits, 1/4" and 5/16" Nutsetters, T25 and T30 Star Drive Bits, Phillips Flathead Adapter, Percussion Adapter, Drive Sleeve, and 1/8" Allen Wrench



CARBON STEEL FINISHED SILVER HEX WASHER FLANGE HEAD

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM2ELC145*	1/4" x 1-3/4"	3/16"	1,500
DFM2ELG510*	1/4" x 1-3/4"	3/16"	1,500
DFM2ELC151	1/4" x 2-1/4"	3/16"	1,000
DFM2ELG512	1/4" x 2-1/4"	3/16"	1,000
DFM2ELC160	1/4" x 2-3/4"	3/16"	1,000
DFM2ELC170	1/4" x 3-1/4"	3/16"	1,000



CARBON STEEL FINISHED BRONZE HEX WASHER HEAD

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM2ELE465	1/4" x 4"	3/16"	500



CARBON STEEL FINISHED BRONZE T25 STAR DRIVE FLAT TRIM HEAD

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM2ELG832S	1/4" x 2-3/4"	3/16"	1,000
DFM2ELG862S	1/4" x 3-1/4"	3/16"	1000
DFM2ELG892S	1/4" x 3-3/4"	3/16"	500



CARBON STEEL FINISHED BRONZE T25 STAR DRIVE FLAT HEAD

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM2ELG612S	3/16" x 2-3/4"	5/32"	1,500



ULTRACon+ STRAIGHT SHANK BIT

CAT #	SIZE
DFX153255	5/32" x 5-1/2"
DFX131645	3/16" x 4-1/2"
DFX131675	3/16" x 7-1/2"



ULTRACon+ HEX SDS+ BIT

CAT #	SIZE
DW5381	5/32" x 7"
DW5382	3/16" x 7"

SCREW ANCHORS

UltraCon®

Description



The UltraCon® fastening system is a complete family of screw anchors for light to medium duty applications in concrete and masonry block base materials. The UltraCon® is available in 5/16" diameter which provides increased shear and tensile strength to meet the needs of more demanding applications.

Approvals



FBC
FLORIDA
BUILDING
CODE

Miami-Dade NOA
Florida Building Code

Base Materials

Normal-weight concrete,
Grouted concrete masonry
(CMU), Hollow concrete
masonry (CMU), Wood

Anchor Material

Carbon steel



CARBON STEEL STALGARD SILVER FINISHED HEX WASHER HEAD

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM5ELG481	5/16" x 1-3/4"	1/4"	1,000
DFM5ELG486	5/16" x 2-1/4"	1/4"	1,000
DFM5ELG491	5/16" x 2-3/4"	1/4"	500
DFM5ELG496	5/16" x 3-1/4"	1/4"	500
DFM5ELG501	5/16" x 3-3/4"	1/4"	500
DFM5ELG506	5/16" x 4"	1/4"	500
DFM5ELG511	5/16" x 5"	1/4"	250
DFM5ELG516	5/16" x 6"	1/4"	250



CARBON STEEL STALGARD SILVER FINISHED HEX WASHER TRIM HEAD

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM5ELG482	5/16" x 1-3/4"	1/4"	1,000
DFM5ELG487	5/16" x 2-1/4"	1/4"	1,000
DFM5ELG492	5/16" x 2-3/4"	1/4"	500
DFM5ELG497	5/16" x 3-1/4"	1/4"	500
DFM5ELG502	5/16" x 3-3/4"	1/4"	500



CARBON STEEL STALGARD SILVER FINISHED T30 STAR DRIVE FLAT HEAD

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM5ELG941S	5/16" x 2-1/4"	1/4"	1,000
DFM5ELG948S	5/16" x 2-3/4"	1/4"	500
DFM5ELG960S	5/16" x 3-1/4"	1/4"	500
DFM5ELG979S	5/16" x 4"	1/4"	500
DFM5ELG992S	5/16" x 5"	1/4"	250
DFM5ELG998S	5/16" x 6"	1/4"	250



CARBON STEEL STALGARD SILVER FINISHED T30 STAR DRIVE FLAT OVERSIZED HEAD

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM5ELG945S	5/16" x 2-1/4"	1/4"	1,000
DFM5ELG955S	5/16" x 2-3/4"	1/4"	500
DFM5ELG965S	5/16" x 3-1/4"	1/4"	500
DFM5ELG972S	5/16" x 3-3/4"	1/4"	500
DFM5ELG976S	5/16" x 4"	1/4"	500
DFM5ELG991S	5/16" x 5"	1/4"	250



CARBON STEEL STALGARD SILVER FINISHED T30 STAR DRIVE FLAT OVERSIZED HEAD

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM5ELG203S	5/16" x 3"	1/4"	50
DFM5ELG204S	5/16" x 4"	1/4"	50
DFM5ELG205S	5/16" x 5"	1/4"	50
DFM5ELG206S	5/16" x 6"	1/4"	50

SCREW ANCHORS

UltraCon® SS4

Description



The UltraCon® SS4 anchor is a 410 stainless steel screw anchor for light to medium duty applications in concrete and masonry block base materials. UltraCon® SS4 anchors feature a Stalgard coating and provide enhanced corrosion resistance over carbon steel fasteners.

Approvals



FBC
FLORIDA
BUILDING
CODE

Miami-Dade NOA

Florida Building Code

Base Materials

Normal-weight concrete, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU)

Anchor Material

410 Stainless Steel



410 STAINLESS STEEL STALGARD SILVER FINISHED HEX WASHER HEAD

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM4EUH310	1/4" x 1-1/4"	3/16"	100
DFM4EUH315	1/4" x 1-3/4"	3/16"	100
DFM4EUH325	1/4" x 2-1/4"	3/16"	100
DFM4EUH335	1/4" x 2-3/4"	3/16"	100
DFM4EUH345	1/4" x 3-1/4"	3/16"	100
DFM4EUH355	1/4" x 3-3/4"	3/16"	100
DFM4EUH365	1/4" x 4"	3/16"	100
DFM4EUH375	1/4" x 5"	3/16"	100
DFM4EUH385	1/4" x 6"	3/16"	100



410 STAINLESS STEEL STALGARD SILVER FINISHED T25 STAR FLAT HEAD

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM4EUF310S	1/4" x 1-1/4"	3/16"	100
DFM4EUF315S	1/4" x 1-3/4"	3/16"	100
DFM4EUF325S	1/4" x 2-1/4"	3/16"	100
DFM4EUF335S	1/4" x 2-3/4"	3/16"	100
DFM4EUF345S	1/4" x 3-1/4"	3/16"	100
DFM4EUF355S	1/4" x 3-3/4"	3/16"	100
DFM4EUF365S	1/4" x 4"	3/16"	100



ULTRA CON+ STRAIGHT SHANK BIT

CAT #	SIZE
DFX153255	5/32" x 5-1/2"
DFX131645	3/16" x 4-1/2"
DFX131675	3/16" x 7-1/2"



ULTRA CON+ HEX SDS+ BIT

CAT #	SIZE
DW5381	5/32" x 7"
DW5382	3/16" x 7"

SCREW ANCHORS

Crete-Flex®

Description



The Crete-Flex® anchor is a 410 stainless steel screw anchor for light to medium duty applications in concrete and masonry block base materials. Crete-Flex® anchors feature a Stalgard coating and provide enhanced corrosion resistance over carbon steel fasteners.

Approvals



Miami-Dade NOA
Florida Building Code

Base Materials

Normal-weight concrete, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Wood

Anchor Material

410 Stainless Steel



410 STAINLESS STEEL STALGARD SILVER FINISHED HEX WASHER HEAD

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM4EMH500	3/16" x 1-1/4"	5/32"	100
DFM4EMH510	3/16" x 1-3/4"	5/32"	100
DFM4EMH530	3/16" x 2-1/4"	5/32"	100
DFM4EMH550	3/16" x 2-3/4"	5/32"	100
DFM4EMF310	#14 x 1-1/4"	7/32"	100
DFM4EMF330	#14 x 1-3/4"	7/32"	100
DFM4EMF350	#14 x 2-1/4"	7/32"	100
DFM4EMF370	#14 x 2-3/4"	7/32"	100
DFM4EMF390	#14 x 3-1/4"	7/32"	100
DFM4EMF410	#14 x 3-3/4"	7/32"	100
DFM4EMF430	#14 x 4"	7/32"	100
DFM4EMF450	#14 x 5"	7/32"	100
DFM4EMF470	#14 x 6"	7/32"	100



410 STAINLESS STEEL STALGARD SILVER FINISHED HEX WASHER FLANGE HEAD

CAT #	SIZE	DRILL BIT DIA.	CTN
DFM4EMF340	#14 x 1-3/4"	7/32"	100
DFM4EMF360	#14 x 2-1/4"	7/32"	100



410 STAINLESS STEEL STALGARD SILVER FINISHED T25 STAR DRIVE FLAT TRIM HEAD

CAT #	SIZE	DRILL BIT DIA.	CTN
DFM4EMF510S	#14 x 1-3/4"	7/32"	100
DFM4EMF530S	#14 x 2-1/4"	7/32"	100
DFM4EMF550S	#14 x 2-3/4"	7/32"	100



DRILL BITS

CAT #	DESCRIPTION
DFX153255	5/32" x 5-1/2" ULTRA-CON+ STRAIGHT SHANK BIT
DW5381	5/32" x 7" ULTRA-CON+ SDS PLUS BIT
DW5410	7/32" x 6" SDS PLUS 2-CUTTER BIT
DW5412	7/32" x 10" SDS PLUS 2-CUTTER BIT

SCREW ANCHORS

Crete-Flex®

Description



The Crete-Flex® anchor is a 410 stainless steel screw anchor for light to medium duty applications in concrete and masonry block base materials. Crete-Flex® anchors feature a Stalgard coating and provide enhanced corrosion resistance over carbon steel fasteners.

Approvals



FBC
FLORIDA
BUILDING
CODE

Miami-Dade NOA
Florida Building Code

Base Materials

Normal-weight concrete, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Wood

Anchor Material

Carbon steel



**410 STAINLESS STEEL STALGARD
SILVER FINISHED T25 STAR DRIVE FLAT HEAD**

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM4EMF610S	3/16" x 1-1/4"	5/32"	100
DFM4EMF620S	3/16" x 1-3/4"	5/32"	100
DFM4EMF630S	3/16" x 2-1/4"	5/32"	100
DFM4EMF640S	3/16" x 2-3/4"	5/32"	100
DFM4EMF650S	3/16" x 3-1/4"	5/32"	100
DFM4EMF690S	#14 x 1-1/4"	7/32"	100
DFM4EMF710S	#14 x 1-3/4"	7/32"	100
DFM4EMF730S	#14 x 2-1/4"	7/32"	100
DFM4EMF750S	#14 x 2-3/4"	7/32"	100
DFM4EMF770S	#14 x 3-1/4"	7/32"	100
DFM4EMF790S	#14 x 3-3/4"	7/32"	100
DFM4EMF810S	#14 x 4"	7/32"	100
DFM4EMF830S	#14 x 5"	7/32"	100
DFM4EMF850S	#14 x 6"	7/32"	100



DRILL BITS

CAT #	DESCRIPTION
DFX153255	5/32" x 5-1/2" ULTRAON+ STRAIGHT SHANK BIT
DW5381	5/32" x 7" ULTRAON+ SDS PLUS HEX BIT
DW5410	7/32" x 6" SDS PLUS 2-CUTTER BIT
DW5412	7/32" x 10" SDS PLUS 2-CUTTER BIT



SCREW ANCHORS

Aggre-Gator®

Description



The Aggre-Gator® is a 300 Stainless Steel bi-metal screw anchor for light to medium duty applications in concrete and masonry block base materials. Aggre-Gator® anchors provide excellent corrosion resistance in demanding applications, such as those in exposed environments.

Approvals



FBC
FLORIDA
BUILDING
CODE

Miami-Dade NOA
High Velocity
Hurricane Zone
Florida Building Code

Base Materials

Normal-weight concrete, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Solid brick masonry, wood

Anchor Material

Bi-Metal 300 Series
Stainless Steel



300 STAINLESS STEEL STALGARD GB SILVER FINISHED HEX WASHER HEAD

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM3EML300	1/4" x 1-1/4"	3/16"	50
DFM3EML315	1/4" x 1-3/4"	3/16"	50
DFM3EML325	1/4" x 2-1/4"	3/16"	50
DFM3EML335	1/4" x 2-3/4"	3/16"	50
DFM3EML345	1/4" x 3-1/4"	3/16"	50
DFM3EML365	1/4" x 4"	3/16"	50



TFH TRIM FIT FLATHEAD T25 STAR DRIVE

CAT #	SIZE	DRILL BIT DIA.	PACK
DFM3EMM300S	1/4" x 1-1/4"	3/16"	50
DFM3EMM310S	1/4" x 1-3/4"	3/16"	50
DFM3EMM320S	1/4" x 2-1/4"	3/16"	50
DFM3EMM330S	1/4" x 2-3/4"	3/16"	50
DFM3EMM340S	1/4" x 3-1/4"	3/16"	50
DFM3EMM360S	1/4" x 4"	3/16"	50



ULTRACON+ STRAIGHT SHANK BIT

CAT #	SIZE
DFX131645	3/16" x 4-1/2"
DFX131675	3/16" x 7-1/2"



ULTRACON+ HEX SDS+ DRIVER BIT

CAT #	SIZE
DW5382	3/16" x 7"

INSTALLATION KIT

CAT #	DESCRIPTION
DW5366	5/32" AND 3/16" SDS+ DRILL BITS, 1/4" AND 5/16" NUTSETTERS, T25 AND T30 STAR DRIVE BITS, PHILLIPS FLATHEAD ADAPTER, PERCUSSION ADAPTER, DRIVE SLEEVE, AND 1/8" ALLEN WRENCH

ROD HANGING SYSTEMS

Hangermate[®]+ for Concrete

Description



The Hangermate[®]+ concrete screw is a rod hanging anchor designed for consistent performance in cracked concrete and seismic conditions for use in attaching fire protection systems, ventilation systems, electrical conduit, pipe hanging and cable trays.

Approvals



ICC-ES ESR-3889 (Concrete)

IBC & IRC 2021, 2018, 2015, 2012

Recognition in cracked & uncracked concrete including seismic and wind loading (Category 1 Anchors)

Full FM listings in product brochure or at www.DEWALT.com

Base Materials

Normal-weight concrete, Lightweight concrete, Concrete over steel deck, Hollow core concrete

Anchor Material

Carbon steel



HANGERMATE+ FOR CONCRETE - INTERNALLY THREADED - VERTICAL

CAT #	ROD DIA.	1/4" HEX DRIVER	DESCRIPTION	PACK	CTN
PFM2211100	1/4"	PFM1491050	1/4" x 1-5/8"	25	125
PFM2211200	3/8"	PFM1491100	1/4" x 1-5/8"	25	125
PFM2211250	3/8"	PFM1491100	1/4" x 2-1/2"	25	125
PFM2211260	3/8"	PFM1491100	3/8" x 1-5/8"	25	125
PFM2211270	3/8"	PFM1491100	3/8" x 2"	25	125
PFM2211280	1/2"	—	3/8" x 2"	25	125



HANGERMATE+ FOR CONCRETE - EXTERNALLY THREADED - VERTICAL

CAT #	ROD DIA.	SOCKET	DESCRIPTION	PACK	CTN
PFM1421000	3/8"	DWMT19052B	1/4" x 1-5/8"	25	125
PFM1421050	3/8"	DWMT19052B	1/4" x 2-1/2"	25	125

ROD HANGING SYSTEMS

Hangermate[®] for Concrete

Description



The Hangermate[®] concrete screw is a rod hanging anchor designed for attaching fire protection systems, ventilation systems, electrical conduit, pipe hanging and cable trays.

Approvals



Full FM listings in product brochure or at www.DEWALT.com

Base Materials

Normal-weight concrete, Lightweight concrete, Concrete over steel deck

Anchor Material

Carbon steel



HANGERMATE BASIC FOR CONCRETE INTERNALLY THREADED - VERTICAL

CAT #	ROD DIA.	1/4" HEX DRIVER	DESCRIPTION	PACK	CTN
PFM2217171	1/4"	PFM1491050	1/4" x 1-1/4"	100	600
PFM2217173	3/8"	PFM1491100	1/4" x 1-1/2"	100	600



HANGERMATE FOR CONCRETE - INTERNALLY THREADED - PIVOT

CAT #	ROD DIA.	1/4" HEX DRIVER	DESCRIPTION	PACK	CTN
PFM2281300	3/8"	PFM2201250	1/4" x 2"	25	125

OTHER ACCESSORIES: HANGERMATE FOR CONCRETE

CAT #	DESCRIPTION	PACK	CTN
PFM2201050	3/8" TO 1/2" ADAPTOR ¹	25	125

¹The 3/8" to 1/2" adaptor has a 3/8-16 external thread and a 1/2-13 internal thread.

ROD HANGING SYSTEMS

Hangermate® for Steel

Description



Hangermate® for steel are rod hanging anchors designed for attaching threaded rod for applications such as pipe hanging, fire protection, electrical conduit and cable-tray applications into steel base materials.

Approvals



Full FM & UL listings in product brochure or at www.DEWALT.com

Base Materials

Steel Purlins and Beams

Anchor Material

Carbon steel

¹The 3/8" to 1/2" adapter has a 3/8-16 external thread and a 1/2-13 internal thread.

²The Hangermate pole tool kit is designed for use with standard 1/2" steel conduit tubing (conduit not included) and can be customized to various lengths and ceiling heights. Compatible with standard steel and wood Hangermate.



HANGERMATE FOR STEEL - INTERNALLY THREADED - VERTICAL

CAT #	ROD DIA.	1/4" HEX DRIVER	DESCRIPTION	PACK	CTN
PFM2231000	1/4"	PFM2201200	1/4"-20 x 1" #3	25	125
PFM2231100	3/8"	PFM2201200	1/4"-20 x 1" #3	25	125
PFM223110N	3/8"	PFM2201200	1/4"-20 x 1" #3 W/ NUT	25	125
PFM2231150	3/8"	PFM2201200	1/4"-20 x 1-1/2" #5	25	125
PFM223115N	3/8"	PFM2201200	1/4"-20 x 1-1/2" #5 W/ NUT	25	125
PFM2231200	3/8"	PFM2201200	1/4"-20 x 1-1/2" #3	25	125
PFM223120N	3/8"	PFM2201200	1/4"-20 x 1-1/2" #3 W/ NUT	25	125
PFM2231250	3/8"	PFM2201200	1/4"-20 x 2" #3	25	125



HANGERMATE FOR STEEL - INTERNALLY THREADED - HORIZONTAL

CAT #	ROD DIA.	1/4" HEX DRIVER	DESCRIPTION	PACK	CTN
PFM2241100	3/8"	PFM2201200	1/4"-20 x 1" #3	25	125
PFM224110N	3/8"	PFM2201200	1/4"-20 x 1" 3 W/ NUT	25	125
PFM2241150	3/8"	PFM2201200	1/4"-20 x 1-1/2" #3	25	125
PFM224115N	3/8"	PFM2201200	1/4"-20 x 1-1/2" #3 W/ NUT	25	125
PFM2241200	3/8"	PFM2201200	1/4"-20 x 1-1/2" #5	25	125
PFM224120N	3/8"	PFM2201200	1/4"-20 x 1-1/2" #5 W/ NUT	25	125



HANGERMATE FOR STEEL - INTERNALLY THREADED - PIVOT

CAT #	ROD DIA.	1/4" HEX DRIVER	DESCRIPTION	PACK	CTN
PFM2281150	3/8"	PFM2201250	1/4"-20 x 1" #3	25	125
PFM2281200	3/8"	PFM2201250	1/2"-20 x 1-3/4" #5	25	125
PFM2281250	3/8"	PFM2201250	1/4"-14 x 1" #3	25	125



HANGERMATE FOR STEEL - CEILING SCREW EYELET

CAT #	HOLE DIA.	1/4" HEX DRIVER	DESCRIPTION	PACK	CTN
PFM2231500	3/8"	PFM2201350	3/16" x 2" 1/4-14 x 7/8" #2	25	125
PFM2231550	3/8"	PFM2201350	3/16" x 3-1/4" 1/4-14 x 2" #2	25	125

OTHER ACCESSORIES: HANGERMATE FOR STEEL

CAT #	DESCRIPTION	PACK	CTN
PFM2201050	3/8" TO 1/2" ADAPTOR ¹	25	125
PFM2201100	HANGERMATE POLE TOOL KIT ²	25	125

ROD HANGING SYSTEMS

Hangermate® for Wood

Description



HangerMate® for wood are rod hanging anchors designed for attaching threaded rod for applications such as pipe hanging, fire protection, electrical conduit and cable-tray applications into wood base materials.

Approvals



Base Materials

Wood, Timber

Anchor Material

Carbon steel

¹The 3/8" to 1/2" adaptor has a 3/8-16 external thread and a 1/2-13 internal thread.

²The Hangermate pole tool kit is designed for use with standard 1/2" steel conduit tubing (conduit not included) and can be customized to various lengths and ceiling heights. Compatible with standard steel and wood Hangermate.



HANGERMATE FOR WOOD - INTERNALLY THREADED - VERTICAL

CAT #	ROD DIA.	1/4" HEX DRIVER	DESCRIPTION	PACK	CTN
PFM2251000	1/4"	PFM2201150	1/4" x 2"	25	125
PFM2251050	3/8"	PFM2201150	1/4" x 1"	25	125
PFM2251100	3/8"	PFM2201150	1/4" x 2"	25	125
PFM2251150	3/8"	PFM2201150	5/16" x 2-1/2"	25	125
PFM2251200	3/8"	PFM2201150	1/4" x 3"	25	125
PFM2251250	3/8"	PFM2201150	1/4" x 4"	25	125
PFM2251300	1/2"	PFM2201150	5/16" x 2-1/2"	25	125



HANGERMATE FOR WOOD - INTERNALLY THREADED - HORIZONTAL

CAT #	ROD DIA.	1/4" HEX DRIVER	DESCRIPTION	PACK	CTN
PFM2261000	1/4"	PFM2201150	1/4" x 1"	25	125
PFM2261050	3/8"	PFM2201150	1/4" x 1"	25	125
PFM2261100	3/8"	PFM2201150	1/4" x 2"	25	125
PFM2261150	3/8"	PFM2201150	5/16" x 2-1/2"	25	125



HANGERMATE FOR WOOD - INTERNALLY THREADED - PIVOT

CAT #	ROD DIA.	1/4" HEX DRIVER	DESCRIPTION	PACK	CTN
PFM2281100	3/8"	PFM2201250	3/16" x 2"	25	125



HANGERMATE - WOOD - ACOUSTICAL CEILING SCREW EYELET

CAT #	HOLE DIA.	1/4" HEX DRIVER	DESCRIPTION	PACK	CTN
PFM2251500	3/16"	PFM2201350	3/16" x 3-1/4"	25	125

OTHER ACCESSORIES: HANGERMATE FOR WOOD

CAT #	DESCRIPTION	PACK	CTN
PFM2201050	3/8" TO 1/2" ADAPTOR ¹	25	125
PFM2201100	HANGERMATE POLE TOOL KIT ²	25	125

ROD HANGING SYSTEMS

Suspender® for Concrete

Description



Suspender® rod hanging anchors are end-tapped and cross-tapped to permit both in-line mounting and side-mounting of threaded rod systems.

Approvals



Full FM listings in product brochure or at www.DEWALT.com

Base Materials

Concrete



SUSPENDER FOR CONCRETE - DUAL-DIRECTIONAL

CAT #	ROD DIA.	1/4" HEX DRIVER	DESCRIPTION	PACK	CTN
PFM2271050	3/8"	PFM2201300	5/16" x 2-1/4"	25	125

ROD HANGING SYSTEMS

Suspender® for Steel

Description



Suspender® for steel are rod hanging anchors are end-tapped and cross-tapped to permit both in-line mounting and side-mounting of threaded rod systems.

Approvals



Full FM & UL listings in product brochure or at www.DEWALT.com

Base Materials

Steel



SUSPENDER FOR STEEL - DUAL-DIRECTIONAL

CAT #	ROD DIA.	1/4" HEX DRIVER	DESCRIPTION	PACK	CTN
PFM227110N	3/8"	PFM2201300	1/4-20 x 1" #3/NUT	25	125
PFM227120N	3/8"	PFM2201300	1/4-20 x 1-1/2" #3/NUT	25	125
PFM227130N	3/8"	PFM2201300	1/4-20 x 1-1/2" #5/NUT	25	125

ROD HANGING SYSTEMS

Suspender® for Wood

Description



Suspender® for wood are rod hanging anchors are end-tapped and cross-tapped to permit both in-line mounting and side-mounting of threaded rod systems.

Approvals



Base Materials

Wood



SUSPENDER FOR WOOD - DUAL-DIRECTIONAL

CAT #	ROD DIA.	1/4" HEX DRIVER	DESCRIPTION	PACK	CTN
PFM2271000	3/8"	PFM2201300	5/16" x 2-1/2"	25	125

BOLT & SHIELD ANCHORS

Snake+®

Description



The Snake+® anchor is an internally threaded, self-tapping screw anchor designed for fast installation and consistent performance in cracked and uncracked concrete.

Approvals



ICC-ES ESR-2272
(Concrete)

IBC & IRC 2021, 2018
2015, 2012

Recognition in cracked
& uncracked concrete
including seismic and
wind loading
(Category 1 Anchors)

Full FM listings in product
brochure or at
www.DEWALT.com

Base Materials

Normal-weight concrete,
Lightweight concrete,
Concrete over steel deck

Anchor Material

Carbon steel



SNAKE+

CAT #	SIZE	MIN HOLE DEPTH	INTERNAL THREAD DEPTH	PACK	CTN
6400SD-PWR	1/4"	1-5/8"	22/32"	100	1,000
6401SD-PWR	3/8"	1-5/8"	11/16"	50	500
6403SD-PWR	1/2"	2-1/2"	29/32"	50	300

One setting tool included per pack



EXTRA SNAKE & SNAKE+ SETTING TOOLS

CAT #	SIZE	PACK	CTN
6402SD-PWR	1/4"	1	100
6407SD-PWR	3/8"	1	250
6404SD-PWR	1/2"	1	250



BOLT & SHIELD ANCHORS

Smart DI™

Description



The Smart DI™ is an easy setting internally threaded expansion anchor that can be used in solid concrete, hard stone, and solid block base materials.

Approvals



Full FM & UL listings in product brochure or at www.DEWALT.com



Federal GSA Specification – Meets the descriptive requirements CID A-A 55614

Base Materials

Normal-weight concrete, Lightweight concrete

Anchor Material

Carbon steel



SMART DI

CAT #	SIZE	PACK	CTN
6304SD-PWR	1/4"	100	1,000
6306SD-PWR	3/8"	50	500
6308SD-PWR	1/2"	50	300




DI TOOL

CAT #	SIZE	PACK	CTN
00425SD-PWR	1/4"	1	6
00427SD-PWR	3/8"	1	6
00429SD-PWR	1/2"	1	6



DRILL

CAT #	SIZE	PACK	CTN
00391SD-PWR	3/8" (FOR 1/4" SMART DI)	1	12
00397SD-PWR	1/2" (FOR 3/8" SMART DI)	1	12
00410SD-PWR	5/8" (FOR 1/2" SMART DI)	1	12



BOLT & SHIELD ANCHORS

Steel Dropin™

Description



The Steel Dropin™ is an internally threaded expansion anchor available in carbon and stainless steel. It is designed for use in solid concrete, lightweight concrete, concrete-filled steel deck members and some stone base materials. A coil thread version for forming applications is also available.

Approvals



Full UL listings in product brochure or at www.DEWALT.com

Federal GSA Specification
– Meets the descriptive requirements CID A-A 55614

Base Materials

Normal-weight concrete,
Lightweight concrete

Anchor Material

Carbon Steel
Type 303 Stainless Steel
Type 316 Stainless Steel

*Domestically manufactured anchors include "USA" in the catalog number.



CARBON STEEL SMOOTH WALL DROPIN

CAT# STANDARD	CAT# DOMESTIC ¹	SIZE	LENGTH	DIAMETER	PACK	CTN
06304-PWR	6304USA-PWR	1/4"	1"	3/8"	100	1,000
06306-PWR	6306USA-PWR	3/8"	1-9/16"	1/2"	50	500
06308-PWR	6308USA-PWR	1/2"	2"	5/8"	50	300
06320-PWR	6320USA-PWR	5/8"	2-1/2"	7/8"	25	125
06312-PWR	6312USA-PWR	3/4"	3-13/16"	1"	10	50



CARBON STEEL FLANGED DROPIN (LIPPED)

CAT#	SIZE	LENGTH	DIAMETER	PACK	CTN
06324-PWR	1/4"	1"	3/8"	100	1,000
06326-PWR	3/8"	1-9/16"	1/2"	50	500
06328-PWR	1/2"	2"	5/8"	50	300



CARBON STEEL KNURLED WALL DROPIN

CAT#	SIZE	LENGTH	DIAMETER	PACK	CTN
06340-PWR	1/4"	1"	3/8"	100	1,000
06342-PWR	3/8"	1-9/16"	1/2"	50	500
06344-PWR	1/2"	2"	5/8"	50	300



TYPE 300 SERIES STAINLESS STEEL DROPIN

CAT# STANDARD	CAT# DOMESTIC ¹	SIZE	LENGTH	DIAMETER	PACK	CTN
06204-PWR	6204USA-PWR	1/4"	1"	3/8"	100	1,000
06206-PWR	6206USA-PWR	3/8"	1-9/16"	1/2"	50	500
06208-PWR	6208USA-PWR	1/2"	2"	5/8"	50	300
06210-PWR	6210USA-PWR	5/8"	2-1/2"	7/8"	25	125
06212-PWR	6212USA-PWR	3/4"	3-13/16"	1"	10	50



TYPE 316 STAINLESS STEEL DROPIN

CAT# STANDARD	CAT# DOMESTIC ¹	SIZE	LENGTH	DIAMETER	PACK	CTN
06224-PWR	6224USA-PWR	1/4"	1"	3/8"	100	1,000
06226-PWR	6226USA-PWR	3/8"	1-9/16"	1/2"	50	500
06228-PWR	6228USA-PWR	1/2"	2"	5/8"	50	300
06230-PWR	6230USA-PWR	5/8"	2-1/2"	7/8"	25	125
06232-PWR	6232USA-PWR	3/4"	3-13/16"	1"	10	50

BOLT & SHIELD ANCHORS

Steel Dropin™

Description



The Steel Dropin™ is an internally threaded expansion anchor available in carbon and stainless steel. It is designed for use in solid concrete, lightweight concrete, concrete-filled steel deck members and some stone base materials. A coil thread version for forming applications is also available.

Approvals



Full UL listings in product brochure or at www.DEWALT.com



Federal GSA Specification – Meets the descriptive requirements CID A-A 55614

Base Materials

Normal-weight concrete, Lightweight concrete

Anchor Material

Carbon Steel
Type 303 Stainless Steel
and Type 316 Stainless Steel



CARBON STEEL COIL THREAD DROPIN

CAT#	SIZE	LENGTH	DIAMETER	PACK	CTN
06330-PWR	1/2"	2"	5/8"	50	300
06332-PWR	3/4"	3-3/16"	1"	10	50



SETTING TOOLS FOR STEEL DROPIN

CAT#	ROD/ANCHOR SIZE	PIN LENGTH	PACK
06305-PWR	1/4"	39/64"	1
06307-PWR	3/8"	61/64"	1
06309-PWR	1/2"	1-3/16"	1
06311-PWR	5/8"	1-5/16"	1
06313-PWR	3/4"	1-61/64"	1



ACCU-BIT DRILL STOP FOR STEEL DROPIN

CAT#	ROD/ANCHOR SIZE	DRILL STOP	PACK
DWA5493	1/2" ACCU-BIT FOR 3/8" STEEL DROPIN	1-13/16"	1
DWA5495	5/8" ACCU-BIT FOR 1/2" STEEL DROPIN	2-3/8"	1



BOLT & SHIELD ANCHORS

Hollow-Set Dropin™

Description



The Hollow-Set Dropin™ is an internally threaded expansion anchor designed for anchoring in hollow base materials such as hollow concrete block and precast hollow core plank as well as solid base materials.

Approvals



Full UL listings in product brochure or at www.DEWALT.com

Base Materials

Normal-weight concrete, Precast hollow-core plank, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Brick masonry

Anchor Material

Zamac alloy with carbon or stainless steel cones



ZAMAC BODY WITH CARBON STEEL CONE

CAT #	SIZE	DRILL DIAMETER	OVERALL LENGTH	SLEEVE LENGTH	PACK	CTN
09320-PWR	1/4"	3/8"	7/8"	5/8"	100	1,000
09330-PWR	5/16"	5/8"	1-5/16"	15/16"	50	300
09340-PWR	3/8"	5/8"	1-5/16"	15/16"	50	300
09350-PWR	1/2"	3/4"	1-3/4"	1-1/4"	50	250
09360-PWR	5/8"	1"	2"	1-1/2"	25	125


ZAMAC BODY WITH STAINLESS STEEL CONE

CAT #	SIZE	DRILL DIAMETER	OVERALL LENGTH	SLEEVE LENGTH	PACK	CTN
09420-PWR	1/4"	3/8"	7/8"	5/8"	100	1,000
09440-PWR	3/8"	5/8"	1-5/16"	15/16"	100	500



SOLID BASE MATERIAL SETTING TOOLS

CAT #	SIZE	PACK	CTN
09322-PWR	1/4"	1	200
09342-PWR	5/16" & 3/8"	1	50
09352-PWR	1/2"	1	25
09362-PWR	5/8"	1	—



HOLLOW BASE MATERIAL SETTING TOOLS

CAT #	SIZE	PACK	CTN
09323-PWR	1/4"	1	50
09333-PWR	5/16"	1	50
09343-PWR	3/8"	1	50
09353-PWR	1/2"	1	50
09363-PWR	5/8"	1	—

BOLT & SHIELD ANCHORS

Mini-Undercut+™

Description



The Mini-Undercut+™ anchor is an internally threaded, self-undercutting anchor designed for consistent performance at shallow embedments as low as 3/4 of an inch in cracked and uncracked concrete.

Approvals



ICC-ES ESR-3912
(Concrete)

IBC & IRC 2021, 2018
2015, 2012

Recognition in cracked
& uncracked concrete
including seismic and
wind loading
(Category 1 Anchors)

Base Materials

Post-tension concrete,
Precast hollow-core plank,
Normal-weight concrete,
Lightweight concrete

Anchor Material

Carbon steel



MINI UNDERCUT ANCHOR

CAT #	ANCHOR SIZE	ROD DIAMETER	DRILL DIAMETER	PACK	CTN
PFM2111820	3/8" x 3/4"	3/8"	5/8"	100	600




ACCU-BIT

CAT #	STOP BIT SIZE	ROD DIAMETER	DRILL DIAMETER	DRILL DEPTH	PACK
PPA2431720	5/8" x 3/4"	3/8"	5/8"	3/4"	1



SDS SETTING TOOL

CAT #	SETTING TOOL SIZE	ROD DIAMETER	PACK
PFM2101720	5/8" x 3/4"	3/8"	10



ACCESSORIES FOR INSTALLATION

CAT #	TYPE
DWH003SBH	STOP BIT HEAD NOZZLE KIT
DWH002SBH	STOP BIT HEAD REPLACEMENT 3-PACK

BOLT & SHIELD ANCHORS

Mini Dropin™

Description



The Mini Dropin™ is an internally threaded expansion anchor for use in shallow embedment applications such as precast hollow core plank, post-tensioned concrete slabs and concrete over steel deck.

Approvals



Full FM listings in product brochure or at www.DEWALT.com

Base Materials

Normal-weight concrete,
Lightweight concrete,
Precast hollow-core plank,
Concrete over steel deck


Anchor Material

Carbon steel



MINI DROP-IN

CAT #	SIZE	DRILL DIAMETER	MIN DEPTH	THREAD DEPTH	PACK	CTN
06335-PWR	1/4"	3/8"	5/8"	3/8"	100	1,000
06322-PWR	3/8"	1/2"	3/4"	13/32"	100	1,000
06337-PWR	1/2"	5/8"	1"	5/8"	50	250




SETTING TOOLS FOR MINI DROP-IN ANCHORS

CAT #	SIZE	PACK	CTN
06336-PWR	1/4"	1	50
06323-PWR	3/8"	1	50
06338-PWR	1/2"	1	50



SDS-PLUS ACCU-BIT FOR MINI DROP-IN

CAT #	SIZE	PACK
DWA5491	SDS-PLUS 3/8" (FOR 1/4" MINI DROP-IN)	1
DWA5492	SDS-PLUS 1/2" (FOR 3/8" MINI DROP-IN)	1
DWA5494	SDS-PLUS 5/8" (FOR 1/2" MINI DROP-IN)	1



BOLT & SHIELD ANCHORS

Double™

Description

The Double™ is a Zamac alloy dual expansion machine bolt anchor designed for use in solid concrete, block, brick, and stone. The Double™ is particularly well-suited for base materials of questionable strength when job site testing is done to determine suitability.

Approvals

Federal GSA Specification
– Meets the descriptive requirements of CID A-A 1923A Type 3

Base Materials

Normal-weight concrete, Grout-filled concrete masonry (CMU), Hollow concrete masonry (CMU), Brick masonry, Stone

Anchor Material

Zamac alloy



ZAMAC ALLOY THREADED INTERNALLY					
CAT #	SIZE	DRILL DIAMETER	LENGTH	PACK	CTN
09510-PWR	1/4"	1/2"	1-3/8"	50	500
09515-PWR	5/16"	5/8"	1-5/8"	50	500
09520-PWR	3/8"	3/4"	2"	50	250
09525-PWR	1/2"	7/8"	2-1/2"	25	250
09530-PWR	5/8"	1"	2-3/4"	25	100
09535-PWR	3/4"	1-1/4"	3-15/16"	10	50



DCV585T2



DWV015

BOLT & SHIELD ANCHORS

Lag Shield™

Description



The Lag Shield™ is a screw style anchor designed for use with lag bolts. It is suitable for use in concrete and the mortar joints of block or brick walls. The Lag Shield™ is not recommended for overhead or life safety applications.

Approvals



Federal GSA Specification
– Meets the descriptive requirements of CID A-A 1923A Type 1
Tested in accordance with ASTM E488

Base Materials

Normal-weight concrete, Hollow concrete masonry (CMU), Brick masonry

Anchor Material

Zamac alloy



ZAMAC ALLOY LONG

CAT #	SIZE	DRILL DIAMETER	LENGTH	PACK	CTN
01055-PWR	1/4"	1/2"	1-1/2"	50	500
01105-PWR	5/16"	1/2"	1-3/4"	50	500
01155-PWR	3/8"	5/8"	2-1/2"	50	250
01205-PWR	1/2"	3/4"	3"	50	200
01255-PWR	5/8"	7/8"	3-1/2"	25	125
01305-PWR	3/4"	1"	3-1/2"	25	100

BOLT & SHIELD ANCHORS

Calk-In™

Description



The Calk-In™ is a antimonial lead and Zamac alloy expansion anchor designed for use in concrete, block and brick or stone. The Calk-In™ consists of an antimonial lead alloy calking sleeve and a Zamac alloy internally threaded expanded cone. This anchor is not recommended for use in overhead applications or for life safety.

Approvals



Federal GSA Specification
– Meets the descriptive requirements of CID A-A 1923A Type 3

Base Materials

Normal-weight concrete, Grouted-filled concrete masonry (CMU), Brick masonry

Anchor Material

Zamac alloy and lead



LEAD ANTIMONY ALLOY THREADED INTERNALLY

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
09210-PWR	#10-24	3/8"	100	1,000
09220-PWR	1/4"-20	1/2"	100	600
09225-PWR	5/16"-18	5/8"	50	300
09230-PWR	3/8"-16	3/4"	50	300
09240-PWR	1/2"-13	7/8"	50	250



CALK-IN SETTING TOOLS PURCHASED SEPARATELY

CAT #	SIZE	DRILL DIAMETER	MIN. HOLE DEPTH	PACK	CTN
09211-PWR	#10-24	3/8"	5/8"	100	1,000
09221-PWR	1/4"-20	1/2"	7/8"	100	600
09226-PWR	5/16"-18	5/8"	1"	50	300
09231-PWR	3/8"-16	3/4"	1-1/4"	50	300
09241-PWR	1/2"-13	7/8"	1-1/2"	50	250

RAPIDSET

RapidSet® Tools

Description

The fastest, easiest and most reliable way to install machine screw anchors.

Efficient RapidSet® tools eliminate clumsy hammer and setting processes or expensive, slow expander tools.*

- Specifications
- For machine screw anchor sizes #10, 1/4" and 3/8"
 - Designed for use with power tools, including battery impact drivers

STANDARD RAPIDSET TOOL

CAT #	FOR INSERT-ANCHOR SIZE
EZB790	#10-24
EZB800	1/4-20
EZB820	3/8-16

RAPIDSET MAXX TOOL

CAT #	FOR INSERT-ANCHOR SIZE
EZB810	1/4-20

REPAIR KITS


CAT #	FOR INSERT-ANCHOR SIZE
EZB811	REPAIR KIT FOR EZB810 (RAPIDSET MAXX TOOL)
EZB801	REPAIR KIT FOR EZB800 (RAPIDSET TOOL FOR 1/4-20 INSERTS)

*Note: RapidSet tools draw the anchor's internal insert up into the anchor's outer sleeve; this installation process eliminates the need to maintain a back bearing surface (required by hammer setting tools).



DCH293X2
20V MAX® XR® 1-1/8 In.
Brushless Cordless SDS PLUS
L-Shape Rotary Hammer Kit

**GUARANTEED
TOUGH.®**



DEWALT

ANCHORS & FASTENERS



WWW.ANCHORS.DEWALT.COM

CAST-IN ANCHOR INSERTS

Bang-It®+

Description



Bang-It®+ concrete inserts are cast-in-place anchors designed for mechanical, electrical, plumbing (MEP) and fire protection systems and are installed on composite steel decking.

Approvals



ICC-ES ESR-3657
(Concrete)

IBC & IRC 2021, 2018,
2015, 2012

Recognition in cracked
& uncracked concrete
including seismic and wind
loading
(Category 1 Anchors)

Full FM & UL listings in
product brochure or at
www.DEWALT.com

Base Materials

Normal-weight concrete,
Lightweight concrete

Anchor Material

Carbon steel and
engineered plastic



BANG-IT+ DOUBLE THREAD

CAT #	ROD SIZE	COLOR	PACK
PFM3523812	3/8" & 1/2"	GREY	100
PFM3525834	5/8" & 3/4"	BLACK	50

BANG-IT+ TRIPLE THREAD

CAT #	ROD SIZE	COLOR	PACK
PFM353143812	1/4" & 3/8" & 1/2"	AQUA	50
PFM353381258	3/8" & 1/2" & 5/8"	ORANGE	50

BANG-IT+ PUSH-IN THREAD

CAT #	ROD SIZE	COLOR	PACK
PFM3610038	3/8"	GREEN	50
PFM3610012	1/2"	YELLOW	50

RECOMMENDED INSTALLATION POWER TOOLS

CAT #	TYPE	PACK
DCD996P2	20V MAX XR LITHIUM ION CORDLESS DRILL DRIVER KIT (5.0AH)	1

ACCESSORIES

CAT #	TYPE	PACK
PFM3611000	BANG-IT+ DECK DRILLER EXTENSION 28" (USE WITH 1/2" DRILL DRIVER)	1
1779804	5L ARBOR, 3/8" SOLID HEX SHANK	1
1779801	2L ARBOR, 1/2" SOLID HEX SHANK	1
2009314CHC	CARBIDE HOLE CUTTER BIT 7/8" (USE 5L ARBOR, NOT INCLUDED)	1
2009820CHC	CARBIDE HOLE CUTTER BIT 1-1/4" (USE 2L ARBOR, NOT INCLUDED)	1
30912VB12	VARI-BIT STEP DRILL BIT 7/8", 1-1/8", 1-7/32", 1-1/4", 1-3/8"	1
PFM3613000	BANG-IT+ BRIDGE BAR	20

CAST-IN ANCHOR INSERTS

Wood-Knocker® II+

Description



Wood-Knocker® II+ is a wood form cast-in-place concrete insert specifically designed to provide hanger attachments for mechanical, electrical, plumbing (MEP) and fire protection in sizes ranging from 1/4" to 3/4" in diameter.

Approvals



ICC-ES ESR-3657
(Concrete)

IBC & IRC 2021, 2018,
2015, 2012

Recognition in cracked &
uncracked concrete
including seismic and wind
loading
(Category 1 Anchors)

Full FM & UL listings in
product brochure or at
www.DEWALT.com

Base Materials

Normal-weight concrete,
Lightweight concrete

Anchor Material

Carbon steel and
engineered plastic



WOOD-KNOCKER II+ LOW PROFILE

CAT #	ROD SIZE	COLOR	PACK
PFM2501438	1/4" & 3/8"	YELLOW	100

WOOD-KNOCKER II+ DOUBLE THREAD

CAT #	ROD SIZE	COLOR	PACK
PFM2521350	3/8" & 1/2"	GREY	100
PFM2525834	5/8" & 3/4"	BLACK	50

WOOD-KNOCKER II+ TRIPLE THREAD

CAT #	ROD SIZE	COLOR	PACK
PFM253143812	1/4" & 3/8" & 1/2"	AQUA	100
PFM253381258	3/8" & 1/2" & 5/8"	ORANGE	50

WOOD-KNOCKER II+ PUSH-IN THREAD

CAT #	ROD SIZE	COLOR	PACK
PFM2610038	3/8"	GREEN	50
PFM2610012	1/2"	YELLOW	50


ACCESSORIES

CAT #	DESCRIPTION
PFM3612000	WOOD-KNOCKER II+ INSTALLATION TOOL



CAST-IN ANCHOR INSERTS

Wood-Knocker® II Installation Tool



Available Service Parts

PFM3612001




PFM3612002



CAST-IN ANCHOR INSERTS

Deck Driller Extension



CAST-IN ANCHOR INSERTS

Pan-Knocker® II+

Description



Pan-Knocker® II concrete inserts are cast-in-place anchors designed for mechanical, electrical, plumbing (MEP) and fire protection systems and are installed on concrete forms.

Approvals



ICC-ES ESR-3657
(Concrete)

IBC & IRC 2021, 2018,
2015, 2012

Recognition in cracked &
uncracked concrete
including seismic and
wind loading
(Category 1 Anchors)

Full FM & UL listings in
product brochure or at
www.DEWALT.com

Base Materials

Normal-weight concrete,
Lightweight concrete

Anchor Material

Carbon steel and
engineered plastic



PAN-KNOCKER II+ LOW PROFILE

CAT #	ROD SIZE	COLOR	PACK
PFM2501438NN	1/4" & 3/8"	WHITE	100

PAN-KNOCKER II+ DOUBLE THREAD

CAT #	ROD SIZE	COLOR	PACK
PFM2525834NN	5/8" & 3/4"	BLACK	100

PAN-KNOCKER II+ TRIPLE THREAD

CAT #	ROD SIZE	COLOR	PACK
PFM253143812NN	1/4" & 3/8" & 1/2"	AQUA	100

PAN-KNOCKER II+ PUSH-IN THREAD

CAT #	ROD SIZE	COLOR	PACK
PFM2610038NN	3/8"	GREEN	50
PFM2610012NN	1/2"	YELLOW	50


DCS350K1
20V MAX[®] Threaded
Rod Cutter



CAST-IN ANCHOR INSERTS





DDI+™ (Deck Insert)

Description



The DDI+™ is a concrete insert designed for installation in concrete-filled metal deck assemblies. After installation, the threaded male hanger of the insert protrudes below the surface of the deck for hanging utilities.

Approvals



ICC-ES ESR-3958 (Concrete)

Recognition in cracked & uncracked concrete including seismic and wind loading (Category 1 Anchors)

Full FM & UL listings in product brochure or at www.DEWALT.com

Base Materials

Normal-weight concrete, Lightweight concrete

Anchor Material

Plain and zinc plated carbon steel



DDI+			
CAT #	ANCHOR/ROD SIZE	DRILL DIAMETER	INSERT PACK
PFM2511100	3/8"	7/16"	20
PFM2511110	1/2"	9/16"	20
PFM2511120	5/8"	11/16"	20
PFM2511130*	3/4"	13/16"	12

* Parts not included in ESR-3958

RECOMMENDED INSTALLATION POWER TOOLS	
CAT #	TYPE
DCD996P2	20V MAX* XR LITHIUM ION BRUSHLESS 3-SPEED DRILL
PFM3611000	DECK DRILLER EXTENSION
30912VB12	LENOX VARI-BIT STEP DRILL BITS
1779804	LENOX STANDARD HOLE SAW ARBOR 5L 3/8" SOLID HEX SHANK
1779801	LENOX STANDARD HOLE SAW ARBORS 2L ARBOR 1/2" SOLID HEX SHANK
2009314CHC	7/8" LENOX CARBIDE HOLD CUTTER (USE 5L ARBOR NOT INCLUDED)
2009820CHC	1-1/4" LENOX CARBIDE HOLD CUTTER (USE 2L ARBOR NOT INCLUDED)



CAST-IN ANCHOR INSERTS

Push-In Coupler

Description



Push-In Thread Couplers are a high performance coupling device designed for rapid installation of common industrial and commercial hardware connections such as mounting prefabricated hardware and hanger assemblies.

Approvals



ICC-ES ESL-1485

Base Materials

3/8" or 1/2" Threaded Rod

Anchor Material

Zinc Plated Carbon Steel



PUSH-IN THREAD COUPLERS


CAT #	INTERNAL THREAD DIAMETER	THREADS PER INCH	PACK	CTN
PFM3613012	1/2"	16	20	120
PFM3613038	3/8"	13	20	120

Hex Nut Side Enables
Installation With
A Wrench

Cinch Nut Mechanism
Designed To Eliminate
Thread Misalignment

Thread Rod Compatibility
Accepts Burred Or Oiled
Rods And Commonly
Available Standard UNC
Threaded Rods

Double-Sided Separate Thread-In
And Push-In Sides Designed For
Attaching Existing Anchor Points
To Pre-Fabrication Assemblies





ANCHORS & FASTENERS



ANCHORS & FASTENERS

**UP TO 70%
TIME SAVINGS
ON INITIAL
HANGER
PLACEMENT***



*vs. HangerWorks™ 2.0 Hanger Placement in Revit® Design Software

HangerWorks™ PRO

**AUTOMATE HANGER PLACEMENT
AND DESIGN FOR MEP SYSTEMS
SUCH AS PIPE, DUCT,
CONDUIT AND CABLE TRAYS.**



**PREFABRICATION
SPOOLS**



**AUTOMATED POINT
LOADS & SEISMIC
BRACING**



**BILL OF
MATERIALS**



**FIELD
LAYOUT
POINTS**



**CUSTOMIZABLE
DESIGNS**



**CLASH
DETECTION**



**ENGINEERING
QUICK STAMPS**

GUARANTEED TOUGH.®



CAST-IN ANCHOR INSERTS

Bang-It®+ Bridge Bar

Description



The Bridge Bar allows for optional placement of Bang-It®+ inserts through the flute incline or positioned over the lower flute of steel deck profiles.

Base Materials

Normal-weight concrete,
Lightweight concrete

Anchor Material

Carbon steel and
engineered plastic



BANG-IT BRIDGE BAR

CAT #	HOLE SIZES	PACK
PFM3613000	7/8" & 1-1/4"	20



IMPACT, NAIL & PIN ANCHORS

Spike®

Description



The Spike® is a, one-piece, vibration resistant anchor for use in concrete, block or stone. Several head styles, including tamper-proof versions, and anchor materials are available.

Approvals

Tested in accordance with ASTM E488

Base Materials

Normal-weight concrete, Lightweight concrete, Grouted concrete masonry (CMU)

Anchor Material

Carbon steel and Type 316 stainless steel

The published length is measured from below the head to the end of the anchor.



MUSHROOM HEAD GRADE 8.2 CARBON STEEL SPIKE

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
05502-PWR	3/16" x 1"	3/16"	100	1,000
05503-PWR	3/16" x 1-1/4"	3/16"	100	1,000
05504-PWR	3/16" x 1-1/2"	3/16"	100	1,000
05506-PWR	3/16" x 2"	3/16"	100	1,000
05508-PWR	3/16" x 2-1/2"	3/16"	100	600
05510-PWR	3/16" x 3"	3/16"	100	600
05511-PWR	3/16" x 3-1/2"	3/16"	100	600
05512-PWR	3/16" x 4"	3/16"	100	600
05522-PWR	1/4" x 1"	1/4"	100	1,000
05523-PWR	1/4" x 1-1/4"	1/4"	100	1,000
05524-PWR	1/4" x 1-1/2"	1/4"	100	1,000
05526-PWR	1/4" x 2"	1/4"	100	600
05528-PWR	1/4" x 2-1/2"	1/4"	100	600
05530-PWR	1/4" x 3"	1/4"	100	600
05531-PWR	1/4" x 3-1/2"	1/4"	100	600
05532-PWR	1/4" x 4"	1/4"	100	600
05546-PWR	3/8" x 2"	3/8"	25	250
05548-PWR	3/8" x 2-1/2"	3/8"	25	150
05550-PWR	3/8" x 3"	3/8"	25	150
05551-PWR	3/8" x 3-1/2"	3/8"	25	150
05552-PWR	3/8" x 4"	3/8"	25	150
05554-PWR	3/8" x 5"	3/8"	25	150
05556-PWR	3/8" x 6"	3/8"	25	125
05569-PWR	1/2" x 2-3/4"	1/2"	50	200
05571-PWR	1/2" x 3-1/2"	1/2"	50	150
05572-PWR	1/2" x 4"	1/2"	25	125
05574-PWR	1/2" x 5"	1/2"	25	125
05577-PWR	1/2" x 6-1/2"	1/2"	25	100



FLAT HEAD GRADE 8.2 CARBON STEEL SPIKE

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
05608-PWR	3/16" x 2-1/2"	3/16"	100	600
05610-PWR	3/16" x 3"	3/16"	100	600
05612-PWR	3/16" x 4"	3/16"	100	600
05624-PWR	1/4" x 1-1/2"	1/4"	100	1,000
05626-PWR	1/4" x 2"	1/4"	100	600
05628-PWR	1/4" x 2-1/2"	1/4"	100	600
05630-PWR	1/4" x 3"	1/4"	100	600
05631-PWR	1/4" x 3-1/2"	1/4"	100	600
05632-PWR	1/4" x 4"	1/4"	100	500

IMPACT, NAIL & PIN ANCHORS

Spike®

Description



The Spike® is a, one-piece, vibration resistant anchor for use in concrete, block or stone. Several head styles, including tamper-proof versions, and anchor materials are available.

Approvals

Tested in accordance with ASTM E488

Base Materials

Normal-weight concrete, Lightweight concrete, Grouted concrete masonry (CMU)

Anchor Material

Carbon steel and Type 316 stainless steel



MUSHROOM HEAD 316 STAINLESS STEEL SPIKE

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
06602-PWR	3/16" x 1"	3/16"	100	600
06603-PWR	3/16" x 1-1/4"	3/16"	100	600
06604-PWR	3/16" x 1-1/2"	3/16"	100	600
06606-PWR	3/16" x 2"	3/16"	100	1,000
06623-PWR	1/4" x 1-1/4"	1/4"	100	1,000
06624-PWR	1/4" x 1-1/2"	1/4"	100	600
06626-PWR	1/4" x 2"	1/4"	100	600
06628-PWR	1/4" x 2-1/2"	1/4"	100	600
06630-PWR	1/4" x 3"	1/4"	100	600
06646-PWR	3/8" x 2"	3/8"	25	250
06648-PWR	3/8" x 2-1/2"	3/8"	25	250
06650-PWR	3/8" x 3"	3/8"	25	250

The published length is the overall length of the anchor.



SPECIAL APPLICATION

ROD HANGING PIPE SPIKE GRADE 8.2 CARBON STEEL

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
03755-PWR	1/4"	3/16"	100	600
03758-PWR	3/8"	1/4"	50	300



SPECIAL APPLICATION- SUSPENDED CEILINGS

TIE-WIRE SPIKE GRADE 8.2 CARBON STEEL

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
03756-PWR	3/16"	3/16"	100	600
03758-PWR	1/4"	1/4"	50	600



SPECIAL APPLICATION

CONCRETE FORMING SPIKE GRADE 8.2 CARBON STEEL

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
03795-PWR	3/16" x 1-1/2"	3/16"	100	600
03796-PWR	3/16" x 2"	3/16"	100	600
03797-PWR	3/16" x 2-3/4"	3/16"	100	600
03794-PWR	1/4" x 2-3/4"	1/4"	100	500

SPIKE INSTALLATION TOOLS

CAT #	DESCRIPTION	TIP O.D.	PACK	CTN
03790-PWR	SPIKE DRIVER 1000	1/2"	1	10

IMPACT, NAIL & PIN ANCHORS

Drive®

Description



The Drive® pin anchor is a one-piece, tamper-proof, pre-formed anchor available in carbon steel for use in concrete. The Drive® is available in multiple head configurations for a variety of anchoring applications.

Approvals



UL listings at
www.DEWALT.com

Base Materials

Normal-weight concrete

Anchor Material

Carbon steel



ROUND HEAD DRIVE

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
03211-PWR	1/4" x 1-1/4"	1/4"	100	1000
03241-PWR	1/4" x 1-1/2"	1/4"	100	1,000
03271-PWR	1/4" x 2"	1/4"	100	600
03301-PWR	1/4" x 2-1/2"	1/4"	100	600
03601-PWR	3/8" x 2"	3/8"	25	250
03631-PWR	3/8" x 2-1/2"	3/8"	25	150
03691-PWR	3/8" x 3-1/2"	3/8"	25	150
03781-PWR	1/2" x 3"	1/2"	25	150



FLAT HEAD DRIVE

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
03092-PWR	3/16" x 1-1/2"	3/16"	100	1,000
03122-PWR	3/16" x 2"	3/16"	100	1,000
03152-PWR	3/16" x 2-1/2"	3/16"	100	600
03162-PWR	3/16" x 3"	3/16"	100	600
03242-PWR	1/4" x 1-1/2"	1/4"	100	1,000
03272-PWR	1/4" x 2"	1/4"	100	600
03302-PWR	1/4" x 2-1/2"	1/4"	100	600
03332-PWR	1/4" x 3"	1/4"	100	600
03362-PWR	1/4" x 3-1/2"	1/4"	100	600
03392-PWR	1/4" x 4"	1/4"	100	600



TIE-WIRE DRIVE (13/64" TIE-WIRE HOLE)

CAT #	SIZE	DRILL HOLE DIAMETER	EYELET HOLE DIAMETER	PACK	CTN
03244-PWR	1/4" x 1-3/4"	1/4"	13/64"	500	—
03245-PWR	1/4" x 1-3/4"	1/4"	13/64"	100	1,000

IMPACT, NAIL & PIN ANCHORS

Zamac Hammer-Screw®

Description



The Zamac Hammer-Screw® is an improved performance, removable Zamac nail anchor designed for use in concrete, block, brick or stone with higher tension load capacities compared with traditional nailin anchors in concrete.

Approvals



Federal GSA Specification
– Meets the descriptive requirements of CID A-A 1925A Type 1

Base Materials

Normal-weight concrete, Concrete masonry (CMU), Brick masonry, Stone

Anchor Material

Zamac alloy with carbon steel or Perma-Seal drive screw



**ZAMAC HAMMER-SCREW -
MUSHROOM HEAD / NO. 2 PHILLIPS TYPE SCREW CARBON STEEL**

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
02839-PWR	1/4" x 3/4"	1/4"	100	500
02939-PWR	1/4" x 3/4"	1/4"	1,000	—
02840-PWR	1/4" x 1"	1/4"	100	500
02940-PWR	1/4" x 1"	1/4"	1,000	—
02842-PWR	1/4" x 1-1/4"	1/4"	100	500
02942-PWR	1/4" x 1-1/4"	1/4"	1,000	—
02844-PWR	1/4" x 1-1/2"	1/4"	100	500
02944-PWR	1/4" x 1-1/2"	1/4"	1,000	—
02846-PWR	1/4" x 2"	1/4"	100	500
02946-PWR	1/4" x 2"	1/4"	1,000	—
02848-PWR	1/4" x 2-1/4"	1/4"	100	500
02948-PWR	1/4" x 2-1/4"	1/4"	1,000	—
02850-PWR	1/4" x 3"	1/4"	100	500
02949-PWR	1/4" x 3"	1/4"	1,000	—

The published size includes the diameter and length of the anchor measured from under the shoulder of the anchor body.



DCH133M2
20V MAX® 1 In. Brushless
Cordless SDS PLUS D-Handle
Rotary Hammer Kit

IMPACT, NAIL & PIN ANCHORS

Zamac Nailin®

Description



The Zamac Nailin® is a nail drive anchor which has a body formed from Zamac alloy. Drive nails are available in carbon or stainless steel. The anchor can be used in concrete, block, brick or stone.

Approvals



Federal GSA Specification
—Meets the descriptive requirements of CID A-A 1925A Type 1 (mushroom head) & Type 2 (flat head)

Base Materials

Normal-weight concrete, Concrete masonry (CMU), Brick masonry, Stone

Anchor Material

Zamac alloy with carbon or stainless steel screw



ZAMAC NAILIN MUSHROOM HEAD WITH CARBON STEEL NAIL

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
02802-PWR	3/16" x 7/8"	3/16"	100	500
02803-PWR	3/16" x 7/8"	3/16"	1,000	—
02806-PWR	1/4" x 3/4"	1/4"	100	500
02807-PWR	1/4" x 3/4"	1/4"	1,000	—
02808-PWR	1/4" x 1"	1/4"	100	500
02809-PWR	1/4" x 1"	1/4"	1,000	—
02814-PWR	1/4" x 1-1/4"	1/4"	100	500
02815-PWR	1/4" x 1-1/4"	1/4"	1,000	—
02820-PWR	1/4" x 1-1/2"	1/4"	100	500
02821-PWR	1/4" x 1-1/2"	1/4"	1,000	—
02826-PWR	1/4" x 2"	1/4"	100	500
02827-PWR	1/4" x 2"	1/4"	1,000	—
02804-PWR	1/4" x 3"	1/4"	100	500
02805-PWR	1/4" x 3"	1/4"	1,000	—

The published size includes the diameter and length of the anchor measured from under the shoulder of the anchor body.



ZAMAC NAILIN MUSHROOM HEAD WITH STAINLESS STEEL NAIL

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
02858-PWR	1/4" x 1"	1/4"	100	500
02864-PWR	1/4" x 1-1/4"	1/4"	100	500
02870-PWR	1/4" x 1-1/2"	1/4"	100	500
02876-PWR	1/4" x 2"	1/4"	100	500

The published size includes the diameter and length of the anchor measured from under the shoulder of the anchor body.



ZAMAC NAILIN FLAT HEAD WITH CARBON STEEL NAIL

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
02836-PWR	1/4" x 1-1/2"	1/4"	100	500
02838-PWR	1/4" x 2"	1/4"	100	500

The published size includes the diameter and length of the anchor measured from under the shoulder of the anchor body.

IMPACT, NAIL & PIN ANCHORS

Nylon Nailin®

Description



The Nylon Nailin® is a nail drive anchor with an engineered plastic body and drive nails available in carbon and stainless steel. The anchor can be used in concrete, block, brick or stone.

Approvals



Federal GSA Specification
—Meets the descriptive requirements of CID A-A 1925A Type 1 (mushroom head) & Type 2 (flat head)

Base Materials

Normal-weight concrete, Concrete masonry (CMU), Brick masonry, Stone

Anchor Material

Engineered nylon with carbon or stainless steel drive pin



ROUND HEAD NYLON NAILIN - CARBON STEEL NAIL

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
02431-PWR	3/16" x 1"	3/16"	100	1,000
02451-PWR	3/16" x 1-1/2"	3/16"	100	1,000
02521-PWR	1/4" x 1"	1/4"	100	1,000
02541-PWR	1/4" x 1-1/2"	1/4"	100	1,000



FLAT HEAD NYLON NAILIN - CARBON STEEL NAIL

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
02542-PWR	1/4" x 1-1/2"	1/4"	100	1,000
02562-PWR	1/4" x 2"	1/4"	100	1,000



MUSHROOM HEAD NYLON NAILIN CARBON STEEL NAIL

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
02433-PWR	3/16" x 1"	3/16"	100	1,000
02513-PWR	1/4" x 3/4"	1/4"	100	1,000
02523-PWR	1/4" x 1"	1/4"	100	1,000
02543-PWR	1/4" x 1-1/2"	1/4"	100	1,000
02563-PWR	1/4" x 2"	1/4"	100	1,000
02573-PWR	1/4" x 3"	1/4"	100	1,000
02583-PWR	1/4" x 4"	1/4"	100	1,000



MUSHROOM HEAD NYLON NAILIN STAINLESS STEEL NAIL

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
02528-PWR	1/4" x 1"	1/4"	100	1,000
02548-PWR	1/4" x 1-1/2"	1/4"	100	1,000




MUSHROOM HEAD BODIES ONLY

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
02574-PWR	1/4" x 3"	1/4"	2,500	—

IMPACT, NAIL & PIN ANCHORS

Heli-Pin™

Description



The Heli-Pin™ facade anchor is a one-piece stainless steel helical wall tie system used for anchoring existing brick veneers to the back-up structural members without exposing hardware. They are ideal for stabilizing areas with missing or corroded wall ties as well as retrofits to multiple width masonry wall sections.

Approvals


Tested in accordance with CSA70

Base Materials

Normal-weight concrete, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Brick masonry, Wood studs, Metal studs, Natural Stone


Anchor Material

304 stainless steel




HELI-PIN ANCHOR

CAT #	SIZE	PACK	CTN
08341-PWR	8MM (5/16") x 6"	100	600
08342-PWR	8MM (5/16") x 8"	100	300
08343-PWR	8MM (5/16") x 10"	100	400
08344-PWR	8MM (5/16") x 12"	50	100



HELI-PIN SETTING TOOL


CAT #	DESCRIPTION	PACK	CTN
08345-PWR	SDS SETTING TOOL	1	2



IMPACT, NAIL & PIN ANCHORS

Safe-T™ Pin

Description



The Safe-T™ Pin is a nail anchor designed for use in concrete, grouted block and brick for a variety of anchoring applications. The Safe-T™ Pin is an improved alternative to traditional Zamac Nailin anchors where overhead use is not recommended.

Approvals

Tested in accordance with ASTM E 488


Tested in accordance with ICC-ES AC193 for use in structural concrete

Base Materials

Normal-weight concrete, Sand-lightweight concrete, Grout-filled concrete masonry (CMU), Brick masonry


Anchor Material

Zinc plated carbon steel



SAFE-T PIN ANCHOR

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
2800SD-PWR	6MM (1/4") x 1-3/8"	6MM	100	600



SAFE-T PIN DRILL BIT

CAT #	SIZE	USABLE LENGTH	PACK	CTN
02800-PWR	6MM	3-1/4"	250	—

LIGHT DUTY ANCHORS

Toggle Bolt

Description



The Toggle Bolt is a spring wing type wall anchor designed for hollow wall base materials and is available in multiple head styles and diameters.

Base Materials

Wallboard, Plaster, Hollow concrete masonry (CMU), Hollow core concrete plank, Plywood, Light gauge steel

Anchor Material

Carbon Steel



COMBO MUSHROOM HEAD

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
04023-PWR	1/8" x 2"	3/8"	50	500
04033-PWR	1/8" x 3"	3/8"	50	500
04043-PWR	1/8" x 4"	3/8"	50	500
04133-PWR	3/16" x 3"	1/2"	50	500
04143-PWR	3/16" x 4"	1/2"	50	500
04233-PWR	1/4" x 3"	5/8"	50	500
04243-PWR	1/4" x 4"	5/8"	50	500



COMBO ROUND HEAD

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
04021-PWR	1/8" x 2"	3/8"	50	500
04031-PWR	1/8" x 3"	3/8"	50	500
04041-PWR	1/8" x 4"	3/8"	50	500
04121-PWR	3/16" x 2"	1/2"	50	500
04131-PWR	3/16" x 3"	1/2"	50	500
04141-PWR	3/16" x 4"	1/2"	50	500
04151-PWR	3/16" x 5"	1/2"	50	500
04161-PWR	3/16" x 6"	1/2"	50	500
04231-PWR	1/4" x 3"	5/8"	50	500
04241-PWR	1/4" x 4"	5/8"	50	500
04251-PWR	1/4" x 5"	5/8"	50	500
04261-PWR	1/4" x 6"	5/8"	50	500
04431-PWR	3/8" x 3"	7/8"	25	250
04441-PWR	3/8" x 4"	7/8"	25	250
04451-PWR	3/8" x 5"	7/8"	25	125
04461-PWR	3/8" x 6"	7/8"	25	125
04541-PWR	1/2" x 4"	1-1/4"	25	125



SLOTTED HEX HEAD

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
04038-PWR	1/8" x 3"	3/8"	50	500

LIGHT DUTY ANCHORS


Toggle Bolt

Description



The Toggle Bolt is a spring wing type wall anchor designed for hollow wall base materials and is available in multiple head styles and diameters.

Base Materials	Wallboard, Plaster, Hollow concrete masonry (CMU), Hollow core concrete plank, Plywood, Light gauge steel
Anchor Material	Carbon Steel



CAT #	SIZE	DRILL DIAMETER	PACK	CTN
04132-PWR	3/16" x 3"	1/2"	50	500
04142-PWR	3/16" x 4"	1/2"	50	500
04232-PWR	1/4" x 3"	5/8"	50	500



TIE WIRE ACOUSTICAL TOGGLE				
CAT #	SIZE	DRILL DIAMETER	WIRE HOLE SIZE	PACK
04247-PWR	1/4" x 4"	5/8"	7/32"	100
04257-PWR	1/4" x 5"	5/8"	7/32"	100



TOGGLE WINGS ONLY				
CAT #	SIZE	DRILL DIAMETER	PACK	CTN
04000-PWR	1/8"	3/8"	100	500
04020-PWR	3/16"	1/2"	100	1,000
04220-PWR	1/4"	5/8"	100	1,000
04430-PWR	3/8"	7/8"	50	500
04540-PWR	1/2"	1 1/4"	25	125

DWH050K
Large Hammer Dust
Extraction-Hole Cleaning





LIGHT DUTY ANCHORS

Strap-Toggle™

Description




The Strap-Toggle™ is a heavy duty hollow wall anchor consisting of a carbon steel wing and a locking cap/ratchet leg assembly molded from engineered plastic. It is available in multiple diameters and is removable.

Base Materials

Wallboard, Hollow concrete masonry (CMU)

Anchor Material

Engineered plastic and carbon steel wings



STRAP-TOGGLE (NOT PACKED WITH SCREWS)

CAT #	SIZE	DRILL DIAMETER	WALL THICKNESS	PACK	CTN
04052-PWR	3/16" x 4	1/2"	3/8" - 2-1/2"	50	300
04054-PWR	1/4" x 4-1/2"	1/2"	3/8" - 2-1/2"	50	300
04056-PWR	3/8" x 4"	3/4"	3/8" - 2-1/2"	25	150
04058-PWR	1/2" x 4	3/4"	3/8" - 2-1/2"	25	150

STRAP-TOGGLE INSTALLATION



LIGHT DUTY ANCHORS

Zip-Toggle®

Description



The Zip-Toggle® is a self drilling hollow gypsum wallboard anchor designed to provide superior performance without the need to pre-drill larger diameter holes. The Zip-Toggle is packaged with its own No. 6 x 2" lubricated screw.

Base Materials

Wallboard

Anchor Material

Zinc



ZIP-TOGGLE

CAT #	SIZE	SCREWS	PACK	CTN
02295-PWR	METAL ZIP-TOGGLE WITH SCREWS	NO. 6 x 2"	50	250

LIGHT DUTY ANCHORS

Wall Dog®

Description



The Wall-Dog® is a one-piece screw anchor, with high-profile corkscrew-like threads that provide a powerful hold in multiple materials. It is available in several color finishes and head styles and is self drilling in some base materials.

Base Materials

Grout-filled concrete masonry, Hollow concrete masonry, Brick masonry, Wallboard, Plywood, Plaster

Anchor Material

Carbon steel

*Screws with a white finish have a white head and a zinc body



WALL-DOG COMBO HEX WASHER HEAD

CAT #	SCREW LENGTH	COLOR	PACK	CTN
02265-PWR	1-1/4"	ZINC	5,000	—
02271-PWR	1-1/4"	ZINC	100	500



WALL-DOG PHILLIPS WAFER HEAD

CAT #	SCREW LENGTH	COLOR	PACK	CTN
02277-PWR	1-1/2"	WHITE*	100	500
02278-PWR	2"	WHITE*	100	500
02279-PWR	2-1/4"	WHITE*	100	500
02280-PWR	2-1/2"	WHITE*	100	500

Phillips® is a registered trademark of Phillips Consumer Electronics Corporation.



WALL-DOG ROBERTSON HEAD

CAT #	SCREW LENGTH	COLOR	PACK	CTN
02266-PWR	1-1/4"	ZINC	100	500
02281-PWR	1-1/4"	ZINC	5,000	—



WALL-DOG PHILLIPS OVAL HEAD

CAT #	SCREW LENGTH	COLOR	PACK	CTN
02288-PWR	1-1/4"	BLACK	100	500
02314-PWR	1-1/4"	ZINC	100	1,000
02317-PWR	1-1/4"	ZINC	5,000	—
02328-PWR	1-1/4"	WHITE*	100	1,000



WALL-DOG PHILLIPS PAN HEAD

CAT #	SCREW LENGTH	COLOR	PACK	CTN
02273-PWR	1-1/2"	WHITE*	100	600
02274-PWR	1-1/2"	BRONZE	100	600
02275-PWR	1-1/2"	ZINC	100	600
02276-PWR	1-1/2"	BLACK	100	600
02286-PWR	1-1/4"	BLACK	100	500
02294-PWR	1-1/4"	BRASS	100	500
02315-PWR	1-1/4"	ZINC	5,000	—
02316-PWR	1-1/4"	ZINC	100	1,000
02330-PWR	1-1/4"	WHITE*	100	1,000
02398-PWR	1-1/4"	WHITE*	5,000	—

LIGHT DUTY ANCHORS

Zip-It® & Zip-It® Jr.

Description



The Zip-It® anchor is a one-piece self drilling anchor designed for use in gypsum wallboard. It is available in both engineered nylon and Zamac alloy designed for use with No. 8 screws. The Zip-It® Jr. is also available in engineered nylon and Zamac alloy designed for use with No. 6 screws.

Base Materials

Wallboard

Anchor Material

Engineered Plastic or
Zamac Alloy



NYLON ZIP-IT

CAT #	DESCRIPTION	WALL THICKNESS	PACK	CTN
02345-PWR	NYLON ZIP-IT NO SCREWS	3/8" - 1"	100	1,000
02348-PWR	NYLON ZIP-IT WITH #8 x 1" SCREWS	3/8" - 1"	100	1,000
02355-PWR	NYLON ZIP-IT NO SCREWS (BULK)	3/8" - 1"	5,000	—
09630-PWR	NYLON ZIP-IT NO SCREWS (BULK)	3/8" - 1"	5,000	—



NYLON ZIP-IT JR.

CAT #	DESCRIPTION	WALL THICKNESS	PACK	CTN
02350-PWR	NYLON ZIP-IT JR. NO SCREWS	3/8" - 5/8"	100	1,000
02351-PWR	NYLON ZIP-IT JR. WITH #6 x 1" SCREWS	3/8" - 5/8"	100	1,000
02365-PWR	NYLON ZIP-IT JR. NO SCREWS (BULK)	3/8" - 5/8"	5,000	—



ZINC ZIP-IT

CAT #	DESCRIPTION	WALL THICKNESS	PACK	CTN
02346Z-PWR	ZINC ZIP-IT NO SCREWS	3/8" - 1"	100	1,000
02349Z-PWR	ZINC ZIP-IT WITH #8 x 1" SCREWS	3/8" - 1"	100	1,000
02356Z-PWR	ZINC ZIP-IT NO SCREWS (BULK)	3/8" - 1"	5,000	—




ZINC ZIP-IT JR.

CAT #	DESCRIPTION	WALL THICKNESS	PACK	CTN
02362Z-PWR	ZINC ZIP-IT JR. NO SCREWS	3/8" - 5/8"	100	1,000
02363Z-PWR	ZINC ZIP-IT JR. NO SCREWS (BULK)	3/8" - 5/8"	5,000	—
02364Z-PWR	ZINC ZIP-IT JR. WITH #6 x 1" SCREWS	3/8" - 5/8"	100	1,000

LIGHT DUTY ANCHORS
Zip-It® & Zip-It® Jr.

Description




The Zip-It® anchor is a one-piece self drilling anchor designed for use in gypsum wallboard. It is available in both engineered nylon and Zamac alloy designed for use with No. 8 screws. The Zip-It® Jr. is also available in engineered nylon and Zamac alloy designed for use with No. 6 screws.

Base Materials Wallboard

Anchor Material Engineered Plastic or Zamac Alloy



ZIP-IT KITS				
CAT #	DESCRIPTION	WALL THICKNESS	PACK	CTN
02368-PWR	50 NYLON ZIP-IT ANCHORS WITH #8 x 1" SCREWS	3/8" - 1"	1	—
02369Z-PWR	50 ZINC ZIP-IT ANCHORS WITH #8 x 1" SCREWS	3/8" - 1"	1	—



ZIP-IT JR. KITS				
CAT #	DESCRIPTION	WALL THICKNESS	PACK	CTN
02367-PWR	50 NYLON ZIP-IT JR. WITH #6 x 1" SCREWS (INCLUDES #2 PHILLIPS DRIVER BIT)	3/8" - 5/8"	1	—



LIGHT DUTY ANCHORS

Poly-Toggle®

Description



The Poly-Toggle® is a screw actuated hollow wall anchor for use in paneling, wallboard, and solid masonry. The Poly-Toggle anchor is available in 6 sizes to match the most common wall thicknesses of hollow base materials. In solid base materials, the anchor can be used by removing the outer wings.

Base Materials

Solid base materials, Wallboard, Hollow concrete masonry (CMU)

Anchor Material

Engineered plastic



POLY-TOGGLE

CAT #	SIZE	WALL THICKNESS	DRILL DIAMETER	PACK	CTN
02303-PWR	SHORT	3/8"	5/16"	100	1,000
02304-PWR	MEDIUM	1/2"	5/16"	100	1,000
02305-PWR	LONG	5/8"	5/16"	100	1,000

LIGHT DUTY ANCHORS

Sharkie™

Description



The Sharkie™ is a light duty wall anchor engineered for strength in a variety of base materials. During installation, the screw extrudes and compresses the anchor into the base material while distributing the forces over the maximum area possible.

Base Materials

Concrete, Brick, Cinder block, Wood, Masonry, Ceramic tile, Plaster, Stone, Stucco, Aerated concrete, Flakeboard, Wallboard

Anchor Material

Engineered plastic




SHARKIE ANCHOR

CAT #	DESCRIPTION	PACK	CTN
07580-PWR	SHARKIE ANCHOR FLANGE #4 - #10	100	1,000
07582-PWR	SHARKIE ANCHOR FLANGE #6 - #12	100	1,000
07584-PWR	SHARKIE ANCHOR FLANGE #8 - #14	100	500

LIGHT DUTY ANCHORS


Bantam Plug

Description



The Bantam Plug is an injection molded engineered plastic anchor designed for use with lightweight fixtures using sheet metal or wood screws.

Base Materials	Normal-weight concrete, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Solid or hollow brick masonry, Gypsum wallboard
Anchor Material	Engineered plastic



BANTAM PLUG (NOT PACKED WITH SCREWS)

CAT #	SIZE	DRILL DIAMETER	PACK	CTN
07559-PWR	#6 - #8 x 3/4"	3/16"	100	5,000
07569-PWR	#8 - #10 x 7/8"	3/16"	100	5,000
07579-PWR	#10 - #12 x 1"	1/4"	100	5,000
07589-PWR	#14 - #16 x 1-1/2"	5/16"	50	2,500

MASTER PACK

CAT #	KIT #	ANCHOR SIZE	SCREW SIZE	ANCHORS & SCREWS	PACK	CTN
08934-PWR	B-8	#8 - #10	#8 x 1"	100	1	10
08936-PWR	B-10	#10 - #12	#10 x 1"	100	1	10
08938-PWR	B-12	#10 - #12	#12 x 1"	100	1	10




BANTAM KITS

CAT #	DESCRIPTION	PACK	CTN
008937-PWR	#10 x 1-1/4" PAN HEAD ANCHOR KIT: 10 - 12 BANTAM ANCHORS (100 QTY.) 10 x 1-1/4" TAPPING PAN COMBO SCREWS (100 QTY.) 1/4 C/T DRILL BIT (1 QTY.)	1	10
008941-PWR	#10 x 1" HEX HEAD ANCHOR KIT: 10 x 1" BANTAM ANCHORS (100 QTY.) 10 x 1" HEX WASHER HEAD SCREWS (100 QTY.) 1/4 C/T DRILL BIT (1 QTY.) 5/16 HEX DRIVER (1 QTY.)	1	10
008948-PWR	#10 SUPER YELLOW ANCHOR KIT: #10 - 12 YELLOW RIBBED ANCHORS (100 QTY.) #10 x 1" PAN HD SCREWS (100 QTY.) 1/4 x 4 MASONRY BIT (1 QTY.)	1	10

LIGHT DUTY ANCHORS

Fluted Plastic Anchor

Description



The Fluted Plastic Anchor is an injected molded engineered ductile plastic anchor designed for light duty fastening applications in multiple base materials. It is designed to be used with sheet metal or wood screws.

Base Materials	Normal-weight concrete
Anchor Material	Engineered plastic



FLUTED PLASTIC ANCHOR

CAT #	SIZE	COLOR	DRILL DIAMETER	PACK	CTN
07500-PWR	#4 - #6 x 1"	WHITE	3/16"	100	5,000
07510-PWR	#10 - #12 x 1"	GREEN	1/4"	100	5,000
07515-PWR	#10 - #12 x 1-1/4"	GREEN	1/4"	100	1,000
07520-PWR	#10 - #12 x 1-1/2"	GREEN	1/4"	100	1,000
07530-PWR	#14 x 1-1/2"	BLUE	5/16"	100	1,000

CHEMICAL ANCHORING

AC200+™

Description



AC200+™ is a two-component, fast curing, ultra high strength adhesive anchoring system that is designed for bonding threaded rod and reinforcing bar hardware into drilled holes in concrete base materials and for post-installed reinforcing bar connections (rebar development).

Approvals



ICC-ES ESR-4027
(Concrete & PIR)

Conforms to AC308 / ACI 355.4

Compliant with
NSF/ANSI Standard 61
for drinking water system
components

Department of
Transportation listings

Base Materials

Normal-weight concrete,
Lightweight concrete,
Grouted concrete masonry
(CMU)

Size Range

3/8" to 2" diameter
threaded rod
No. 3 to No. 14 rebar

Installation Conditions

Dry concrete, Water-
saturated concrete (Wet),
Water-filled holes (Flooded)



AC200+ CARTRIDGES

CAT #	DESCRIPTION	PACK	CTN	PALLET
PFC1271050	9.5 FL. OZ. QUICK-SHOT	12	36	648
PFC1271150	28 FL. OZ. DUAL CARTRIDGE	8	—	240

A PFC1641600 mixing nozzle is packaged with each cartridge.

AC200+ mixing nozzles must be used to ensure complete and proper mixing of the adhesive.

AC200+ EXTRA MIXING NOZZLES

CAT #	DESCRIPTION	PACK	CTN
PFC1641600	MIXING NOZZLE (WITH 8" EXTENSION)	2	24

DISPENSERS

CAT #	TYPE
08437-PWR	STANDARD QUICK-SHOT MANUAL - 9 OZ. / 9.5 OZ.
DCE560B	20V QUICK-SHOT ADHESIVE DISPENSER (BARE)
DCE560D1	20V QUICK-SHOT ADHESIVE DISPENSER (KIT)
08494-PWR	STANDARD MANUAL 10:1 - 28 OZ.
DCE595B	20V ACRYLIC DISPENSER 10:1 28 OZ. (BARE)
DCE595D1	20V ACRYLIC DISPENSER 10:1 28 OZ. (KIT)
08496SD-PWR	PNEUMATIC 10:1 DISPENSER - 28 OZ.



CHEMICAL ANCHORING

AC100+ Gold®

Description



AC100+ Gold® is a two-component, fast curing, high strength adhesive anchoring system that is designed for bonding threaded rod and reinforcing bar elements into drilled holes in concrete and masonry base materials. It can be considered for use in solid base materials as well as hollow base materials with screen tubes.

Approvals



ICC-ES ESR-2582 (Concrete); ICC-ES ESR-3200 (Masonry); ESR-4105 (Unreinforced Masonry (URM))
Compliant with NSF/ANSI Standard 61 for drinking water system components
Conforms to ASTM C 881 and AASHTO M235 Types I, II, IV, and V Grade 3 Classes A & B
Department of Transportation listings

Base Materials

Normal-weight concrete, Lightweight concrete, Grouted concrete/masonry (CMU), Hollow concrete masonry (CMU), Hollow core concrete, Brick masonry, Unreinforced masonry (URM Walls)

Size Range

3/8" to 1-1/4" diameter threaded rod No. 3 to No. 10 rebar

Installation Conditions

Dry concrete, Water-saturated concrete (Wet), Water-filled holes (Flooded)



AC100+ GOLD CARTRIDGES

CAT #	DESCRIPTION	PACK	CTN	PALLET
8478SD-PWR	9.5 FL. OZ. QUICK-SHOT	12	36	684
8490SD-PWR	28 FL. OZ. DUAL CARTRIDGE	8	—	240

A 08293-PWR mixing nozzle is included with each 9.5 oz. cartridge and a PFC1641600 mixing nozzle is included with each 28 oz. cartridge.

AC100+ Gold mixing nozzles must be used to ensure complete and proper mixing of the adhesive.

AC100+ GOLD EXTRA MIXING NOZZLES

CAT #	DESCRIPTION	PACK	CTN
08293-PWR	MIXING NOZZLE FOR AC100+ GOLD	2	24
PFC1641600	MIXING NOZZLE (WITH 8" EXTENSION)	2	24

DISPENSERS

CAT #	TYPE
08437-PWR	STANDARD QUICK-SHOT MANUAL - 9 OZ. / 9.5 OZ.
DCE560B	20V QUICK-SHOT ADHESIVE DISPENSER (BARE)
DCE560D1	20V QUICK-SHOT ADHESIVE DISPENSER (KIT)
08494-PWR	STANDARD MANUAL 10:1 - 28 OZ.
DCE595B	20V ACRYLIC DISPENSER 10:1 28 OZ. (BARE)
DCE595D1	20V ACRYLIC DISPENSER 10:1 28 OZ. (KIT)
08496SD-PWR	PNEUMATIC 10:1 DISPENSER - 28 OZ.



CHEMICAL ANCHORING

AC50™

Description



AC50™ is a two-component, fast curing, adhesive anchoring system that is designed for bonding threaded rod and reinforcing bar hardware into drilled holes in solid concrete base materials.

Approvals



Conforms to ASTM C 881 and AASHTO M235 Types I, II, IV, and V Grade 3 Classes A & B

Department of Transportation listings

Base Materials

Normal-weight concrete

Size Range

3/8" to 1" diameter threaded rod
No. 3 to No. 8 rebar

Installation Conditions

Dry concrete



AC50 CARTRIDGES

CAT #	DESCRIPTION	PACK	CTN	PALLET
08497-PWR	28 FL. OZ. DUAL CARTRIDGE	8	—	240

A PFC1641600 mixing nozzle is packaged with each cartridge.

AC50+ mixing nozzles must be used to ensure complete and proper mixing of the adhesive.

AC50 EXTRA MIXING NOZZLES

CAT #	DESCRIPTION	PACK	CTN
PFC1641600	MIXING NOZZLE (WITH 8" EXTENSION)	2	24

DISPENSERS

CAT #	TYPE
08494-PWR	STANDARD MANUAL 10:1 - 28 OZ.
DCE595B	20V ACRYLIC DISPENSER 10:1 28 OZ. (BARE)
DCE595D1	20V ACRYLIC DISPENSER 10:1 28 OZ. (KIT)
08496SD-PWR	PNEUMATIC 10:1 DISPENSER - 28 OZ.



CHEMICAL ANCHORING

Pure220+™

Description



Pure220+™ is a two-component, standard curing, ultra high strength adhesive anchoring system that is designed for bonding threaded rod and reinforcing bar hardware into drilled holes in concrete base materials and for post-installed reinforcing bar connections (rebar development).

Approvals



ICC-ES ESR-5144
(Concrete & PIR)

Conforms to requirements of ASTM C881 including C882 and AASHTO M235, Types I, II, IV and V, Grade 3, Classes B & C

Compliant with NSF/ANSI 61 for drinking water system components

Florida Building Code

Department of Transportation listings

Approved for use in diamond core drilled holes.

Base Materials

Normal-weight concrete, Lightweight concrete, Grouted concrete masonry

Size Range

3/8" to 2" diameter threaded rod
No. 3 to No.14 rebar

Installation Conditions

Dry concrete, Water-saturated concrete (Wet), Water-filled holes (Flooded), Underwater concrete (Submerged)



PURE220+ CARTRIDGES (1:1 MIX RATIO)

CAT #	DESCRIPTION	PACK	PALLET
DFC114110	PURE220+ 9.5 FL. OZ. QUICK-SHOT CARTRIDGE	12	846
DFC114121	PURE220+ 20.5 FL. OZ. DUAL CARTRIDGE	12	720

A PFC1641600 mixing nozzle is packaged with each cartridge.

Pure220+ mixing nozzles must be used to ensure complete and proper mixing of the adhesive.

Pure220+ adhesive cartridges are Made In the USA. Installation accessories are globally sourced.

CARTRIDGE SYSTEM MIXING NOZZLES AND NOZZLE EXTENSIONS

CAT #	DESCRIPTION	PACK	CTN
PFC1641600	MIXING NOZZLE (WITH 8" EXTENSION)	2	24
08609-PWR	HIGH FLOW MIXING NOZZLE (WITH 8" EXTENSION)	2	24
08281-PWR	MIXING NOZZLE EXTENSION, 8" LONG	2	24
08297-PWR	MIXING NOZZLE EXTENSION, 20" LONG	1	12
PFC1640600	FLEXIBLE EXTENSION HOSE, 25 FT. (5/8" O.D.)	1	12

DISPENSING TOOLS FOR INJECTION ADHESIVE

CAT #	DESCRIPTION	PACK	CTN
08437-PWR	MANUAL CAULKING GUN FOR QUICK-SHOT CARTRIDGE	1	12
DCE560D1	CORDLESS 20V BATTERY POWERED DISPENSING TOOL FOR QUICK-SHOT	1	—
08409-PWR	20.5 FL. OZ. STANDARD METAL MANUAL TOOL	1	10
DCE591B	20.5 FL. OZ. CORDLESS 20V BATTERY POWERED DISPENSING TOOL (BARE)	1	—
DCE591D1	20.5 FL. OZ. CORDLESS 20V BATTERY POWERED DISPENSING TOOL (KIT)	1	—
08459-PWR	20.5 FL. OZ. PNEUMATIC TOOL	1	—

CHEMICAL ANCHORING

Pure110+®

Description



Pure110+® is a two-component, standard curing, high strength adhesive anchoring system that is designed for bonding threaded rod and reinforcing bar hardware into drilled holes in concrete base materials and for post-installed reinforcing bar connections (rebar development).

Approvals



ICC-ES ESR-3298
(Concrete & PIR)

Conforms to ASTM C 881 and AASHTO M235 Types I, II, IV, and V Grade 3 Classes B & C

Compliant with NSF/ANSI 61 for drinking water system components

Department of Transportation listings

Base Materials

Normal-weight concrete, Lightweight concrete, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU)

Size Range

3/8" to 1-1/4" diameter threaded rod No.3 to No.11 rebar

Installation Conditions

Dry concrete, Water-saturated concrete (Wet), Water-filled holes (Flooded), Underwater concrete (Submerged)



PURE110+ CARTRIDGES (1:1 MIX RATIO)

CAT #	DESCRIPTION	PACK	PALLET
08310SD-PWR	PURE110+ 9.5 FL. OZ. QUICK-SHOT CARTRIDGE	12	432
08321SD-PWR	PURE110+ 20.5 FL. OZ. DUAL CARTRIDGE	12	540

A PFC1641600 is included with each 9.5 oz. cartridge and a 08609-PWR is included with each 20.5 oz. cartridge.

Pure110+ mixing nozzles must be used to ensure complete and proper mixing of the adhesive.

Pure110+ adhesive cartridges are Made In the USA. Installation accessories are globally sourced.

CARTRIDGE SYSTEM MIXING NOZZLES AND NOZZLE EXTENSIONS

CAT #	DESCRIPTION	PACK	CTN
PFC1641600	MIXING NOZZLE (WITH 8" EXTENSION)	2	24
08609-PWR	HIGH FLOW MIXING NOZZLE (WITH 8" EXTENSION)	2	24
08281-PWR	MIXING NOZZLE EXTENSION, 8" LONG	2	24
08297-PWR	MIXING NOZZLE EXTENSION, 20" LONG	1	12
PFC1640600	FLEXIBLE EXTENSION HOSE, 25 FT. (5/8" O.D.)	1	12

DISPENSING TOOLS FOR INJECTION ADHESIVE

CAT #	DESCRIPTION	PACK	CTN
08437-PWR	MANUAL CAULKING GUN FOR QUICK-SHOT CARTRIDGE	1	12
DCE560D1	CORDLESS 20V BATTERY POWERED DISPENSING TOOL FOR QUICK-SHOT	1	—
08409-PWR	20.5 FL. OZ. STANDARD METAL MANUAL TOOL	1	10
DCE591D1	20.5 FL. OZ. CORDLESS 20V BATTERY POWERED DISPENSING TOOL	1	—
08459-PWR	20.5 FL. OZ. PNEUMATIC TOOL	1	—



CHEMICAL ANCHORING

Pure50+™

Description



Pure50+™ is a two-component, standard curing, adhesive anchoring system that is designed for bonding threaded rod and reinforcing bar hardware into drilled holes in solid concrete base materials. It can also be considered for bonding together cured concrete and masonry materials together as well as filling large cracks and abandoned holes.

Approvals



ICC-ES ESR-3576
(Concrete)

Conforms to ASTM C 881 and AASHTO M235 Types I, II, IV, and V Grade 3 Classes B & C (also meets Type III except for elongation)

Compliant with NSF/ANSI Standard 61 for Drinking Water System Components

Department of Transportation listings

Base Materials

Normal-weight concrete, Lightweight concrete

Size Range

3/8" to 1-1/4" diameter threaded rod No. 3 to No. 10 rebar

Installation Conditions

Dry concrete, Water-saturated concrete (Wet), Water-filled holes (Flooded)



PURE50+ CARTRIDGES

CAT #	DESCRIPTION	PACK	PALLET
08600-PWR	PURE50+ 9.5 FL. OZ. QUICK-SHOT CARTRIDGE	12	432
08605-PWR	PURE50+ 20.5 FL. OZ. CARTRIDGE	12	540

A PFC1641600 is included with each 9.5 oz. cartridge and a 08609-PWR is included with each 20.5 oz. cartridge.

Pure50+ mixing nozzles must be used to ensure complete and proper mixing of the adhesive.

CARTRIDGE SYSTEM MIXING NOZZLES AND NOZZLE EXTENSIONS

CAT #	DESCRIPTION	PACK	CTN
PFC1641600	MIXING NOZZLE (WITH 8" EXTENSION) FOR PURE50+ QUICK-SHOT	1	12
08609-PWR	HIGH FLOW MIXING NOZZLE (WITH 8" EXTENSION)	2	24
08281-PWR	MIXING NOZZLE EXTENSION, 8" LONG	2	24
08297-PWR	MIXING NOZZLE EXTENSION, 20" LONG	1	12

DISPENSING TOOLS FOR INJECTION ADHESIVE

CAT #	DESCRIPTION	PACK	CTN
08437-PWR	MANUAL CAULKING GUN FOR QUICK-SHOT CARTRIDGE	1	12
DCE560D1	QUICK-SHOT 20V BATTERY POWERED DISPENSING TOOL	1	—
08409-PWR	20.5 FL. OZ. STANDARD METAL MANUAL TOOL	1	10
DCE591D1	20.5 FL. OZ. 20V BATTERY POWERED DISPENSING TOOL	1	—
08459-PWR	20.5 FL. OZ. PNEUMATIC TOOL	1	—



**GLASS CAPSULE
CHEMICAL ANCHORS**

Hammer-Capsule®

Description



The Hammer-Capsule® system consists of a self contained, single use, two-part glass capsule into which threaded anchor rod or reinforcing bars can be directly driven without the need for a chisel point or spinning action. It is designed for use in the installation of 3/8" through 1" diameter threaded rod in solid concrete and masonry materials. It can also be used to install reinforcing bars.

Approvals



Department of
Transportation listings

Base Materials

Normal-weight concrete,
Grouted concrete masonry
(CMU)

Size Range

3/8" to 1" diameter
threaded rod
No. 3 to No. 8 rebar

Installation Conditions

Dry concrete, Water-
saturated concrete (Wet),
Water-filled holes (Flooded)



HAMMER-CAPSULE

CAT #	DESCRIPTION	PACK	CTN
06702-PWR	3/8" HAMMER - CAPSULE	10	500
06703-PWR	1/2" HAMMER - CAPSULE	10	200
06704-PWR	5/8" HAMMER - CAPSULE	10	100
06705-PWR	3/4" HAMMER - CAPSULE	6	60
06706-PWR	7/8" HAMMER - CAPSULE	6	60
06707-PWR	1" HAMMER - CAPSULE	6	60

Fast easy installation - no special adapters required for setting.

Excellent chemical resistance.

Components are mixed during installation of rod or rebar.

Pre-measured chemical component volumes – no waste and simplified placement.



DCH775X2
60V MAX® 2 in. Brushless Cordless
SDS MAX Combination Rotary
Hammer Kit

ADHESIVE SEALANTS

PowerStick™

Description



PowerStick™ is a one-component universal adhesive/sealant with high bond strength and superior flexibility. PowerStick is non-shrink, can be applied on wet surfaces, is virtually odorless, has excellent UV resistance, features high aggressive initial tack, is nonreactive with the substrate, and can be painted after curing.

Base Materials

Concrete, Masonry, Metals, Plastics, Wood



POWERSTICK

CAT #	DESCRIPTION	COLOR	PACK	PALLET
08166N-PWR	POWERSTICK 10 OZ.	WHITE	12	1,200
08168N-PWR	POWERSTICK 10 OZ.	GRAY	12	1,200

DISPENSING TOOLS FOR INJECTION ADHESIVE

CAT #	DESCRIPTION	PACK	CTN
08437-PWR	MANUAL CAULKING GUN FOR QUICK-SHOT CARTRIDGE	1	12
DCE560D1	QUICK-SHOT 20V BATTERY POWERED DISPENSING TOOL	1	—

EXPANSION FOAMS

PowerFoam™

Description



PowerFoam™ is a single component, moisture curing expanding polyurethane foam used to seal and fill various types of building elements. It has a 2-3 times expansion rate and an R-5 insulation value. PowerFoam™ can be used in a wide variety of applications. Use it to fill, seal or insulate. It is used to block drafts, stop leaks, save energy, adhere to all types of construction material, deadens sound, acts as a buoyancy material once cured, controls radon, confines asbestos fibers, and can be used in HVAC applications. PowerFoam™ also seals and keeps out insects and rodents.

Approvals



Full UL listings in product brochure or at www.DEWALT.com

Base Materials

Concrete, Masonry, Wood, Metal, Aluminum, Steel



POWERFOAM

CAT #	DESCRIPTION	PACK	PALLET
08130N-PWR	POWERFOAM 12 OZ.	12	1,020
08132N-PWR	POWERFOAM 29 OZ.	12	612

One-part polyurethane expanding foam that sets and cures into its final form by reacting to moisture and humidity present in the air.

PowerFoam's exceptional ability to bond allows it to be applied to various building elements including the surfaces of concrete brick block wood steel aluminum and other miscellaneous metals.

As it is being dispensed PowerFoam has a neutral odor.

Cured foam is standard yellow.

EXPANSION FOAMS

TriggerFoam™ Pro

Description



TriggerFoam™ Pro is a family of one part polyurethane expanding foam used to seal and fill various types of building elements. TriggerFoam™ Pro Fire Block Formula is designed to effectively block the spread of smoke and flame in Type V residential construction. TriggerFoam™ Pro Window and Door features a low pressure formulation that will not distort windows and door frames. TriggerFoam™ Pro All Season Formula features an extended temperature range that allows application temperatures as low as 23°F (-5°C). TriggerFoam™ Pro is dispensed through a special gun that allows the user to control the rate of flow as well as the size of the bead for more precise placement of the product.

Approvals



ICC-ES ESR-3263 Thermal and Moisture Protection and annular space protection for wood fire blocking: FireBlock Formula Window & Door Formula All Season Formula

Full UL listings in product brochure or at www.DEWALT.com

Base Materials

Concrete, Masonry, Wood, Metal, Aluminum, Steel



TRIGGERFOAM PRO

CAT #	DESCRIPTION	PACK	PALLET
08133P-PWR	FIRE BLOCK FORMULA 29 OZ.	12	612
08134P-PWR	WINDOW & DOOR FORMULA 29 OZ.	12	612
08135P-PWR	ALL SEASON FORMULA 29 OZ.	12	612
08136N-PWR	STANDARD FORMULA 29 OZ.	12	612



TRIGGERFOAM PRO DISPENSERS

CAT #	TYPE	PACK	CTN
08128-PWR	DELUXE METAL GUN	1	10

DISPENSING ACCESSORIES

CAT #	TYPE	PACK	CTN
08147-PWR	TRIGGERFOAM PRO CLEANER 17 FL. OZ.	1	6

Professional gun applied normal expansion polyurethane foam sealant with an extended temperature range which allows for use at temperatures as low as 23°F.

It is designed to seal gaps insulate and deaden sound.

Recommended for use in heating and air conditioning electrical and plumbing applications.

ADHESIVE ACCESSORIES

Dispensing Tools

Description



Manual, pneumatic, and battery operated dispensing tools for the full line of DEWALT adhesive anchoring products.



STANDARD MANUAL DISPENSERS		
CAT #	DESCRIPTION	PACK
08437-PWR	STANDARD QUICK-SHOT MANUAL DISPENSER 9 / 9.5 OZ.	1
08409-PWR	STANDARD 1:1 MANUAL DISPENSER 20.5 OZ.	1
08494-PWR	STANDARD 10:1 MANUAL DISPENSER 28 OZ.	1



PNEUMATIC DISPENSERS		
CAT #	DESCRIPTION	PACK
08459-PWR	PNEUMATIC 1:1 DISPENSER 20.5 OZ.	1
8496SD-PWR	PNEUMATIC 10:1 DISPENSER 28 OZ.	1



CORDLESS 20V DISPENSERS		
CAT #	DESCRIPTION	PACK
DCE560B	20V QUICK-SHOT DISPENSER (BARE)	1
DCE560D1	20V QUICK-SHOT DISPENSER (KIT)	1
DCE591B	20V EPOXY DISPENSER 1:1 20.5 OZ. (BARE)	1
DCE591D1	20V EPOXY DISPENSER 1:1 20.5 OZ. (KIT)	1
DCE595B	20V ACRYLIC DISPENSER 10:1 28 OZ. (BARE)	1
DCE595D1	20V ACRYLIC DISPENSER 10:1 28 OZ. (KIT)	1

ADHESIVE ACCESSORIES

Hole Cleaning Tools & Accessories

Description



Specialty wire brushes for the hole cleaning process used for adhesive anchoring.



STEEL PREMIUM BRUSHES (REQUIRED FOR AC200+ & PURE220+)

CAT #	DESCRIPTION	PACK
PFC1671050	STEEL PREMIUM BRUSH FOR 7/16" HOLE	1
PFC1671100	STEEL PREMIUM BRUSH FOR 1/2" HOLE	1
PFC1671150	STEEL PREMIUM BRUSH FOR 9/16" HOLE	1
PFC1671200	STEEL PREMIUM BRUSH FOR 5/8" HOLE	1
PFC1671225	STEEL PREMIUM BRUSH FOR 11/16" HOLE	1
PFC1671250	STEEL PREMIUM BRUSH FOR 3/4" HOLE	1
PFC1671300	STEEL PREMIUM BRUSH FOR 7/8" HOLE	1
PFC1671350	STEEL PREMIUM BRUSH FOR 1" HOLE	1
PFC1671400	STEEL PREMIUM BRUSH FOR 1-1/8" HOLE	1
PFC1671450	STEEL PREMIUM BRUSH FOR 1-3/8" HOLE	1
PFC1671500	STEEL PREMIUM BRUSH FOR 1-1/2" HOLE	1
PFC1671000	PREMIUM MANUAL BRUSH WOOD HANDLE	1
PFC1671010	PREMIUM BRUSH EXTENSION	1
PFC1671820	PREMIUM STEEL BRUSH EXTENSION 12"	1
PFC1671830	PREMIUM STEEL BRUSH SDS ADAPTER	1
PFC1671960	PREMIUM STEEL BRUSH DRILL CHUCK ADAPTER	1



WIRE BRUSHES

CAT #	DESCRIPTION	PACK
08284-PWR	WIRE BRUSH FOR 7/16" ANSI HOLE	1
08285-PWR	WIRE BRUSH FOR 9/16" ANSI HOLE	1
08275-PWR	WIRE BRUSH FOR 5/8" ANSI HOLE	1
08286-PWR	WIRE BRUSH FOR 11/16" ANSI HOLE	1
08278-PWR	WIRE BRUSH FOR 3/4" ANSI HOLE	1
08287-PWR	WIRE BRUSH FOR 7/8" ANSI HOLE	1
08288-PWR	WIRE BRUSH FOR 1" ANSI HOLE	1
08289-PWR	WIRE BRUSH FOR 1-1/8" ANSI HOLE	1
08290-PWR	WIRE BRUSH FOR 1-3/8" ANSI HOLE	1
08291-PWR	WIRE BRUSH FOR 1-1/2" ANSI HOLE	1
08299-PWR	WIRE BRUSH FOR 1-3/4" HOLE	1
08271-PWR	WIRE BRUSH FOR 2" HOLE	1
08272-PWR	WIRE BRUSH FOR 2-3/16" HOLE	1
08282-PWR	BRUSH EXTENSION 12"	1
08283-PWR	SDS PLUS ADAPTER FOR WIRE BRUSH	1
08296-PWR	JACOBS CHUCK ADAPTER	1

ADHESIVE ACCESSORIES

Hole Cleaning Tools & Accessories

Description



Dust removal tools used in the hole cleaning process for adhesive anchoring.


ADHESIVE ACCESSORIES

Mixing Nozzles and Nozzle Extensions

Description



Mixing nozzles and extensions used to properly mix and dispense adhesive anchoring products.




AIR NOZZLE		
CAT #	DESCRIPTION	PACK
08292-PWR	AIR NOZZLE WITH EXTENSION	1



HAND PUMP		
CAT #	DESCRIPTION	PACK
08280-PWR	HAND PUMP / DUST BLOWER 25.OZ.	1



MIXING NOZZLES			
CAT #	DESCRIPTION	PACK	CTN
PFC1641600	AC200+/PURE110+/PURE50+ QUICK-SHOT NOZZLE	2	21
08609-PWR	PURE110+ 20.5/50.5 OZ. HIGH FLOW NOZZLE	2	24
08293-PWR	AC100+GOLD 9.5 OZ. NOZZLE	2	24
08294-PWR	AC50 NOZZLE	2	24
08281-PWR	MIXER EXTENSION 8"	1	12



FLEXIBLE EXTENSIONS			
CAT #	DESCRIPTION	PACK	CTN
PFC1640600	FLEXIBLE EXTENSION HOSE 25 FT.	1	12

ADHESIVE ACCESSORIES

Adhesive Piston Plugs

Description



Adhesive Piston Plugs are used to dispense anchoring adhesives into vertical, upward-oriented and overhead holes.



PREMIUM PISTON PLUGS

CAT #	DESCRIPTION	ANSI BIT DIAMETER	ROD DIAMETER	REBAR SIZE	PACK
PFC1691510	PREMIUM PLUG	5/8" HOLE	—	#4	1
PFC1691515	PREMIUM PLUG	11/16" HOLE	5/8"	—	1
PFC1691520	PREMIUM PLUG	3/4" HOLE	5/8"	#5	1
PFC1691530	PREMIUM PLUG	7/8 HOLE	3/4"	#6	1
PFC1691540	PREMIUM PLUG	1" HOLE	7/8"	#7	1
PFC1691550	PREMIUM PLUG	1-1/8" HOLE	1"	#8	1
PFC1691560	PREMIUM PLUG	1-3/8" HOLE	1-1/4"	#9	1
PFC1691570	PREMIUM PLUG	1-1/2" HOLE	—	#10	1
PFC1691580	PREMIUM PLUG	1-3/4" HOLE	1-1/2"	#11	1
PFC1691590	PREMIUM PLUG	2" HOLE	—	#14	1
PFC1691600	PREMIUM PLUG	2-3/16" HOLE	2-3/16"	—	1



ADHESIVE ACCESSORIES

Screen Tubes

Description



Screen tubes are used in hollow masonry base materials together with anchoring adhesives and threaded rods or reinforcing bars. The screen tubes hold the adhesive in position in the masonry wall face during installation of the steel elements.



PLASTIC SCREEN TUBES

CAT #	DESCRIPTION	DRILL DIAMETER	PACK
08470-PWR	1/4" x 1-3/4"	1/2"	25
08310-PWR	3/8" x 3-1/2"	9/16"	25
08311-PWR	3/8" x 6"	9/16"	25
08313-PWR	3/8" x 8"	9/16"	25
08315-PWR	1/2" x 3-1/2"	3/4"	25
08317-PWR	1/2" x 6"	3/4"	25
08321-PWR	5/8" x 6"	7/8"	25
08323-PWR	3/4" x 6"	1"	10



STAINLESS STEEL SCREEN TUBES

CAT #	DESCRIPTION	DRILL DIAMETER	PACK
07960-PWR	1/4" x 2"	3/8"	25
07862-PWR†	1/4" x 6"	3/8"	25
07864-PWR†	1/4" x 8"	3/8"	25
07866-PWR	1/4" x 10"	3/8"	25
07856-PWR	3/8" x 2"	1/2"	25
07961-PWR	3/8" x 3-1/2"	1/2"	25
07962-PWR†	3/8" x 6"	1/2"	25
07963-PWR†	3/8" x 8"	1/2"	25
07964-PWR†	3/8" x 10"	1/2"	25
07959-PWR†	3/8" x 12"	1/2"	25
07857-PWR	1/2" x 2"	5/8"	25
07965-PWR	1/2" x 3-1/2"	5/8"	25
07966-PWR†	1/2" x 6"	5/8"	25
07967-PWR†	1/2" x 8"	5/8"	25
07968-PWR†	1/2" x 10"	5/8"	25
07858-PWR	5/8" x 2"	3/4"	25
07969-PWR	5/8" x 4-1/2"	3/4"	20
07970-PWR	5/8" x 6"	3/4"	20
07971-PWR†	5/8" x 8"	3/4"	20
07972-PWR†	5/8" x 10"	3/4"	20
07859-PWR	3/4" x 2"	7/8"	25
07973-PWR	3/4" x 6"	7/8"	10
07977-PWR	3/4" x 8"	7/8"	10
07974-PWR	3/4" x 10"	7/8"	10
07975-PWR	3/4" x 13"	7/8"	10
07978-PWR	3/4" x 17"	7/8"	10
07855-PWR	15/16" x 2"	1"	25
07865-PWR	15/16" x 8"	1"	10
07867-PWR	15/16" x 13"	1"	25
07869-PWR†	15/16" x 18"	1"	10

† Includes extension tubes

**GUARANTEED
TOUGH.®**

THE FIRST CORDLESS ADHESIVE ANCHOR INSTALLATION SYSTEM



DRILL + EXTRACT + ANCHOR

DUSTX+[™]
ANCHOR INSTALLATION SYSTEM



**ICC
ES**
APPROVED

DWV015



PFC1271050

DFC114110

08310SD-PWR

08600-PWR



	DIAMETER	OVERALL LENGTH	USABLE LENGTH
 DWA54038	3/8"	9-3/4"	14-1/2"
DWA54012	1/2"	14-1/2"	9-3/4"
DWA54916	9/16"	14-1/2"	9-3/4"
DWA54058	5/8"	14-1/2"	9-3/4"
DWA54034	3/4"	14-1/2"	9-3/4"
DWA58078	3/4"	23-5/8"	15-3/4"
DWA58001	1"	23-5/8"	15-3/4"
 DWA58116	11/16"	23-5/8"	15-3/4"
DWA58118	1-1/8"	23-5/8"	15-3/4"
DWA58958	5/8"	39-3/8"	47-1/4"
DWA58934	3/4"	39-3/8"	47-1/4"
DWA58978	7/8"	39-3/8"	47-1/4"
DWA58901	1"	39-3/8"	47-1/4"
DWA58918	1-1/8"	39-3/8"	47-1/4"
DWA58918	1-1/4"	39-3/8"	47-1/4"
DWA58138	1-3/8"	39-3/8"	47-1/4"
DWA58112	1-1/2"	39-3/8"	47-1/4"



DUST X+™ ANCHOR INSTALLATION SYSTEM

**PERFORM
PROTECT**

USE WITH DWV012
for OSHA silica dust
Table 1 Compliance.

*System is compliant to the
Exposure Control Methods
described in Table 1 of 29 CFR
1926.1153 when outlined
components are operating and
maintained in accordance to
manufacturer's instructions.

OSHA COMPLIANT
1926.1153

**SDS MAX
Y-CUTTER
CARBIDE**
for positioning
and hole
starting.

**HOLLOW
DRILL BIT**
bit extracts
while drilling
for less dust
fast holes.

**AIR
LOCK**



AirLock™ Adapter
allows for quick,
easy and durable
connection
between 1-1/4"
vacuum hose
and various
DeWALT tools
and shrouds.

**AIRLOCK™
ADAPTER**
connects directly
to DeWALT's
AirLock™ Adapter
System forming a
secure locking
connection
between bit and
dust extractor.

**SDS MAX
AND SDS
PLUS
sizes
available.**



CORDLESS DIRECT FASTENING

Cordless Tools

Description



The 20V MAX* Cordless Concrete Nailers are a gas-free fastening system designed for use in concrete, concrete masonry block and steel applications. running on only a DEWALT 20V MAX* battery, these tools eliminate the need for fuel cells and powder loads. There are no special licensing requirements, and can be used for commercial framing, track installation, light gauge mechanical and electrical installations, insulation, lathing, and other applications.

Base Materials

Normal-weight concrete, Lightweight concrete, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Steel

Anchor Size Range

1/2" - 2-1/4" length
.102 to .145 diameter

Tool Platform

DEWALT 20V MAX*

*Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.



20V MAX* 1" MAGAZINE CORDLESS CONCRETE NAILER (TOOL ONLY)

CAT #	DESCRIPTION
DCN891B	INCLUDES: (1) DCN891 20V MAX* CORDLESS CONCRETE NAILER (1) DCN8904 STANDARD/DRYWALL NOSE PIECE (1) KIT BOX
	INCLUDES: (1) DCN891 20V MAX* CORDLESS CONCRETE NAILER (2) DCB205 20V MAX* XR LITHIUM ION BATTERIES (1) DCB115 CHARGER (1) DCN8904 STANDARD/DRYWALL NOSE PIECE (1) KIT BOX



20V MAX* XR 2-1/4" MAGAZINE CORDLESS CONCRETE NAILER KIT

CAT #	DESCRIPTION
DCN890P2	INCLUDES: (1) DCN890 20V MAX* CORDLESS CONCRETE NAILER (2) DCB205 5.0AH BATTERIES (1) DCB115 CHARGER (1) DCN8904 STANDARD/DRYWALL NOSE PIECE (1) DCN8903 NOSE PIECE (1) KIT BOX



CORDLESS DIRECT FASTENING

CCN Cordless Fasteners

Description	CCN Cordless Fasteners are a range of specialty fasteners specifically designed for use in the Cordless Concrete Nailer (CCN) for use in concrete, steel, and other specialty applications such as plywood or gypsum sheathing to steel studs, metal track to hard concrete, and attaching Stick-E™ accessories.
Approvals	ICC-ES ESR-4076
Base Materials	Normal-weight concrete, Lightweight concrete, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Steel
Anchor Size Range	1/2" - 2-1/4" length .102 to .145 diameter
Tool Platform	DEWALT 20V MAX*



*Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.



CONCRETE FASTENERS				
CAT #	SHANK DIAMETER	SHANK LENGTH	PACK	CTN
DCN890075	0.102"	3/4"	1,000	6,000
DCN890100	0.102"	1"	1,000	6,000
DCN890125	0.102"	1-1/4"	1,000	6,000
DCN890150	0.102"	1-1/2"	1,000	6,000
DCN8912075	0.120"	3/4"	1,000	6,000
DCN890225	0.137"	2-1/4"	500	3,000
DCN891075	0.145"	3/4"	1,000	6,000



STEEL FASTENERS				
CAT #	SHANK DIAMETER	SHANK LENGTH	PACK	CTN
DCN8910500	0.120"	1/2"	1,000	6,000



SPECIALTY FASTENERS					
CAT #	SHANK DIAMETER	SHANK LENGTH	STEP DIAMETER	PACK	CTN
DCN8907804	0.102"	0.78"	0.088"	1,000	6,000
DCN8941380	0.108"	1-3/8"	—	1,000	6,000
DCN8910680	0.120"	0.68"	0.102"	1,000	6,000
DCN8917300	0.120"	0.73"	0.102"	1,000	6,000



CORDLESS DIRECT FASTENING

STICK-E™ Direct Fastening Assemblies

Description



STICK-E™ assemblies are specially designed components for various fastening attachments into concrete, concrete masonry block and steel. They are used in conjunction with pins driven by the Cordless Concrete Nailer (CCN) or Trak-It® tools for various light duty applications.



STICK-E WASHERS

CAT #	DESCRIPTION	PACK	CTN
DFD405112	STICK-E STRAP METAL WASHER 1/2"	100	1,000
DFD405102	STICK-E STAINLESS STEEL SEALING WASHER 3/4"	100	1,000
DFD405101	STICK-E LATHING WASHER 1"	100	1,000
DFD405610	STICK-E SQUARE WASHER 1"	100	1,000
DFD405100	LATHING WASHER (NO STICK-E) 1"	100	1,000
DFD405901	STICK-E DENZ GLASS WASHER 1-1/4"	250	2,500
DFD405716	STICK-E INSTALLATION WASHER 1-7/16"	100	1,000



STICK-E CONDUIT CLIP ASSEMBLIES

CAT #	DESCRIPTION	PACK	CTN
DFD405338	STICK-E BX CLIP 3/8"	100	1,000
DFD405312R	STICK-E MINI CONDUIT CLIP 1/2"	100	1,000
DFD405334R	STICK-E MINI CONDUIT CLIP 3/4"	100	1,000
DFD405310R	STICK-E MINI CONDUIT CLIP 1"	100	1,000



STICK-E™ CEILING CLIP ASSEMBLIES

CAT #	DESCRIPTION	PACK	CTN
DFD405530	STICK-E ANGLE CLIP 60°	100	1,000
DFD405550	STICK-E RIGHT ANGLE CLIP 90°	100	1,000

CORDLESS DIRECT FASTENING

STICK-E™ Direct Fastening Assemblies

Description




STICK-E™ assemblies are specially designed components for various fastening attachments into concrete, concrete masonry block and steel. They are used in conjunction with pins driven by the Cordless Concrete Nailer (CCN) or Trak-It® tools for various light duty applications.



STICK-E CONDUIT STRAP ASSEMBLIES

CAT #	DESCRIPTION	PACK	CTN
DFD405412	STICK-E CONDUIT CLAMP 1/2"	50	200
DFD405434	STICK-E CONDUIT CLAMP 3/4"	50	200
DFD405410	STICK-E CONDUIT CLAMP 1"	50	100



STICK-E ROD HANGER AND NUT

CAT #	DESCRIPTION	PACK	CTN
DFD405214	STICK-E ROD HANGER 1/4"-20	100	1,000
DFD405238	STICK-E ROD HANGER 3/8"-16	100	1,000

STICK-E POST NUT ROD HANGER

CAT #	DESCRIPTION	PACK	CTN
DFD405215	STICK-E POST NUT ROD HANGER 1/4"-20	100	1,000
DFD405239	STICK-E POST NUT ROD HANGER 3/8"-16	100	1,000



STICK-E MISC. ASSEMBLIES

CAT #	DESCRIPTION	PACK	CTN
DFD405902	STICK-E CABLE TIE DONUT 1-1/4"	100	1,000
DFD405300	STICK-E REBAR / DOWEL BASKET CLIP	100	1,000

CORDLESS DIRECT FASTENING
Cordless Accessories



ACCESSORIES

CAT #	SIZE	PACK	CTN
DCN8905	6' POLE TOOL (FOR CORDLESS CONCRETE NAILER ONLY). POLE TOOL CAN BE USED AS 3' OR 6' EXTENSION	1	—
DCN8902	MAGNETIC STICK-E CONTACT TRIP (NOSE PIECE)	1	40
DCN8901	REPLACEMENT DRIVER BLADE	1	40
DCN8904	STANDARD / DRYWALL CONTACT TRIP (NOSE PIECE)	1	40
DCN8903	STICK-E CONTACT TRIP (NOSE PIECE)	1	40
DCN8907	1" DEEP TOOL MAGAZINE	1	—
DCN8906	2-1/4" DEEP TOOL MAGAZINE	1	—

GAS FASTENING

Trak-It® C5

Description

The Trak-It® C5 Gas Fastening System is a cordless nailer developed to attach drywall track to concrete, lightweight concrete, block or steel. It can also be used for attaching lath to concrete or block, furring strips to concrete or block, and plywood to concrete or block base materials. The system is designed for speed, efficiency and consistency and does not require specialty licensing.

Base Materials

Normal-weight concrete, Lightweight concrete, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Steel



TRAK-IT C5 TOOL		
CAT #	DESCRIPTION	BOX
55142-PWR	TRAK-IT C5 TOOL W/ DEEP TRACK	1
55148-PWR	TRAK-IT C5 TOOL W/ LONG TRACK	1




GAS FASTENING

Trak-It® C5 Pins

Description




Track-It® C5 Pins are a range of specialty fasteners specifically designed for use in the Trak-It® C5 Cordless Gas Nailer for use in concrete, steel, and other specialty applications such as plywood or gypsum sheathing to steel studs, metal track to hard concrete, and attaching Stick-E™ accessories.



TRAK-IT C5 CONCRETE AND CONCRETE MASONRY (CMU)

CAT #	SHANK DIA.	LENGTH	STEP DIA.	SHANK TYPE	BOX	CTN
55310-PWR	0.102"	3/4"	—	STRAIGHT, SMOOTH	800	4,000
55312-PWR	0.102"	1"	—	STRAIGHT, SMOOTH	800	4,000
55314-PWR	0.102"	1-1/4"	—	STRAIGHT, SMOOTH	800	4,000
55316-PWR	0.102"	1-1/2"	—	STRAIGHT, SMOOTH	800	4,000
55318-PWR	0.145"	3/4"	—	STRAIGHT, SMOOTH	800	4,000
55320-PWR	0.145"	1"	—	STRAIGHT, SMOOTH	800	4,000
55322-PWR	0.145"	1-1/4"	0.102"	STEP, SMOOTH	800	4,000
55324-PWR	0.145"	1-1/2"	0.102"	STEP, SMOOTH	800	4,000



TRAK-IT C5 STEEL PINS

CAT #	SHANK DIA.	LENGTH	STEP DIA.	SHANK TYPE	BOX	CTN
55325-PWR	0.120"	1/2"	—	STRAIGHT, SMOOTH	800	4,000
55343-PWR	0.120"	3/4"	—	STRAIGHT	800	4,000
55336-PWR	0.145"	1"	0.120"	STEP, KNURLED	800	4,000
55338-PWR	0.145"	1-1/4"	0.120"	STEP, KNURLED	800	4,000



TRAK-IT C5 SPECIALTY PINS

CAT #	SHANK DIA.	LENGTH	STEP DIA.	BOX	CTN
55328-PWR	0.120"	0.680"	0.102"	800	4,000
55330-PWR	0.120"	0.730"	0.102"	800	4,000
55340-PWR	0.108"	1-3/8"	—	800	4,000
55342-PWR	0.102"	0.780"	0.088"	800	4,000

GAS FASTENING

Trak-It® C5 Fuel Cell

Description



Trak-It® C5 Fuel Cells power the C5 Trak-It® Nailer. Each Fuel Cell contains enough gas to install up to 800 fasteners for long intervals between changes.



FUEL CELL

CAT #	DESCRIPTION	PK QTY	CTN
55302-PWR	TRAK-IT C5 FUEL CELL	20	80

GAS FASTENING

Trak-It® C5 Accessories

Description



Trak-It® C5 Accessories include various products used to compliment the Trak-It® C5 Nailer.



ACCESSORIES

CAT #	DESCRIPTION	PK QTY
55619-PWR	TRAK-IT C5 110V ADAPTER CORD	1
55583-PWR	TRAK-IT C5 BATTERY	1
55618-PWR	TRAK-IT C5 CHARGER BASE	1
56342-PWR	ACCESSORY DEEP TRACK FOR TRAK-IT C5 (UP TO 1-1/4" PINS - 42 PIN CAPACITY)	1
56344-PWR	ACCESSORY LONG TRACK FOR TRAK-IT C5 (UP TO 1-1/2" PINS - 42 PIN CAPACITY)	1
56346-PWR	ACCESSORY SHORT TRACK FOR TRAK-IT C5 (UP TO 1-1/2" PINS - 22 PIN CAPACITY)	1

**POWDER-ACTUATED
DIRECT FASTENING**

DFD270 Tool

Description



The DFD270 Tool is a low velocity, fully-automatic, .27 caliber powder-actuated tool with adjustable power. The DFD270 drives both 8mm and 0.300" head fasteners and clips in lengths from 1/2" – 2-7/8", as well as 1/4" threaded studs. The DFD270 tool features a power dial that allows for adjustment with-in .27 caliber load colors, tool-free disassembly, automatic piston return, and is available in single-shot or magazine versions for high capacity commercial operations.

Load Type

.27 Caliber (Short) Load
Safety Strips
Brown (2) Green (3)
Yellow (4) Red (5)

Pin Type

0.300" and 8mm Head
Drive Pins 1/4"-20
Threaded Studs

Pin Length

1/2" to 2-7/8"



DFD270

CAT #	DESCRIPTION	PACK
DFD270SK	DFD270 TOOL SINGLE SHOT (DELUXE KIT)	1
DFD270MK	DFD270 TOOL SINGLE SHOT AND MAGAZINE (DELUXE KIT)	1



DFD2701



DFD2705



DFD2702



DFD2703



DFD2704

ACCESSORIES

CAT #	DESCRIPTION	PACK	CTN
DFD2704	CLEANING KIT FOR DFD270 TOOL	1	—
DFD2705	REPLACEMENT DRIVER PISTON FOR DFD270 TOOL (DOMED FOR CSI AND 8MM HEAD DRIVE PINS)	1	40
DFD2701	REPLACEMENT DRIVER PISTON FOR DFD270 TOOL (FLAT FOR .300" HEAD DRIVE PINS)	1	40
DFD2703	MAGAZINE NOSE PIECE FOR DFD270	1	—
DFD2702	REPLACEMENT SINGLE SHOT NOSE PIECE FOR DFD270 TOOL	1	—

Powder Actuated Tool Operation: Powder actuated tools may be used only by properly trained and licensed operators as described in ANSI Standard A 10.3. For complete tool operation details completely review the tool manual and contact your local DEWALT branch office or distributor for training.



POWDER-ACTUATED DIRECT FASTENING

Sniper™ Tool

Description



The Sniper pole tool is a low-velocity, .27 caliber, semi-automatic powder-actuated tool that is designed for installing overhead ceiling clips mounted with pins up to 1-1/2" long. The tool features an internal safety sequence strip loading mechanism, that must be manually pulled to advance the next load.

Load Type

.27 Caliber (Short) Load
Safety Strips
Brown (2) Green (3)
Yellow (4) Red (5)

Pin Type

0.300" and 8mm
Head Drive Pins

Pin Length

1/2" – 1-1/2"



SNIPER TOOL

CAT #	DESCRIPTION	PACK	CTN
52051-PWR	SNIPER TOOL	1	—

Powder Actuated Tool Operation: Powder actuated tools may be used only by properly trained and licensed operators as described in ANSI Standard A 10.3. For complete tool operation details completely review the tool manual and contact your local DEWALT branch office or distributor for training.

POWDER-ACTUATED DIRECT FASTENING

P3600 Tool

Description



The P3600 Tool is a powerful, heavy-duty low-velocity, .27 caliber, semi-automatic, trigger-fired powder-actuated tool that is used to install 10mm head drive pins, and 3/8" threaded studs and drive pins. The P3600 Tool is specifically designed for applications requiring a purple load, such as attaching 2x4s to hard aggregate concrete or steel.

Load Type

.27 Caliber (Short) Load
Safety Strips
Brown (2) Green (3)
Yellow (4) Red (5)

Pin Type

0.300" and 10mm
Head Drive Pins
3/8" Head Drive Pins 3/8"
Threaded Studs

Pin Length

1/2" – 3"



P3600

CAT #	DESCRIPTION	PACK	CTN
52010-PWR	P3600 TOOL	1	—

Powder Actuated Tool Operation: Powder actuated tools may be used only by properly trained and licensed operators as described in ANSI Standard A 10.3. For complete tool operation details completely review the tool manual and contact your local DEWALT branch office or distributor for training.

**POWDER-ACTUATED
DIRECT FASTENING**

P3500 Tool

Description



The P3500 Tool is a low-velocity, .27 caliber, semi-automatic, trigger-fired powder-actuated tool that is designed for attaching construction materials to concrete and steel.

Load Type .27 Caliber (Short) Load Safety Strips Brown (2) Green (3) Yellow (4) Red (5)

Pin Type 0.300" and 8mm Head Drive Pins 1/4"-20 Threaded Studs

Pin Length 1/2" – 3"



P3500

CAT #	DESCRIPTION	PACK	CTN
DDF212035P	P3500 TOOL	1	—
52000-PWR	P3500 TOOL (DELUXE KIT)	1	—

Powder Actuated Tool Operation: Powder actuated tools may be used only by properly trained and licensed operators as described in ANSI Standard A 10.3. For complete tool operation details completely review the tool manual and contact your local DEWALT branch office or distributor for training.

**POWDER-ACTUATED
DIRECT FASTENING**

PA3500 Tool

Description



The PA3500 Tool is a low-velocity, .27 caliber, semi-automatic, trigger-fired powder-actuated tool that is designed for attaching construction materials to concrete and steel. The PA3500 Tool includes a power adjuster, allowing the operator to effectively decrease the power level of the load being used by up to two levels.

Load Type .27 Caliber (Short) Load Safety Strips Brown (2) Green (3) Yellow (4) Red (5)

Pin Type 0.300" and 8mm Head Drive Pins 1/4"-20 Threaded Studs

Pin Length 1/2" – 3"



PA3500


CAT #	DESCRIPTION	PACK	CTN
52019-PWR	PA3500 TOOL	1	—

Powder Actuated Tool Operation: Powder actuated tools may be used only by properly trained and licensed operators as described in ANSI Standard A 10.3. For complete tool operation details completely review the tool manual and contact your local DEWALT branch office or distributor for training.

**POWDER-ACTUATED
DIRECT FASTENING**

P2201 Tool

Description



The P2201 Tool is a low velocity, single shot, trigger-fired, .22 caliber tool which can be used to install 0.300" or 8mm head drive pins and 1/4"-20 threaded studs, up to 3" in total length.

Load Type

.22 Caliber (Short) Brown
(2) Green (3) Yellow (4)

Pin Type

0.300" and 8mm Head
Drive Pins 1/4"-20
Threaded Studs

Pin Length

1/2" – 3"



P2201

CAT #	DESCRIPTION	PACK	CTN
DDF211022P	P2201 TOOL	1	4

Powder Actuated Tool Operation: Powder actuated tools may be used only by properly trained and licensed operators as described in ANSI Standard A 10.3. For complete tool operation details completely review the tool manual and contact your local DEWALT branch office or distributor for training.

**POWDER-ACTUATED
DIRECT FASTENING**

T1000 Tool

Description



The T1000 Tool is a hammer-fired, low velocity, single shot, trigger-fired, .22 caliber, do-it-yourself (DIY) powder actuated tool. Engineered for high reliability, low maintenance and speed.

Load Type

.22 Caliber (Short) Brown
(2) Green (3) Yellow (4)

Pin Type

0.300" and 8mm Head
Drive Pins 1/4"-20
Threaded Studs

Pin Length

1/2" – 3"



T1000

CAT #	DESCRIPTION	PACK	CTN
DDF211010P	T1000 TOOL	1	5

Powder Actuated Tool Operation: Powder actuated tools may be used only by properly trained and licensed operators as described in ANSI Standard A 10.3. For complete tool operation details completely review the tool manual and contact your local DEWALT branch office or distributor for training.

POWDER-ACTUATED
DIRECT FASTENING

P1000 Tool

Description



The P1000 Tool is a hammer-fired, low velocity, single shot, .22 caliber, do-it-yourself (DIY) powder actuated tool. Engineered for high reliability, low maintenance and speed.

Load Type

.22 Caliber (Short) Brown
(2) Green (3) Yellow (4)

Pin Type

0.300" and 8mm Head
Drive Pins 1/4"-20
Threaded Studs

Pin Length

1/2" – 3"



P1000

CAT #	DESCRIPTION	PACK	CTN
DDF211000P	P1000 TOOL	1	5

Powder Actuated Tool Operation: Powder actuated tools may be used only by properly trained and licensed operators as described in ANSI Standard A 10.3. For complete tool operation details completely review the tool manual and contact your local DEWALT branch office or distributor for training.



POWDER-ACTUATED DIRECT FASTENING

CSI Spiral Drive Pins

Description

CSI Spiral Drive Pins are designed for permanently fastening a fixture to concrete, concrete over steel deck, concrete masonry walls and A36 or A572 / A992 structural steel. The fasteners are manufactured with an 8mm head and various shank diameters based on application. A spiral knurled shank design provides consistent optimized performance in steel base materials. The fasteners are available in single and collated strips.

Approvals

ICC-ES ESR-2024

Base Materials


Normal-weight concrete, Lightweight concrete, Concrete over steel deck, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Steel

K = Knurled



CSI SPIRAL DRIVE PINS (8MM HEAD DIAMETER)

CAT #	SHANK DIAMETER	SHANK LENGTH	PACK	CTN
50178-PWR	0.145"	1/2" (13MM) (K)	100	5,000
50179-PWR	0.157"	1/2" (13MM) (K)	100	1,000
51201-PWR	0.157"	5/8" (16MM) (K)	100	1,000
50203-PWR	0.157"	3/4" (19MM) (K)	100	1,000
50204-PWR	0.157"	7/8" (22MM) (K)	100	1,000
50205-PWR	0.157"	1" (27MM) (K)	100	1,000
50208-PWR	0.157"	1-1/4" (32MM) (K)	100	1,000
50207-PWR	0.157"	1-1/2" (37MM) (K)	100	1,000
50209-PWR	0.157"	2" (52MM) (K)	100	1,000
50241-PWR	0.157"	2-1/2" (62MM) (K)	100	1,000
50211-PWR	0.157"	2-7/8" (72MM) (K)	100	1,000



CSI SPIRAL DRIVE PINS WITH WASHER (8MM HEAD DIAMETER)

CAT #	SHANK DIAMETER	SHANK LENGTH	PACK	CTN
50245-PWR	0.157"	3/4" (19MM) (K)	100	1,000
50247-PWR	0.157"	1" (27MM) (K)	100	1,000
50261-PWR	0.157"	1-1/4" (32MM) (K)	100	1,000
50263-PWR	0.157"	2-1/2" (62MM) (K)	100	1,000
50265-PWR	0.157"	2-7/8" (72MM) (K)	100	1,000



POWDER-ACTUATED
DIRECT FASTENING

CSI Spiral Drive Pins

Description



CSI Spiral Drive Pins are designed for permanently fastening a fixture to concrete, concrete over steel deck, concrete masonry walls and A36 or A572 / A992 structural steel. The fasteners are manufactured with an 8mm head and various shank diameters based on application. A spiral knurled shank design provides consistent optimized performance in steel base materials. The fasteners are available in single and collated strips.

Approvals



ICC-ES ESR-2024

Base Materials

Normal-weight concrete,
Lightweight concrete,
Concrete over steel deck,
Grouted concrete masonry
(CMU), Hollow concrete
masonry (CMU), Steel

K = Knurled



CSI SPIRAL DRIVE PINS COLLATED (8MM HEAD DIAMETER)

CAT #	SHANK DIAMETER	SHANK LENGTH	PACK	CTN
50238N-PWR	0.145"	1/2"(13MM) (K)	100	1,000
51449-PWR	0.157"	1/2"(13MM) (K)	100	1,000
51450-PWR	0.157"	5/8" (16MM) (K)	100	1,000
50452-PWR	0.157"	3/4" (19MM) (K)	100	1,000
50454-PWR	0.157"	7/8" (22MM) (K)	100	1,000
50456-PWR	0.157"	1" (27MM) (K)	100	1,000
50458-PWR	0.157"	1-1/4" (32MM) (K)	100	1,000
50460-PWR	0.157"	1-1/2" (37MM) (K)	100	1,000
50461-PWR	0.157"	1-5/8" (42MM) (K)	100	1,000
50462-PWR	0.157"	2" (52MM) (K)	100	1,000
50463-PWR	0.157"	2-1/2" (62MM) (K)	100	1,000



POWDER-ACTUATED DIRECT FASTENING

0.300" Head Drive Pins

Description



0.300" Head Drive Pins are standard performance flat head powder actuated drive pins with a 0.300" diameter head. They are designed for permanently fastening a fixture to concrete, concrete over steel deck, concrete masonry walls and A36 or A572 / A992 structural steel. The fasteners are manufactured with a 0.145" diameter shank in various lengths. Knurled shank designs are available for installations in thick steel base materials. The fasteners are also available in with a mechanically galvanized (MG) coating for use in treated lumber.

Approvals

ICC-ES ESR-2024



Base Materials

Normal-weight concrete, Lightweight concrete, Concrete over steel deck, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Steel

K = Knurled
BO = Black Oxide



0.300" DIAMETER HEAD DRIVE PINS

CAT #	SHANK DIAMETER	SHANK LENGTH	PACK	CTN
50012-PWR	0.145"	1/2" (K)	100	5,000
50016-PWR	0.145"	5/8" (K)	100	5,000
50022-PWR	0.145"	3/4"	100	5,000
50023-PWR	0.145"	3/4" (BO)	100	5,000
50026-PWR	0.145"	1"	100	5,000
50032-PWR	0.145"	1-1/4"	100	1,000
50034-PWR	0.145"	1-1/2"	100	1,000
50038-PWR	0.145"	2"	100	1,000
50040-PWR	0.145"	2-1/4"	100	1,000
50044-PWR	0.145"	2-1/2"	100	1,000
50048-PWR	0.145"	3"	100	1,000



0.300" DIAMETER HEAD DRIVE PINS (MECHANICALLY GALVANIZED)

CAT #	SHANK DIAMETER	SHANK LENGTH	PACK	CTN
50038MG-PWR	0.145"	2"	100	1,000
50045MG-PWR	0.145"	2-1/2"	100	1,000
50047MG-PWR	0.145"	3"	100	1,000



0.300" DIAMETER HEAD DRIVE PINS WITH TOP HAT

CAT #	SHANK DIAMETER	SHANK LENGTH	PACK	CTN
50136-PWR	0.145"	1/2" (K)	100	5,000
50140-PWR	0.145"	3/4"	100	5,000
50144-PWR	0.145"	1"	100	5,000



0.300" DIAMETER HEAD BALLISTIC POINT DRIVE PINS

CAT #	SHANK DIAMETER	SHANK LENGTH	PACK	CTN
50057-PWR	0.181/0.150"	1-7/8"	100	1,000

POWDER-ACTUATED
DIRECT FASTENING

0.300" Head Drive Pins

Description



0.300" Head Drive Pins are standard performance flat head powder actuated drive pins with a 0.300" diameter head. They are designed for permanently fastening a fixture to concrete, concrete over steel deck, concrete masonry walls and A36 or A572 / A992 structural steel. The fasteners are manufactured with a 0.145" diameter shank in various lengths. Knurled shank designs are available for installations in thick steel base materials. The fasteners are also available in with a mechanically galvanized (MG) coating for use in treated lumber.


Approvals



ICC-ES ESR-2024

Base Materials

Normal-weight concrete, Lightweight concrete, Concrete over steel deck, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Steel




0.300" DIAMETER HEAD DRIVE PINS WITH 3/4" WASHER

CAT #	SHANK DIAMETER	SHANK LENGTH	PACK	CTN
50070-PWR	0.145"	3/4"	100	1,000



0.300" DIAMETER HEAD DRIVE PINS WITH 7/8" WASHER

CAT #	SHANK DIAMETER	SHANK LENGTH	PACK	CTN
50090-PWR	0.145"	1"	100	1,000
50092-PWR	0.145"	1-1/4"	100	1,000
50094-PWR	0.145"	1-1/2"	100	1,000
50096-PWR	0.145"	2"	100	1,000
50098-PWR	0.145"	2-1/2"	100	1,000
50100-PWR	0.145"	3"	100	1,000



0.300" DIAMETER HEAD DRIVE PINS WITH 1" WASHER

CAT #	SHANK DIAMETER	SHANK LENGTH	PACK	CTN
50108-PWR	0.145"	1-1/4"	100	1,000
50110-PWR	0.145"	1-1/2"	100	1,000
50112-PWR	0.145"	2"	100	1,000
50114-PWR	0.145"	2-1/2"	100	1,000
50116-PWR	0.145"	3"	100	1,000
50120-PWR*	0.145"	3"	100	1,000

*Square Washer



0.300" DIAMETER HEAD DRIVE PINS WITH 1" WASHER
(MECHANICALLY GALVANIZED)

CAT #	SHANK DIAMETER	SHANK LENGTH	PACK	CTN
50110MG-PWR	0.145"	1-1/2"	100	1,000
50112MG-PWR	0.145"	2"	100	1,000
50113MG-PWR	0.145"	2-1/2"	100	1,000
50115MG-PWR	0.145"	3"	100	1,000

**POWDER-ACTUATED
DIRECT FASTENING**

0.300" Head Drive Pins



Description

0.300" Head Drive Pins are standard performance flat head powder actuated drive pins with a 0.300" diameter head. The fasteners are manufactured with a 0.145" diameter shank in various lengths.


Approvals

ICC-ES ESR-2024



Base Materials

Normal-weight concrete,
Lightweight concrete,
Concrete over steel deck,
Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Steel



0.300" DIAMETER HEAD DRIVE PINS WITH 1-7/8" INSULATION WASHER				
CAT #	SHANK DIAMETER	SHANK LENGTH	PACK	CTN
50122-PWR	0.145"	1-1/2"	100	1,000
50126-PWR	0.145"	2-1/2"	50	500

**POWDER-ACTUATED
DIRECT FASTENING**

8mm Head Drive Pins



Description

8mm Head Drive Pins are standard performance, domed head, top hat drive pins with an 8mm diameter head. The fasteners are manufactured with a 0.145" diameter shank in various lengths. A knurled shank is available for installations in thick steel base materials.


Approvals

ICC-ES ESR-2024



Base Materials

Normal-weight concrete,
Lightweight concrete,
Concrete over steel deck,
Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Steel



8MM DIAMETER HEAD DRIVE PINS WITH TOP HAT				
CAT #	SHANK DIAMETER	SHANK LENGTH	PACK	CTN
50210-PWR	0.145"	16MM (5/8")	100	5,000
50214-PWR	0.145"	22MM (7/8")	100	5,000
50216-PWR	0.145"	27MM (1")	100	5,000

**POWDER-ACTUATED
DIRECT FASTENING**

Ceiling Clip Assemblies

Description



Ceiling Clips are used for acoustical applications, suspended ceiling systems, fixtures and wire components to concrete, concrete-filled steel deck and steel. Several styles and types of angled clips with pre-mounted pins are available. A ceiling clip without a premounted pin is also offered.

Approvals


ICC-ES ESR-2024



Base Materials


Normal-weight concrete, Lightweight concrete, Concrete over steel deck, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Steel

TH = Top Hat




CSI SPIRAL DRIVE PIN WITH CEILING CLIP (90 DEGREE)

CAT #	HOLE SIZE	SHANK DIAMETER	SHANK LENGTH	PACK	CTN
50212-PWR	0.313"	0.157"	22MM (7/8") (TH)	100	1,000
50213-PWR	0.313"	0.157"	27MM (1") (TH)	100	1,000
50218-PWR	0.313"	0.157"	32MM (1-1/4") (TH)	100	1,000



CEILING CLIP WITHOUT PIN (90 DEGREE)

CAT #	DESCRIPTION	PACK	CTN
50400-PWR	CEILING CLIP (NO PIN) 3/4-INCH WIDE AND 14 GAUGE THICK. LONG LEG IS 1-1/4" LONG WITH 7/32" HOLE; SHORT LEG IS 5/8" LONG WITH 5/16" HOLE.	100	1,000



8MM HEAD PIN WITH CEILING CLIP (90 DEGREE)

CAT #	HOLE SIZE	SHANK DIAMETER	SHANK LENGTH	PACK
50206-PWR	0.313"	0.177"	27MM (1") (TH)	100
50272-PWR	0.279"	0.145"	27MM (1") (TH)	100

POWDER-ACTUATED DIRECT FASTENING

Ceiling Clip Assemblies

Description



Ceiling Clips are used for acoustical applications, suspended ceiling systems, fixtures and wire components to concrete, concrete-filled steel deck and steel. Several styles and types of angled clips with pre-mounted pins are available. A ceiling clip without a premounted pin is also offered.

Approvals



ICC-ES ESR-2024

Base Materials

Normal-weight concrete, Lightweight concrete, Concrete over steel deck, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Steel

TH = Top Hat

POWDER-ACTUATED DIRECT FASTENING

Threaded Studs

Description



Threaded studs are used for applications where it may be desirable to remove the fixture or where shimming may be required or for suspending small diameter pipe.

Approvals



ICC-ES ESR-2024

Base Materials

Normal-weight concrete, Lightweight concrete, Concrete over steel deck, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Steel

K = Knurled



0.300" HEAD DRIVE PINS WITH CEILING CLIPS (90 DEGREE)

CAT #	HOLE SIZE	SHANK DIAMETER	SHANK LENGTH	PACK
DFD3373**	0.278"	0.145"	1"	100
DFD3374**	0.278"	0.145"	1-1/4"	100
50364-PWR*	0.278"	0.145"	1"	100
50370-PWR*	0.278"	0.145"	1-1/4"	100

*Clips are 3/4 inch wide and 2 mm thick. **Extended Length (XL) clips.



0.300" HEAD DRIVE PINS WITH ECONOMY CEILING CLIPS (60 DEGREE)

CAT #	HOLE SIZE	SHANK DIAMETER	SHANK LENGTH	PACK
50368-PWR	0.278"	0.145"	1-1/8"	100

BALLISTIC POINT DRIVE PIN WITH CEILING CLIP

CAT #	HOLE SIZE	SHANK DIAMETER	SHANK LENGTH	CTN
50366-PWR	7/8" (TH)	0.300"	0.150"	100
50058-PWR	1-1/4"	0.300"	0.181/0.150"	100



1/4"-20 THREADED STUDS (UNC THREAD)

CAT #	SHANK DIAMETER	SHANK LENGTH	THREAD DIAMETER	PACK	CTN
50322-PWR	0.145"	1/2" (K)	3/4"	100	1,000
50326-PWR	0.145"	3/4"	3/4"	100	1,000
50328-PWR	0.145"	1"	1/2"	100	1,000
50330-PWR	0.145"	1"	3/4"	100	1,000
50336-PWR	0.145"	1-1/4"	3/4"	100	1,000
50338-PWR	0.145"	1-1/4"	1-1/4"	100	1,000



3/8"-16 THREADED STUDS (UNC THREAD)

CAT #	SHANK DIAMETER	SHANK LENGTH	THREAD DIAMETER	PACK	CTN
50340-PWR	0.205"	3/4" (K)	1-1/4"	100	1,000
50342-PWR	0.205"	1"	1-1/4"	100	1,000
50344-PWR	0.205"	1-1/4"	1-1/4"	100	1,000

**POWDER-ACTUATED
DIRECT FASTENING**

Conduit Clip Assemblies

Description



BX and EMT conduit clips are provided in various sizes for attaching conduit to base materials where easy removal is not a requirement.

Approvals

ICC-ES ESR-2024



Base Materials

Normal-weight concrete, Lightweight concrete, Concrete over steel deck, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Steel



0.300" HEAD DRIVE PINS WITH BX CABLE STRAPS

CAT #	SHANK DIAMETER	SHANK LENGTH	PACK	CTN
50150-PWR	0.145"	1"	100	1,000



0.300" HEAD DRIVE PINS WITH CONDUIT CLIPS

CAT #	CLIP SIZE	SHANK DIAMETER	SHANK LENGTH	PACK	CTN
50382-PWR	1/2" EMT (DOMED CLIP)	0.145"	1"	50	500
50385-PWR	3/4" EMT	0.145"	1"	50	500
50388-PWR	1" EMT	0.145"	1"	25	250
50386-PWR	3/4" EMT (DOMED CLIP)	0.145"	1-1/8"	50	500
50384-PWR	3/4" EMT (DOMED CLIP)	0.145"	1-1/4"	50	500



8MM HEAD DRIVE PINS WITH EMT CONDUIT CLIPS

CAT #	CLIP SIZE	SHANK DIAMETER	SHANK LENGTH	PACK	CTN
50278-PWR	3/4" EMT	0.145"	1"	500	1,000
50280-PWR	1" EMT	0.145"	1"	250	500

POWDER-ACTUATED DIRECT FASTENING

Rod Hanging Clip Assemblies

Description




Rod hangers and post nut hanger clips are available for suspending mechanical and electrical components from concrete and steel.

Base Materials


Normal-weight concrete,
Lightweight concrete,
Concrete over steel deck,
Grouted concrete masonry
(CMU), Hollow concrete
masonry (CMU), Steel

XL = Extended Length




**CSI SPIRAL AND 8MM HEAD DRIVE PINS WITH ROD HANGER
(UNC THREAD)**

CAT #	HANGER SIZE	SHANK DIAMETER	SHANK LENGTH	PACK
50215-PWR	1/4"-20	0.157"	1-1/4"	100
50219-PWR	1/4"-20	0.145"	1-1/4"	100
50221-PWR	3/8"-16	0.145"	1-1/4"	100



0.300" HEAD DRIVE PINS WITH POST NUT ROD HANGER (UNC THREAD)

CAT #	SHANK DIAMETER	SHANK LENGTH	HANGER SIZE	PACK	CTN
50376-PWR	0.145"	1-1/8"	1/4"-20" (DOMED RIGHT ANGLE CLIP)	100	1,000
DFD3388	0.145"	1"	1/4"-20" (XL RIGHT ANGLE CLIP)	50	500
50378-PWR	0.145"	1-1/4"	1/4"-20" (DOMED RIGHT ANGLE CLIP)	100	1,000
DFD3389	0.145"	1-1/4"	1/4"-20" (XL RIGHT ANGLE CLIP)	50	500



8MM HEAD DRIVE PINS WITH REBAR/DOWEL BASKET CLIPS

CAT #	SHANK DIAMETER	SHANK LENGTH	HANGER SIZE	PACK	CTN
50704-PWR	0.145"	37MM (1-1/2")	STD. BASKET CLIP	100	500
50712-PWR	0.145"	52MM (2")	STD. BASKET CLIP	100	500
50716-PWR	0.145"	62MM (2-1/2")	STD. BASKET CLIP	50	500

POWDER-ACTUATED DIRECT FASTENING

Rebar/Dowel Basket Assemblies

Description



Rebar basket clips are typically used in highway construction and paving applications.

Base Materials

Normal-weight concrete,
Lightweight concrete,
Concrete over steel deck,
Grouted concrete masonry
(CMU), Hollow concrete
masonry (CMU), Steel

**POWDER-ACTUATED
DIRECT FASTENING**

Powder-Actuated Loads

Description



Powder-Actuated Loads are designed for consistent and reliably attaching drive pins into concrete and steel base materials. Specific load types are designed for each caliber powder actuated tool. They are offered as single cartridge units for single shot tools and also collated in groups of 10 into plastic strips for semi-automatic tools.



.22 CALIBER (SHORT) LOADS

CAT #	SIZE	LOAD POWER	PACK	CTN
50502-PWR	.22 SHORT	BROWN (2)	100	10,000
50504-PWR	.22 SHORT	GREEN (3)	100	10,000
50506-PWR	.22 SHORT	YELLOW (4)	100	10,000



.27 CALIBER (SHORT) SAFETY STRIP LOAD

CAT #	SIZE	LOAD POWER	PACK	CTN
50620-PWR	.27 SAFETY STRIP	BROWN (2)	100	10,000
50622-PWR	.27 SAFETY STRIP	GREEN (3)	100	10,000
50626-PWR	.27 SAFETY STRIP	YELLOW (4)	100	10,000
50630-PWR	.27 SAFETY STRIP	RED (5)	100	10,000



**POWDER-ACTUATED
DIRECT FASTENING**

Powder-Actuated Accessories

Description



Powder-Actuated Accessories include pole tools to extend the reach of the P3500, PA3500, PA3600, and Sniper powder-actuated tools allowing overhead fastening without the need for ladders. There is also a cleaning kit which is compatible with all semi-automatic and single shot tools.



ACCESSORIES

CAT #	DESCRIPTION	PACK
50065-PWR	6' POLE TOOL (P3500, PA3500, PA3600)	1
50066-PWR	8' POLE TOOL (P3500, PA3500, PA3600)	1
52053-PWR	6' POLE TOOL FOR SNIPER TOOL	1
52061-PWR	8' POLE TOOL FOR SNIPER TOOL	1
52070-PWR	TOOL CLEANING KIT FOR SEMI-AUTOMATIC AND SINGLE SHOT TOOLS	1

HAMMER-DRIVE
Hammer Drive Pin

Description

Hammer Drive pins are manually driven fasteners designed for permanently fastening a fixture to concrete and some types of concrete block. This fastener is designed for use in a standard hand tool and should not be used in a powder actuated tool. The pins are formed with a 1/4" diameter head on one end, and a 0.140" diameter shank in various lengths, and have a specially designed point to allow proper penetration into the base material.

Approvals

Tested in accordance with E488

Base Materials

Normal-weight concrete, Lightweight concrete, Concrete over steel deck, Grouted concrete masonry (CMU), Hollow concrete masonry (CMU), Steel

Anchor Material

Hardened carbon steel
0.250" diameter head
0.140" diameter shank
3/8" diameter washer



1/4" HEAD HAMMER DRIVE PINS			
CAT #	DESCRIPTION	PACK	CTN
50294-PWR	HAMMER DRIVE PIN 3/4"	100	5,000
50296-PWR	HAMMER DRIVE PIN 1"	100	5,000
50298-PWR	HAMMER DRIVE PIN 1 1/4"	100	1,000

HAMMER DRIVE SETTING TOOL			
CAT #	DESCRIPTION	PACK	CTN
50310-PWR	HAMMER DRIVE TOOL STANDARD	1	6



INSTALL TOOL

SELF-DRILLING METAL SCREWS

Drillit® Standard Drill Screws

Description



Drillit® self-drilling fasteners eliminate separate drilling and tapping operations for faster, more economical installations. For improved corrosion resistance, some Drillit® fasteners feature a Stalgard® coating which typically shows no red rust or other base metal corrosion on significant surfaces after 1000 hours of salt spray exposure in accordance with ASTM B117 when compared to standard zinc coatings.

Approvals



ICC-ES ESR-3294
available on most SKUs


Specifications

- Diameters: #6 to #8
- Lengths: 3/8" to 1-1/2"
- Drill Points: Drillit® forged
- Drive Systems: Hex and Phillips
- Material: Carbon steel
- Finishes: Stalgard® coating or zinc



#6 DIAMETER, 1/4" HEX WASHER HEAD

ELCO CAT #	DeWALT CAT#	DESCRIPTION	POINT TYPE	FINISH	PACK
EDA135-I-100	DFSEDA135-100	#6-20 x 3/8"	#2	ZINC	100
EDA140-I-100	DFSEDA140-100	#6-20 x 1/2"	#2	ZINC	100
EDA146-I-100	DFSEDA146-100	#6-20 x 5/8"	#2	ZINC	100
EDA160-I-100	DFSEDA160-100	#6-20 x 3/4"	#2	ZINC	100
EDA190-I-100	DFSEDA190-100	#6-20 x 1"	#2	ZINC	100



#8 DIAMETER, #2 PHILLIPS PAN HEAD

ELCO CAT #	DeWALT CAT#	DESCRIPTION	POINT TYPE	FINISH	PACK
EDD251-I	DFSEDD251	#8-18 x 1/2"	#2	STALGARD	10,000
EDD251-I-100	DFSEDD251-100	#8-18 x 1/2"	#2	STALGARD	100
EDD266-I	DFSEDD266	#8-18 x 3/4"	#2	STALGARD	10,000



#8 DIAMETER, 1/4" HEX WASHER HEAD

ELCO CAT #	DeWALT CAT#	DESCRIPTION	POINT TYPE	FINISH	PACK
EDA235-I-100	DFSEDA235-100	#8-18 x 1/2"	#2	ZINC	100
EDA236-I	DFSEDA236	#8-18 x 1/2"	#2	STALGARD	10,000
EDA236-I-100	DFSEDA236-100	#8-18 x 1/2"	#2	STALGARD	100
EDA250-I-100	DFSEDA250-100	#8-18 x 5/8"	#2	ZINC	100
EDA260-I	DFSEDA260	#8-18 x 3/4"	#2	ZINC	8,000
EDA260-I-100	DFSEDA260-100	#8-18 x 3/4"	#2	ZINC	100
EDA261-I	DFSEDA261	#8-18 x 3/4"	#2	STALGARD	8,000
EDA261-I-100	DFSEDA261-100	#8-18 x 3/4"	#2	STALGARD	100
EDA285-I-100	DFSEDA285-100	#8-18 x 1"	#2	ZINC	100
EDA286-I	DFSEDA286	#8-18 x 1"	#2	STALGARD	5,000
EDA290-I-100	DFSEDA290-100	#8-18 x 1-1/4"	#2	ZINC	100
EDA295-I-100	DFSEDA295-100	#8-18 x 1-1/2"	#2	ZINC	100

SELF-DRILLING METAL SCREWS

Drillit® Standard Drill Screws

Description



Drillit® self-drilling fasteners eliminate separate drilling and tapping operations for faster, more economical installations. For improved corrosion resistance, some Drillit® fasteners feature a Stalgard® coating which typically shows no red rust or other base metal corrosion on significant surfaces after 1000 hours of salt spray exposure in accordance with ASTM B117 when compared to standard zinc coatings.

Approvals



ICC-ES ESR-3294
available on most SKUs

Specifications

- Diameters: #10
- Lengths: 1/2" to 3"
- Drill Points: Drillit® forged
- Drive Systems: Hex and Phillips
- Material: Carbon steel
- Finishes: Stalgard® coating or zinc



#10 DIAMETER 1/4" HEX WASHER HEAD

ELCO CAT #	DeWALT CAT#	DESCRIPTION	POINT TYPE	FINISH	PACK
EDA431-I-100	DFSEDA431-100	#10-16 x 1/2"	#2	STALGARD	100
EDB600-I-100	DFSEDB600-100	#10-24 x 1/2"	#2	ZINC	100
EDB401-I	DFSEDB401	#10-16 x 1/2"	#2	STALGARD	5,000
EDB401-I-100	DFSEDB401-100	#10-16 x 1/2"	#2	STALGARD	100
EDB426-I	DFSEDB426	#10-16 x 5/8"	#3	STALGARD	6,000
EDB426-I-100	DFSEDB426-100	#10-16 x 5/8"	#3	STALGARD	100
EDC450-I	DFSEDC450	#10-16 x 3/4"	#1	STALGARD	5,000
EDC450-I-500	DFSEDC450-500	#10-16 x 3/4"	#1	STALGARD	500
EDB445-I-100	DFSEDB445-100	#10-16 x 3/4"	#3	ZINC	100
EDB446-I	DFSEDB446	#10-16 x 3/4"	#3	STALGARD	6,000
EDB446-I-500	DFSEDB446-500	#10-16 x 3/4"	#3	STALGARD	500
EDB485-I	DFSEDB485	#10-16 x 1"	#3	ZINC	5,000
EDB485-I-100	DFSEDB485-100	#10-16 x 1"	#3	ZINC	100
EDB486-I	DFSEDB486	#10-16 x 1"	#3	STALGARD	5,000
EDB486-I-100	DFSEDB486-100	#10-16 x 1"	#3	STALGARD	100
EDB490-I-100	DFSEDB490-100	#10-16 x 1-1/4"	#3	ZINC	100
EDB540-I	DFSEDB540	#10-16 x 1-1/2"	#3	ZINC	3,000
EDB540-I-100	DFSEDB540-100	#10-16 x 1-1/2"	#3	ZINC	100
EDB541-I	DFSEDB541	#10-16 x 1-1/2"	#3	STALGARD	3,000
EDB541-I-100	DFSEDB541-100	#10-16 x 1-1/2"	#3	STALGARD	100
EDB550-I-100	DFSEDB550-100	#10-16 x 1-3/4"	#3	ZINC	100
EDB570-I-100	DFSEDB570-100	#10-16 x 2"	#3	ZINC	100
EDB571-I	DFSEDB571	#10-16 x 2"	#3	STALGARD	2,000
EDB580-I-025	DFSEDB580-25	#10-16 x 3"	#3	ZINC	25



#10 DIAMETER, 5/16" HEX WASHER HEAD WITH SERRATIONS

ELCO CAT #	DeWALT CAT#	DESCRIPTION	POINT TYPE	FINISH	PACK
EDC576-I-100	DFSEDC576-100	#10-16 x 3/4"	#3	STALGARD	100
EFC460-I	DFSEFC460	#10-16 x 3/4"	#3	ZINC	6,000



#10 DIAMETER, #2 PHILLIPS PAN HEAD

ELCO CAT #	DeWALT CAT#	DESCRIPTION	POINT TYPE	FINISH	PACK
EDD501-I	DFSEDD501	#10-16 x 1"	#2	ZINC	5,000

SELF-DRILLING METAL SCREWS

Drillit® Standard Drill Screws

Description



Drillit® self-drilling fasteners eliminate separate drilling and tapping operations for faster, more economical installations. For improved corrosion resistance, some Drillit® fasteners feature a Stalgard® coating which typically shows no red rust or other base metal corrosion on significant surfaces after 1000 hours of salt spray exposure in accordance with ASTM B117 when compared to standard zinc coatings.

Approvals



ICC-ES ESR-3294
available on most SKUs


Specifications

- Diameters:
#12 to 1/4"
- Lengths: 3/4" to 4"
- Drill Points:
Drillit® forged
- Drive System:
Hex
- Material: Carbon steel
- Finishes: Stalgard®
coating or zinc




#12 DIAMETER, 5/16" HEX WASHER HEAD

ELCO CAT #	DeWALT CAT#	DESCRIPTION	POINT TYPE	FINISH	PACK
EDC745-I	DFSEDC745	#12-14 x 3/4"	#1	STALGARD	5,000
EDC745-I-500	DFSEDC745-500	#12-14 x 3/4"	#1	STALGARD	500
EDB740-I	DFSEDB740	#12-14 x 3/4"	#3	ZINC	5,000
EDB740-I-100	DFSEDB740-100	#12-14 x 3/4"	#3	ZINC	100
EDB741-I	DFSEDB741	#12-14 x 3/4"	#3	STALGARD	5,000
EDB741-I-100	DFSEDB741-100	#12-14 x 3/4"	#3	STALGARD	100
EDB760-I	DFSEDB760	#12-14 x 1"	#3	ZINC	4,000
EDB760-I-100	DFSEDB760-100	#12-14 x 1"	#3	ZINC	100
EDB761-I	DFSEDB761	#12-14 x 1"	#3	STALGARD	4,000
EDB761-I-100	DFSEDB761-100	#12-14 x 1"	#3	STALGARD	100
EDB780-I-100	DFSEDB780-100	#12-14 x 1-1/4"	#3	ZINC	100
EDB782-I	DFSEDB782	#12-14 x 1-1/4"	#3	STALGARD	3,000
EDB782-I-050	DFSEDB782-050	#12-14 x 1-1/4"	#3	STALGARD	50
EDB800-I	DFSEDB800	#12-14 x 1-1/2"	#3	ZINC	2,500
EDB800-I-050	DFSEDB800-050	#12-14 x 1-1/2"	#3	ZINC	50
EDB801-I	DFSEDB801	#12-14 x 1-1/2"	#3	STALGARD	2,500
EDB820-I-050	DFSEDB820-050	#12-14 x 2"	#3	ZINC	50
EDB821-I	DFSEDB821	#12-14 x 2"	#3	STALGARD	2,000
EDB821-I-100	DFSEDB821-100	#12-14 x 2"	#3	STALGARD	100
EDB829-I-050	DFSEDB829-050	#12-14 x 2-1/2"	#3	ZINC	50
EDB830-I	DFSEDB830	#12-14 x 2-1/2"	#3	STALGARD	1,500
EDB839-I-025	DFSEDB839-025	#12-14 x 3"	#3	ZINC	25
EDB840-I	DFSEDB840	#12-14 x 3"	#3	STALGARD	1,000
EDB845-I	DFSEDB845	#12-14 x 4"	#3	STALGARD	500



1/4" DIAMETER, 5/16" HEX WASHER HEAD

ELCO CAT #	DeWALT CAT#	DESCRIPTION	POINT TYPE	FINISH	PACK
EDC930-I	DFSEDC930	1/4"-14 x 7/8"	#1	STALGARD	4,000



1/4" DIAMETER, 3/8" HEX OVERSIZED (11/16") WASHER HEAD

CAT #	DeWALT CAT#	DESCRIPTION	POINT TYPE	FINISH	PACK
EDB947-I	DFSEDB947	1/4"-14 x 1"	#3	ZINC	2,000

SELF-DRILLING METAL SCREWS

Drillit® Standard Drill Screws

Description



Drillit® self-drilling fasteners eliminate separate drilling and tapping operations for faster, more economical installations. For improved corrosion resistance, some Drillit® fasteners feature a Stalgard® coating which typically shows no red rust or other base metal corrosion on significant surfaces after 1000 hours of salt spray exposure in accordance with ASTM B117 when compared to standard zinc coatings.

Approvals



ICC-ES ESR-3294
available on most SKUs

Specifications

- Diameters: 1/4" to 5/16"
- Lengths: 3/4" to 4"
- Drill Points: Drillit® forged
- Drive Systems: Hex and Phillips
- Material: Carbon steel
- Finishes: Stalgard® coating or zinc



1/4" DIAMETER, 3/8" HEX WASHER HEAD

ELCO CAT #	DeWALT CAT#	DESCRIPTION	POINT TYPE	FINISH	PACK
EDB935-I	DFSEDB935	1/4"-14 x 3/4"	#3	ZINC	3,500
EDB935-I-100	DFSEDB935-100	1/4"-14 x 3/4"	#3	ZINC	100
EDB936-I	DFSEDB936	1/4"-14 x 3/4"	#3	STALGARD	3,500
EDB945-I	DFSEDB945	1/4"-14 x 1"	#3	ZINC	3,000
EDB945-I-050	DFSEDB945-050	1/4"-14 x 1"	#3	ZINC	50
EDB946-I	DFSEDB946	1/4"-14 x 1"	#3	STALGARD	3,000
EDB955-I-050	DFSEDB955-050	1/4"-14 x 1-1/4"	#3	ZINC	50
EDB956-I	DFSEDB956	1/4"-14 x 1-1/4"	#3	STALGARD	2,000
EDB960-I-050	DFSEDB960-050	1/4"-14 x 1-1/2"	#3	ZINC	50
EDB961-I	DFSEDB961	1/4"-14 x 1-1/2"	#3	STALGARD	2,000
EDB976-I	DFSEDB976	1/4"-14 x 2-1/2"	#3	STALGARD	1,000
EDB965-I-050	DFSEDB965-050	1/4"-14 x 1-3/4"	#3	ZINC	50
EDB970-I-050	DFSEDB970-050	1/4"-14 x 2"	#3	ZINC	50
EDB971-I	DFSEDB971	1/4"-14 x 2"	#3	STALGARD	1,500
EDB975-I-025	DFSEDB975-025	1/4"-14 x 2-1/2"	#3	ZINC	25
EDB980-I-025	DFSEDB980-025	1/4"-14 x 3"	#3	STALGARD	25
EDB981-I	DFSEDB981	1/4"-14 x 3"	#3	ZINC	800
EDB983-I	DFSEDB983	1/4"-14 x 4"	#3	STALGARD	500
EDB970-I	DFSEDB970	1/4"-14 x 2"	#3	ZINC	50



5/16" DIAMETER, 3/8" HEX WASHER HEAD

ELCO CAT #	DeWALT CAT#	DESCRIPTION	POINT TYPE	FINISH	PACK
EDB990-I-010	DFSEDB990-010	5/16"-18 x 1"	#3	ZINC	10
EDB991-I	DFSEDB991	5/16"-18 x 1"	#3	STALGARD	1,000
EDB993-I-010	DFSEDB993-010	5/16"-18 x 1-1/4"	#3	ZINC	10
EDB994-I	DFSEDB994	5/16"-18 x 1-1/4"	#3	STALGARD	1,000
EDB997-I-010	DFSEDB997-010	5/16"-18 x 1-1/2"	#3	ZINC	10
EDB998-I	DFSEDB998	5/16"-18 x 1-1/2"	#3	STALGARD	1,000

SELF-DRILLING METAL SCREWS

**Drillit® Screws with Bonded
Sealing Washers**

Description



Drillit® self-drilling fasteners eliminate separate drilling and tapping operations for faster, more economical installations. For improved corrosion resistance, some Drillit® fasteners feature a Stalgard® coating which typically shows no red rust or other base metal corrosion on significant surfaces after 1000 hours of salt spray exposure in accordance with ASTM B117 when compared to standard zinc coatings. Screws with EPDM Bonded Sealing washers are available in multiple sizes and configurations for applications requiring a weather-tight seal.

Approvals



ICC-ES ESR-3294
available on most SKUs

Specifications

- Diameters: #8 to #10
- Lengths: 3/4" to 1-1/2"
- Head Styles:
Hex washer
- Drive System: Hex
- Point Types: #1 to #5
- Material: Carbon steel
- Finish: Stalgard®
coating or zinc



#8 DIAMETER, 1/4" HEX WASHER HEAD


ELCO CAT #	DEWALT CAT#	DESCRIPTION	POINT TYPE	FINISH	WASHER DIA.	PACK
EHL100-I-050	DFSEHL100-050	#8-18 x 3/4"	#2	ZINC	1/2"	50



#8 DIAMETER, 1/4" HEX WASHER HEAD

ELCO CAT #	DEWALT CAT#	DESC.	POINT TYPE	FINISH	WASHER DIA.	PACK
EHL111-I	DFSEHL111	#10-16 x 3/4"	#3	STALGARD	1/2"	3,000
EHL112-I-100	DFSEHL112-100	#10-16 x 3/4"	#3	ZINC	1/2"	100
EHL115-I-100	DFSEHL115-100	#10-16 x 1"	#3	ZINC	1/2"	100
EHL146-I	DFSEHL146	#10-16 x 1-1/2"	#3	STALGARD	1/2"	2,000

To assure a weather-tight seal, fasteners must be properly installed.



SELF-DRILLING METAL SCREWS

Drilit® Screws with Bonded Sealing Washers

Description



Drilit® self-drilling fasteners eliminate separate drilling and tapping operations for faster, more economical installations. For improved corrosion resistance, some Drilit® fasteners feature a Stalgard® coating which typically shows no red rust or other base metal corrosion on significant surfaces after 1000 hours of salt spray exposure in accordance with ASTM B117 when compared to standard zinc coatings. Screws with EPDM Bonded Sealing washers are available in multiple sizes and configurations for applications requiring a weather-tight seal.

Approvals



ICC-ES ESR-3294
available on most SKUs

Specifications

- Diameters: #12 to 1/4"
- Lengths: 3/4" to 4"
- Head Styles:
Hex washer
- Drive System: Hex
- Point Types: #1 to #5
- Material: Carbon steel
- Finish: Stalgard® coating or zinc



#12 DIAMETER, 5/16" HEX WASHER HEAD

ELCO CAT #	DEWALT CAT#	DESC.	POINT TYPE	FINISH	WASHER DIA.	PACK
EHL160-I-100	DFSEHL160-100	#12-14 x 3/4"	#3	ZINC	9/16"	100
EHL165-I	DFSEHL165	#12-14 x 3/4"	#3	STALGARD	9/16"	3,000
EHL351-I	DFSEHL351	#12-24 x 7/8"	#4	STALGARD	9/16"	2,500
EHL180-I-100	DFSEHL180-100	#12-14 x 1"	#3	ZINC	9/16"	100
EHL181-I	DFSEHL181	#12-14 x 1"	#3	STALGARD	9/16"	2,500
EHL235-I	DFSEHL235	#12-14 x 1-1/4"	#3	STALGARD	9/16"	2,000
EHL371-I	DFSEHL371	#12-24 x 1-1/4"	#4.5	STALGARD	9/16"	2,500
ECW725-I	DFSECW725	#12-24 x 1-1/4"	#5	STALGARD	9/16"	2,500
ECW725-I-050	DFSECW725-050	#12-24 x 1-1/4"	#5	STALGARD	9/16"	50
EHL276-I	DFSEHL276	#12-14 x 1-1/2"	#3	STALGARD	9/16"	2,000
ECW745-I	DFSECW745	#12-24 x 1-1/2"	#5	STALGARD	9/16"	2,000
EHL280-I	DFSEHL280	#12-14 x 2"	#3	STALGARD	9/16"	1,500
ECW755-I	DFSECW755	#12-24 x 2"	#5	STALGARD	9/16"	1,000
EHL285-I	DFSEHL285	#12-14 x 2-1/2"	#3	STALGARD	9/16"	1,000
EHL295-I	DFSEHL295	#12-14 x 3"	#3	STALGARD	9/16"	1,000
EHL310-I	DFSEHL310	#12-14 x 4"	#3	STALGARD	9/16"	500



1/4" DIAMETER, 5/16" HEX WASHER HEAD

ELCO CAT #	DEWALT CAT#	DESC.	POINT TYPE	FINISH	WASHER DIA.	PACK
EHK315-I	DFSEHK315	1/4"-14 x 7/8"	#1	STALGARD	9/16"	2,500

SELF-DRILLING METAL SCREWS

Drillit® Screws with Bonded Sealing Washers

Description



Drillit® self-drilling fasteners eliminate separate drilling and tapping operations for faster, more economical installations. For improved corrosion resistance, some Drillit® fasteners feature a Stalgard® coating which typically shows no red rust or other base metal corrosion on significant surfaces after 1000 hours of salt spray exposure in accordance with ASTM B117 when compared to standard zinc coatings. Screws with EPDM Bonded Sealing washers are available in multiple sizes and configurations for applications requiring a weather-tight seal.

Approvals



ICC-ES ESR-3294
available on most SKUs

Specifications

- Diameters: 1/4"
- Lengths: 3/4" to 4"
- Head Styles:
Hex washer
- Drive System: Hex
- Point Types: #1 to #5
- Material: Carbon steel
- Finish: Stalgard®
coating or zinc



1/4" DIAMETER, 3/8" HEX WASHER HEAD

ELCO CAT #	DEWALT CAT#	DESC.	POINT TYPE	FINISH	WASHER DIA.	PACK
EHL514-I-050	DFSEHL514-050	1/4"-14 x 3/4"	#3	ZINC	5/8"	50
EHL515-I	DFSEHL515	1/4"-14 x 3/4"	#3	STALGARD	5/8"	2,500
EHL525-I-050	DFSEHL525-050	1/4"-14 x 1"	#3	ZINC	5/8"	50
EHL530-I	DFSEHL530	1/4"-14 x 1"	#3	STALGARD	5/8"	2,000
EHL555-I-050	DFSEHL555-050	1/4"-14 x 1-1/4"	#3	ZINC	5/8"	50
EHL556-I	DFSEHL556	1/4"-14 x 1-1/4"	#3	STALGARD	5/8"	1,500
EHL575-I-050	DFSEHL575-050	1/4"-14 x 1-1/2"	#3	ZINC	5/8"	50
EHL577-I	DFSEHL577	1/4"-14 x 1-1/2"	#3	STALGARD	5/8"	1,500
EHL584-I-050	DFSEHL584-050	1/4"-14 x 2"	#3	ZINC	5/8"	50
EHL585-I	DFSEHL585	1/4"-14 x 2"	#3	STALGARD	5/8"	1,000
EHL600-I	DFSEHL600	1/4"-14 x 3"	#3	STALGARD	5/8"	800
EHL610-I	DFSEHL610	1/4"-14 x 4"	#3	STALGARD	5/8"	500

SELF-DRILLING METAL SCREWS

Drillit® Drill Screws for Wood-to-Metal Applications

Description



Drillit® self-drilling fasteners eliminate separate drilling and tapping operations for faster, more economical installations. For improved corrosion resistance, some Drillit® fasteners feature a Stalgard® coating which typically shows no red rust or other base metal corrosion on significant surfaces after 1000 hours of salt spray exposure in accordance with ASTM B117 when compared to standard zinc coatings.

Approvals

ICC-ES ESR-4367



Finish: Stalgard®

Specifications

- Diameters: #10, #12, and 1/4"
- Lengths: 3/4" to 4"
- Head Styles: Flat and wafer
- Drive System: Phillips
- Point Types: #2 to #4
- Material: Carbon steel
- Finish: Grey Stalgard® coating



#10 DIAMETER, #2 PHILLIPS WAFER HEAD

ELCO CAT #	DeWALT CAT#	DESC.	POINT TYPE	WOOD THICK.	DRILLING CAP.	PACK
EDM582-I	DFSEDM582	#10-24 x 3/4"	#3	1/4"	.036" - .187"	8,000
EDM592-I	DFSEDM592	#10-24 x 1"	#3	1/2"	.036" - .187"	6,000
EDM607-I	DFSEDM607	#10-24 x 1-1/4"	#3	5/8"	.036" - .187"	5,000
EDM607-I-100	DFSEDM607-100	#10-24 x 1-1/4"	#3	5/8"	.036" - .187"	100
EDT602-I	DFSEDT602	#10-24 x 1-7/16"	#3 W/ WINGS	3/4"	.036" - .187"	4,000
EDM622-I	DFSEDM622	#10-16 x 1-1/2"	#3	3/4"	.036" - .187"	3,500
EDM622-I-100	DFSEDM622-100	#10-16 x 1-1/2"	#3	3/4"	.036" - .187"	100
EDM635-I	DFSEDM635	#10-16 x 1-13/16"	#3 W/ PILOT	3/4"	.036" - .150"	2,500



#12 DIAMETER, #3 PHILLIPS WAFER HEAD

ELCO CAT #	DeWALT CAT#	DESC.	POINT TYPE	WOOD THICK.	DRILLING CAP.	PACK
EDT720-I	DFSEDT720	#12-24 x 1-3/4"	#4 W/ WINGS	3/4"	.060" - .312"	2,000



#12 DIAMETER, #3 PHILLIPS WAFER HEAD

ELCO CAT #	DeWALT CAT#	DESC.	POINT TYPE	WOOD THICK.	DRILLING CAP.	PACK
EDT267-I	DFSEDT267	#12-24 x 2-1/4"	#4 W/ WINGS	1-1/4"	.060" - .312"	2,000
EDT282-I	DFSEDT282	#12-24 x 2-3/4"	#4 W/ WINGS	1-5/8"	.060" - .312"	1,500
EDJ867-I	DFSEDJ867	#12-14 x 3-5/8"	#2 W/ PILOT	1-5/8"	.036" - .150"	1,000



1/4" DIAMETER, #3 PHILLIPS FLAT HEAD

ELCO CAT #	DeWALT CAT#	DESC.	POINT TYPE	WOOD THICK.	DRILLING CAP.	PACK
EDT442-I	DFSEDT442	1/4"-20 x 3"	#4 W/ WINGS	2"	.060" - .312"	1,000
EDT470-I	DFSEDT470	1/4"-20 x 4"	#4 W/ WINGS	3"	.060" - .312"	1,000

SELF-DRILLING METAL SCREWS

**Drilit® Screws with Extended
Drilling Capacity**

Description



Drilit® self-drilling fasteners eliminate separate drilling and tapping operations for faster, more economical installations. For improved corrosion resistance, some Drilit® fasteners feature a Stalgard® coating which typically shows no red rust or other base metal corrosion on significant surfaces after 1000 hours of salt spray exposure in accordance with ASTM B117 when compared to standard zinc coatings.

Approvals



ICC-ES ESR-3294 available on most SKUs

Specifications

- Diameters: #12
- Lengths: 7/8" to 2"
- Head Styles: Flat and wafer
- Drive System: Phillips
- Point Types: #4 to #5
- Material: Carbon steel
- Finish: Grey Stalgard® coating



**#12 DIAMETER 5/16" HEX WASHER HEAD
FOR STEEL .175" TO 500" THICK**

ELCO CAT #	DeWALT CAT#	DESCRIPTION	POINT TYPE	FINISH	PACK
EDC801-I	DFSEDC801	#12-24 x 7/8"	#4	STALGARD	4,500
EDC816-I	DFSEDC816	#12-24 x 1-1/4"	#4.5	STALGARD	3,500
ECC720-I	DFSECC720	#12-24 x 1-1/4"	#5	STALGARD	4,000
ECC720-I-100	DFSECC720-100	#12-24 x 1-1/4"	#5	STALGARD	100
EDC846-I	DFSEDC846	#12-24 x 1-1/2"	#4.5	STALGARD	2,500
ECC740-I	DFSECC740	#12-24 x 1-1/2"	#5	STALGARD	2,500
ECC750-I	DFSECC750	#12-24 x 2"	#5	STALGARD	2,000

SELF-DRILLING METAL SCREWS

Drilit® Screws with Extended Drilling Capacity



Description

Drilit® self-drilling fasteners eliminate separate drilling and tapping operations for faster, more economical installations. For improved corrosion resistance, some Drilit® fasteners feature a Stalgard® coating which typically shows no red rust or other base metal corrosion on significant surfaces after 1000 hours of salt spray exposure in accordance with ASTM B117 when compared to standard zinc coatings.

Approvals


ICC-ES ESR-3294
available on most SKUs

- Specifications**
- Diameters: 1/4"
 - Lengths: 3" to 8"
 - Head Styles: Flat and wafer
 - Drive System: Phillips
 - Point Types: #5
 - Material: Carbon steel
 - Finish: Grey Stalgard® coating



1/4" DIAMETER, 5/16" HEX WASHER HEAD
FOR STEEL .175" TO .500" THICK

ELCO CAT #	DeWALT CAT#	DESCRIPTION	POINT TYPE	FINISH	PACK
ECC940-I	DFSECC940	1/4"-20 x 3"	#5	STALGARD	1,000
ECC950-I	DFSECC950	1/4"-20 x 4"	#5	STALGARD	500



1/4" DIAMETER, 3/8" HEX WASHER HEAD
FOR STEEL .175" TO .500" THICK

ELCO CAT #	DeWALT CAT#	DESCRIPTION	POINT TYPE	FINISH	PACK
ECC960-I	DFSECC960	1/4"-20 x 5"	#5	STALGARD	500
ECC970-I	DFSECC970	1/4"-20 x 6"	#5	STALGARD	500
ECC980-I	DFSECC980	1/4"-20 x 8"	#5	STALGARD	150

SELF-DRILLING METAL SCREWS

Dril-Flex® Structural Drill Screws

Description



Dril-Flex® Structural Drill Screws are dual heat treated self-drilling tapping screws that provide the strength, ductility and resistance to embrittlement required for critical applications such as curtain walls, window walls/glazing, and solar panel systems. Dril-Flex® Screws feature either a Stalgard or Stalgard® SUB coating for improved corrosion resistance.

Approvals



- ICC-ES ESR-3332
- ICC-ES ESR-4367
- ICC-ES ESR-4374

Specifications

- Diameters: #10 to #12
- Lengths: 3/4" to 3"
- Head/Drive Styles: Hex washer, Phillips pan, wafer and undercut flat
- Point Types: #2, #3, and #5
- Material: Alloy steel
- Heat Treat: Grade 5
- Finish:
S = Silver Stalgard®
SS = Stalgard® SUB



#10 DIAMETER, 5/16" HEX WASHER HEAD

ELCO CAT #	DeWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EA430	DFSEAF430	#10-16 x 3/4"	#3	STALGARD SUB	6,000
EA460	DFSEAF460	#10-16 x 1-1/2"	#3	STALGARD SUB	2,500
EA470	DFSEAF470	#10-16 x 2"	#3	STALGARD SUB	2,000
EA480	DFSEAF480	#10-16 x 2-1/2"	#3	STALGARD SUB	1,500



#10 DIAMETER, #2 PHILLIPS PAN HEAD

ELCO CAT #	DeWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EDX445	DFSEDX445	#10-16 x 3/4"	#2	STALGARD	6,000



#10 DIAMETER, #2 PHILLIPS WAFER HEAD

ELCO CAT #	DeWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EBL530	DFSEBL530	#10-24 x 1-1/4"	#3	STALGARD	5,000



#12 DIAMETER, 5/16" HEX WASHER HEAD

ELCO CAT #	DeWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EA621*	DFSEAF621*	#12-14 x 7/8"	#3	STALGARD SUB	5,000
EA641	DFSEAF641	#12-14 x 1"	#3	STALGARD SUB	4,000
EA661	DFSEAF661	#12-14 x 1-1/4"	#3	STALGARD SUB	2,500
EA681	DFSEAF681	#12-14 x 1-1/2"	#3	STALGARD SUB	2,500
EA755	DFSEAF755	#12-24 x 1-3/4"	#5	STALGARD SUB	2,500
EA690	DFSEAF690	#12-14 x 2"	#3	STALGARD SUB	2,000
EA715	DFSEAF715	#12-14 x 3"	#2	STALGARD SUB	1,000

SELF-DRILLING METAL SCREWS

Dril-Flex® Structural Drill Screws

Description



Dril-Flex® Structural Drill Screws are dual heat treated self-drilling tapping screws that provide the strength, ductility and resistance to embrittlement required for critical applications such as curtain walls, window walls/glazing, and solar panel systems. Dril-Flex® Screws feature either a Stalgard or Stalgard® SUB coating for improved corrosion resistance.


Approvals



- ICC-ES ESR-3332
- ICC-ES ESR-4367
- ICC-ES ESR-4374

Specifications

- Diameters: #12 to 1/4"
- Lengths: 1" to 4"
- Head/Drive Styles: Hex washer, Phillips pan, wafer and undercut flat
- Point Types: #3, #4 and #5
- Material: Alloy steel
- Heat Treat: Grade 5
- Finish: S = Silver Stalgard® SS = Stalgard® SUB



#12 DIAMETER, #3 PHILLIPS UNDERCUT FLAT HEAD

ELCO CAT #	DEWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EBL215	DFSEBL215	#12-14 x 1"	#3	STALGARD	4,000
EBL220	DFSEBL220	#12-14 x 1-1/4"	#3	STALGARD	3,000
EBL223	DFSEBL223	#12-14 x 1-1/2"	#3	STALGARD	2,500



1/4" DIAMETER, 3/8" HEX WASHER HEAD

ELCO CAT #	DEWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EA816	DFSEAF816	1/4"-14 x 1"	#3	STALGARD SUB	3,000
EA865	DFSEAF865	1/4"-20 x 1-1/8"	#4	STALGARD SUB	2,500
EA841	DFSEAF841	1/4"-14 x 1-1/2"	#3	STALGARD SUB	2,000
EA876	DFSEAF876	1/4"-20 x 1-1/2"	#4	STALGARD SUB	2,000
EA888	DFSEAF888	1/4"-20 x 1-3/4"	#5	STALGARD SUB	1,000
EA846	DFSEAF846	1/4"-14 x 2"	#3	STALGARD SUB	1,500
EA886	DFSEAF886	1/4"-20 x 2"	#4	STALGARD SUB	1,500
EA890	DFSEAF890	1/4"-20 x 2-1/2"	#4	STALGARD SUB	1,000
EA900	DFSEAF900	1/4"-20 x 3-3/8"	#4	STALGARD SUB	500
EA910	DFSEAF910	1/4"-20 x 4"	#4	STALGARD SUB	500

SELF-DRILLING METAL SCREWS

Dril-Flex® Structural Drill Screws

Description



Dril-Flex® Structural Drill Screws are dual heat treated self-drilling tapping screws that provide the strength, ductility and resistance to embrittlement required for critical applications such as curtain walls, window walls/glazing, and solar panel systems. Dril-Flex® Screws feature either a Stalgard or Stalgard® SUB coating for improved corrosion resistance.


Approvals



- ICC-ES ESR-3332
- ICC-ES ESR-4367
- ICC-ES ESR-4374

Specifications

- Diameters: 1/4" to 5/16"
- Lengths: 3/4" to 4"
- Head/Drive Styles: Hex washer, Phillips pan, wafer and undercut flat
- Point Types: #3 and #4
- Material: Alloy steel
- Heat Treat: Grade 5
- Finish:
S = Silver Stalgard®
SS = Stalgard® SUB



1/4" DIAMETER, #3 PHILLIPS UNDERCUT FLAT HEAD

ELCO CAT #	DEWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EBL330	DFSEBL330	1/4"-20 x 3"	#4	STALGARD	500
EBL340	DFSEBL340	1/4"-20 x 4"	#4	STALGARD	500



5/16" DIAMETER, 3/8" HEX WASHER HEAD

ELCO CAT #	DEWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EAF940	DFSEAF940	5/16"-18 x 1-1/2"	#3	STALGARD SUB	1,000
EAF960	DFSEAF960	5/16"-24 x 1-1/2"	#4	STALGARD SUB	1,000
EAF970	DFSEAF970	5/16"-24 x 2"	#4	STALGARD SUB	1,000

SELF-DRILLING METAL SCREWS

Bi-Flex® 300 Stainless Steel Bi-Metal Self-Drilling Screws

Description



Bi-Flex® structural screws are bi-metal self-drilling tapping screws that provide the corrosion resistance of 300 series stainless steel and the efficiency of drill screws. Bi-Flex® screws are suitable for use in both steel and aluminum.

Approvals



ICC-ES ESR-4374
available on most SKUs

Specifications

- Diameters: #8 and #10
- Lengths: 3/4" to 1-1/2"
- Drive Systems:
Hex and Phillips
- Material: Hardened steel tapping threads and point fused onto an 18-8 stainless steel shank and head
- Finish:
SGB = Stalgard® GB (Galvanic Barrier)



#8 DIAMETER, 1/4" HEX WASHER HEAD

ELCO CAT #	DEWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EAJ100	DFSEAJ100	#8-18 x 3/4"	#2	STALGARD GB	5,000
EAJ102	DFSEAJ102	#8-18 x 1"	#2	STALGARD GB	5,000



#8 DIAMETER, #2 PHILLIPS PAN HEAD

ELCO CAT #	DEWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EAX100	DFSEAX100	#8-18 x 3/4"	#2	STALGARD GB	5,000
EAX102	DFSEAX102	#8-18 x 1"	#2	STALGARD GB	5,000



#10 DIAMETER, 5/16" HEX WASHER HEAD

ELCO CAT #	DEWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EAJ110	DFSEAJ110	#10-16 x 3/4"	#2	STALGARD GB	5,000
EAJ120	DFSEAJ120	#10-16 x 1"	#2	STALGARD GB	5,000
EAJ140	DFSEAJ140	#10-16 x 1-1/2"	#2	STALGARD GB	2,500



#8 DIAMETER, #2 PHILLIPS PAN HEAD

ELCO CAT #	DEWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EAX100	DFSEAX100	#8-18 x 3/4"	#2	STALGARD GB	5,000
EAX102	DFSEAX102	#8-18 x 1"	#2	STALGARD GB	5,000



#10 DIAMETER, #2 PHILLIPS PANCAKE HEAD

ELCO CAT #	DEWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EBN300	DFSEBN300	#10-16 x 1"	#2	STALGARD GB	4,000

SELF-DRILLING METAL SCREWS

**Bi-Flex® 300 Stainless Steel
Bi-Metal Self-Drilling Screws**

Description



Bi-Flex® structural screws are bi-metal self-drilling tapping screws that provide the corrosion resistance of 300 series stainless steel and the efficiency of drill screws. Bi-Flex® screws are suitable for use in both steel and aluminum.

Approvals



ICC-ES ESR-4374
available on most SKUs

Specifications

- Diameters: #12
- Lengths: 1" to 2-1/2"
- Drive Systems:
Hex and Phillips
- Material: Hardened
steel tapping threads
and point fused onto an
18-8 stainless steel
shank and head
- Finish:
SGB = Stalgard® GB
(Galvanic Barrier)



#12 DIAMETER, 5/16" HEX WASHER HEAD

ELCO CAT #	DeWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EAJ185	DFSEAJ185	#12-14 x 1"	#2	STALGARD GB	3,000
EAJ190	DFSEAJ190	#12-14 x 1"	#3	STALGARD GB	4,000
EAJ200	DFSEAJ200	#12-14 x 1-1/4"	#3	STALGARD GB	2,500
EAJ215	DFSEAJ215	#12-14 x 1-1/2"	#2	STALGARD GB	2,500
EAJ220	DFSEAJ220	#12-14 x 1-1/2"	#3	STALGARD GB	2,500
EAJ320	DFSEAJ320	#12-24 x 1-1/2"	#5	STALGARD GB	2,500
EAJ240	DFSEAJ240	#12-14 x 2"	#2	STALGARD GB	1,500
EAJ340	DFSEAJ340	#12-24 x 2"	#5	STALGARD GB	2,000
EAJ260	DFSEAJ260	#12-14 x 2-1/2"	#3	STALGARD GB	1,000



#12 DIAMETER, #3 PHILLIPS UNDERCUT FLAT HEAD

ELCO CAT #	DeWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EBN200	DFSEBN200	#12-14 x 1"	#2	STALGARD GB	4,000
EBN220	DFSEBN220	#12-14 x 1-1/4"	#2	STALGARD GB	2,500
EBN240	DFSEBN240	#12-14 x 1-1/2"	#2	STALGARD GB	2,500



#12 DIAMETER, #2 PHILLIPS PANCAKE HEAD

ELCO CAT #	DeWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EBN320	DFSEBN320	#12-14 x 1"	#3	STALGARD GB	4,000

SELF-DRILLING METAL SCREWS

Bi-Flex® 300 Stainless Steel Bi-Metal Self-Drilling Screws

Description



Bi-Flex® structural screws are bi-metal self-drilling tapping screws that provide the corrosion resistance of 300 series stainless steel and the efficiency of drill screws. Bi-Flex® screws are suitable for use in both steel and aluminum.

Approvals



ICC-ES ESR-4374
available on most SKUs


Specifications

- Diameters: 1/4"
- Lengths: 1" to 8"
- Drive Systems: Hex and Phillips
- Material: Hardened steel tapping threads and point fused onto an 18-8 stainless steel shank and head
- Finish: SGB = Stalgard® GB (Galvanic Barrier)



1/4" DIAMETER, 3/8" HEX WASHER HEAD

ELCO CAT #	DEWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EAJ415	DFSEAJ415	1/4"-14 x 1"	#2	STALGARD GB	2,500
EAJ540	DFSEAJ540	1/4"-20 x 1"	#3	STALGARD GB	2,500
EAJ430	DFSEAJ430	1/4"-14 x 1-1/2"	#2	STALGARD GB	1,000
EAJ580	DFSEAJ580	1/4"-20 x 1-1/2"	#3	STALGARD GB	1,000
EAJ600	DFSEAJ600	1/4"-20 x 1-1/2"	#5	STALGARD GB	1,000
EAJ445	DFSEAJ445	1/4"-14 x 2"	#2	STALGARD GB	1,500
EAJ610	DFSEAJ610	1/4"-20 x 2"	#3	STALGARD GB	1,500
EAJ615	DFSEAJ615	1/4"-20 x 2"	#5	STALGARD GB	1,500
EAJ640	DFSEAJ640	1/4"-20 x 2-1/2"	#3	STALGARD GB	1,000
EAJ650	DFSEAJ650	1/4"-20 x 3"	#3	STALGARD GB	500
EAJ630	DFSEAJ630	1/4"-20 x 3"	#5	STALGARD GB	500
EAJ660	DFSEAJ660	1/4"-20 x 4"	#3	STALGARD GB	500
EAJ670	DFSEAJ670	1/4"-20 x 4"	#5	STALGARD GB	500
EAJ675	DFSEAJ675	1/4"-20 x 5"	#5	STALGARD GB	250
EAJ680	DFSEAJ680	1/4"-20 x 6"	#5	STALGARD GB	250
EAJ690C	DFSEAJ690C	1/4"-20 x 8"	#5	STALGARD GB	150



1/4" DIAMETER, #3 PHILLIPS UNDERCUT FLAT HEAD

ELCO CAT #	DEWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EBN630	DFSEBN630	1/4"-20 x 3"	#3	STALGARD GB	500
EBN640	DFSEBN640	1/4"-20 x 4"	#3	STALGARD GB	500

SELF-DRILLING METAL SCREWS

Alumi-Flex® 302 (18-8) Stainless Steel Drill Screws

Description



Alumi-Flex® structural drill screws are 300 series (18-8) stainless steel self-drilling tapping screws. The screw body is entirely stainless steel and can be an excellent solution for fastening to aluminum when corrosion resistance and galvanic reaction are a primary concern.

Approvals



ICC-ES ESR-4374

Specifications

- Diameters: #10, #12, and 1/4"
- Lengths: 1/2" to 1-1/2"
- Head Style: Hex washer and Phillips undercut
- Drive System: Hex
- Point Types: #3 and #4
- Material: 302 stainless steel
- Finish: Stalgard® GB (Galvanic Barrier) coating



#10 DIAMETER, 5/16" HEX WASHER HEAD

ELCO CAT #	DeWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EAH445-I	DFSEAH445	#10-16 x 3/4"	#3	STALGARD GB	6,000
EAH460-I	DFSEAH460	#10-16 x 1"	#3	STALGARD GB	5,000



#10 DIAMETER, #2 PHILLIPS UNDERCUT FLAT HEAD

ELCO CAT #	DeWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EBM160-I	DFSEBM160	#10-16 x 3/4"	#3	STALGARD GB	10,000



#12 DIAMETER, 5/16" HEX WASHER HEAD

ELCO CAT #	DeWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EAH630-I	DFSEAH630	#12-14 x 3/4"	#3	STALGARD GB	5,000
EAH650-I	DFSEAH650	#12-14 x 1"	#3	STALGARD GB	5,000
EAH680-I	DFSEAH680	#12-14 x 1-1/2"	#3	STALGARD GB	3,000



1/4" DIAMETER, 3/8" HEX WASHER HEAD

ELCO CAT #	DeWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EAH800-I	DFSEAH800	1/4"-14 x 3/4"	#3	STALGARD GB	3,500
EAH820-I	DFSEAH820	1/4"-14 x 1"	#3	STALGARD GB	3,000
EAH835-I	DFSEAH835	1/4"-14 x 1-1/2"	#3	STALGARD GB	2,000
EAH870-I	DFSEAH870	1/4"-20 x 1"	#4	STALGARD GB	2,000
EAH880-I	DFSEAH880	1/4"-20 x 1-1/2"	#4	STALGARD GB	2,000



1/4" DIAMETER, #3 PHILLIPS UNDERCUT FLAT HEAD

ELCO CAT #	DeWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EBM260-I	DFSEBM260	1/4"-14 x 1"	#3	STALGARD GB	4,500

SELF-DRILLING METAL SCREWS


Architectural Roof Clip Fasteners

Description



Architectural roof Clip Fasteners are self-drilling screws that offer a low-profile head design for wood and steel applications and are ideal for attaching metal roof clips to metal and wood.


Approvals



ICC-ES ESR-3294
available on most SKUs


Specifications

- Diameters: #10 to #12
- Lengths: 1" to 2"
- Head/Drive Styles: Pancake, Phillips
- Material: Carbon steel
- Finish: Silver or gray Stalgard® coating



#10 DIAMETER, #2 PHILLIPS PANCAKE HEAD

ELCO CAT #	DEWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
ED0450-I	DFSED0450	#10-16 x 1"	#3	STALGARD	4,000
ED0460-I	DFSED0460	#10-16 x 1-1/2"	#3	STALGARD	3,000
ED0470-I	DFSED0470	#10-16 x 2"	#3	STALGARD	2,000
ETA850-I	DFSETA850	#10-12 x 1"	PIERCE POINT	STALGARD	4,000
ETA855-I	DFSETA855	#10-12 x 1-1/2"	PIERCE POINT	STALGARD	3,000
ETA860-I	DFSETA860	#10-12 x 2"	PIERCE POINT	STALGARD	2,000



#12 DIAMETER, #2 PHILLIPS PANCAKE HEAD

ELCO CAT #	DEWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
ED0735-I	DFSED0735	#12-14 x 1"	#3	STALGARD	4,000
ETA870-I	DFSETA870	#12-11 x 1"	PIERCE POINT	STALGARD	4,000



DCF622M2
20V MAX XR® VERSA-CLUTCH™
Adjustable Torque Screwgun Kit

SELF-TAPPING METAL SCREWS

Tap-Flex® Thread-Forming Structural Screws

Description



Tap-Flex® Thread-Forming Structural Screws are thread-forming, dual heat treated self-tapping fasteners that provide the strength, ductility, and resistance to embrittlement failures required in critical curtain wall and dissimilar metal applications. Tap-Flex® fasteners are designed to offer a replacement option for traditional nut and bolt assemblies and are an excellent solution for blind connections.

Specifications

- Diameters: 3/8", 1/2", and 5/8"
- Head Style: Hex washer
- Threads: E-Form® five-lobe thread forming
- Material: Alloy steel
- Finish: Silver Stalgard® SUB coating
- Heat Treat: Grade 5; meets ASTM A449 specifications (120 KSI strength)



3/8" DIAMETER, 9/16" HEX WASHER HEAD WITH SERRATIONS

ELCO CAT #	DeWALT CAT#	DESC.	DRILL BIT	FINISH	PACK
ESU310	DFSESU310	3/8"-16 x 1-1/2"	8.5 MM	STALGARD SUB	500
ESU320	DFSESU320	3/8"-16 x 2"	8.5 MM	STALGARD SUB	500
ESU330	DFSESU330	3/8"-16 x 2-1/2"	8.5 MM	STALGARD SUB	400
ESU340	DFSESU340	3/8"-16 x 3"	8.5 MM	STALGARD SUB	250
ESU350	DFSESU350	3/8"-16 x 4"	8.5 MM	STALGARD SUB	250
ESU360	DFSESU360	3/8"-16 x 5"	8.5 MM	STALGARD SUB	150



1/2" DIAMETER, 3/4" HEX WASHER HEAD WITH SERRATIONS

ELCO CAT #	DeWALT CAT#	DESC.	DRILL BIT	FINISH	PACK
ESU410	DFSESU410	1/2"-13 x 1-1/2"	29/64"	STALGARD SUB	250
ESU420	DFSESU420	1/2"-13 x 2"	29/64"	STALGARD SUB	250
ESU430	DFSESU430	1/2"-13 x 2-1/2"	29/64"	STALGARD SUB	200
ESU440	DFSESU440	1/2"-13 x 3"	29/64"	STALGARD SUB	150
ESU450	DFSESU450	1/2"-13 x 4"	29/64"	STALGARD SUB	150
ESU460	DFSESU460	1/2"-13 x 5"	29/64"	STALGARD SUB	100




5/8" DIAMETER, 15/16" HEX WASHER HEAD WITH SERRATIONS

ELCO CAT #	DeWALT CAT#	DESC.	DRILL BIT	FINISH	PACK
ESU510	DFSESU510	5/8"-11 x 1-1/2"	37/64"	STALGARD SUB	200
ESU520	DFSESU520	5/8"-11 x 2"	37/64"	STALGARD SUB	150
ESU530	DFSESU530	5/8"-11 x 2-1/2"	37/64"	STALGARD SUB	150
ESU540	DFSESU540	5/8"-11 x 3"	37/64"	STALGARD SUB	100
ESU550	DFSESU550	5/8"-11 x 4"	37/64"	STALGARD SUB	100
ESU560	DFSESU560	5/8"-11 x 5"	37/64"	STALGARD SUB	50

SELF-TAPPING METAL SCREWS

TapFast® Fasteners

Description



TapFast® Metal-to-Wood Self-Drilling Screws are high-performance fasteners designed specifically for attaching light gauge metal panels (18 ga. maximum) to wood frame structures.

- Specifications
- Size: #10, Lengths: 1" to 3"
 - Head/Drive: 1/4" HWH
 - Thread: Hi-lo, Point: Type 17
 - Material: Carbon steel
 - Finish: Stalgard® coating



#10 DIAMETER 1/4" HEX WASHER HEAD / ALUMINIUM BONDED SEALING WASHER

ELCO CAT #	DeWALT CAT#	DESC.	POINT TYPE	FINISH	PACK
EHH210-I	DFSEHH210	#10-16 x 1"	#17	STALGARD	3,000
EHH210-I-100	DFSEHH210-100	#10-16 x 1"	#17	STALGARD	100
EHH230-I	DFSEHH230	#10-16 x 1-1/2"	#17	STALGARD	2,500
EHH230-I-100	DFSEHH230-100	#10-16 x 1-1/2"	#17	STALGARD	100
EHH250-I	DFSEHH250	#10-16 x 2"	#17	STALGARD	1,500
EHH250-I-050	DFSEHH250-050	#10-16 x 2"	#17	STALGARD	50
EHH265-I	DFSEHH265	#10-16 x 2-1/2"	#17	STALGARD	1,000
EHH265-I-050	DFSEHH265-050	#10-16 x 2-1/2"	#17	STALGARD	50
EHH280-I	DFSEHH280	#10-16 x 3"	#17	STALGARD	800
EHH280-I-050	DFSEHH280-050	#10-16 x 3"	#17	STALGARD	50



DW267
2,000 RPM VSR
VERSA-CLUTCH™ Screwgun

PANEL RIVETS

Fab-Lok[®]

Description




Fab-Lok[®] Panel Rivets are vibration resistant fasteners that combine a screw and a slotted aluminum sleeve to provide resistance to loosening in high-stress and high-vibration environments, and are excellent for use with insulated metal panels.

Specifications




- Drive System: Hex
- Materials: Low carbon steel or 300 series stainless steel screw with aluminum sleeve
- Finish: Zinc



Before Installation



After Installation



Can be easily used in blind applications



CARBON STEEL

ELCO CAT #	DeWALT CAT#	GRIP RANGE	MAX PEN. LENGTH	HEAD HEIGHT	HEAD DIA.	PACK
EZJ100	DFSEZJ100	.062"-.250"	1.300"	0.385"	0.710"	1,000
EZJ120	DFSEZJ120	.250"-.500"	1.600"	0.385"	0.710"	1,000
EZJ140	DFSEZJ140	.500"-.750"	1.800"	0.385"	0.710"	1,000



H3 (300 SERIES) STAINLESS STEEL

ELCO CAT #	DeWALT CAT#	GRIP RANGE	MAX PEN. LENGTH	HEAD HEIGHT	HEAD DIA.	PACK
EZJ210	DFSEZJ210	.062"-.250"	1.300"	0.385"	0.710"	1,000
EZJ230	DFSEZJ230	.250"-.500"	1.600"	0.385"	0.710"	1,000
EZJ250	DFSEZJ250	.500"-.750"	1.800"	0.385"	0.710"	1,000

FAB-LOK DRIVE TOOLS*

CAT #	DeWALT CAT#	GRIP RANGE	PACK
EZJ900	DFSEZJ900	HOLDING SLEEVE WITH SOCKET	1

*Fab-Lok fastener is inserted into a 5/16" hole (hole size is not critical) then installed with a power driver equipped with a Fab-Lok holding sleeve, with a socket designed to fit DeWALT[®] tools DCF622, DW267, DW268 and DW269. Max. 1000 rpm during installation.

BUILDING PROTECTION SYSTEMS

Panelmate®

Description Panelmate® Storm Panel Anchoring System is a family of screw anchors available in both internally and externally threaded variations. Originally designed for installing hurricane panels, these versatile anchors can be used wherever 1/4"-20 threaded hardware needs to be attached to concrete, masonry or wood.

Specifications

- Accepts standard 1/4"-20 threaded hardware
- Available in multiple styles: Externally-threaded heads, internally-threaded heads or inserts
- Fasteners coated with Stalgard® typically show no red rust or other base metal corrosion on significant surfaces after 1000 hours of salt spray exposure in accordance with ASTM B117
- Stalgard® coating provides superior corrosion resistance compared with fasteners with standard zinc plating



PANELMATE PRO - DOUBLE-ENDED STUDS WITH STOP COLLAR

DeWALT CAT#	ANCHOR LENGTH	1/4"-20 STUD LENGTH	1/4"-20 STUD THREAD LENGTH	#14-10 FASTENER THREAD LENGTH	PACK
PANELMATE PRO					
DFSENT225	2-1/4"	1-1/8"	7/8"	2"	800
DFSENT325	3-1/4"	1-1/8"	7/8"	3"	500
DFSENT450	4-1/2"	1-1/8"	7/8"	3"	250
PANELMATE TVAS PRO (THROUGH-VENEER ANCHORING SYSTEM)					
DFSENT737	7-3/8"	1-1/8"	7/8"	3"	400



PANELMATE FEMALE ID (INTERNAL DRIVE) - INTERNALLY THREADED

DeWALT CAT#	ANCHOR LENGTH	INTERNAL DRIVE COUPLER LENGTH¹	#14-10 FASTENER THREAD LENGTH	PACK
PANELMATE FEMALE ID				
DFSENW260	2-5/8"	7/8"	1-3/4"	1,000
DFSENW325	3-1/4"	7/8"	2"	500
DFSENW550	5-1/2"	7/8"	3"	500
PANELMATE TVAS FEMALE ID (THROUGH-VENEER ANCHORING SYSTEM)				
DFSENW737	7-3/8"	7/8"	3"	300

¹The coupler contains approximately 0.25" of 1/4"-20 female thread.



PANELMATE INSERTS - INTERNALLY THREADED INSERT¹²

DeWALT CAT#	ANCHOR LENGTH	1/4"-20 INTERNAL THREAD LENGTH	PACK
PANELMATE L INSERT			
DFSENX305	2-1/8"	1"	500







¹The S inserts are through drilled to offer the option to accept longer hardware.

²The L inserts have a yellow nylon locking patch to resist loosening.

INSTALLATION TOOLS AND MATING HARDWARE

DeWALT CAT#	DESCRIPTION	PANELMATE TYPE	PACK	CASE
DFSENY156	3/16" x 1-1/2" PANELMATE PRO DRIVE SOCKET	PRO, TVAS PRO	1	25
DFSENY176-050	WING NUTS¹	PRO, TVAS PRO	50	1,500
DFSENY192	3" PANELMATE INSERT DRIVER	FEMALE ID, TVAS FEMALE ID, INSERTS	1	100

¹Wing nuts are produced in Zamac alloy.

	FASTENER TYPE	SELF-DRILLING TAPPING SCREWS						SELF-PIERCING TAPPING SCREWS		THREAD FORMING WTAP-PING SCREWS			PANEL RIVETS
	Fastener Family	Drilit - Dril-Flex - Bi-Flex - Alumi-Flex Architectural Roof - Clip Fasteners (For Steel)						TapFast Architectural Roof Clip Fasteners (For Wood)		Tap-Flex			Fab-Lok
	Diameter	#6	#8	#10	#12	1/4"	5/16"	#10	#12	3/8"	1/2"	5/8"	—
	DeWALT 20V MAX* XR® Versa-Clutch™ ADJUSTABLE TORQUE SCREWGUN DCF622	●	●	●	●	●		●	●				●
	DeWALT 2,000 rpm VSR™ Versa-Clutch™ SCREWGUN DW267	●	●	●	●	●		●	●				●
	DeWALT 1,000 rpm VSR™ Versa-Clutch™ SCREWGUN DW269				○	○	●						●
	20V MAX* 3/8" CORDLESS IMPACT WRENCH WITH HOG RING ANVIL DCF923									●	○	○	
	20V MAX* 1/2" IMPACT WRENCH WITH HOG RING ANVIL DCF921									●	○	○	
	20V MAX* XR® 1/2" MID-RANGE IMPACT WRENCH WITH HOG RING ANVIL DCF891									○	●	●	

• Optimal ○ Suitable

For 20V MAX Maximum initial battery voltage measured without a workload is 20 volts. Nominal voltage is 18.

Impact tools are not recommended for the installation of self drilling screws. A max 2500 rpm screw gun with torque sensing nose pieces should be used.

DRILL BITS

SDS+ Full Head Carbide

Description The DEWALT Elite Series™ SDS+ Drill bits are designed with full carbide heads to resist breakage when striking rebar and have up to twice the life of standard 2-Cutter bits.

Shank / Tip



Tool Rotary hammer with SDS + (slotted drive shaft) type chuck

Base Materials Concrete block, brick, and soft stone

Size Range 5/32" x 6-1/2" to 1-1/8" x 18"



SDS+ FULL HEAD CARBIDE

CAT #	DIAMETER	USABLE LENGTH	OVERALL LENGTH
DW5503	3/16"	4"	6-1/2"
DW5504	3/16"	5"	8-1/2"
DW5506	3/16"	10"	12"
DW5512	7/32"	8"	10"
DW5517	1/4"	4"	6"
DW5518	1/4"	6"	8-1/2"
DW55200	1/4"	10"	12"
DW5521	1/4"	12"	14"
DW5524	5/16"	4"	6"
DW5526	5/16"	10"	12"
DW5527	3/8"	4"	6-1/2"
DW5529	3/8"	8"	10"
DW5530	3/8"	10"	12"
DW5531	3/8"	16"	18"
DW5537	1/2"	4"	6"
DW5538	1/2"	8"	10-1/2"
DW5539	1/2"	10"	12"
DW5540	1/2"	16"	18"

DRILL BITS

SDS+ 2-Cutter Carbide

Description SDS+ Rotary Hammer Drill Bits have two sharp cutting edges for true holes, rock carbide tips for longer bit life and elongated four flute helix for faster material removal.

Shank / Tip



Tool Rotary hammer with SDS + (slotted drive shaft) type chuck

Base Materials Concrete block, brick, and soft stone

Size Range 5/32" x 6-1/2" to 1-1/8" x 16"



SDS+ 2-CUTTER CARBIDE

CAT #	DIAMETER	USABLE LENGTH	OVERALL LENGTH
DW5438_1	5/32"	4-1/2"	6-1/2"
DW5400	5/32"	2"	4"
DW5403	3/16"	4-1/2"	6-1/2"
DW5404	3/16"	6-1/2"	8-1/2"
DW5407	3/16"	12"	14"
DW5408	3/16"	14"	16"
DW5406	3/16"	10"	12"
DW5405	3/16"	8"	10"
DW5402	3/16"	2"	4"
DW5410	7/32"	4"	6"
DW5412	7/32"	4"	6"
DW5416	1/4"	2"	4"
DW5417	1/4"	4"	6"
DW5418	1/4"	6-1/2"	8-1/2"
DW5420	1/4"	10"	12"
DW5421	1/4"	12"	14"
DW5424	5/16"	4"	6"
DW5426	5/16"	10"	12"
DW5432	3/8"	22"	24"
DW5430	3/8"	10"	12"
DW5427	3/8"	4"	6"
DW5429	3/8"	8"	10"
DW5431	3/8"	16"	18"
DW5435	7/16"	10"	12"

DRILL BITS

SDS+ 2-Cutter Carbide

Description SDS+ Rotary Hammer Drill Bits have two sharp cutting edges for true holes, rock carbide tips for longer bit life and elongated four flute helix for faster material removal.

Shank / Tip



Tool Rotary hammer with SDS + (slotted drive shaft) type chuck

Base Materials Concrete block, brick, and soft stone

Size Range 5/32" x 6-1/2" to 1-1/8" x 16"



SDS+ 2-CUTTER CARBIDE

CAT #	DIAMETER	USABLE LENGTH	OVERALL LENGTH
DW5437	1/2"	4"	6"
DW5436	7/16"	16"	18"
DW5437	1/2"	4"	6"
DW5438	1/2"	8"	10"
DW5439	1/2"	10"	12"
DW5440	1/2"	16"	18"
DW5441	1/2"	22"	24"
DW5442	9/16"	4"	6"
DW5443	9/16"	10"	12"
DW5444	9/16"	16"	18"
DW5446	5/8"	6"	8"
DW5448	5/8"	16"	18"
DW5447	5/8"	10"	12"
DW5449	5/8"	22"	24"
DW5450	11/16"	6"	8"
DW5455	3/4"	10"	12"
DW5453	3/4"	6"	8"
DW5456	3/4"	16"	18"
DW5457	3/4"	22"	24"
DW5460	7/8"	6"	8"
DW5462	7/8"	16"	18"
DW5464	1"	8"	10"
DW5466	1"	16"	18"
DW5468	1-1/8"	8"	10"
DW5469	1-1/8"	16"	18"

DRILL BITS

SDS+ 4-Cutter Carbide

Description SDS+ Rotary Hammer Drill Bits have four sharp cutting edges for true holes, rock carbide tips for longer bit life and elongated four flute helix for faster material removal.

Shank / Tip



Tool Rotary hammer with SDS + (slotted drive shaft) type chuck

Base Materials Concrete block, brick, and soft stone

Size Range 5/8" x 10" to 1-1/8" x 18"



SDS+ 4-CUTTER CARBIDE

CAT #	DIAMETER	USABLE LENGTH	OVERALL LENGTH
DW5471	5/8"	8"	10"
DW5472	5/8"	16"	18"
DW5474	3/4"	8"	10"
DW5475	3/4"	16"	18"
DW5477	7/8"	8"	10"
DW5478	7/8"	16"	18"
DW5479	1"	8"	10"
DW5480	1"	16"	18"
DW5481	1-1/8"	8"	10"
DW5482	1-1/8"	6"	18"

DRILL BITS

SDS MAX 2-Cutter Carbide

Description SDS MAX Rotary Hammer Drill Bits have two sharp cutting edges for fast drilling, rock carbide tips for longer bit life and elongated four flute helix for faster material removal.

Shank / Tip



Tool Rotary hammer with SDS Max (slotted drive shaft) type chuck

Base Materials Concrete block, brick, and soft stone

Size Range 9/16" x 13-1/2" to 1-1/4" x 22-1/2"



SDS MAX 2-CUTTER CARBIDE

CAT #	DIAMETER	USABLE LENGTH	OVERALL LENGTH
DW5801	9/16"	8"	13-1/2"
DW5803	1/2"	8"	13-1/2"
DW5804	1/2"	16"	21-1/2"
DW5806	5/8"	8"	13-1/2"
DW5809	5/8"	16"	21-1/2"
DW5810	3/4"	8"	13-1/2"
DW5812	3/4"	16"	21-1/2"
DW5815	7/8"	8"	13-1/2"
DW5816	7/8"	16"	21-1/2"
DW5818	1"	8"	13-1/2"
DW5819	1"	16"	21-1/2"
DW5821	1-1/8"	10"	15"
DW5822	1-1/8"	18"	22-1/2"
DW5824	1-1/4"	10"	15"
DW5825	1-1/4"	18"	22-1/2"
DW5881	1-1/4"	18"	22-1/2"

DRILL BITS

SDS MAX 4-Cutter Carbide

Description SDS MAX Rotary Hammer Drill Bits have four sharp cutting edges for true holes, rock carbide tips for longer bit life and elongated four flute helix for faster material removal.

Shank / Tip



Tool Rotary hammer with SDS Max (slotted drive shaft) type chuck

Base Materials Concrete block, brick, and soft stone

Size Range 5/8" x 13-1/2" to 1-1/4" x 22-1/2"



SDS MAX 4-CUTTER CARBIDE

CAT #	DIAMETER	USABLE LENGTH	OVERALL LENGTH
DW5806	5/8"	8"	13-1/2"
DW5809	5/8"	16"	21-1/2"
DW5807	5/8"	31"	36"
DW5808	11/16"	16"	21-1/2"
DW5810	3/4"	8"	13-1/2"
DW5812	3/4"	16"	21-1/2"
DW5813	3/4"	31"	36"
DW5814	13/16"	16"	21-1/2"
DW5815	7/8"	8"	13-1/2"
DW5816	7/8"	16"	21-1/2"
DW5851	7/8"	31"	36"
DW5818	1"	8"	13-1/2"
DW5819	1"	16"	21-1/2"
DW5852	1"	24"	29"
DW5820	1"	31"	36"
DW5821	1-1/8"	10"	15"
DW5822	1-1/8"	18"	22-1/2"
DW5853	1-1/8"	24"	29"
DW5854	1-1/8"	31"	36"
DW5824	1-1/4"	10"	15"
DW5825	1-1/4"	18"	22-1/2"
DW5825	1-1/4"	18"	22-1/2"

DRILL BITS

SDS+ Carbide Hollow Drill Bit

Description SDS+ Hollow Drill Bits have improved drilling speed and a hollow design that allows dust to be removed when drilling which improves drilling speed. Hollow Drill Bits are OSHA Table 1 Compliant when used with an approved dust extractor.

Approvals



Shank / Tip



Tool

Rotary hammer with SDS+ or SDS Max type chuck

Base Materials

Concrete block, brick, and soft stone

Size Range

1/2" x 14-1/2" to
1-1/2" x 47-1/4"



SDS+ CARBIDE HOLLOW DRILL BIT

CAT #	DIAMETER	USABLE LENGTH	OVERALL LENGTH
DWA54038	3/8"	9-3/4"	14-1/2"
DWA54012	1/2"	9-3/4"	14-1/2"
DWA54916	9/16"	9-3/4"	14-1/2"
DWA54058	5/8"	9-3/4"	14-1/2"
DWA54116	11/16"	9-3/4"	14-1/2"
DWA54034	3/4"	9-3/4"	14-1/2"
DWA54316	13/16"	9-3/4"	14-1/2"

DRILL BITS

SDS MAX Carbide Hollow Drill Bit

Description SDS MAX Hollow Drill Bits have faster drilling speeds and a hollow design that allows dust to be removed when drilling which improves drilling speed. Hollow Drill Bits are OSHA Table 1 Compliant when used with an approved dust extractor.

Approvals



Shank / Tip



Tool

Rotary hammer with SDS+ or SDS Max type chuck

Base Materials

Concrete block, brick, and soft stone

Size Range

1/2" x 14-1/2" to
1-1/2" x 47-1/4"



SDS MAX CARBIDE HOLLOW DRILL BIT

CAT #	DIAMETER	USABLE LENGTH	OVERALL LENGTH
DWA58058	5/8"	15-3/4"	23-5/8"
DWA58034	3/4"	15-3/4"	23-5/8"
DWA58078	7/8"	15-3/4"	23-5/8"
DWA58001	1"	15-3/4"	23-5/8"
DWA58116	11/16"	15-3/4"	23-5/8"
DWA58118	1-1/8"	15-3/4"	23-5/8"
DWA58115	1-1/4"	15-3/4"	23-5/8"
DWA58958	5/8"	47-1/4"	39-3/8"
DWA58934	3/4"	47-1/4"	39-3/8"
DWA58978	7/8"	47-1/4"	39-3/8"
DWA58901	1"	47-1/4"	39-3/8"
DWA58918	1-1/8"	47-1/4"	39-3/8"
DWA58114	1-1/4"	47-1/4"	39-3/8"
DWA58138	1-3/8"	47-1/4"	39-3/8"
DWA58112	1-1/2"	47-1/4"	39-3/8"

INSTALLATION TOOLS

Hand Tools and Accessories

Description	Hammers, torque wrenches, and sockets.
-------------	--



HAMMER/SLEDGE		
CAT #	DESCRIPTION	PACK
DWHT51064	22 OZ. ONE-PIECE STEEL HAMMER HEAD LENGTH 5-1/2" HEAD WEIGHT 22 OZ. OVERALL LENGTH 16" OVERALL WEIGHT 2 LBS.	1
J1433G	PROTO 2.5 LB SLEDGE HAMMER	1



MICROMETER TORQUE WRENCHES						
CAT #	DRIVE SIZE	TORQUE RANGE	HEAD WIDTH	HEAD DEPTH	OVERALL LENGTH	PACK
DWMT75463	3/8"	20-100 FT-LBS	1-9/16"	78	17-5/16"	1
DWMT75462	1/2"	50-250 FT-LBS	—	1	27-1/2"	1



DRIVE IMPACT RATED UNIVERSAL SOCKETS SET		
CAT #	DESCRIPTION	PACK
DWMT19228	3/8" DRIVE IMPACT UNIVERSAL SOCKET SET (12PC): SAE 5/16", 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8", 15/16", 1"	1
DWMT19240	1/2" DRIVE 6PT IMPACT SOCKET SET (19PC): SAE 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8", 15/16", 1", 1-1/16", 1-1/8", 1-3/16", 1-1/4", 1-5/16", 1-3/8", 1-7/16", 1-1/2"	1



INSTALLATION TOOLS

Hand Tools and Accessories

Description Sockets for various anchors.



MANUAL SOCKETS FOR POWER-STUDS

CAT #	ANCHOR DIAMETER	SOCKET SIZE	SOCKET DRIVE	PACK
DWMT88977	1/4"	7/16"	3/8" DRIVE	1
DWMT86443	1/4"	7/16"	1/2" DRIVE	1
DWMT88979	3/8"	9/16"	3/8" DRIVE	1
DWMT86445	3/8"	9/16"	1/2" DRIVE	1
DWMT88982	1/2"	3/4"	3/8" DRIVE	1
DWMT86449	1/2"	3/4"	1/2" DRIVE	1
DWMT19573	5/8"	15/16"	3/8" DRIVE	1
DWMT86453	5/8"	15/16"	1/2" DRIVE	1
DWMT86457	3/4"	1-1/8"	1/2" DRIVE	1
DWMT17211	7/8"	1-15/16"	1/2" DRIVE	1
DWMT17227	1"	1-1/2"	1/2" DRIVE	1
DWMT74658	1-1/4"	1-7/8"	1/2" DRIVE	1

MANUAL SOCKETS FOR POWER BOLTS

CAT #	ANCHOR DIAMETER	SOCKET SIZE	SOCKET DRIVE	PACK
DWMT88980	1/2"	5/8"	3/8" DRIVE	1
DWMT88766	1/2"	5/8"	1/2" DRIVE	1
DWMT88982	5/8"	3/4"	3/8" DRIVE	1
DWMT86449	5/8"	3/4"	1/2" DRIVE	1
DWMT19573	3/4"	15/16"	3/8" DRIVE	1
DWMT86453	3/4"	15/16"	1/2" DRIVE	1

MANUAL SOCKETS FOR LOK BOLT ACORN NUT & HEX HEAD

CAT #	ANCHOR DIAMETER	SOCKET SIZE	SOCKET DRIVE	PACK
DWMT88976	1/4"	3/8"	3/8" DRIVE	1
DWMT88977	5/16"	7/16"	3/8" DRIVE	1
DWMT88978	3/8"	1/2"	3/8" DRIVE	1
DWMT88979	1/2"	9/16"	3/8" DRIVE	1
DWMT88982	5/8"	3/4"	3/8" DRIVE	1
DWMT19573	3/4"	15/16"	3/8" DRIVE	1

INSTALLATION TOOLS

Hand Tools and Accessories

Description Impact rated sockets for various anchor installations, and threaded rod cutter.



IMPACT RATED SOCKETS FOR SCREW-BOLT+, 316 SS WEDGE-BOLT & TAP-FLEX SCREWS

CAT #	ANCHOR DIAMETER	SOCKET SIZE	SOCKET DRIVE	PACK
DWMT751200SP	1/4"	7/16"	1/2" DRIVE	1
DWMT751220SP	3/8"	9/16"	1/2" DRIVE	1
DWMT751130SP	1/2"	3/4"	1/2" DRIVE	1
DWMT751040SP	5/8"	15/16"	1/2" DRIVE	1
DWMT746590SP	3/4"	1-1/8"	1/2" DRIVE	1



IMPACT RATED SOCKET FOR HANGERMATE+ (EXTERNALLY THREADED CONCRETE ANCHOR)

CAT #	NOM. ANCHOR SIZE	SOCKET SIZE	PACK
DWMT739340SP	3/8"	1/2"	1




20V MAX* THREADED ROD CUTTER KIT


CAT #	DESCRIPTION	PACK
DCS350D1	<p>KIT INCLUDES:</p> <p>DCS371B THREADED ROD CUTTER</p> <p>DCB203 2 AH LITHIUM ION BATTERY</p> <p>DCB112 CHARGER</p> <p>(2) DCS3501B3 4 SIDED CUTTING DIES CUTTING DIE</p> <p>ADJUSTMENT WRENCH</p> <p>CUTS 1/4", 3/8", 1/2" MILD STEEL COARSE THREADED ROD AND 1/4" 3/8" STAINLESS STEEL COARSE THREADED ROD</p>	1



SDS+ ROTARY HAMMERS
<1" SDS+ Cordless L-Shape

 <p>DCH072D2</p> <p>DCH172D2</p>	CATALOG #	DCH072D2	DCH172D2
	MOTOR TYPE	12V	N/A
	IMPACT ENERGY (JOULES)**	1.1	1.4
	RPM	910	1,060
	BPM	4,280	4,980
	OPTIMAL DRILLING RANGE	5/32" – 3/8"	5/32" – 3/8"
	BATTERY VOLTAGE/AMPS	12V	20V
	KIT BATTERY AH	(2) 3.0 AH	(2) 2.0 AH
	WEIGHT (LBS.)	3.69	4.72
	VIBRATION CONTROL	NO	N/A
	VIBRATION M/S ²	9.7	8.8
	SERVICE CONTRACT	1 YEAR FREE SERVICE	2 YEARS FREE SERVICE


SDS+ ROTARY HAMMERS
1" SDS+ Cordless L-Shape

 <p>DCH273P2</p>	CATALOG #	DCH273P2
	IMPACT ENERGY (JOULES)**	2.1
	RPM	1,100
	BPM	4,600
	OPTIMAL DRILLING RANGE	3/16" - 1/2"
	ROTATION CONTROL	✓
	BATTERY VOLTAGE/AMPS	20V
	KIT BATTERY AH	(2) 20V 5.0 Ah
	WEIGHT (LBS.)	6.8
	VIBRATION CONTROL	✓
	VIBRATION M/S ²	6.6
	CHIPPING	✓
	CORDLESS DUST EXTRACTOR	DWH303
	SERVICE CONTRACT	2 YEARS FREE SERVICE




SDS+ ROTARY HAMMERS

1" SDS+ Cordless/Corded D-Handle

 DCH133M2 D2526K	CATALOG #	DCH133M2	D2526K
	IMPACT ENERGY (JOULES)**	2.6	2.8
	RPM	1,500	1,500
	BPM	5,500	5,540
	OPTIMAL DRILLING RANGE	5/32" – 5/8"	5/32" – 5/8"
	ROTATION CONTROL	INTEGRAL CLUTCH	INTEGRAL CLUTCH
	BATTERY VOLTAGE/AMPS	12V MAX*	8 AMPS
	BATTERY AH	4.0 AH	N/A
	WEIGHT (LBS.)	5.5	6.6
	VIBRATION CONTROL	NO	✓
	VIBRATION M/S²	N/A	9.6
	CHIPPING	✓	✓
	SERVICE CONTRACT	1 YEAR FREE SERVICE	2 YEARS FREE SERVICE

SDS+ ROTARY HAMMERS



1-1/8" SDS+ Corded L-Shape

 D25333K	CATALOG #	D25333K
	IMPACT ENERGY (JOULES)**	3.5
	RPM	1,150
	BPM	5,200
	OPTIMAL DRILLING RANGE	3/16" - 7/8"
	ROTATION CONTROL	INTEGRAL CLUTCH
	BATTERY VOLTAGE/AMPS	8.5 AMPS
	BATTERY AH	N/A
	WEIGHT (LBS.)	8.2
	VIBRATION CONTROL	✓
	VIBRATION M/S²	10
	CHIPPING	✓
	SERVICE CONTRACT	2 YEARS FREE SERVICE




SDS+ ROTARY HAMMERS

1-1/8" SDS+ Cordless/Corded D-Handle

 DCH263R2  D25263K	CATALOG #	DCH263R2	D25263K
	IMPACT ENERGY (JOULES)**	3	3
	RPM	1,165	1,450
	BPM	4,300	5,350
	OPTIMAL DRILLING RANGE	1/4" – 3/4"	1/4" – 3/4"
	ROTATION CONTROL	✓	INTEGRAL CLUTCH
	BATTERY VOLTAGE/AMPS	20V	8.5 Amps
	BATTERY AH	(2) 6.0 Ah	N/A
	WEIGHT (LBS.)	5.95	6.8
	CORDLESS DUST EXTRACTOR	DWH205DH	NO
	VIBRATION CONTROL	✓	NO
	VIBRATION M/S ²	9.1	9.8
CHIPPING		✓	✓
SERVICE CONTRACT		2 YEARS FREE SERVICE	2 YEARS FREE SERVICE

SDS+ ROTARY HAMMERS



1-1/8" SDS+ Cordless L-Shape

 DCH293R2	CATALOG #	DCH293R2
	IMPACT ENERGY (JOULES)**	3.5
	RPM	1,000
	BPM	4,480
	OPTIMAL DRILLING RANGE	1/4" x 7/8"
	ROTATION CONTROL	E-CLUTCH®
	BATTERY VOLTAGE/AMPS	20V
	BATTERY AH	(2) 20V 6.0 Ah
	WEIGHT (LBS.)	6.8
	CORDLESS DUST EXTRACTOR	✓
	VIBRATION CONTROL	✓
	VIBRATION M/S ²	8.2
CHIPPING		✓
SERVICE CONTRACT		2 YEARS FREE SERVICE



SDS+ ROTARY HAMMERS


1 1/4" SDS+ Cordless/Corded L-Shape

 <p>DCH416X2</p>  <p>D25416K</p>	CATALOG #	DCH416X2	D25416K
	IMPACT ENERGY (JOULES)**	4.5	4.2
	RPM	725	1,150
	BPM	4,200	4700
	OPTIMAL DRILLING RANGE	5/8" - 1-1/8"	3/16" - 7/8"
	ROTATION CONTROL	E-CLUTCH®	INTEGRAL CLUTCH
	BATTERY VOLTAGE/AMPS	60V	9 AMPS
	BATTERY AH	(2) 9 Ahr	N/A
	WEIGHT (LBS.)	9	14.35
	VIBRATION CONTROL	SHOCKS®	SHOCKS®
	VIBRATION M/S²	6.3	8.5
	CHIPPING	YES	YES
	WIRELESS TOOL READY	YES	NO
	TAG READY	YES	NO
	SERVICE CONTRACT	2 YEARS FREE SERVICE	2 YEARS FREE SERVICE



DUST EXTRACTION

Onboard Dust Extractor for 1-1/8" SDS+ D-Handle Hammers

 <p>DWH205DH</p>	CATALOG #	DWH205DH
	COMPATIBILITY	DCH263B, DCH263R2
	INTERCHANGEABLE DRILLING NOZZLES	3
	OPTIMAL BIT TYPE (NOZZLE 1)	STOP BIT
	OPTIMAL BIT LENGTH (NOZZLE 2)	UP TO 1/2"
	OPTIMAL BIT LENGTH (NOZZLE 3)	UP TO 1"
	MAX DRILLING LENGTH	10"
	ADJUSTABLE DEPTH GAUGE	YES
	WEIGHT (LBS.)	3.42


DUST EXTRACTION

Onboard Dust Extractor for 1-1/8" SDS+ Hammers

 <p>DWH304DH</p>	CATALOG #	DWH304DH
	COMPATIBILITY	DCH293B, DCH293R2, DCH293X2, AND D25333K
	OPTIMAL DRILLING RANGE	UP TO 1"
	OPTIMAL BIT LENGTH	UP TO 8"
	MAX BIT LENGTH	10"
	WEIGHT (LBS.)	3.5

DUST EXTRACTION

20V Max* Brushless Universal Dust Extractor

 <p>DWH161D1</p>	CATALOG #	DWH161D1
	COMPATIBILITY	D25301D, DWH200D
	VOLTAGE	20V MAX*
	AIRFLOW	19 CFM
	NOZZLE INSIDE DIAMETER	1"
	WIRELESS TOOL CONTROL™	YES
	AIRLOCK CONNECTOR READY	YES
	WET OR DRY	DRY ONLY
	WEIGHT (LBS.)	3.62


DUST EXTRACTION


Large Hammer Dust Extraction - Hole Cleaning


 <p>DWH050</p>	CATALOG #	DWH050
	COMPATIBILITY	SDS PLUS SDS MAX SPLINE
	INTERCHANGEABLE DRILLING HEADS	2
	OPTIMAL DRILLING RANGE (HEAD 1)	UP TO 1-1/2"
	OPTIMAL DRILLING RANGE (HEAD 2)	UP TO 2"
	AIRLOCK CONNECTOR READY	YES
	WEIGHT (LBS.)	1.32


DUST EXTRACTION


Onboard Dust Extractor for 1-1/8" SDS+ D-Handle Hammers

 <p>DWH205DH</p>	CATALOG #	DWH205DH
	COMPATIBILITY	DCH263B, DCH263R2
	INTERCHANGEABLE DRILLING NOZZLES	3
	OPTIMAL BIT TYPE (NOZZLE 1)	STOP BIT
	OPTIMAL BIT LENGTH (NOZZLE 2)	UP TO 1-1/2"
	OPTIMAL BIT LENGTH (NOZZLE 3)	UP TO 1"
	MAX DRILLING LENGTH	10"
	ADJUSTABLE DEPTH GAUGE	YES
	WEIGHT (LBS.)	3.42

DUST EXTRACTION		
1-1/8" Hex Demolition Dust Collection Attachment		
 DWH052	CATALOG #	DWH052
	COMPATIBILITY	1 - 1/8" HEX
	MAX CHISEL WIDTH	1-1/4"
	AIRLOCK CONNECTOR READY	YES
	WEIGHT (LBS.)	1.32


DUST EXTRACTION		
FLEXVOLT® 60V Max* Dust Extractor		
 DCV585T2	CATALOG #	DCV585T2
	COMPATIBILITY	DWH050, DWH052, DWH053
	VOLTAGE	60V MAX*
	TANK SIZE	2 GAL
	AIRFLOW	125 CFM
	HOSE LENGTH	8 FT
	WIRELESS TOOL CONTROL™	YES
	AIRLOCK CONNECTOR READY	YES
	WET OR DRY	BOTH
	WEIGHT (LBS.)	17.6

DUST EXTRACTION		
Onboard Dust Extractor for 1" SDS+ Hammers		
 DWH303DH	CATALOG #	DWH303DH
	COMPATIBILITY	DCH273B, DCH273P2
	OPTIMAL DRILLING RANGE	UP TO 5/8"
	OPTIMAL BIT LENGTH	UP TO 4"
	MAX BIT LENGTH	6"
	ADJUSTABLE DEPTH GAUGE	YES
	WEIGHT (LBS.)	3.08

DUST EXTRACTION		
SDS Rotary Hammer Dust Box Evacuator		
 DWH079D	CATALOG #	DWH079D
	ON-BOARD EXTRACTOR COMPATIBILITY	DWH205DH, DWH302DH, DWH304DH, DWH303DH, D25303DH
	EXTRACTOR COMPATIBILITY	DCV585T2, DCV010, DCV012
	AIRLOCK CONNECTOR READY	YES
	WEIGHT (LBS.)	0.78


DUST EXTRACTION

Dust Extraction Tube Kit with Hose

 DWH200D	CATALOG #	DWH200D
	COMPATIBILITY	SDS PLUS EXCLUDING D25416K
	CLEAR DUST TUBES	3
	OPTIMAL BIT TYPE (TUBE 1)	STOP BIT
	OPTIMAL BIT LENGTH (TUBE 2)	UP TO 6"
	OPTIMAL BIT LENGTH (TUBE 3)	UP TO 10"
	HOSE LENGTH	4 FT
	AIRLOCK CONNECTOR READY	YES
	WEIGHT (LBS.)	0.89


DUST EXTRACTION

SDS Max Chiseling Dust Collection Attachment

 DWH053	CATALOG #	DWH053
	COMPATIBILITY	SDS MAX 1-1/8" HEX
	OPTIMAL CHISEL LENGTH	10" TO 18"
	DUST BOOTS	3
	AIRLOCK CONNECTOR READY	YES
	WEIGHT (LBS.)	1.32


DUST EXTRACTION





































8 Gallon Wet/Dry HEPA/RRP Dust Extractor

 DWV010	CATALOG #	DWV010
	COMPATIBILITY	DWH050, DWH052, DWH053
	AMPS	15
	TANK SIZE	8 GAL
	AIRFLOW	150 CFM
	HOSE LENGTH	15 FT
	WET OR DRY	BOTH
	WEIGHT (LBS.)	21.0

DUST EXTRACTION

10 Gallon Wet/Dry HEPA/RRP Dust Extractor

 DWV015	CATALOG #	DWV015
	COMPATIBILITY	DWH050, DWH052, DWH053
	AMPS	15
	TANK SIZE	10 GAL
	AIRFLOW	155 CFM
	HOSE LENGTH	15 FT
	WET OR DRY	BOTH
	VARIABLE-SPEED DIAL	YES
	WEIGHT (LBS.)	33.5

SDS+ DRILLING	 DCH273P2 DCH273B	 DWH303DH	 SDS PLUS Hollow Bit	 DWH050 Large Hammer Drilling Dust Extraction
	 DCH293R2 DCH293B, D25333K	 DWH304DH	OR	+
	 DCH263R2 DCH263B	 DWH205DH		+
	 DCH133M2 DCH133B, D25133K, D25262K, D25263K, D25416K, DCH416X2, DCH416B		 DWH050 Large Hammer Drilling Dust Extraction	 DWH050 Large Hammer Drilling Dust Extraction
SDS MAX DRILLING	 DCH273P2 DCH273B, D25133K, DCH133B, DCH133M2, D25262K, D25263K, DCH263B, DCH263R2, D25333K, DCH072G2, DCH072B, DCH172D2, DCH172B, DCH172E2	 DWH200D Dust Extractor Telescope with Hose	OR	 D25301D Dust Extractor Telescope with Hose
		 DWH050 Large Hammer Drilling Dust Extraction	+	 DWH050 Large Hammer Drilling Dust Extraction
		 DWH050 Large Hammer Drilling Dust Extraction	+	 DWH050 Large Hammer Drilling Dust Extraction
		 DWH050 Large Hammer Drilling Dust Extraction	+	 DWH050 Large Hammer Drilling Dust Extraction
CHIPPING & DEMOLITION	 DCH775X2 DCH481B, D25481K, D25614K, DCH614B, DCH614X2, DCH832X1, DCH892X1, D25733K, DCH733B, DCH733X2, D25773K, DCH773Y2, DCH735X2, DCH775X2	 SDS MAX Hollow Bit	+	 DWH050 Large Hammer Drilling Dust Extraction
			OR	 DWH050 Large Hammer Drilling Dust Extraction
			+	 DWH050 Large Hammer Drilling Dust Extraction
			+	 DWH050 Large Hammer Drilling Dust Extraction
CHIPPING & DEMOLITION	 D25832K D25810K, D25872K, D25892K, DCH832X1, DCH892X1	 DWH053 SDS MAX Chiseling Dust Collection Attachment	+	 DCV585 Dust Extractor
	 D25901K D25899K, D25951K		+	 DWH050 Large Hammer Drilling Dust Extraction
	 D25901K D25899K, D25951K		+	 DWH050 Large Hammer Drilling Dust Extraction
	 D25901K D25899K, D25951K	 DWH052 Breaker Dust Extraction	+	 DWH050 Large Hammer Drilling Dust Extraction



CORDLESS IMPACT DRIVERS & WRENCHES


	DCF901	DCF903	DCF911	DCF913
BATTERY PLATFORM	12V MAX*	12V MAX*	20V MAX*	20V MAX*
ANVIL SIZE	1/2"	3/8"	1/2"	3/8"
ANVIL TYPE	HOG RING	HOG RING	HOG RING	HOG RING
MAX FWD TORQUE	250 FT-LBS	250 FT-LBS	250 FT-LBS	250 FT-LBS
MAX BREAKAWAY TORQUE	400 FT-LBS	400 FT-LBS	400 FT-LBS	400 FT-LBS



	DCF921	DCF922	DCF923	DCF891
BATTERY PLATFORM	20V MAX*	20V MAX*	20V MAX*	20V MAX*
ANVIL SIZE	1/2"	1/2"	3/8"	1/2"
ANVIL TYPE	HOG RING	DETENT	HOG RING	HOG RING
MAX FWD TORQUE	300 FT-LBS	300 FT-LBS	300 FT-LBS	600 FT-LBS
MAX BREAKAWAY TORQUE	450 FT-LBS	500 FT-LBS	450 FT-LBS	800 FT-LBS



	DCF899	DCF898	DCF900	DCF961
BATTERY PLATFORM	20V MAX*	20V MAX*	20V MAX*	20V MAX*
ANVIL SIZE	1/2"	7/16"	1/2"	1/2"
ANVIL TYPE	DETENT	QC	HOG RING	HOG RING
MAX FWD TORQUE	700 FT-LBS	700 FT-LBS	1,030 FT-LBS	1,200 FT-LBS
MAX BREAKAWAY TORQUE	1,200 FT-LBS	1,200 FT-LBS	1,400 FT-LBS	1,750 FT-LBS

*Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

PRODUCT	PAGE
0.300" Head Drive Pins.....	110-112
316 Stainless Steel Wedge-Bolt™.....	30
8mm Head Top Hat Drive Pins.....	112
AC100+ Gold®.....	80
AC200+™.....	79
AC50™.....	81
Adhesive Piston Plugs.....	91
Aggre-Gator®.....	40
Alumi-Flex® 302 SS Drill Screws.....	135
Architectural Roof Clip Fasteners.....	136
Bang-It®+.....	56
Bang-It®+ Bridge Bar.....	63
Bantam Plug.....	78
Bi-Flex® 300 SS Bi-Metal Self-Drilling Screws.....	132-134
Calk-In™.....	53
CCN Cordless Fasteners.....	96
CCU+™.....	20-22
Ceiling Clip Assemblies.....	113-114
Conduit Clip Assemblies.....	115
Cordless Fastening Accessories.....	99
Cordless Impact Drivers and Wrenches.....	157
Crete-Flex®.....	38-39
CSI Spiral Drive Pins.....	108-109
D25263K.....	151
D2526K.....	150
D25301D.....	156
D25333K.....	150
D25416.....	152
D25832K.....	156
D25901K.....	156
D25960K.....	156
D25980K.....	156
DCF622.....	136, 141
DCF891.....	141, 157
DCF898.....	157
DCF899.....	157
DCF900.....	157
DCF901.....	157
DCF903.....	157
DCF911.....	157
DCF913.....	157
DCF921.....	141, 157
DCF922.....	157

PRODUCT	PAGE
DCF923.....	141, 157
DCF961.....	157
DCH072.....	149
DCH133.....	67, 150, 156
DCH172.....	149
DCH263.....	26, 151, 156
DCH273.....	46, 149, 156
DCH293.....	54, 151, 156
DCH416.....	15, 27, 152
DCH614.....	23, 27
DCH775.....	85, 156
DCN890P.....	95
DCN891.....	95, 160
DCS350.....	59, 148
DCV585.....	27, 52, 154, 155
DDI+™ (Deck Insert).....	60
Deck Driller Extension.....	58
DFD270 Tool.....	103
Dispensing Tools.....	88
Double™.....	52
Dril-Flex® Structural Drill Screws.....	129-131
Drillit® Drill Screws for Wood-to-Metal.....	126
Drillit® Screws with Bonded Sealing Washers.....	123-125
Drillit® Screws with Extended Drilling Capacity....	127-128
Drillit® Standard Drill Screws.....	119-122
Drive®.....	66
Dust Extraction.....	152-156
DW267.....	138, 141
DW269.....	141
DWH050.....	72, 153, 156
DWH052.....	154
DWH053.....	155, 166
DWH079D.....	154
DWH161.....	156
DWH200D.....	155, 156
DWH205DH.....	152, 153, 156
DWH303DH.....	154, 156
DWH304DH.....	153, 156
DWV010.....	27, 155, 156
DWV015.....	27, 52, 155, 156
Fab-Lok®.....	139
Fluted Plastic Anchor.....	78
Hammer Drive Pin.....	118

PRODUCT	PAGE
Hammer-Capsule®	85
Hand Tools and Accessories	146-148
Hangermate® for Concrete	41
Hangermate® for Steel.....	42
Hangermate® for Wood.....	43
Hangermate®+ for Concrete.....	41
Heli-Pin™	70
Hole Cleaning Tools & Accessories.....	89-90
Hollow-Set Dropin™	49
Lag Shield™	53
Lok-Bolt AS®	24-25
Mini Dropin™	51
Mini-Undercut+™	50
Mixing Nozzles and Extensions.....	90
Nylon Nailin®	69
P1000 Tool	107
P2201 Tool	106
P3500 Tool	105
P3600 Tool	104
PA3500 Tool	105
Panelmate®	140
Pan-Knocker® II+.....	59
Poly-Toggle®	77
Powder-Actuated Accessories.....	117
Powder-Actuated Loads.....	117
Power-Bolt®	26
Power-Bolt®+	23
PowerFoam™	86
PowerStick™	86
Power-Stud® - 304 Stainless	17
Power-Stud® - 316 Stainless	18
Power-Stud®+ HD5	16
Power-Stud®+ SD1	12
Power-Stud®+ SD2	13
Power-Stud®+ SD4	14
Power-Stud®+ SD6	15
Pure110+®	83
Pure220+™	82
Pure50+™	84
Push-In Coupler	61
RapidSet® Tools	54
Rebar/Dowel Basket Assemblies.....	116
Rod Hanging Clip Assemblies	116

PRODUCT	PAGE
Safe-T™ Pin	70
Screen Tubes	92
Screw-Bolt™ +	28-29
SDS MAX 2-Cutter Carbide.....	144
SDS MAX 4-Cutter Carbide.....	144
SDS MAX Carbide Hollow Drill Bit.....	145
SDS+ 2-Cutter Carbide.....	142-143
SDS+ 4-Cutter Carbide.....	143
SDS+ Carbide Hollow Drill Bit.....	145
SDS+ Full Head Carbide	142
SDS+ Rotary Hammers.....	149-152
Sharkie™	77
Single™	52
Smart DI Anchors (Drop In).....	46
Snake+®	45
Sniper™ Tool.....	104
Spike®	64-65
Steel-Dropin™	47-48
STICK-E™	97-98
Strap-Toggle™	73
Suspender®	44
T1000 Tool.....	106
TapFast® Fasteners	138
Tap-Flex® Thread-Forming Structural Screws	137
Threaded Rod Cutter Kit	148
Threaded Studs.....	114
Toggle Bolt.....	71-72
Trak-It® C5	100
Trak-It® C5 Accessories	102
Trak-It® C5 Fuel Cell	102
Trak-It® C5 Pins.....	101
TriggerFoam™ Pro.....	87
Ultracon®	36
Ultracon® SS4	37
Ultracon®+	31-35
Wall Dog®	74
Wood-Knocker® II Installation Tool	58
Wood-Knocker® II+.....	57
Zamac Hammer-Screw®.....	67
Zamac Nailin®	68
Zip-It® & Zip-It® Jr.	75
Zip-Toggle®	73



ANCHORS & FASTENERS

NOTES

NOTES



ANCHORS & FASTENERS

NOTES

DEWALT®

ANCHORS & FASTENERS

- **GAS-FREE OPERATION:**
Runs on DEWALT 20V MAX* battery.
- **1IN. MAGAZINE:** Reduces weight vs. DCN890 and allows for improved access into deep track. Interchangeable with 2-1/4 in. magazine.**
- **BRUSHLESS MOTOR:**
Comparable application speed to gas concrete nailers.
- **FIELD SERVICEABLE PISTON:** Can be replaced by user in the field in under 2 minutes.



* Maximum initial battery voltage (measured without a work-load) is 20 volts. Nominal voltage is 18.

** 2-1/4" magazine and pins also available.

20V MAX* 1 in. Magazine Cordless Concrete Nailer



DCN891P2



DEWALT®

GUARANTEED TOUGH.®



VISIT **ANCHORS.DEWALT.COM** FOR:

DOWNLOADS • TRAINING • SUPPORT • SOFTWARE

CUSTOMER SERVICE

Call: 1-800-524-3244

Email: DEWALTanchors@sbdinc.com

ENGINEERING & PRODUCT SUPPORT

Call: 1-800-524-3244

Email: anchors@DEWALT.com

1-800-4 DEWALT

www.DEWALT.com