

## **ANCHORS & FASTENERS**

## **Single Expansion Anchor**

PRE-ASSEMBLED SET OF **EXPANSION SHIELDS** AND EXPANDER CONE

CORROSION **RESISTANT ZAMAC ALLOY SLEEVE AND THREADED EXPANSION** CONE



### **Double Expansion Anchor**



#### **TYPICAL APPLICATIONS**

- Ideal for masonry materials
- > Useful for solid concrete, block, brick & stone
- Suited for base materials of questionable strength
- Not recommended for overhead attachments

#### SINGLE: APPROVALS

#### **BASE MATERIALS**



**ASTM E488** 



## **DOUBLE: APPROVALS**



Federal GSA Specification









**BASE MATERIALS** 









Precast Hollow Core Plank



Stone

SINGLE EXPANSION ANCHOR										
CAT #	SIZE	LENGTH	DRILL DIA	CTN	MSTR					
09650	1/4"	1/2"	1-3/8"	50	250					
09655	5/16"	5/8"	1-5/8"	50	250					
09665	3/8"	5/8"	1-5/8"	50	250					
09675	1/2"	7/8"	2-1/2"	25	125					
09685	5/8"	1"	2-3/4"	25	125					

DOUBLE EXPANSION ANCHOR										
CAT #	SIZE	LENGTH	DRILL DIA	MIN HOLE DEPTH	CTN	MSTR				
09510	1/4"	1-3/8"	1/2"	1-1/4"	50	500				
09515	5/16"	1-5/8"	5/8"	1-1/2"	50	500				
09520	3/8"	2"	3/4"	1-3/4"	50	250				
09525	1/2"	2-1/2"	7/8"	2-1/4"	25	250				
09530	5/8"	2-3/4"	1"	2-1/2"	25	100				
09535	3/4"	3-15/16"	1-1/4"	3-1/2"	10	50				



Ideal for masonry applications

### **RELATED PRODUCTS**



**DCH293R2DH** 20V MAX\* XR® SDS PLUS ROTARY HAMMER W/DUST COLLECTION



DCH273P2DH0 20V MAX\* XR® SDS PLUS ROTARY HAMMER W/ON-BOARD DUST EXTRACTOR



**DWH050K**LARGE HAMMER DUST
EXTRACTION - HOLE CLEANING



\*For 20V MAX\* Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

# 1-800-4-**DEWALT**

# www. **DEWALT**.com

Copyright ©2021 DEWALT. The following are trademarks for one or more DEWALT power tools, accessories, anchors and concrete adhesives: The yellow and black color scheme; the "D"-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool. ICDWDBLSGLSS