

according to HPR, Schedule 1

Reviewed on 04/26/2023

1 Identification

Product identifier

- · Trade name: POWERFOAM
- · Application of the substance / the mixture One-component polyurethane foam hand held
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier: DEWALT Industrial Tools 701 East Joppa Road Towson, MD 21286 USA

· Information department:

Phone +1 800-524-3244

Fax +1 877-871-1965

· Emergency telephone number:

CHEMTREC: 800-424-9300 (within continental USA) CHEMTREC: +1 703 527-3887 (outside USA)

2 Hazard identification

Classification of the substance or mixture

Flammable Aerosols - Category 1	H222-H229	Extremely flammable aerosol. Pressurized container: may burst if heated.			
Acute Toxicity (Inhalation) - Category 4	H332	Harmful if inhaled.			
Skin Irritation - Category 2	H315	Causes skin irritation.			
Eye Irritation - Category 2A	H319	Causes serious eye irritation.			
Respiratory Sensitizer - Category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.			
Skin Sensitizer - Category 1	H317	May cause an allergic skin reaction.			
Carcinogenicity – Category 2	H351	Suspected of causing cancer.			
Specific Target Organ Toxicity - Single Exposure - Category 3	H335	May cause respiratory irritation.			
Specific Target Organ Toxicity - Repeated Exposure - Category 2	e H373	May cause damage to organs through prolonged or repeated exposure.			

Label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

(Contd. on page 2)

[·] GHS label elements



according to HPR, Schedule 1

Printing date 04/26/2023 Reviewed on 04/26/2023

Trade name: POWERFOAM

(Contd. of page 1)

· Hazard-determining components of labeling:

diphenylmethanediisocyanate,isomeres and homologues

Hazard statements

Extremely flammable aerosol. Recipiente a presión: Puede reventar si se calienta.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Keep out of reach of children.

Obtain special instructions before use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Do not breathe vapours/spray.

Wear protective gloves/protective clothing/eye protection.

In case of inadequate ventilation wear respiratory protection (a protective mask with an appropriate gas filter - i.e. type A1 according to standard EN 14387).

IF ON SKIN: Wash with plenty of water/soap.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of container to in accordance with local/regional/national/international regulation.

· Additional information:

- Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used. Contains isocyanates. May produce an allergic reaction.

Information pertaining to particular dangers for man and environment:

NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)





according to HPR, Schedule 1

Printing date 04/26/2023 Reviewed on 04/26/2023

Trade name: POWERFOAM

(Contd. of page 2)

3 Composition/Information on ingredients

Chemical characterization: Mixtures

· **Description**: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:					
CAS: 9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	35-45% w/w *			
CAS: 13674-84-5	tris(2-chlorisopropyl)-phosphate	10-15% w/w *			
CAS: 75-28-5	isobutane	1-10% w/w *			
CAS: 115-10-6	dimethyl ether	1-10% w/w *			
CAS: 74-98-6	propane	1-10% w/w *			

^{*} Actual concentration ranges are withheld as a trade secret.

4 First-aid measures

Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture

Carbon monoxide (CO)

Nitrogen oxides (NOx)

Hydrogen cyanide (HCN)

- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- Additional information Cool endangered receptacles with water spray.

CA



according to HPR, Schedule 1

Printing date 04/26/2023 Reviewed on 04/26/2023

Trade name: POWERFOAM

(Contd. of page 3)

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

Information about storage in one common storage facility:

Store away from oxidizing agents.

Do not store together with acids.

Do not store together with alkalis (caustic solutions).

· Further information about storage conditions:

Keep receptacle tightly sealed.

Store in dry conditions.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Storage class: 2B

* Specific end use(s) No further relevant information available.



according to HPR, Schedule 1

Printing date 04/26/2023 Reviewed on 04/26/2023

Trade name: POWERFOAM

(Contd. of page 4)

8 Exposure controls/ Personal protection

Additional information about design of technical systems:

No further data; see section 7.

Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

EL TWA: 0.005 ppm Ceiling: 0.01 ppm

CAS: 115-10-6 dimethyl ether

EL TWA: 1000 ppm

· Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation


Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:





according to HPR, Schedule 1

Printing date 04/26/2023 Reviewed on 04/26/2023

Trade name: POWERFOAM

· Body protection: Protective work clothing

(Contd. of page 5)

Physical and chemical prope	7.000	
Information on basic physica	al and chemical properties	
General Information		
Appearance:	Agrand	
Form: Color:	Aerosol According to product specification	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Not applicable, as aerosol.	
Flash point:	Not applicable, as aerosol.	
Flammability (solid, gaseous):	Not applicable.	
Auto igniting:	235 °C	
Decomposition temperature:	Not determined.	
Ignition temperature:	Product is not selfigniting.	
Danger of explosion:	Not determined.	
Explosion limits:		
Lower:	1.8 Vol %	
Upper:	8.5 Vol %	
Vapor pressure at 20 °C:	3000 hPa	
Density:	Not determined.	
Relative density	Not determined.	
Vapor density Evaporation rate	Not determined.	
•	Not applicable.	
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wa		
· · · · · · · · · · · · · · · · · · ·	. Not determined.	
Viscosity: Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content/VOC content:		

(Contd. on page 7)



according to HPR, Schedule 1

Printing date 04/26/2023 Reviewed on 04/26/2023

Trade name: POWERFOAM

(Contd. of page 6)

Other information

No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- Possibility of hazardous reactions No dangerous reactions known.
- * Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products:

Nitrogen oxides (NOx)

Hydrogen cyanide (prussic acid)

Carbon monoxide

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

CAS: 115-10-6 dimethyl ether

Inhalative LC50/4 h 308 mg/l (rat)

CAS: 13674-84-5 tris(2-chlorisopropyl)-phosphate

Oral LD50 3,600 mg/kg (rat)

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

- Subacute to chronic toxicity:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

3

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.

(Contd. on page 8)



according to HPR, Schedule 1

Printing date 04/26/2023 Reviewed on 04/26/2023

Trade name: POWERFOAM

(Contd. of page 7)

Behavior in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
- · Recommendation:

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- *Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14	ŀΤ	rar	าร	p	ort	t i	ní	fο	rr	na	ıti	O	n

· UN-Number

• **DOT/TDG** UN1950 • **ADR, IMDG, IATA** 1950

UN proper shipping name

DOT/TDG Aerosols, flammable
 ADR 1950 Aerosols
 IMDG, IATA AEROSOLS

Transport hazard class(es)

· DOT, IMDG, IATA

· Class 2.1 Gases · Label 2.1

· ADR

· Class 2 5F Gases · Label 2.1

Packing group

· DOT/TDG, ADR, IMDG, IATA Void

Environmental hazards:

· Marine pollutant: No

· Special precautions for user Warning: Gases

• EMS Number: F-D,S-U

(Contd. on page 9)



according to HPR, Schedule 1

Printing date 04/26/2023 Reviewed on 04/26/2023

Trade name: POWERFOAM

(Contd. of page 8)

UN "Model Regulation": **UN 1950 AEROSOLS, 2.1**

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

· TSCA (Toxic Substances Control Act):					
CAS: 9016-87-9	diphenylmethanediisocvanate.isomeres and homologues				

CAS: 115-10-6 dimethyl ether

CAS: 13674-84-5 tris(2-chlorisopropyl)-phosphate

· Canadian substance listings:

· Canadian Domestic Substances List (DSL)

All ingredients are listed.

· Canadian Non-Domestic Substances List (NDSL)

None of the ingredients is listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

· Canadian Ingredient Disclosure list (limit 1%)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

diphenylmethanediisocyanate,isomeres and homologues

· Hazard statements

Extremely flammable aerosol. Recipiente a presión: Puede reventar si se calienta.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Suspected of causing cancer.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Keep out of reach of children.

Obtain special instructions before use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 10)



according to HPR, Schedule 1

Printing date 04/26/2023 Reviewed on 04/26/2023

Trade name: POWERFOAM

(Contd. of page 9)

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Do not breathe vapours/spray.

Wear protective gloves/protective clothing/eye protection.

In case of inadequate ventilation wear respiratory protection (a protective mask with an appropriate gas filter - i.e. type A1 according to standard EN 14387).

IF ON SKIN: Wash with plenty of water/soap.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of container to in accordance with local/regional/national/international regulation.

* Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Contact:
- Date of the latest revision of the safety data sheet 04/26/2023

CA