

DEWALT®

ANCHORS & FASTENERS

Adhesive Anchor Installation System



HIGH PERFORMANCE

AC200+™

Pure110+®

FEATURED

AC100+ Gold®

Pure50+™

BASIC

AC50™

PureGP™

DEWALT®

ANCHORS & FASTENERS



Introducing The First Cordless

DUST X+™

ANCHOR INSTALLATION SYSTEM



Adhesive Anchor Installation System

ANCHORS & FASTENERS



ICC-ES APPROVED

RELIABLE INSTALLATION

PERFORM
PROTECT™

OSHA COMPLIANT
1926.1153



4

DUST X+™

ANCHOR INSTALLATION SYSTEM

	ADHESIVE ANCHORS					
	HIGH PERFORMANCE		MEDIUM DUTY		BASIC	
						
	Hybrid Acrylic 1:1 & 10:1 Cartridges	High Strength Epoxy 1:1 & 3:1 Cartridges	Hybrid Acrylic 1:1 & 10:1 Cartridges	Epoxy 1:1 Cartridges	Hybrid Acrylic 10:1 Cartridges	Epoxy 1:1 Cartridges
BASE MATERIAL INSTALLATION TEMP. RANGE	14 – 104°F	41 – 104°F	14-104°F	50 – 104°F	5 – 95°F	50 – 104°F
BASE MATERIAL						
Concrete	■	■	■	■	■	■
Lightweight Concrete	■	■	■	■	□	□
Hollow Core Plank		□	□	□		
Grout Filled Concrete Masonry	□	■	■	■	□	□
Hollow Concrete Masonry		■	■	■		
Solid Brick	□	■	■	□	□	□
Hollow Brick		□	■	□		
Unreinforced Masonry		□	■	□		
ANCHOR DIAMETER	3/8" – 1-1/4" #3 – #10 Rebar	3/8" – 1-1/4" #3 – #10- Rebar	3/8" – 1-1/4" #3 – #10 Rebar	3/8" – 1-1/4" #3 – #10 Rebar	3/8" – 1" #3 – #8 Rebar	3/8" – 1" #3 – #8 Rebar
WKG LOAD (CONCRETE)	▲▲▲	▲▲▲	▲▲	▲▲	▲	▲
APPROVALS						
ICC-ES	■	■	■	■		
NSF 61	■	■	■	■		
LEED	■	■	■	■		
Cored Holes		□				
COMPATIBLE WITH DUSTX+™	■	■	□	■	□	□
PRICE PER INSTALLED OZ	\$\$\$	\$\$\$	\$\$	\$\$	\$	\$

■ Suitable
□ May Be Suitable

DEWALT

ANCHORS & FASTENERS



ICC-ES APPROVED

approved for cracked and uncracked concrete

SEISMIC

approved for seismic design categories A-F

BOND STRENGTH
high performance

CONVENIENT

wide installation temperature range with small edge distances and spacings

EASY TO USE


fast hardening adhesive; reliable installation and easy to dispense

CLEANING

hand or power brush clean; or use the Hollow Drill Bit / DustX+™ cleaning method

(Dust X+™ Approval Pending)

EMBEDMENT
depths ranging from 4d to 20d



CODE LISTED
ICC-ES ESR-4027

Competitive Comparison

	DEWALT AC200+™	Simpson AT-XP®	Red Head® Epon S7™	Hilti HY 200
Code Approvals	ESR-4027 (Dec. 2016)	ER-263 (Sept. 2016)	ESR-2308 (June 2016)	ESR-3187 (Nov. 2016)
Saturated Concrete	Yes	Yes	Yes	Yes
Seismic	Yes	Yes	Yes	Yes
Bond Strength* (PSI)	1040	1035	726	1120
Min. Cure Time at 68°F	30 Minutes	60 Minutes	30 Minutes	45 Minutes
Hollow Drill Bit Approval	Yes	Yes	No	Yes

* Bond strength based on 1/2" diameter, cracked concrete, long term loading, dry concrete


AT-XP is a registered trademark of Simpson Strong-Tie Company Inc. Epon and S7 are trademarks of ITW Commercial Construction, North America. Hilti HY200 is a trademark of Hilti Corporation



AC200+™ Acrylic Adhesive Anchoring System



Permissible Installation Conditions




Dispensing Configurations

Quik-Shot 1:1 Mixing Ratio	Dual Cartridge 10:1 Mixing Ratio

High Performance Bond Strength

AC200+™ vs. Hilti HY 200
Factored Tension Loads, Cracked Concrete



* Maximum initial battery
voltage (measured
without a workload)
is 20 volts. Nominal
voltage is 18.

	PFC1271050	PFC1271150
Dispensing Configurations	9.5oz. Quik-Shot	28oz. Dual Cartridge
Mixing Nozzles		
PFC1641600	✓	✓
20V MAX* Dispensers		
DCE560D1	✓	
DCE595D1		✓
Standard Manual Dispenser		
08437	✓	
08494		✓
High Performance Manual Dispensers		
08479	✓	
08485		
Pneumatic Dispensers		
08496		✓
Premium Brushes (required for max load values)		
See page 20	✓	✓
Premium Piston Plugs		
See page 21	✓	✓
Flex Tubing		
See page 21	✓	✓

DeWALT®

ANCHORS & FASTENERS



SEISMIC
approved for
seismic design
categories A-F

BOND STRENGTH
high bond
strength at
110°F; no
reduction in
bond strength
due to service
temperature
shifts


CONVENIENT
easy hole
cleaning methods
and fast curing
times



ICC-ES APPROVED
approved for
cracked and
uncracked
concrete, and
seismic
applications

VERSATILE
dispensing
options -
1:1 and 3:1

ICC-ES APPROVED
for post-installed rebar



CODE LISTED
ICC-ES ESR-3298

Competitive Comparison

	DeWALT Pure110+®	Hilti RE500-V3	Simpson SET-3G	Red Head Epon C6+
Code Approval	ESR-3298 (July 2016)	ESR-3814 (Jan 2017)	ESR-4057 (April 2018)	ESR-3577 (August 2016)
Water Filled Holes	Yes	Yes	Yes	Yes
Seismic	Yes	Yes	Yes	Yes
Min. Cure Time at 68°F	8 hrs	7 hrs	24 hrs	7 hrs
Min. Cure Time at 50°F	24 hrs	16 hrs	72 hrs	24 hrs
Hollow Drill Bit Approval	Yes	Yes	Yes	No
Post-Installed Rebar Approval	Yes**	Yes	No	No
Storage Temperature	41°F-86°F	41°F-77°F	45°F-90°F	50°F-77°F

Hilti RE500-V3 is a trademark of Hilti Corporation
SET-XP is a registered trademark of Simpson Strong-Tie Company Inc.
Epon and C6+ are trademarks of ITW Commercial Construction, North America.



Premium Piston Plugs
are used for deep
embedment depths.
The length and
dense plastic material
provide stability,
while the stepped collar fits
over flexible plastic tubing.



PFC1640600

Pure110+[®] Epoxy Adhesive Anchoring System

Permissible Installation Conditions




Dispensing Configurations

Quik-Shot 1:1 Mixing Ratio	Dual Cartridge 1:1 Mixing Ratio	Dual Cartridge 3:1 Mixing Ratio

High Performance Bond Strength

Pure110+[®] vs. Hilti RE 500 V3 vs.
Simpson SET-XP



	08310SD	08313SD	08320SD	08321SD	08351SD
Dispensing Configurations	1:1 Formula 9oz. Quik-Shot	3:1 Formula 13oz. Dual Cartridge	3:1 Formula 19.5oz. Dual Cartridge	1:1 Formula 20.5oz. Dual Cartridge	1:1 Formula 50.5oz. Dual Cartridge
Mixing Nozzles					
08609		✓	✓	✓	✓
PFC16641600	✓				
20V MAX* Dispensers					
DCE560D1	✓				
DCE591D1				✓	
DCE593D1		✓			
Standard Manual Dispensers					
08298		✓	✓		
08437	✓				
08409				✓	
High Performance Manual Dispensers					
08479	✓				
08421				✓	
Pneumatic Dispensers					
08438					✓
08459				✓	
08496					
08497SD		✓	✓		
Standard Brushes					
See page 20	✓	✓	✓	✓	✓
Premium Piston Plugs					
See page 21	✓	✓	✓	✓	✓
Flex Tubing					
See page 21	✓	✓	✓	✓	✓

* Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

DeWALT®

ANCHORS & FASTENERS



SEISMIC
approved for seismic design categories A-F


ICC-ES APPROVED
approved for cracked and uncracked concrete, grouted or hollow masonry and unreinforced masonry

LOW TEMPERATURE DISPENSING
approved for dispensing down to 14°F

VERSATILE
low odor formula with quick cure time

DOT
wide range of listings; 27 states

CERTIFIED TO NSF/ANSI 61
drinking water system components



Competitive Comparison, Concrete

	DeWALT AC100+ Gold®	Hilti HY 100	Simpson AT-XP	ITW Epon S7
Code Approval (Concrete)	ICC-ES ESR-2582 (June 2016)	ICC-ES ESR-3574 (Aug. 2016)	IAMPO ER-263 (Sept. 2016)	ICC-ES ESR-2308 (June 2016)
Cracked Concrete	Yes	Yes	Yes	Yes
Water-Filled Holes	Yes	No	No	Yes
Seismic	Yes	No	Yes	Yes
DOT Rebar Dowel	28 states	Multiple States	Multiple States	Multiple States
Min. Install Temperature	14° F	14° F	14° F	14° F
Min. Cure Time @ 68° F	45 Min	30 Min	60 Min	30 Min
Post-Installed Rebar Approval	Yes	No	No	Yes

Hilti HY 100 is a trademark of Hilti Corporation
AT-XP is a registered trademark of Simpson Strong-Tie Company Inc.
Epon and S7 are trademarks of ITW Commercial Construction, North America.

Competitive Comparison, Masonry

	DeWALT AC100+ Gold®	Hilti HY 70	Simpson AT-XP	ITW Epon S7
Code Approval (CMU)	ICC-ES ESR-3200 (Dec. 2016)	ICC-ES ESR-2682 (Aug. 2016)	IAMPO ER-281 (Mar. 2016)	-
Grout-filled CMU	Yes	Yes	Yes	No
Top of Walls	Yes	Yes	No	No
Hollow CMU (install w. screen tube)	Yes	Yes	No	No
Min. Install Temperature	14° F	14° F	14° F	NA
Min. Cure Time @ 68° F	45 Minutes	1.5 Hours	60 Minutes	NA

*CMU = concrete masonry

Hilti HY 70 is a trademark of Hilti Corporation
AT-XP is a registered trademark of Simpson Strong-Tie Company Inc.
Epon and S7 are trademarks of ITW Commercial Construction, North America.

AC100+ Gold® Acrylic Adhesive Anchoring System



CODE LISTED

ICC-ES ESR-2582
ICC-ES ESR-3200
ICC-ES ESR-4105



AC100+ Gold® DOT Approval

Alabama	Louisiana	Ohio
Arizona	Maine	Pennsylvania
Arkansas	Maryland	Rhode Island
Colorado	Michigan	Tennessee
Connecticut	Minnesota	Texas
Illinois	Mississippi	Vermont
Indiana	Missouri	Virginia
Iowa	Nebraska	Washington
Kansas	New Jersey	Wisconsin
Kentucky	New York	
Approved on a Project-By Project Acceptance*		
Alaska	New Hampshire	South Dakota
Delaware	North Dakota	West Virginia
Hawaii	South Carolina	Wyoming
Montana		

*Some states do not maintain an approval list for anchoring systems. For approval, contact local engineering authority for acceptance project by project.

Visit www.DEWALT.com/approvals for the most up-to-date list of approvals

Permissible Installation Conditions



Dispensing Configurations

Quik-Shot 1:1 Mixing Ratio	Dual Cartridge 10:1 Mixing Ratio

	8478SD	8486SD	8490SD
Dispensing Configuration	9.5oz. Quik-Shot	11.5oz. Dual Cartridge	28oz. Dual Cartridge
Mixing Nozzles			
08293	✓	✓	
08294			✓
20V MAX* Dispensers			
DCE560D1	✓		
DCE595D1			✓
Standard Manual Dispenser			
08437	✓	✓	
08494			✓
High Performance Manual Dispensers			
08479	✓		
08485		✓	
Pneumatic Dispensers			
08496			✓
Standard Brushes			
See page 20	✓	✓	✓
Standard Piston Plugs			
See page 21	✓	✓	✓
Flex Tubing			
See page 21	✓	✓	✓

* Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

DeWALT®

ANCHORS & FASTENERS



ICC-ES APPROVED
approved for cracked
and uncracked concrete

**EVALUATED AND
RECOGNIZED**
for long and
short term
loading

TESTED
for creep
resistance

DESIGNED
specifically
with road, bridge
and concrete
contractors
in mind



**INSTALLATION
TEMPERATURE**
can be installed
in a wide range
of base material
temperatures

**EVALUATED AND
RECOGNIZED**
for freeze/thaw
performance



Competitive Comparison

	DeWALT Pure50+™	ITW Epcon G5	Hilti HTE50	ATC HS 200	Simpson SET-XP
Code Approvals	ESR-3576	ESR-1137	No Approval	No Approval	ESR-2508
Wet Hole Suitable	Yes	Yes	No	No	Yes
Full cure at 70°F	8 hrs	24 hrs	24 hrs	24 hrs	24 hrs
Full cure at 50°F	24 hrs	NA	51 hrs	51 hrs	72 hrs
DOT Approvals	31 States	26 States	32 States	32 States	4 States
Hole Cleaning Procedure: Brushing	2X	4X	2X	4X	4X

Epcon and G5 are trademarks of ITW Commercial Construction, North America.
Hilti HTE500 is a trademark of Hilti Corporation
HS 200 is a trademark of Adhesives Technology Corp.
SET-XP is a registered trademark of Simpson Strong-Tie Company Inc.

Pure50+™ Epoxy Adhesive Anchoring System

Pure50+™ DOT Approval

Alabama	Kentucky	New Mexico
Arizona	Louisiana	New York
Arkansas	Maine	North Carolina
Colorado	Maryland	Ohio
Connecticut	Michigan	Oklahoma
Florida	Minnesota	Rhode Island
Georgia	Missouri	Tennessee
Idaho	Nebraska	Texas
Indiana	Nevada	Utah
Iowa	New Jersey	Virginia
Kansas		
Pure50+ DOT Approval Pending		
California	Mississippi	
Approved on a Project-By Project Acceptance*		
Alaska	New Hampshire	South Dakota
Delaware	North Dakota	West Virginia
Hawaii	South Carolina	Wyoming
Montana		
*Some states do not maintain an approval list for anchoring systems. For approval, contact local engineering authority for acceptance project by project.		
Visit www.DeWALT.com/approvals for the most up-to-date list of approvals		

Permissible Installation Conditions



Dispensing Configurations

Quik-Shot 1:1 Mixing Ratio	Dual Cartridge 1:1 Mixing Ratio

	08600	08605	08651
Dispensing Configurations	9oz. Quik-Shot	20.5oz. Dual Cartridge	50.5oz. Dual Cartridge
Mixing Nozzles			
PFC16641600	✓		
08294		✓	
08609			✓
20V MAX* Dispensers			
DCE560D1	✓		
DCE591D1		✓	
Standard Manual Dispensers			
08437	✓		
08409		✓	
High Performance Manual Dispensers			
08479	✓		
08421		✓	
Pneumatic Dispensers			
08438			✓
08459		✓	
Standard Brushes			
See page 20	✓	✓	✓
Premium Piston Plugs			
See page 21	✓	✓	✓
Flex Tubing			
See page 21	✓	✓	✓

* Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.



ANCHORS & FASTENERS

AC50™ Acrylic Adhesive Anchoring System

ASTM C 881
Type I, II, IV & V
Grade 3
(Class A & B)



PureGP™ Epoxy Adhesive Anchoring System

ASTM C 881 &
AASHTO M235,
Types I, II, IV
and V Grade 3,
Classes B & C



DESIGNED
for use with
threaded rod
and rebar

CURES
down to
5°F

**INSTALLATION
TEMPERATURE**
installs in a
wide range of
material
temperatures

**EVALUATED AND
RECOGNIZED**
for long and
short term
loading



Dispensing Configurations



Dual Cartridge
10:1 Mixing Ratio

Permissible Installation Conditions



8497	28oz Dual Cartridge
Dispensing Configuration	
Mixing Nozzles	
08294	✓
20V MAX* Dispensers	
DCE595D1	✓
20V MAX* Dispensers	
08494	✓
Pneumatic Dispenser	
08496	✓

* Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

Dispensing Configurations



Dual Cartridge
1:1 Mixing Ratio

Permissible Installation Conditions



08821	20.5oz. Dual Cartridge
Dispensing Configurations	
Mixing Nozzles	
08294	✓
20V MAX* Dispensers	
DCE591D1	✓
Standard Manual Dispenser	
8409	✓
High Performance Manual Dispenser	
08421	✓



Cordless Dispensing Tools For Adhesive Cartridges

PRODUCTIVE

up to 24 tubes per battery charge at room temperature

DOSAGE DIAL

controls the length of time that the adhesive is being dispensed

SPEED DIAL

controls the flow rate of the adhesive being dispensed



AVAILABLE IN 4 SIZES

- DCE591D1* Epoxy Dispenser 1:1 Cartridges
- DCE593D1* Epoxy Dispenser 3:1 Cartridges
- DCE595D1* Acrylic Dispenser 10:1 Cartridges
- DCE560D1* 20V Quik-Shot Single Cartridge

* Also available without battery.
Add suffix B (Bare) to item number


20V MAX*
Battery System

For 20V MAX Maximum initial battery voltage measured without a workload is 20 volts. Nominal voltage is 18.

Available Dispensing Configurations

Quik-Shot 1:1 Mixing Ratio	Dual Cartridge 1:1 Mixing Ratio	Dual Cartridge 3:1 Mixing Ratio	Dual Cartridge 10:1 Mixing Ratio

Single cartridge dispenser for use with Quik-Shot





ANCHORS & FASTENERS

1-9/16" FLEXVOLT® SDS MAX Rotary Hammer DCH481



FLEXVOLT®
technology; 60V Max* battery system

* Maximum initial battery voltage measured without a workload is 60 volts. Nominal voltage is 54.

RECOMMENDED
impact energy
for SDS Max
hollow bits



**DCB1800B
PORTABLE POWER STATION™**
and parallel battery charger

1-3/4" SDS MAX Combination Hammer D25604K



RECOMMENDED
impact energy
for SDS Max
hollow bits

ROTATION CONTROL
anti-rotation E-Clutch®



DCH481X2

Bit Style:	SDS MAX
Optimal Drilling Range:	1/2" - 1-1/8"
Impact Energy (Joules):**	6.1
RPM:	0 - 540
BPM:	0 - 3,150
Rotation Control:	E-Clutch®
Battery Voltage:	60V MAX* (20V MAX*)
Battery Ah:	3.0 (9.0)
Tool Weight:	14.33lbs
Vibration Control:	SHOCKS™
Vibration:	9.4 m/s2
Service Warranty:	2 Years

D25604K

Bit Style:	SDS MAX
Optimal Drilling Range:	1/2" - 1-3/8"
Impact Energy (Joules):**	8.0
Rotation Control:	E-Clutch®
Amps:	13.5
Tool Weight:	15.1lbs
Vibration Control:	SHOCKS™
Vibration:	9.1 m/s2
Service Warranty:	2 Years

**According to EPTA - Procedure 05/2009



DUST X+™

ANCHOR INSTALLATION SYSTEM

**PERFORM
PROTECT.**

USE WITH DWV012
for OSHA silica dust
Table 1 Compliance

* System is compliant to the Exposure Control Methods described in Table 1 of 29 CFR 1926.1153 when outlined components are operating and maintained in accordance to manufacturer's instructions.

OSHA COMPLIANT
1926.1153

**SDS MAX
Y-CUTTER
CARBIDE**

for positioning
and hole starting

**HOLLOW
DRILL BIT**

bit extracts
while drilling
for less dust,
fast holes

**NEWLY
ADDED LONG
LENGTHS**

up to 39-3/8"
usable length
available for
5/8" - 1-1/2"
diameters



Airlock™ Adapter
allows for quick,
easy and durable
connection
between 1-1/4"
vacuum hose
and various
DEWALT tools
and shrouds



AIRLOCK™ ADAPTER
connects directly
to DEWALT's
Airlock System
forming a secure,
locking connection
between bit and
dust extractor

**SDS MAX AND
SDS PLUS**
sizes available





ANCHORS & FASTENERS

	CAT #	DESCRIPTION
	DCH481X2	1-9/16" Flexvolt® SDS Max* Brushless Combination Hammer w/ 9Ah Battery
	DCH263R2DH	1-1/8" D-Handle SDS+ Brushless Rotary Hammer w/Dust Extractor 20V Max*
	DCH273P2	1" SDS+ Brushless Rotary Hammer w/5Ah Battery 20V Max*
	DCH273P2DH0	1" SDS+ Brushless Rotary Hammer w/Dust Extractor 20V Max*
	DCH293R2	1-1/8" SDS+ Brushless Rotary Hammer 3.5J w/ 6Ah Battery 20V Max*
	DCH293R2DH	1-1/8" SDS+ Brushless Rotary Hammer 3.5J w/ 9Ah Battery 20V Max*
	DWV012	10 Gallon Wet/Dry HEPA/RRP Dust Extractor DWV9402 Fleece bag (5 pack) for DEWALT dust extractors DWV9316 Replacement Anti-Static Hose DWV9320 Replacement HEPA Filter Set (Type 1)
	DWH050K	Dust Extraction with two interchangeable drilling heads
	DCB1800B	1800 Watt Portable Power Station & Parallel Battery Charger
	DCB609	20V/60V Max* Flexvolt® 9.0Ah Battery
	DCB205	20V Max* Premium XR 5.0Ah Lithium Ion Battery Pack
	DCB206	20V Max* Premium XR 6.0Ah Lithium Ion Battery Pack
	D25604K	1-3/4" SDS Max* Combination Hammer / Corded E-Clutch®

For 20V MAX Maximum initial battery voltage measured without a workload is 20 volts. Nominal voltage is 18. *For 60V MAX* Maximum initial battery voltage measured without a workload is 60 volts. Nominal voltage is 54.

Hole Preparation

Drilling Tools, Bits & Dust Management

SDS Max 4-Cutter Carbide Drill Bits

CAT #	DIA	USABLE LENGTH	OVERALL LENGTH
DW5806	5/8"	8"	13-1/2"
DW5809	5/8"	16"	21-1/2"
DW5807	5/8"	31"	36"
DW5808	11/16"	16"	21-1/2"
DW5810	3/4"	8"	13-1/2"
DW5812	3/4"	16"	21-1/2"
DW5813	3/4"	31"	36"
DW5814	13/16"	16"	21-1/2"
DW5815	7/8"	8"	13-1/2"
DW5816	7/8"	16"	21-1/2"
DW5851	7/8"	31"	36"
DW5817	27/32"	16"	21-1/2"
DW5818	1"	8"	13-1/2"
DW5819	1"	16"	22-1/2"
DW5852	1"	24"	29"
DW5820	1"	31"	36"
DW5821	1-1/8"	10"	15"
DW5822	1-1/8"	18"	22-1/2"
DW5853	1-1/8"	24"	29"
DW5854	1-1/8"	31"	36"
DW5824	1-1/4"	10"	15"
DW5825	1-1/4"	18"	22-1/2"

SDS+ Full Head Carbide Drill Bits

CAT #	DIA	USABLE LENGTH	OVERALL LENGTH
DW5502	3/16"	2"	4-1/2"
DW5503	3/16"	4"	6-1/2"
DW5504	3/16"	5"	8-1/2"
DW5506	3/16"	10"	12"
DW5512	7/32"	8"	10"
DW5517	1/4"	4"	6"
DW5518	1/4"	6"	8-1/2"
DW55200	1/4"	10"	12"
DW5521	1/4"	12"	14"
DW5524	5/16"	4"	6"
DW5526	5/16"	10"	12"
DW5527	3/8"	4"	6-1/2"
DW5529	3/8"	8"	10"
DW55300	3/8"	10"	12"
DW5531	3/8"	16"	18"
DW5537	1/2"	4"	6"
DW5538	1/2"	8"	10-1/2"
DW5539	1/2"	10"	12"
DW5540	1/2"	16"	18"

SDS+ 4-Cutter Carbide Drill Bits

CAT #	DIA	USABLE LENGTH	OVERALL LENGTH
DW5471	5/8"	8"	10"
DW5472	5/8"	16"	18"
DW5474	3/4"	8"	10"
DW5475	3/4"	16"	18"
DW5477	7/8"	8"	10"
DW5478	7/8"	16"	18"
DW5479	1"	8"	10"
DW5480	1"	16"	18"
DW5481	1-1/8"	8"	10"
DW5482	1-1/8"	6"	18"

Hollow Drill Bits

	CAT #	DIA	OVERALL LENGTH	USABLE LENGTH
SDS+	DWA54012	1/2"	14-1/2"	9-3/4"
	DWA54916	9/16"	14-1/2"	9-3/4"
	DWA54058	5/8"	14-1/2"	9-3/4"
	DWA54034	3/4"	14-1/2"	9-3/4"
SDS MAX	DWA58058	5/8"	23-3/4"	15-3/4"
	DWA58958	5/8"	47-1/4"	39-3/8"
	DWA58116	11/16"	23-3/4"	15-3/4"
	DWA58034	3/4"	23-3/4"	15-3/4"
	DWA58934	3/4"	47-1/4"	39-3/8"
	DWA58078	7/8"	23-3/4"	15-3/4"
	DWA58978	7/8"	47-1/4"	39-3/8"
	DWA58001	1"	23-3/4"	15-3/4"
	DWA58901	1"	47-1/4"	15-3/4"
	DWA58118	1-1/8"	23-3/4"	15-3/4"
	DWA58918	1-1/8"	47-1/4"	39-3/8"
	DWA58114	1-1/4"	47-1/4"	39-3/8"
	DWA58112	1-1/2"	47-1/4"	39-3/8"
	DWA58138	1-3/8"	47-1/4"	39-3/8"



ANCHORS & FASTENERS

Adhesive Cartridges

CAT #	DESCRIPTION	QTY	MSTR	PAL
08310SD	Pure110+ 1:1 Ratio 9oz QS Cartridge	12	36	648
08321SD	Pure110+ 1:1 Ratio 21oz Dual Cartridge	12	-	360
08351SD	Pure110+ 1:1 Ratio 51oz Dual Cartridge	5	-	150
08313SD	Pure110+ 3:1 Ratio 13oz Dual Cartridge	12	-	624
08320SD	Pure110+ 3:1 Ratio 20oz Dual Cartridge	12	-	360
PFC1271050	AC200+ 10oz QS Cartridge	12	36	648
PFC1271150	AC200+ 28oz Dual Cartridge	8	-	240
8478SD	AC100+ Gold 10oz QS Cartridge	12	36	648
8486SD	AC100+ Gold 12oz Dual Cartridge	12	-	540
8490SD	AC100+ Gold 28oz Dual Cartridge	8	-	240
08600	Pure50+ 9oz QS Cartridge	12	36	648
08605	Pure50+ 21oz Dual Cartridge	12	-	360
08651	Pure50+ 51oz Dual Cartridge	5	-	150
08497	AC50 28oz Dual Cartridge	8	-	240
08821	PureGP 21oz Dual Cartridge	12	-	360

Dispensers

CAT #	DESCRIPTION	QTY	MSTR
			
DCE591D1			
DCE560D1	20V Quik-Shot Adhesive Dispenser Kit	1	-
DCE560B	20V Quik-Shot Adhesive Dispenser Bare	1	-
DCE591D1	20V Epoxy Dispenser 1:1 20.5oz Kit	1	-
DCE591B	20V Epoxy Dispenser 1:1 20.5oz Bare	1	-
DCE593D1	20V Epoxy Dispenser 3:1 13/19.5oz	1	-
DCE593B	Epoxy Dispenser 3:1 13/19.5oz Bare	1	-
DCE595D1	Acrylic Dispenser 10:1 28oz Kit	1	-
DCE595B	Acrylic Dispenser 10:1 28oz Bare	1	-
			
08437			
08409	Standard Manual Dispenser 20.5oz	1	8
08437	Standard Manual Dispenser 9/10oz	1	12
08494	Standard Manual Dispenser 28oz	1	10
			
08479			
08298	High Performance Manual Dispenser 13oz / 19.5oz	1	5
08421	High Performance Manual Dispenser 20.5oz	1	10
08479	High Performance Manual Dispenser 9/10oz	1	12
08485	High Performance Manual Tool 8, 9.5, 11.5 oz	1	20
			
08496			
08459	Pneumatic Dispenser 20.5oz	1	-
08496	Pneumatic Dispenser 28oz	1	1
8497SD	Pneumatic Dispenser 13 / 19.5oz	1	6
08438	Pneumatic Dispenser 50.5oz	1	-

Hole Cleaning Tools and Accessories

CAT #	DESCRIPTION	QTY
		
PFC1671100		
PFC1671050	Steel Premium Brush For 7/16" Hole	1
PFC1671100	Steel Premium Brush For 1/2" Hole	1
PFC1671150	Steel Premium Brush For 9/16" Hole	1
PFC1671200	Steel Premium Brush For 5/8" Hole	1
PFC1671225	Steel Premium Brush For 11/16" Hole	1
PFC1671250	Steel Premium Brush For 3/4" Hole	1
PFC1671300	Steel Premium Brush For 7/8" Hole	1
PFC1671350	Steel Premium Brush For 1" Hole	1
PFC1671400	Steel Premium Brush For 1-1/8" Hole	1
PFC1671450	Steel Premium Brush For 1-3/8" Hole	1
PFC1671500	Steel Premium Brush For 1-1/2" Hole	1
PFC1671000	Premium Manual Brush Wood Handle	1
PFC1671010	Premium Brush Extension	1
PFC1671820	Premium Steel Brush Extension 12"	1
PFC1671830	Premium Steel Brush SDS Adapter	1
PFC1671960	Premium Steel Brush Drill Chuck Adapter	1
		
08284		
08275	Wire Brush For 5/8" ANSI Hole, No. 4 Rebar	1
08284	Wire Brush For 7/16" ANSI Hole	1
08287	Wire Brush For 7/8" ANSI Hole	1
08285	Wire Brush For 9/16" ANSI Hole	1
08278	Wire Brush For 3/4" ANSI Hole	1
08286	Wire Brush For 11/16" ANSI Hole	1
08288	Wire Brush For 1" ANSI Hole	1
08289	Wire Brush For 1-1/8" ANSI Hole	1
08290	Wire Brush For 1-3/8" ANSI Hole	1
08291	Wire Brush For 1-1/2" ANSI Hole	1
08299	Wire Brush For 1-3/4" Hole, No. 11 Rebar	1
08282	Brush Extension 12"	1
08283	SDS Plus Adapter For Wire Brush	1
08296	Jacobs Chuck Adapter	1
		
07933		
07933	Nylon Brush For 3/4" ANSI Hole	1
07932	Nylon Brush For 9/16" ANSI Hole	1
07931	Nylon Brush For 7/16" ANSI Hole	1
07934	Nylon Brush For 3/4" ANSI Hole	1
07935	Nylon Brush For 1-1/4" ANSI Hole	1
52073	Adhesive Cleaning Kit	1
		
08292		
08292	Air Nozzle W/Extension	1
		
08280		
08280	Hand Pump / Dust Blower 25oz.	1

For 20V MAX Maximum initial battery voltage measured without a workload is 20 volts. Nominal voltage is 18.

Adhesive Installation

Cartridges and Delivery Accessories

Adhesive Piston Plugs

CAT #	DESCRIPTION	ANSI BIT DIA	ROD DIA	REBAR SIZE	QTY
<i>08301</i>					
08302	9/16" Plug	9/16"	1/2"	#4	10
08304	5/8" Plug	5/8"	-	#4	10
08258	11/16" Plug	11/16"	5/8"	#5	10
08259	3/4" Plug	3/4"	5/8"	#5	10
08300	7/8" Plug	7/8"	3/4"	#6	10
08301	1" Plug	1"	7/8"	#7	10
08303	1-1/8" Plug	1-1/8"	1"	#8	10
08305	1-3/8" Plug	1-3/8"	1-1/4"	#9	10
08309	1-1/2" Plug	1-1/2"	-	#10	10
<i>PFC1691540</i>					NEW!
PFC1691510	Premium Plug	5/8" Hole	-	#4	10
PFC1691520	Premium Plug	3/4" Hole	5/8"	#5	10
PFC1691530	Premium Plug	7/8 Hole	3/4"	#6	10
PFC1691540	Premium Plug	1" Hole	7/8"	#7	10
PFC1691550	Premium Plug	1-1/8" Hole	1"	#8	10
PFC1691560	Premium Plug	1-3/8" Hole	1-1/4"	#9	10
PFC1691570	Premium Plug	1-1/2" Hole	-	#10	10
PFC1691580	Premium Plug	1-3/4" Hole	1-1/2"	#11	10

Mixing Nozzles and Nozzle Extensions

CAT #	DESCRIPTION	QTY	MSTR
<i>PFC1641600</i>			Required for AC200+
PFC1641600	Mixing Nozzle for all AC200+ sizes, Pure110+ 9oz and Pure50+ 9oz	2	24
08609	Extra High Flow Mixing Nozzle	2	24
08293	Mixing Nozzle for AC100+ Gold 9.5 & 11.5 oz	2	24
08294	Mixing Nozzle	2	24
<i>PFC1640600</i>			
08281	8" Extension	1	12
08297	18" Extension	1	12
PFC1640600	Flexible Extension Hose 25 Ft	1	12

Plastic Screen Tubes

NUMBER	DESCRIPTION	DRILL DIA	QTY
<i>08310</i>			
08310	3/8" x 3-1/2"	9/16"	25
08311	3/8" x 6"	9/16"	25
08313	3/8" x 8"	9/16"	25
08315	1/2" x 3-1/2"	3/4"	25
08317	1/2" x 6"	3/4"	25
08321	5/8" x 6"	7/8"	25
08323	3/4" x 6"	1"	10

Stainless Steel Screen Tubes

NUMBER	DESCRIPTION	DRILL DIA	QTY
<i>07967</i>			
07960	1/4" x 2"	3/8"	25
07862	1/4" x 6"	3/8"	25
07864	1/4" x 8"	3/8"	25
07856	3/8" x 2"	1/2"	25
07961	3/8" x 3-1/2"	1/2"	25
07962	3/8" x 6"	1/2"	25
07963	3/8" x 8"	1/2"	25
07964	3/8" x 10"	1/2"	25
07959	3/8" x 12"	1/2"	25
07857	1/2" x 2"	5/8"	25
07965	1/2" x 3-1/2"	5/8"	25
07966	1/2" x 6"	5/8"	25
07967	1/2" x 8"	5/8"	25
07968	1/2" x 10"	5/8"	25
07858	5/8" x 2"	3/4"	25
07969	5/8" x 4-1/2"	3/4"	20
07970	5/8" x 6"	3/4"	20
07971	5/8" x 8"	3/4"	20
07972	5/8" x 10"	3/4"	20
07859	3/4" x 2"	7/8"	25
07855	15/16" x 2"	1"	25



ANCHORS & FASTENERS

			Adhesive Installation System: Drill Bits				
			20V MAX* SDS Plus Rotary Hammers Drill Bits			Flexvolt® SDS Max Drill Bits	SDS Max Combination Hammer (Corded) Drill Bits
For 20V MAX Maximum initial battery voltage measured without a workload is 20 volts. Nominal voltage is 18.							
ROD/REBAR SIZE	HOLE SIZE	EMBEDMENT	DCH273P2DH0 1" L-SHAPE	DCH263R2DH 1-1/8" D-HANDLE	DCH293R2DH 1-1/8" L-SHAPE W/ E-CLUTCH	DCH481X2 1-9/16" W/ E-CLUTCH	D25481K 1-9/16" / CORDED
							
			SDS+	SDS+	SDS+	SDS MAX	
3/8" or #3	1/2"	4"	DW5537	DW5437	DW5537		
3/8" or #3	1/2"	8"	DW5538	DW5438	DW5538		
3/8" or #3	1/2"	10"	DW5539	DW5439	DW5539		
3/8" or #3	1/2"	16"	DW5540	DW5440	DW5540		
3/8" or #3	1/2"	22"	DW55410	DW5441	DW55410		
1/2"	5/8"	6"	DW5471	DW5446	DW5471	DW5806	
1/2" or #4	5/8"	8"	DW5471	DW5447	DW5471	DW5806	
1/2" or #4	5/8"	16"	DW5472	DW5448	DW5472	DW5809	
1/2" or #4"	5/8"	22"		DW5449		DW5807	
1/2" or #4	5/8"	31"				DW5807	
5/8" or #5	3/4"	6"			DW5474	DW5810	
5/8" or #5	3/4"	10"			DW5475	DW5812	
5/8" or #5	3/4"	16"			DW5475	DW5812	
5/8" or #5	3/4"	22"				DW5813	
3/4" or #6	7/8"	6"			DW5477	DW5815	
3/4" or #6	7/8"	10"			DW5478	DW5816	
3/4" or #6	7/8"	16"			DW5478	DW5816	
7/8" or #7	1"	8"			DW5479	DW5818	
7/8" or #7	1"	16"			DW5480	DW5819	
7/8" or #7	1"	24"				DW5852	
7/8" or #7	1"	31"				DW5820	
1" or #8	1-1/8"	8"			DW5481	DW5821	
1" or #8	1-1/8"	16"			DW5482	DW5822	
1" or #8	1-1/8"	24"				DW5853	
1" or #8	1-1/8"	31"				DW5854	
* 7/16" may be needed in some circumstance for 3/8" rod ** 9/16" may be needed in some circumstance for 1/2" rod							

The System

			Adhesive Installation System: Hollow Drill Bits					Accessories			
			20V MAX* SDS Plus Rotary Hammers Hollow Drill Bit			Flexvolt® SDS Max Hollow Drill Bit	SDS Max Combination Hammer (Corded) Hollow Drill Bit				
											
ROD/ REBAR SIZE	HOLE SIZE	EMBD.	DCH273P2 1" L-SHAPE	DCH263R2 1-1/8" D-HANDLE	DCH293R2 1-1/8" L-SHAPE W/ E-CLUTCH	DCH481X2 1-9/16" W/ E-CLUTCH	D25481K 1-9/16" / CORDED	PREMIUM PISTON PLUGS	STANDARD PISTON PLUGS	PREMIUM BRUSH	STANDARD BRUSH
											
3/8" or #3	1/2"	4"	DWA54012	DWA54012	DWA54012			08302-PWR		PFC1671100	
3/8" or #3	1/2"	8"	DWA54012	DWA54012	DWA54012			08302-PWR		PFC1671100	
3/8" or #3	1/2"	10"	DWA54012	DWA54012	DWA54012			08302-PWR		PFC1671100	
3/8" or #3	1/2"	16"						08302-PWR		PFC1671100	
3/8" or #3	1/2"	22"						08302-PWR		PFC1671100	
1/2"	5/8"	6"	DWA54058	DWA54058	DWA54058	DWA58058	DWA58058	PFC1691510	08258-PWR	PFC1671200	08275-PWR
1/2" or #4	5/8"	8"	DWA54058	DWA54058	DWA54058	DWA58058	DWA58058	PFC1691510	08258-PWR	PFC1671200	08275-PWR
1/2" or #4	5/8"	16"	DWA54058	DWA54058	DWA54058	DWA58058	DWA58058	PFC1691510	08258-PWR	PFC1671200	08275-PWR
1/2" or #4"	5/8"	22"				DWA58958	DWA58958	PFC1691510	08258-PWR	PFC1671200	08275-PWR
1/2" or #4	5/8"	31"				DWA58958	DWA58958	PFC1691510	08258-PWR	PFC1671200	08275-PWR
5/8" or #5	3/4"	6"		DWA54034	DWA54034	DWA58034	DWA58034	PFC1691520	08259-PWR	PFC1671250	08278-PWR
5/8" or #5	3/4"	10"		DWA54034	DWA54034	DWA58034	DWA58034	PFC1691520	08259-PWR	PFC1671250	08278-PWR
5/8" or #5	3/4"	16"				DWA58034	DWA58034	PFC1691520	08259-PWR	PFC1671250	08278-PWR
5/8" or #5	3/4"	22"				DWA58934	DWA58934	PFC1691520	08259-PWR	PFC1671250	08278-PWR
3/4" or #6	7/8"	6"				DWA58078	DWA58078	PFC1691530	08300-PWR	PFC1671300	08287-PWR
3/4" or #6	7/8"	10"				DWA58078	DWA58078	PFC1691530	08300-PWR	PFC1671300	08287-PWR
3/4" or #6	7/8"	16"				DWA58078	DWA58078	PFC1691530	08300-PWR	PFC1671300	08287-PWR
7/8" or #7	1"	8"				DWA58001	DWA58001	PFC1691540	08301-PWR	PFC1671350	08288-PWR
7/8" or #7	1"	16"				DWA58001	DWA58001	PFC1691540	08301-PWR	PFC1671350	08288-PWR
7/8" or #7	1"	24"				DWA58901	DWA58901	PFC1691540	08301-PWR	PFC1671350	08288-PWR
7/8" or #7	1"	31"				DWA58901	DWA58901	PFC1691540	08301-PWR	PFC1671350	08288-PWR
1" or #8	1-1/8"	8"				DWA58118	DWA58118	PFC1691550	08303-PWR	PFC1671400	08288-PWR
1" or #8	1-1/8"	16"				DWA58118	DWA58118	PFC1691550	08303-PWR	PFC1671400	08288-PWR
1" or #8	1-1/8"	24"				DWA58918	DWA58918	PFC1691550	08303-PWR	PFC1671400	08288-PWR
1" or #8	1-1/8"	31"				DWA58918	DWA58918	PFC1691550	08303-PWR	PFC1671400	08288-PWR

DeWALT**ANCHORS & FASTENERS**

DeWALT Locations			Field Service	DEWALT Tool Service	Anchor Distribution Ctr.
ALASKA	Anchorage	907-561-7181			
ALABAMA	Mobile	251-602-1000			
ARKANSAS	North Little Rock	501-372-3040			
ARIZONA	Phoenix	602-437-1200			
	Phoenix	602-431-8024			
	Phoenix	480-710-5225			
CALIFORNIA	Anaheim	714-414-0369			
	Anaheim	206-679-4218			
	Anaheim	818-395-7325			
	Hayward	(650)391-5403			
	Ontario	909-930-1437			
	Ontario	909-214-4183			
	Ontario	951-258-2903			
	Sacramento	916-419-7259			
	Sacramento	916-291-5367			
	San Diego	858-279-2011			
	Tustin	714-731-2500			
COLORADO	Denver	303-922-8325			
	Denver	303-922-9202			
	Denver	720-439-1100			
CONNECTICUT	Wethersfield	860-563-5800			
FLORIDA	Davie	954-321-6635			
	Davie	786-545-5881			
	Orlando	407-657-0474			
	Orlando	321-544-9284			
	Tampa	813-884-0434			
	Tampa	314-620-0244			
	W. Palm Beach	561-689-3247			
GEORGIA	Norcross	770-246-1710			
	Norcross	678-966-0000			
	Norcross	770-307-6867			
HAWAII	Honolulu	808-842-9925			
IOWA	Des Moines	515-270-1340			
ILLINOIS	Addison	630-521-1097			
	Addison	630-960-3156			
	Addison	630-461-3078			
	Addison	630-461-3076			
	Addison	708-675-9721			
INDIANA	Indianapolis	317-243-8308			
KANSAS	Overland Park	913-495-4330			
	Overland Park	816-349-9573			
KENTUCKY	Louisville	502-380-3748			
LOUISIANA	Baton Rouge	225-296-3191			
	Baton Rouge	469-647-1551			
	Elmwood	504-734-3413			
	Elmwood	504-872-2902			
MASSACHUSETTS	Westwood	781-329-3407			
	Westwood	347-602-2617			
MARYLAND	Capitol Heights	301-773-1722			
	Capitol Heights	301-333-0865			
	Capitol Heights	410-693-4745			
MICHIGAN	Grandville	616-261-0425			
	Madison Heights	248-597-5000			
MINNESOTA	Eden Prairie	952-884-9191			
	Eden Prairie	612-331-3770			
	Eden Prairie	612-206-0551			
MISSOURI	St Louis	314-997-9100			

Adhesive Anchor Installation System

DeWALT Locations			Field Service	DEWALT Tool Service	Anchor Distribution Ctr.
NEVADA	Las Vegas	702-889-6025			
	Las Vegas	702-296-4990			
NEW JERSEY	Elmwood Park	201-475-3524			
NEW YORK	Farmingdale	631-952-2008			
	Woodside	718-335-1042			
NORTH CAROLINA	Charlotte	704-392-0245			
	Charlotte	704-375-5012			
	Greensboro	336-852-1300			
	Raleigh	919-878-0357			
OHIO	Columbus	614-895-3112			
	Maumee	419-297-5348			
	Parma	440-842-9100			
OKLAHOMA	Oklahoma City	405-634-8403			
	Tulsa	918-249-8641			
OREGON	Portland	503-255-6556			
	Portland	503-702-9767			
PENNSYLVANIA	Philadelphia	215-271-5500			
	Philadelphia	267-207-0098			
	Pittsburgh	412-642-0204			
	Pittsburgh	412-721-9005			
	York	717-755-3441			
	York	717-368-6472			
SOUTH CAROLINA	Greenville	864-213-5903			
	Greenville	843-758-8194			
TENNESSEE	Nashville	615-242-1633			
	Nashville	615-248-2667			
	Nashville	214-458-7401			
TEXAS	Carrollton	972-446-2996			
	Carrollton	972-506-9258			
	Carrollton	469-647-1551			
	Fort Worth	817-831-3828			
	Houston	713-466-1194			
	Houston	281-731-2865			
	San Antonio	210-732-1221			
	San Antonio	415-260-4928			
UTAH	Salt Lake City	801-486-5828			
	Salt Lake City	801-466-9428			
	Salt Lake City	801-808-3843			
VIRGINIA	Virginia Beach	757-363-0091			
WASHINGTON	Kent	844-483-4232			
	Seattle	206-763-2010			
	Seattle	713-446-5003			
	Spokane	509-535-9252			
WISCONSIN	West Milwaukee	414-645-4285			
	West Milwaukee	414-645-8821			
	West Milwaukee	414-217-0169			
DeWALT, ELCO, & POWERS Anchors and Fasteners Inquiries: 800-524-3244					
DeWALT, ELCO, & POWERS Anchors and Fasteners Technical Questions: email: engineering@powers.com					

1-800-4 **DeWALT**

www.DeWALT.com