

DEWALT®



UltraCon®+
Blue
Carbon Steel
3/16" & 1/4"
Diameters

UltraCon®+
Bronze
Carbon Steel
3/16" & 1/4"
Diameters

UltraCon®+
White
Carbon Steel
3/16" & 1/4"
Diameters

UltraCon®
Silver
Carbon Steel
5/16" Diameter

UltraCon® SS4
410 Stainless Steel
1/4" Diameter

Crete-Flex®
410 Stainless Steel
3/16" & #14
Diameters

Aggre-Gator®
304 Stainless Steel
1/4" Diameter

TYPICAL APPLICATIONS

- › Temporary bracing
- › Sill plate
- › Furring strips
- › Conduit clips
- › Window frames
- › Storm shutters

BASE MATERIALS



Normal Weight Concrete



Masonry



Brick



Chemically Treated Lumber



Wood

UltraCon+	UltraCon+	UltraCon+	UltraCon+	UltraCon+
UltraCon (5/16")	UltraCon (5/16")			UltraCon (5/16")
Aggre-Gator	Aggre-Gator		Aggre-Gator	
Crete-Flex	Crete-Flex			
UltraCon SS4	UltraCon SS4			

**CARBON STEEL & STAINLESS STEEL
CONCRETE SCREW ANCHORS**

Concrete Screws

THE MOST ICC-ES APPROVALS FOR MECHANICAL AND ADHESIVE ANCHORS IN THE INDUSTRY

CONCRETE SCREW APPROVALS



ESR-3068 Concrete
ESR-3196 Masonry
ESR-3213 Chemically Treated Lumber
ESR-3042 Wood-to-Wood



Miami-Dade NOA
Notice of
Acceptance



Florida
Building
Code

UltraCon+*	UltraCon+	UltraCon+
	UltraCon (5/16")	UltraCon (5/16")
	Aggre-Gator	Aggre-Gator
	Crete-Flex	Crete-Flex
	UltraCon SS4	UltraCon SS4

*3/16" & 1/4" carbon steel UltraCon+ diameters are ICC approved in select lengths



UltraCon+ ICC-ES Approved for use in concrete, masonry, chemically treated lumber and wood-to-wood applications.

HEADSTYLE OFFERINGS

	COLOR	HEX WASHER	HEX TRIMFIT	HEX FLANGE	PHILLIPS FLAT	PHILLIPS TRIMFIT	PHILLIPS OVERSIZED	SIZE RANGE
UltraCon+*	Blue Stalgard Coating							Hex Washer Head: 3/16" x 1-1/4" to 3/16" x 4" 1/4" x 1" to 1/4" x 6" Phillips Flat Head: 3/16" x 1-1/4" to 3/16" x 4" 1/4" x 1-1/4" to 1/4" x 6"
	White Stalgard Coating							Hex Washer Head: 3/16" x 1-1/4" to 3/16" x 3-1/4" 1/4" x 1-1/4" to 1/4" x 6" Hex Flange Head: 1/4" x 1-3/4" to 1/4" x 3-1/4" Phillips Flat Head: 3/16" x 1-1/4" to 3/16" x 3-3/4" 1/4" x 1-1/4" to 1/4" x 3-1/4" Phillips Trimfit Head: 1/4" x 1-3/4" to 1/4" x 4"
	Silver Stalgard Coating							Hex Washer Head: 1/4" x 1-1/4" to 1/4" x 3-1/4" Hex Flange Head: 1/4" x 1-3/4" to 1/4" x 3-1/4" Phillips Flat Head: 3/16" x 1-1/4" to 3/16" x 3-3/4" Phillips Trimfit Head: 1/4" x 1-1/4" to 1/4" x 4"
	Bronze Stalgard Coating							Phillips Trimfit Head: 3/16" x 2-3/4" to 3/16" x 2-3/4" 1/4" x 2-3/4" to 1/4" x 4"
UltraCon® (5/16")	Silver Stalgard Coating							Hex Washer Head: 5/16" x 1-3/4" to 5/16" x 6" Hex Trimfit Washer Head: 5/16" x 1-3/4" to 5/16" 3-3/4" Phillips Flat Head: 5/16" x 2-1/4" to 5/16" x 6" Phillips Trimfit Head: 5/16" x 2-1/4" to 5/16" x 5"
Crete-Flex®	Silver Stalgard Coating							Hex Washer Head: 3/16" x 1-1/4" to 3/16" x 2-3/4" #14 x 1-1/4" to #14 x 3-3/4" Hex Flange Head: #14 x 1-3/4" to #14 x 2-1/4" Phillips Flat Head: 3/16" x 1-1/4" to 3/16" x 3-1/4" #14 x 1-1/4" to #14 x 6" Phillips Trimfit Head: #14 x 1-3/4" to #14 x 2-3/4" Phillips Oversized Head: 5/16" x 3" to 5/16" x 6"
Aggre-Gator®	Silver Stalgard Coating							Hex Washer Head: 1/4" x 1-1/4" to 1/4" x 4" Phillips Trimfit Head: 1/4" x 1-1/4" to 1/4" x 4"
UltraCon® SS4	Silver Stalgard Coating							Hex Washer Head: 1/4" x 1-1/4" to 1/4" x 6" Phillips Flat Head: 1/4" x 1-1/4" to 1/4" x 4"

DEWALT®



GET THE
SYSTEM
OSHA COMPLIANT
1926.1153

DRILL / FASTEN	ACCESSORIES	EXTRACTORS	DRILL / DRIVE SYSTEM
 <p>DCH273 20V MAX* XR Brushless 1" L-Shape SDS Plus Rotary Hammer</p>  <p>DCH263 20V MAX XR Brushless 1-1/8" D-Handle Rotary Hammer</p>	 <p>DWH303DH Dust Extractor for DCH273 1" L-Shape SDS Plus Rotary Hammer</p>  <p>DWH205DH Dust Extractor for DCH263 1-1/8" D-Handle SDS Plus Rotary Hammer</p>  <p>DWH050 Large Hammer Dust Extraction - Hole Cleaning</p>  <p>DWH200D Dust Extraction Tube Kit With Hose</p>	 <p>DCV585 Flexvolt® 60V MAX* Dust Extractor</p>  <p>DWH161D1 20V MAX* Brushless Universal Dust Extractor Kit</p>  <p>DWV010 8 Gallon Wet/Dry HEPA/RRP Dust Extractor</p>  <p>DWV012 10 Gallon Wet/Dry HEPA/RRP Dust Extractor</p>	<p>DW5366 UltraCon+ Installation Kit:</p>  <p>Case</p>  <p>5/32" UltraCon+ Bit</p>  <p>3/16" UltraCon+ Bit</p>  <p>Drive Sleeve</p>  <p>#2 Phillips Bit</p>  <p>#3 Phillips Bit</p>  <p>1/4" Hex Socket</p>  <p>5/16" Hex Socket</p>

For 20V MAX Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

1-800-4-DEWALT

www.DEWALT.com

Copyright ©2019 DEWALT. The following are trademarks for one or more DEWALT power tools, accessories, anchors and concrete adhesives: The yellow and black color scheme; the "D"-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool.

ICDWULTRACONSS