

DEWALT®

ANCHORS & FASTENERS

CONCRETE SCREWS

**CARBON STEEL &
STAINLESS STEEL
CONCRETE SCREW ANCHORS**

GUARANTEED TOUGH.®

ICDWULTRAONBR



UltraCon®+

Blue, Carbon Steel
3/16 in. & 1/4 in. Diameters

UltraCon®+

Bronze, Carbon Steel
3/16 in. & 1/4 in. Diameters

UltraCon®+

Silver, Carbon Steel
3/16 in. & 1/4 in. Diameters

UltraCon®+

White, Carbon Steel
3/16 in. & 1/4 in. Diameters

UltraCon®

Silver, Carbon Steel
5/16 in. Diameter

UltraCon® SS4

410 Stainless Steel
1/4 in. Diameter

Crete-Flex®

410 Stainless Steel
3/16 in. & #14 Diameters


Aggre-Gator®

304 Stainless Steel
1/4 in. Diameter

TYPICAL APPLICATIONS

- Temporary Framing
- Window Frames
- Conduit Clips
- Furring Strips
- Sill Plate
- Storm Shutters

BASE MATERIALS

					
	Concrete	Masonry	Brick	Chemically Treated Lumber	Wood
UltraCon®+	■	■	■	■	■
UltraCon® (5/16 in.)	■	■	□	□	■
UltraCon® SS4	■	■	□	□	□
Crete-Flex®	■	■	□	□	■
Aggre-Gator®	■	■	■	■	■

■ : Suitable base material. □ : May be considered.

GUARANTEED TOUGH.®

ICDWULTRA CONBR

NEW 6-LOBE STAR DRIVE FLAT HEAD

- **More Consistent Driving**
- **Better Bit Grip**
- **Less Susceptible to Cam-Out**
- **Longer Bit-Tip Life**
- **Featured in All Colors & Sizes**



APPROVALS



ESR-3068 Concrete
ESR-3196 Masonry
ESR-3213 Chemically
Treated Lumber
ESR-3042 Wood-to-Wood

UltraCon®+^{★★}

Miami-Dade NOA Notice of Acceptance

UltraCon®+
UltraCon® (5/16 in.)

Aggre-Gator®

Crete-Flex®

UltraCon® SS4



**Florida
Building
Code
(including
Residential)**

UltraCon®+

UltraCon® (5/16 in.)

Aggre-Gator®

Crete-Flex®

UltraCon® SS4

UltraCon+ ICC-ES Approved for use in concrete, masonry, chemically treated lumber and wood-to-wood applications.

HEADSTYLE OFFERINGS

COLOR								SIZE RANGE			
	HEX WASHER	HEX TRIMFIT	HEX FLANGE	FLAT HEAD	TRIMFIT HEAD	OVERSIZED HEAD					
UltraCon®+	Blue Stalgard Coating						HEX WASHER HEAD: 3/16 in. x 1-1/4 in. to 3/16 in. x 4 in. 1/4 in. x 1 in. to 1/4 in. x 6 in.		T25 STAR DRIVE FLAT HEAD 3/16 in. x 1-1/4 in. to 3/16 in. x 4 in. 1/4 in. x 1-1/4 in. to 1/4 in. x 6 in.		
	White Stalgard Coating						HEX WASHER HEAD: 3/16 in. x 1-1/4 in. to 3/16 in. x 3-1/4 in., 1/4 in. x 1-1/4 in. to 1/4 in. x 6 in.	HEX FLANGE HEAD: 1/4 in. x 1-3/4 in. to 1/4 in. x 3-1/4 in.	T25 STAR DRIVE FLAT HEAD 3/16 in. x 1-1/4 in. to 3/16 in. x 3-3/4 in. 1/4 in. x 1-1/4 in. to 1/4 in. x 3-1/4 in.	T25 STAR DRIVE TRIMFIT HEAD 1/4 in. x 1-3/4 in. to 1/4 in. x 4 in.	
	Silver Stalgard Coating						HEX WASHER HEAD: 1/4 in. x 1-1/4 in. to 1/4 in. x 3-1/4 in.	HEX FLANGE HEAD: 1/4 in. x 1-3/4 in. to 1/4 in. x 3-1/4 in.	T25 STAR DRIVE FLAT HEAD 3/16 in. x 1-1/4 in. to 3/16 in. x 3-3/4 in. 1/4 in. x 3-3/4 in.	T25 STAR DRIVE TRIMFIT HEAD 1/4 in. x 1-1/4 in. to 1/4 in. x 4 in.	
	Bronze Stalgard Coating							HEX WASHER HEAD: 1/4 in. x 4 in. to 1/4 in. x 4 in.			T25 STAR DRIVE TRIMFIT HEAD 3/16 in. x 2-3/4 in. to 3/16 in. x 2-3/4 in., 1/4 in. x 2-3/4 in. to 1/4 in. x 4 in.
UltraCon® (5/16 in.)	Silver Stalgard Coating						HEX WASHER HEAD: 5/16 in. x 1-3/4 in. to 5/16 in. x 6 in.	HEX TRIMFIT WASHER HEAD: 5/16 in. x 1-3/4 in. to 5/16 in. x 3-3/4 in.	T30 STAR DRIVE FLAT HEAD 5/16 in. x 2-1/4 in. to 5/16 in. x 6 in.	T30 STAR DRIVE TRIMFIT HEAD 5/16 in. x 2-1/4 in. to 5/16 in. x 5 in.	
Crete-Flex®	Silver Stalgard Coating						HEX WASHER HEAD: 3/16 in. x 1-1/4 in. to 3/16 in. x 2-3/4 in., #14 x 1-1/4 in. to #14 x 3-3/4 in.	HEX FLANGE HEAD: #14 x 1-3/4 in. to #14 x 2-1/4 in.	T25 STAR DRIVE FLAT HEAD 3/16 in. x 1-1/4 in. to 3/16 in. x 3-1/4 in., #14 x 1-1/4 in. to #14 x 6 in. T25 STAR DRIVE TRIMFIT HEAD #14 x 1-3/4 in. to #14 x 2-3/4 in.	T25 STAR DRIVE TRIMFIT HEAD 5/16 in. x 3 in. to 5/16 in. x 6 in.	
Aggre-Gator®	Silver Stalgard Coating						HEX WASHER HEAD: 1/4 in. x 1-1/4 in. to 1/4 in. x 4 in.			T25 STAR DRIVE TRIMFIT HEAD 1/4 in. x 1-1/4 in. to 1/4 in. x 4 in.	
UltraCon® SS4	Silver Stalgard Coating						HEX WASHER HEAD: 1/4 in. x 1-1/4 in. to 1/4 in. x 6 in.		T25 STAR DRIVE FLAT HEAD 1/4 in. x 1-1/4 in. to 1/4 in. x 4 in.		

GUARANTEED TOUGH.®

ICDWULTRACONBR



RELATED PRODUCTS & ACCESSORIES

DRILL / FASTEN



DCH273
20V MAX[®] XR[®] Brushless 1 in.
L-Shape SDS Plus Rotary Hammer



DCH172
20V MAX[®] ATOMIC Brushless 5/8 in.
SDS+ Rotary Hammer Drill



DCH263
20V MAX[®] XR[®] Brushless
1-1/8 in. D-Handle Rotary Hammer

ACCESSORIES



DWH303DH
Dust Extractor for DCH273
1 in. L-Shape SDS Plus
Rotary Hammer



DWH205DH
Dust Extractor for DCH263
1-1/8 in. D-Handle SDS
Plus Rotary Hammer



DWH050
Large Hammer Dust
Extraction - Hole Cleaning



DWH200D
Dust Extraction Tube
Kit With Hose

EXTRACTORS



DCV585
DEWALT FLEXVOLT[®]
60V MAX[®] Dust Extractor



DWH161
20V MAX[®] Brushless
Universal Dust Extractor Kit



DWV010
8 Gallon Wet/Dry HEPA/
RRP Dust Extractor



DWV015
10 Gallon Dust Extractor

DRILL / DRIVE SYSTEM


DW5366

UltraCon+
Installation Kit:



DW5381

5/32 in. UltraCon+
Hex SDS+ Bit



DW5382

3/16 in. UltraCon+
Hex SDS+ Bit



Drive Sleeve



DWAF1TX25IR3

DEWALT 1in
T25 FLEXTORQ[®]



DWAF1TX30IR3

DEWALT 1in
T30 FLEXTORQ[®]



1/4 in. Hex Socket



5/16 in. Hex Socket

* Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.
Copyright © 2024 DEWALT. The following are trademarks for one or more DEWALT power tools, accessories, anchors and concrete adhesives: The yellow and black color scheme; the in.Din.-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool.

ICDWULTRACONBR

GUARANTEED TOUGH.®

1-800-4-DEWALT

www.DEWALT.com