

# DEWALT®

**ANCHORS & FASTENERS**

## CONCRETE SCREWS

**CARBON STEEL &  
STAINLESS STEEL  
CONCRETE SCREW ANCHORS**

**GUARANTEED TOUGH.®**

**ICDWULTRAONBR**





#### UltraCon®+

Blue, Carbon Steel  
3/16 in. & 1/4 in. Diameters

#### UltraCon®+

Bronze, Carbon Steel  
3/16 in. & 1/4 in. Diameters

#### UltraCon®+

Silver, Carbon Steel  
3/16 in. & 1/4 in. Diameters

#### UltraCon®+

White, Carbon Steel  
3/16 in. & 1/4 in. Diameters

#### UltraCon®

Silver, Carbon Steel  
5/16 in. Diameter

#### UltraCon® SS4

410 Stainless Steel  
1/4 in. Diameter

#### Crete-Flex®

410 Stainless Steel  
3/16 in. & #14 Diameters






#### Aggre-Gator®

304 Stainless Steel  
1/4 in. Diameter

## TYPICAL APPLICATIONS

- Temporary Framing
- Window Frames
- Conduit Clips
- Furring Strips
- Sill Plate
- Storm Shutters

## BASE MATERIALS

					
	Concrete	Masonry	Brick	Chemically Treated Lumber	Wood
UltraCon®+	■	■	■	■	■
UltraCon® (5/16 in.)	■	■	□	□	■
UltraCon® SS4	■	■	□	□	□
Crete-Flex®	■	■	□	□	■
Aggre-Gator®	■	■	■	■	■

■ : Suitable base material. □ : May be considered.

**GUARANTEED TOUGH.®**

**ICDWULTRA CONBR**

## NEW 6-LOBE STAR DRIVE FLAT HEAD

- **More Consistent Driving**
- **Better Bit Grip**
- **Less Susceptible to Cam-Out**
- **Longer Bit-Tip Life**
- **Featured in All Colors & Sizes**



## APPROVALS



ESR-3068 Concrete  
ESR-3196 Masonry  
ESR-3213 Chemically  
Treated Lumber  
ESR-3042 Wood-to-Wood

**UltraCon®+<sup>★★</sup>**

## Miami-Dade NOA Notice of Acceptance

UltraCon®+  
UltraCon® (5/16 in.)

## Aggre-Gator®

## Crete-Flex®

UltraCon® SS4



**Florida  
Building  
Code  
(including  
Residential)**

**UltraCon®+****UltraCon® (5/16 in.)**

























## Aggre-Gator®

## Crete-Flex®

**UltraCon® SS4**

**UltraCon+ ICC-ES Approved for use in concrete, masonry, chemically treated lumber and wood-to-wood applications.**

## HEADSTYLE OFFERINGS

COLOR								SIZE RANGE			
	HEX WASHER	HEX TRIMFIT	HEX FLANGE	FLAT HEAD	TRIMFIT HEAD	OVERSIZED HEAD					
UltraCon®+	Blue Stalgard Coating						HEX WASHER HEAD: 3/16 in. x 1-1/4 in. to 3/16 in. x 4 in. 1/4 in. x 1 in. to 1/4 in. x 6 in.		T25 STAR DRIVE FLAT HEAD 3/16 in. x 1-1/4 in. to 3/16 in. x 4 in. 1/4 in. x 1-1/4 in. to 1/4 in. x 6 in.		
	White Stalgard Coating						HEX WASHER HEAD: 3/16 in. x 1-1/4 in. to 3/16 in. x 3-1/4 in., 1/4 in. x 1-1/4 in. to 1/4 in. x 6 in.	HEX FLANGE HEAD: 1/4 in. x 1-3/4 in. to 1/4 in. x 3-1/4 in.	T25 STAR DRIVE FLAT HEAD 3/16 in. x 1-1/4 in. to 3/16 in. x 3-3/4 in. 1/4 in. x 1-1/4 in. to 1/4 in. x 3-1/4 in.	T25 STAR DRIVE TRIMFIT HEAD 1/4 in. x 1-3/4 in. to 1/4 in. x 4 in.	
	Silver Stalgard Coating						HEX WASHER HEAD: 1/4 in. x 1-1/4 in. to 1/4 in. x 3-1/4 in.	HEX FLANGE HEAD: 1/4 in. x 1-3/4 in. to 1/4 in. x 3-1/4 in.	T25 STAR DRIVE FLAT HEAD 3/16 in. x 1-1/4 in. to 3/16 in. x 3-3/4 in. 1/4 in. x 3-3/4 in.	T25 STAR DRIVE TRIMFIT HEAD 1/4 in. x 1-1/4 in. to 1/4 in. x 4 in.	
	Bronze Stalgard Coating						HEX WASHER HEAD: 1/4 in. x 4 in. to 1/4 in. x 4 in.			T25 STAR DRIVE TRIMFIT HEAD 3/16 in. x 2-3/4 in. to 3/16 in. x 2-3/4 in., 1/4 in. x 2-3/4 in. to 1/4 in. x 4 in.	
UltraCon® (5/16 in.)	Silver Stalgard Coating						HEX WASHER HEAD: 5/16 in. x 1-3/4 in. to 5/16 in. x 6 in.	HEX TRIMFIT WASHER HEAD: 5/16 in. x 1-3/4 in. to 5/16 in. x 3-3/4 in.	T30 STAR DRIVE FLAT HEAD 5/16 in. x 2-1/4 in. to 5/16 in. x 6 in.	T30 STAR DRIVE TRIMFIT HEAD 5/16 in. x 2-1/4 in. to 5/16 in. x 5 in.	
Crete-Flex®	Silver Stalgard Coating						HEX WASHER HEAD: 3/16 in. x 1-1/4 in. to 3/16 in. x 2-3/4 in., #14 x 1-1/4 in. to #14 x 3-3/4 in.	HEX FLANGE HEAD: #14 x 1-3/4 in. to #14 x 2-1/4 in.	T25 STAR DRIVE FLAT HEAD 3/16 in. x 1-1/4 in. to 3/16 in. x 3-1/4 in., #14 x 1-1/4 in. to #14 x 6 in. T25 STAR DRIVE TRIMFIT HEAD #14 x 1-3/4 in. to #14 x 2-3/4 in.	T25 STAR DRIVE TRIMFIT HEAD 5/16 in. x 3 in. to 5/16 in. x 6 in.	
Aggre-Gator®	Silver Stalgard Coating						HEX WASHER HEAD: 1/4 in. x 1-1/4 in. to 1/4 in. x 4 in.			T25 STAR DRIVE TRIMFIT HEAD 1/4 in. x 1-1/4 in. to 1/4 in. x 4 in.	
UltraCon® SS4	Silver Stalgard Coating						HEX WASHER HEAD: 1/4 in. x 1-1/4 in. to 1/4 in. x 6 in.		T25 STAR DRIVE FLAT HEAD 1/4 in. x 1-1/4 in. to 1/4 in. x 4 in.		

**GUARANTEED TOUGH.®**

# ICDWULTRACONBR





## RELATED PRODUCTS & ACCESSORIES

DRILL / FASTEN	ACCESSORIES		EXTRACTORS		DRILL / DRIVE SYSTEM
					
<b>DCH273</b> 20V MAX <sup>®</sup> XR <sup>®</sup> Brushless 1 in. L-Shape SDS Plus Rotary Hammer	<b>DWH303DH</b> Dust Extractor for DCH273 1 in. L-Shape SDS Plus Rotary Hammer	<b>DWH205DH</b> Dust Extractor for DCH263 1-1/8 in. D-Handle SDS Plus Rotary Hammer	<b>DCV585</b> DEWALT FLEXVOLT <sup>®</sup> 60V MAX <sup>®</sup> Dust Extractor	<b>DWH161</b> 20V MAX <sup>®</sup> Brushless Universal Dust Extractor Kit	<b>DW5366</b> UltraCon+ Installation Kit:
					
<b>DCH172</b> 20V MAX <sup>®</sup> ATOMIC Brushless 5/8 in. SDS+ Rotary Hammer Drill					<b>DW5381</b> 5/32 in. UltraCon+ Hex SDS+ Bit
					
<b>DCH263</b> 20V MAX XR <sup>®</sup> Brushless 1-1/8 in. D-Handle Rotary Hammer	<b>DWH050</b> Large Hammer Dust Extraction - Hole Cleaning	<b>DWH200D</b> Dust Extraction Tube Kit With Hose	<b>DWV010</b> 8 Gallon Wet/Dry HEPA/RRP Dust Extractor	<b>DWV015</b> 10 Gallon Dust Extractor	<b>DW5382</b> 3/16 in. UltraCon+ Hex SDS+ Bit
					
					<b>DWAF1TX25IR3</b> DEWALT 1in T25 FLEXTORQ <sup>®</sup>
					
					<b>DWAF1TX30IR3</b> DEWALT 1in T30 FLEXTORQ <sup>®</sup>
					
					
					1/4 in. Hex Socket
					5/16 in. Hex Socket

\* Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

Copyright © 2024 DEWALT. The following are trademarks for one or more DEWALT power tools, accessories, anchors and concrete adhesives: The yellow and black color scheme; the in.Din.-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool.

ICDWULTRACONBR

**GUARANTEED TOUGH.®**

**1-800-4-DEWALT**

**www.DEWALT.com**