



ANCHORS & FASTENERS

CARBON STEEL OR
STAINLESS STEEL
DRIVE PINS AVAILABLE

FOR LIGHT DUTY,
TAMPERPROOF
APPLICATIONS

CORROSION
RESISTANT
ZAMAC ALLOY
ANCHOR BODY



HEAD STYLES



TYPICAL APPLICATIONS


- › Roof flashing
- › Mechanical attachments
- › Brick ties and masonry anchorage
- › Furring strips
- › Electrical fixtures
- › Maintenance
- › General purpose anchoring
- › Not recommended for overhead, life-safety or sustained tensile loading applications

APPROVALS



Federal GSA Specification
Meets the proof load requirements of
FF-S-325C, Group V, Type 2, Class 3,
(superseded) and CID A-A 1925A,
Type 1 (mushroom head) &
Type 2 (flat head)

BASE MATERIALS



DRIVE PIN ANCHOR

Zamac Nailin®

MUSHROOM HEAD ZAMAC NAILIN
CARBON STEEL NAIL

CAT #	SIZE	DRILL DIA	CTN	MSTR
02802	3/16" x 7/8"	3/16"	500	1000
02806	1/4" x 3/4"	1/4"	500	500
02808	1/4" x 1"	1/4"	500	500
02814	1/4" x 1-1/4"	1/4"	500	500
02820	1/4" x 1-1/2"	1/4"	500	250
02826	1/4" x 2"	1/4"	500	250
02804	1/4" x 3"	1/4"	500	250

MASTER PACK

02803	3/16" x 7/8"	3/16"	1000	500
02807	1/4" x 3/4"	1/4"	1000	500
02809	1/4" x 1"	1/4"	1000	500
02815	1/4" x 1-1/4"	1/4"	1000	500
02821	1/4" x 1-1/2"	1/4"	1000	500
02827	1/4" x 2"	1/4"	1000	250
02805	1/4" x 3"	1/4"	1000	500

MUSHROOM HEAD ZAMAC NAILIN
STAINLESS STEEL NAIL

CAT #	SIZE	DRILL DIA	CTN	MSTR
02858	1/4" x 1"	1/4"	100	500
02864	1/4" x 1-1/4"	1/4"	100	500
02870	1/4" x 1-1/2"	1/4"	100	500
02876	1/4" x 2"	1/4"	100	50

The published size includes the diameter and length of the anchor measured from under the shoulder of the anchor body.

FLAT HEAD ZAMAC NAILIN
CARBON STEEL NAIL

CAT #	SIZE	DRILL DIA	CTN	MSTR
02836	1/4" x 1-1/2"	1/4"	100	500
02838	1/4" x 2"	1/4"	100	500

MUSHROOM HEAD ZAMAC HAMMER-SCREW
#2 PHILLIPS TYPE SCREW CARBON STEEL

CAT #	SIZE	DRILL DIA	CTN	MSTR
02839	1/4" x 3/4"	1/4"	100	500
02840	1/4" x 1"	1/4"	100	500
02842	1/4" x 1-1/4"	1/4"	100	500
02844	1/4" x 1-1/2"	1/4"	100	500
02846	1/4" x 2"	1/4"	100	500
02848	1/4" x 2-1/4"	1/4"	100	500
02850	1/4" x 3"	1/4"	100	500

MASTER PACK

02839	1/4" x 3/4"	1/4"	1000	500
02939	1/4" x 3/4"	1/4"	1000	-
02940	1/4" x 1"	1/4"	1000	-
02942	1/4" x 1-1/4"	1/4"	1000	-
02944	1/4" x 1-1/2"	1/4"	1000	-
02946	1/4" x 2"	1/4"	1000	-
02948	1/4" x 2-1/4"	1/4"	1000	-
02949	1/4" x 3"	1/4"	1000	-



> Furring strips



> Light duty electrical

RELATED PRODUCTS



DCH293R2DH
20V MAX* XR® SDS PLUS
ROTARY HAMMER W/DUST
COLLECTION



DCH273P2DHO
20V MAX* XR® SDS PLUS ROTARY
HAMMER W/ON-BOARD DUST
EXTRACTOR



DCH133M2
20V MAX* XR® 1" D-HANDLE
SDS+ ROTARY HAMMER



DWHT51064
22 OZ ONE-PIECE
STEEL HAMMER

For 20V MAX Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

1-800-4-DEWALT

www.DEWALT.com

Copyright ©2021 DEWALT. The following are trademarks for one or more DEWALT power tools, accessories, anchors and concrete adhesives: The yellow and black color scheme; the "D"-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool.

ICDWZAMNLSS