



March 26, 2019

Attention: Dow Silicones Corporation Customer

Re: **Cleaning and Maintenance of DOWSIL™ Sealants**

In response to your request regarding sealant maintenance and cleaning procedures for silicones, Dow offers the following comments.

Silicones have been used in your quality building project because of their stable properties regardless of environmental conditions. Therefore, cured silicone sealants in weatherproofing joints or remedial repair joints do not require cleaning in order to functionally perform as a weatherseal. However, the joints may become dirty and it is desired by a building owner to clean them for aesthetic reasons. This can be accomplished during regular building washing that may occur annually; or it could be a scheduled maintenance event specific to cleaning the sealant. How often this is required is a decision for the building owner, and will be influenced by building location and the environment around the building. In general, Dow would recommend an annual cleaning procedure if desired to maintain peak aesthetic appearance.

A mild detergent and water solution will remove any dirt and most rundown materials from the sealant or DOWSIL™ 123 Silicone Seal. Examples of detergents could include, but not be limited to: Simple Green and TSP, which are commonly available at hardware stores. A solution using a mild detergent and water could be sprayed on the joint if the building were being pressure washed anyway, and then the dirt from the surface can either be sprayed away or brushed away with a soft bristle brush. Testing or a mock-up would assist in determining if a brush is necessary. Soft bristle brushes with yellow bristles, available at hardware stores, have been found to work well. Sometimes the label on the brush reads "acid brush." You could also choose to clean the joints individually; in which case the excess dirt and debris should be brushed away; then a detergent solution could be rubbed on; and then this solution should be wiped away with a clean rag. Again, the soft bristle brush could be used to loosen dirt which did not easily release.

In order to lessen the amount of materials required, it has also been found that the cleaning sponges that are pre-soaked with a detergent work well in cleaning stains from silicone surfaces. Examples are the "Mr. Clean" pre-soaked sponges. It would still be recommended to remove any excess dirt or debris from the sealant surface first; then if there are spots remaining, the pre-soaked sponges can be used at those areas to further clean the surface.

If the sealant is cleaned using pressure washing during a full building cleaning, Dow recommends that a mock – up area be tested in order to determine the psi required that will clean the sealant or DOWSIL™ 123 Silicone Seal without damaging it. Dow warranties do not cover damage caused by water spray. Sealant joints and designs are unique to each building project, so the best way to proceed with pressure



washing is to test small areas prior to cleaning the entire building. A starting point would be 1500 psi, fan blade, and a distance of 6-8" from the joint. Wheels from swing stages are not recommended to ride on the DOWSIL™ 123 Silicone Seal. Please use caution when wheels need to run over a strip of DOWSIL™ 123 Silicone Seal, which will occur, but attempts should be made to move the wheels away from the building at those points.

On behalf of Dow, we appreciate your business and your commitment to silicone technology. If you have any further questions, please feel free to contact us.

Sincerely,

Dow Silicones Corporation  
Technical Customer Service, Building & Infrastructure  
+1 800 248 2481 Option 2  
[na.info@dow.com](mailto:na.info@dow.com)  
[dow.com/contactus](http://dow.com/contactus)

DOW HIGH PERFORMANCE BUILDING SOLUTIONS

*Imagine the Possibilities*

[dow.com/construction](http://dow.com/construction)

63-6839-01-0420 S2D

®™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow.

©2020 The Dow Chemical Company. All rights reserved.

**DOWSIL™**  
silicones by 

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.