

**DOW CORNING(R) ALLGUARD SILICONE
ELASTOMERIC COATING - MID TINT BASE**

Version 2.0 Revision Date: 10/01/2015 SDS Number: 905942-00005 Date of last issue: 04/03/2015
Date of first issue: 12/05/2014

SECTION 1. IDENTIFICATION

Product name : DOW CORNING(R) ALLGUARD SILICONE ELASTOMERIC COATING - MID TINT BASE

Product code : 000000000004114049

Manufacturer or supplier's details

Company name of supplier : Dow Corning Corporation

Address : South Saginaw Road
Midland Michigan 48686

Telephone : (989) 496-6000

Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900
CHEMTREC : (800) 424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Impregnation agents
Coatings

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Eye irritation : Category 2A

Reproductive toxicity : Category 2

GHS Label element

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H319 Causes serious eye irritation.
H361 Suspected of damaging fertility or the unborn child.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/

DOW CORNING(R) ALLGUARD SILICONE ELASTOMERIC COATING - MID TINT BASE

Version 2.0	Revision Date: 10/01/2015	SDS Number: 905942-00005	Date of last issue: 04/03/2015 Date of first issue: 12/05/2014
----------------	------------------------------	-----------------------------	---

face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Silicone elastomer

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	>= 10 - < 20
Titanium dioxide	13463-67-7	>= 1 - < 5
Silicon dioxide	7631-86-9	>= 1 - < 5
2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol	60828-78-6	>= 1 - < 5
Octamethylcyclotetrasiloxane	556-67-2	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

**DOW CORNING(R) ALLGUARD SILICONE
ELASTOMERIC COATING - MID TINT BASE**

Version	Revision Date:	SDS Number:	Date of last issue: 04/03/2015
2.0	10/01/2015	905942-00005	Date of first issue: 12/05/2014

		for at least 15 minutes. If easy to do, remove contact lens, if worn. Get medical attention.
If swallowed	:	If swallowed, DO NOT induce vomiting. Get medical attention. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed	:	Causes serious eye irritation. Suspected of damaging fertility or the unborn child.
Protection of first-aiders	:	First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
Notes to physician	:	Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	:	None known.
Specific hazards during fire fighting	:	Exposure to combustion products may be a hazard to health.
Hazardous combustion products	:	Carbon oxides Silicon oxides Nitrogen oxides (NO _x) Formaldehyde Metal oxides
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Follow safe handling advice and personal protective equipment.
---	---	--

DOW CORNING(R) ALLGUARD SILICONE ELASTOMERIC COATING - MID TINT BASE

Version 2.0 Revision Date: 10/01/2015 SDS Number: 905942-00005 Date of last issue: 04/03/2015
 Date of first issue: 12/05/2014

		exposure)	concentration	
Limestone	1317-65-3	TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1
		TWA (Respirable)	5 mg/m ³ (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m ³ (Calcium carbonate)	NIOSH REL
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA	10 mg/m ³ (Titanium dioxide)	ACGIH
Silicon dioxide	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m ³ / %SiO ₂ (Silica)	OSHA Z-3
		TWA	6 mg/m ³ (Silica)	NIOSH REL
Octamethylcyclotetrasiloxane	556-67-2	TWA	10 ppm	DCC OEL

Hazardous components without workplace control parameters

Ingredients	CAS-No.
2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol	60828-78-6

Engineering measures : Processing may form hazardous compounds (see section 10).
 Ensure adequate ventilation, especially in confined areas.
 Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection
Material : Impervious gloves

**DOW CORNING(R) ALLGUARD SILICONE
ELASTOMERIC COATING - MID TINT BASE**

Version	Revision Date:	SDS Number:	Date of last issue: 04/03/2015
2.0	10/01/2015	905942-00005	Date of first issue: 12/05/2014

- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:
Safety goggles
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.
For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Corning customer service group.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : viscous liquid
- Color : white
- Odor : slight
- Odor Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : > 100 °C
- Flash point : > 100 °C
Method: closed cup

**DOW CORNING(R) ALLGUARD SILICONE
ELASTOMERIC COATING - MID TINT BASE**

Version	Revision Date:	SDS Number:	Date of last issue: 04/03/2015
2.0	10/01/2015	905942-00005	Date of first issue: 12/05/2014

Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	1.14
Solubility(ies)		
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	37,500 mPa.s
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Molecular weight	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Use at elevated temperatures may form highly hazardous compounds. Can react with strong oxidizing agents. Hazardous decomposition products will be formed at elevated temperatures.
Conditions to avoid	:	None known.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products		
Thermal decomposition	:	Formaldehyde

**DOW CORNING(R) ALLGUARD SILICONE
ELASTOMERIC COATING - MID TINT BASE**

Version	Revision Date:	SDS Number:	Date of last issue: 04/03/2015
2.0	10/01/2015	905942-00005	Date of first issue: 12/05/2014

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Ingredients:**Limestone:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

Titanium dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Silicon dioxide:

Acute oral toxicity : LD50 (Rat): > 3,300 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Information taken from reference works and the literature.
Acute inhalation toxicity : LC50 (Rat): > 2.08 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Information taken from reference works and the literature.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Information taken from reference works and the literature.

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Acute oral toxicity : LD50 (Rat): 3,300 mg/kg

**DOW CORNING(R) ALLGUARD SILICONE
ELASTOMERIC COATING - MID TINT BASE**

Version 2.0 Revision Date: 10/01/2015 SDS Number: 905942-00005 Date of last issue: 04/03/2015
Date of first issue: 12/05/2014

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Octamethylcyclotetrasiloxane:

Acute oral toxicity : LD50 (Rat): > 4,800 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Based on test data

Acute inhalation toxicity : LC50 (Rat): 2975 ppm
Exposure time: 4 h
Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on test data

Acute dermal toxicity : LD50 (Rabbit): > 2.5 ml/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on test data

Skin corrosion/irritation

Not classified based on available information.

Ingredients:**Titanium dioxide:**

Species: Rabbit
Result: No skin irritation

Silicon dioxide:

Result: No skin irritation
Remarks: Information taken from reference works and the literature.

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Result: Skin irritation

Octamethylcyclotetrasiloxane:

Species: Rabbit
Result: No skin irritation
Remarks: Based on test data

Serious eye damage/eye irritation

Causes serious eye irritation.

Ingredients:**Titanium dioxide:**

Species: Rabbit
Result: No eye irritation

Silicon dioxide:

Result: No eye irritation
Remarks: Information taken from reference works and the literature.

**DOW CORNING(R) ALLGUARD SILICONE
ELASTOMERIC COATING - MID TINT BASE**

Version Revision Date: SDS Number: Date of last issue: 04/03/2015
2.0 10/01/2015 905942-00005 Date of first issue: 12/05/2014

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Result: Irreversible effects on the eye

Octamethylcyclotetrasiloxane:

Species: Rabbit

Result: No eye irritation

Remarks: Based on test data

Respiratory or skin sensitization

Skin sensitization: Not classified based on available information.

Respiratory sensitization: Not classified based on available information.

Ingredients:**Titanium dioxide:**

Test Type: Local lymph node assay (LLNA)

Routes of exposure: Skin contact

Species: Mouse

Result: negative

Silicon dioxide:

Assessment: Does not cause skin sensitization.

Test Type: Skin: test type not specified

Species: Guinea pig

Remarks: Information taken from reference works and the literature.

Octamethylcyclotetrasiloxane:

Assessment: Does not cause skin sensitization.

Test Type: Maximization Test

Species: Guinea pig

Remarks: Based on test data

Germ cell mutagenicity

Not classified based on available information.

Ingredients:**Titanium dioxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Result: negative

Silicon dioxide:

Genotoxicity in vitro : Result: negative
Remarks: Information taken from reference works and the literature.

Genotoxicity in vivo : Application Route: Ingestion
Result: negative
Remarks: Information taken from reference works and the

**DOW CORNING(R) ALLGUARD SILICONE
ELASTOMERIC COATING - MID TINT BASE**

Version	Revision Date:	SDS Number:	Date of last issue: 04/03/2015
2.0	10/01/2015	905942-00005	Date of first issue: 12/05/2014

literature.

Germ cell mutagenicity - Assessment : Animal testing did not show any mutagenic effects.

Octamethylcyclotetrasiloxane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on test data

: Test Type: Mutagenicity (in vitro mammalian cytogenetic test)
Result: negative
Remarks: Based on test data

: Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on test data

: Test Type: In vitro sister chromatid exchange assay in mammalian cells
Result: negative
Remarks: Based on test data

: Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative
Remarks: Based on test data

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on test data

Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on test data

Germ cell mutagenicity - Assessment : Animal testing did not show any mutagenic effects.

Carcinogenicity

Not classified based on available information.

Ingredients:**Titanium dioxide:**

Species: Rat
Application Route: inhalation (dust/mist/fume)
Exposure time: 24 Months
Method: OECD Test Guideline 453

DOW CORNING(R) ALLGUARD SILICONE ELASTOMERIC COATING - MID TINT BASE

Version 2.0 Revision Date: 10/01/2015 SDS Number: 905942-00005 Date of last issue: 04/03/2015
Date of first issue: 12/05/2014

Result: positive

Remarks: The mechanism or mode of action may not be relevant in humans.

The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

IARC

Group 2B: Possibly carcinogenic to humans

Titanium dioxide 13463-67-7

OSHA

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Ingredients:

Octamethylcyclotetrasiloxane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat, male and female
Application Route: inhalation (vapor)
Symptoms: Effects on fertility.
Remarks: Based on test data

Effects on fetal development : Test Type: Prenatal development toxicity study (teratogenicity)
Species: Rabbit
Application Route: inhalation (vapor)
Symptoms: No effects on fetal development.
Remarks: Based on test data

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Ingredients:

Octamethylcyclotetrasiloxane:

Routes of exposure: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Routes of exposure: inhalation (vapor)

**DOW CORNING(R) ALLGUARD SILICONE
ELASTOMERIC COATING - MID TINT BASE**

Version 2.0 Revision Date: 10/01/2015 SDS Number: 905942-00005 Date of last issue: 04/03/2015
Date of first issue: 12/05/2014

Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

Routes of exposure: Skin contact

Assessment: No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.

Repeated dose toxicity**Ingredients:****Titanium dioxide:**

Species: Rat
NOAEL: 24,000 mg/kg
Application Route: Ingestion
Exposure time: 28 d

Species: Rat
NOAEL: 10 mg/m³
Application Route: inhalation (dust/mist/fume)
Exposure time: 2 y
Remarks: The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Octamethylcyclotetrasiloxane:

Species: Rat
Application Route: Ingestion
Remarks: Based on test data

Species: Rat
Application Route: inhalation (vapor)
Remarks: Based on test data

Species: Rabbit
Application Route: Skin contact
Remarks: Based on test data

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Further information**Ingredients:****Octamethylcyclotetrasiloxane:**

Remarks: Results from a 2 year repeated vapor inhalation exposure study to rats of octamethylcyclotetrasiloxane (D4) indicate effects (benign uterine adenomas) in the uterus of female animals. This finding occurred at the highest exposure dose (700 ppm) only. Studies to date have not demonstrated if these effects occur through pathways that are relevant to humans. Repeated exposure in rats to D4 resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding

**DOW CORNING(R) ALLGUARD SILICONE
ELASTOMERIC COATING - MID TINT BASE**

Version	Revision Date:	SDS Number:	Date of last issue: 04/03/2015
2.0	10/01/2015	905942-00005	Date of first issue: 12/05/2014

|| to humans is unknown.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Ingredients:****Limestone:**

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): > 10,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 48 h
Toxicity to algae	: EC50 (Desmodesmus subspicatus (green algae)): > 200 mg/l Exposure time: 72 h

Titanium dioxide:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
Toxicity to algae	: EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l Exposure time: 72 h
Toxicity to bacteria	: EC50: > 1,000 mg/l Exposure time: 3 h Method: OECD Test Guideline 209

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 39 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 81.2 mg/l Exposure time: 48 h

Octamethylcyclotetrasiloxane:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): > 0.022 mg/l Exposure time: 96 h Remarks: No toxicity at the limit of solubility.
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia sp.): > 0.015 mg/l Exposure time: 48 h Remarks: No toxicity at the limit of solubility.
Toxicity to algae	: EC50: > 0.022 mg/l Exposure time: 96 h Remarks: No toxicity at the limit of solubility.

DOW CORNING(R) ALLGUARD SILICONE ELASTOMERIC COATING - MID TINT BASE

Version 2.0 Revision Date: 10/01/2015 SDS Number: 905942-00005 Date of last issue: 04/03/2015
Date of first issue: 12/05/2014

	NOEC: 0.022 mg/l Exposure time: 96 h Remarks: No toxicity at the limit of solubility.
Toxicity to fish (Chronic toxicity)	: NOEC (Oncorhynchus mykiss (rainbow trout)): ≥ 0.0044 mg/l Remarks: No toxicity at the limit of solubility.
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): > 0.0079 mg/l Exposure time: 21 d Remarks: No toxicity at the limit of solubility.
Toxicity to bacteria	: IC50: $> 10,000$ mg/l Method: ISO 8192
Ecotoxicology Assessment	
Chronic aquatic toxicity	: May cause long lasting harmful effects to aquatic life.

Persistence and degradability

Ingredients:

2,6,8-Trimethyl-4-nonyloxypolyethyleneoxyethanol:

Biodegradability : Result: Not readily biodegradable.

Octamethylcyclotetrasiloxane:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 3.7 %
Exposure time: 28 d
Method: OECD Test Guideline 310

Stability in water : Degradation half life: 69.3 - 144 h (24.6 °C) pH: 7
Method: OECD Test Guideline 111

Bioaccumulative potential

Ingredients:

Octamethylcyclotetrasiloxane:

Partition coefficient: n-octanol/water : log Pow: 6.48 (25.1 °C)

Mobility in soil

No data available

Other adverse effects

Ingredients:

Octamethylcyclotetrasiloxane:

Results of PBT and vPvB assessment : Remarks: Octamethylcyclotetrasiloxane (D4) meets the current REACh Annex XIII criteria for PBT and vPvB. In Canada, D4 has been assessed and deemed to meet the PiT criteria. However, D4 does not behave similarly to known PBT/vPvB substances. The weight of scientific evidence from field studies shows that D4 is not biomagnifying in aquatic and terres-

**DOW CORNING(R) ALLGUARD SILICONE
ELASTOMERIC COATING - MID TINT BASE**

Version	Revision Date:	SDS Number:	Date of last issue: 04/03/2015
2.0	10/01/2015	905942-00005	Date of first issue: 12/05/2014

trial food webs. D4 in air will degrade by reaction with naturally occurring hydroxyl radicals in the atmosphere. Any D4 in air that does not degrade by reaction with hydroxyl radicals is not expected to deposit from the air to water, to land, or to living organisms.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Resource Conservation and Recovery Act (RCRA) : This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International Regulation****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Formaldehyde	50-00-0	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

DOW CORNING(R) ALLGUARD SILICONE ELASTOMERIC COATING - MID TINT BASE

Version 2.0 Revision Date: 10/01/2015 SDS Number: 905942-00005 Date of last issue: 04/03/2015
 Date of first issue: 12/05/2014

SARA 304 Extremely Hazardous Substances Reportable Quantity

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Formaldehyde	50-00-0	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Acute Health Hazard
Chronic Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Water	7732-18-5	30 - 50 %
Dimethyl, methyl ((diethylamino)oxy) siloxane reaction w/ dimethyl siloxane, hydroxy-terminated	189896-41-1	30 - 50 %
Limestone	1317-65-3	10 - 20 %
Titanium dioxide	13463-67-7	1 - 5 %
Silicon dioxide	7631-86-9	1 - 5 %

New Jersey Right To Know

Water	7732-18-5	30 - 50 %
Dimethyl, methyl ((diethylamino)oxy) siloxane reaction w/ dimethyl siloxane, hydroxy-terminated	189896-41-1	30 - 50 %
Limestone	1317-65-3	10 - 20 %
Titanium dioxide	13463-67-7	1 - 5 %
Silicon dioxide	7631-86-9	1 - 5 %

California Prop. 65 WARNING! This product contains a chemical known in the State of California to cause cancer.

Quartz	14808-60-7
Formaldehyde	50-00-0
Titanium dioxide	13463-67-7

The ingredients of this product are reported in the following inventories:

NZIoC : All ingredients listed or exempt.

REACH : All ingredients (pre-)registered or exempt.

TSCA : All chemical substances in this material are included on or exempted from listing on the Toxic Substances Control Act 8(b) Inventory. One or more chemical substances in this material meet the polymer exemption criteria in 40 CFR

**DOW CORNING(R) ALLGUARD SILICONE
ELASTOMERIC COATING - MID TINT BASE**

Version 2.0	Revision Date: 10/01/2015	SDS Number: 905942-00005	Date of last issue: 04/03/2015 Date of first issue: 12/05/2014
----------------	------------------------------	-----------------------------	---


723.250.

AICS : One or more ingredients are not listed or exempt.

IECSC : All ingredients listed or exempt.

KECI : All ingredients listed, exempt or notified.

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION**Further information****NFPA:****HMIS III:**

HEALTH	 2*
FLAMMABILITY	 1
PHYSICAL HAZARD	 0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

DCC OEL : Dow Corning Guide

NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts

ACGIH / TWA : 8-hour, time-weighted average

DCC OEL / TWA : Time weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek

OSHA Z-1 / TWA : 8-hour time weighted average

OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Sub-

**DOW CORNING(R) ALLGUARD SILICONE
ELASTOMERIC COATING - MID TINT BASE**

Version	Revision Date:	SDS Number:	Date of last issue: 04/03/2015
2.0	10/01/2015	905942-00005	Date of first issue: 12/05/2014

stances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/01/2015

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8