

SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY

Product name: DEFENDAIR™ 200C Air & Weather Barrier Issue Date: 05/20/2021

Coating

Print Date: 05/21/2021

THE DOW CHEMICAL COMPANY encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: DEFENDAIR™ 200C Air & Weather Barrier Coating

Recommended use of the chemical and restrictions on use

Identified uses: Impregnation agents Coatings

COMPANY IDENTIFICATION

THE DOW CHEMICAL COMPANY 2211 H.H. DOW WAY MIDLAND MI 48674 UNITED STATES

Customer Information Number: 800-258-2436

SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: CHEMTREC +1 800-424-9300

Local Emergency Contact: 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Eye irritation - Category 2A Reproductive toxicity - Category 2

Label elements Hazard pictograms





Signal word: WARNING!

Hazards

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

Precautionary statements

Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves, protective clothing, eye protection and/or face protection.

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/ attention. If eye irritation persists: Get medical advice and/or attention.

Storage

Store locked up.

Disposal

Dispose of contents and/or container to an approved waste disposal plant.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Silicone elastomer

This product is a mixture.

Component	CASRN	Concentration
Poly(oxy-1,2-ethanediyl), .alpha[3,5-dimethyl-1-(2-methylpropyl)hexyl]omegahydroxy-	60828-78-6	>= 1.3 - <= 2.0 %
Propane-1,2-diol	57-55-6	>= 0.6 - <= 1.1 %
Octamethyl Cyclotetrasiloxane	556-67-2	>= 0.03 - <= 0.18 %

4. FIRST AID MEASURES

Description of first aid measures

General advice:

Page 2 of 17

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air and keep comfortable for breathing; consult a physician.

Skin contact: Wash off with plenty of water.

Eye contact: Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

Ingestion: Rinse mouth with water. No emergency medical treatment necessary.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Skin contact may aggravate preexisting dermatitis.

5. FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Water spray. Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable extinguishing media: None known...

Special hazards arising from the substance or mixture

Hazardous combustion products: Silicon oxides. Nitrogen oxides (NOx). Formaldehyde. Carbon oxides.

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to health..

Advice for firefighters

Fire Fighting Procedures: Use water spray to cool unopened containers.. Evacuate area.. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage..

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Remove undamaged containers from fire area if it is safe to do so.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus.. Use personal protective equipment..

Page 3 of 17

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions: Do not release the product to the aquatic environment above defined regulatory levels. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Soak up with inert absorbent material. Clean up remaining materials from spill with suitable absorbant. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. See sections: 7, 8, 11, 12 and 13.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not get on skin or clothing. Avoid inhalation of vapour or mist. Do not swallow. Do not get in eyes. Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all (M)SDS and label warnings even after container is emptied.

Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Conditions for safe storage: Keep in properly labelled containers. Store locked up. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents.

Unsuitable materials for containers: None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
Propane-1,2-diol	US WEEL	TWA	10 mg/m3
Octamethyl	US WEEL	TWA	10 ppm
Cyclotetrasiloxane			

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use chemical goggles.

Skin protection

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl chloride ("PVC" or "vinyl"). Natural rubber ("latex"). Avoid gloves made of: Polyvinyl alcohol ("PVA"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if handling at elevated temperatures without sufficient ventilation, use an approved air-purifying respirator.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state viscous liquid

Color grey
Odor slight

Odor Threshold

pH

No data available

No data available

Melting point/range

No data available

Flash point closed cup >100 °C (212 °F)

Evaporation Rate (Butyl Acetate No data available

= 1)

Flammability (solid, gas) Not Applicable

Flammability (liquids)Does not sustain combustion.

Lower explosion limitNo data availableUpper explosion limitNo data availableVapor PressureNo data availableRelative Vapor Density (air = 1)No data available

Relative Density (water = 1) 1.18

Water solubility

No data available

Partition coefficient: n
No data available

octanol/water

Auto-ignition temperatureNo data availableDecomposition temperatureNo data available

Kinematic Viscosity 60000 mm2/s at 25 °C (77 °F)

Explosive properties Not explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

Molecular weight No data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents.

Conditions to avoid: None known.

Incompatible materials: Avoid contact with oxidizing materials.

Hazardous decomposition products:

Decomposition products can include and are not limited to: Formaldehyde.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Information on likely routes of exposure

Inhalation, Eye contact, Skin contact, Ingestion.

Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)

Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):

LD50, > 5,000 mg/kg Estimated.

Information for components:

<u>Poly(oxy-1,2-ethanediyl), .alpha.-[3,5-dimethyl-1-(2-methylpropyl)hexyl]-.omega.-hydroxy-</u>

Page 6 of 17

LD50, Rat, 3,300 mg/kg

Propane-1,2-diol

LD50, Rat, > 20,000 mg/kg

Octamethyl Cyclotetrasiloxane

LD50, Rat, male, > 4,800 mg/kg No deaths occurred at this concentration.

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):

LD50, > 2,000 mg/kg Estimated.

Information for components:

Poly(oxy-1,2-ethanediyl), .alpha.-[3,5-dimethyl-1-(2-methylpropyl)hexyl]-.omega.-hydroxy-

LD50, Rabbit, 8,874 mg/kg

Propane-1,2-diol

LD50, Rabbit, > 2,000 mg/kg No deaths occurred at this concentration.

Octamethyl Cyclotetrasiloxane

LD50, Rat, male and female, > 2,400 mg/kg No deaths occurred at this concentration.

Acute inhalation toxicity

Brief exposure (minutes) is not likely to cause adverse effects. Vapor from heated material may cause respiratory irritation.

As product: The LC50 has not been determined.

Information for components:

<u>Poly(oxy-1,2-ethanediyl), .alpha.-[3,5-dimethyl-1-(2-methylpropyl)hexyl]-.omega.-hydroxy-</u>

The LC50 has not been determined.

Propane-1,2-diol

LC50, Rabbit, 2 Hour, dust/mist, 317.042 mg/l No deaths occurred at this concentration.

Octamethyl Cyclotetrasiloxane

LC50, Rat, male and female, 4 Hour, dust/mist, 36 mg/l OECD Test Guideline 403

Skin corrosion/irritation

Based on information for component(s):

Brief contact is essentially nonirritating to skin.

Prolonged contact may cause slight skin irritation with local redness.

May cause drying and flaking of the skin.

May cause more severe response on covered skin (under clothing, gloves).

Page 7 of 17

Information for components:

<u>Poly(oxy-1,2-ethanediyl), .alpha.-[3,5-dimethyl-1-(2-methylpropyl)hexyl]-.omega.-hydroxy-</u>

Prolonged contact may cause severe skin irritation with local redness and discomfort. May cause more severe response on covered skin (under clothing, gloves).

Propane-1,2-diol

Prolonged contact is essentially nonirritating to skin.

Repeated contact may cause flaking and softening of skin.

Octamethyl Cyclotetrasiloxane

Brief contact is essentially nonirritating to skin.

Serious eye damage/eye irritation

Based on information for component(s):

May cause moderate eye irritation.

May cause moderate corneal injury.

Information for components:

Poly(oxy-1,2-ethanediyl), .alpha.-[3,5-dimethyl-1-(2-methylpropyl)hexyl]-.omega.-hydroxy-

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

Propane-1,2-diol

May cause slight temporary eye irritation.

Corneal injury is unlikely.

Mist may cause eye irritation.

Octamethyl Cyclotetrasiloxane

Essentially nonirritating to eyes.

Sensitization

For skin sensitization:

Contains component(s) which did not cause allergic skin sensitization in guinea pigs.

For respiratory sensitization:

No relevant data found.

Information for components:

<u>Poly(oxy-1,2-ethanediyl), .alpha.-[3,5-dimethyl-1-(2-methylpropyl)hexyl]-.omega.-hydroxy-</u>

For skin sensitization:

No relevant data found.

For respiratory sensitization:

No relevant data found.

Propane-1,2-diol

Did not cause allergic skin reactions when tested in humans.

For respiratory sensitization:

No relevant data found.

Octamethyl Cyclotetrasiloxane

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Available data are inadequate to determine single exposure specific target organ toxicity.

Information for components:

<u>Poly(oxy-1,2-ethanediyl), .alpha.-[3,5-dimethyl-1-(2-methylpropyl)hexyl]-.omega.-hydroxy-</u>

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Propane-1,2-diol

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Octamethyl Cyclotetrasiloxane

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

Information for components:

<u>Poly(oxy-1,2-ethanediyl), .alpha.-[3,5-dimethyl-1-(2-methylpropyl)hexyl]-.omega.-hydroxy-</u>

Based on physical properties, not likely to be an aspiration hazard.

Propane-1,2-diol

Based on physical properties, not likely to be an aspiration hazard.

Octamethyl Cyclotetrasiloxane

May be harmful if swallowed and enters airways.

Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)

Specific Target Organ Systemic Toxicity (Repeated Exposure)

In rare cases, repeated excessive exposure to propylene glycol may cause central nervous system effects.

Contains an additional component(s) that is not expected to be bioavailable due to the physical state of the material under normal handling and processing conditions.

Information for components:

<u>Poly(oxy-1,2-ethanediyl), .alpha.-[3,5-dimethyl-1-(2-methylpropyl)hexyl]-.omega.-</u>hydroxy-

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Propane-1,2-diol

In rare cases, repeated excessive exposure to propylene glycol may cause central nervous system effects.

Octamethyl Cyclotetrasiloxane

In animals, effects have been reported on the following organs:

Kidney.

Liver.

Respiratory tract.

Female reproductive organs.

Carcinogenicity

Contains a component(s) that is/are not expected to be bioavailable due to the physical state of the material under normal handling and processing conditions.

Information for components:

<u>Poly(oxy-1,2-ethanediyl), .alpha.-[3,5-dimethyl-1-(2-methylpropyl)hexyl]-.omega.-hydroxy-</u>

No relevant data found.

Propane-1,2-diol

Did not cause cancer in laboratory animals.

Octamethyl Cyclotetrasiloxane

Results from a 2 year repeated vapour inhalation exposure study to rats of octamethylcyclotetrasiloxane (D4) indicate effects (benign uterine adenomas) in the uterus of female animals. This finding occurred at the highest exposure dose (700 ppm) only. Studies to date have not demonstrated if these effects occur through pathways that are relevant to humans. Repeated exposure in rats to D4 resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

Teratogenicity

Contains component(s) which did not cause birth defects or any other fetal effects in lab animals.

Information for components:

<u>Poly(oxy-1,2-ethanediyl), .alpha.-[3,5-dimethyl-1-(2-methylpropyl)hexyl]-.omega.-</u>hydroxy-

No relevant data found.

Propane-1,2-diol

Did not cause birth defects or any other fetal effects in laboratory animals.

Octamethyl Cyclotetrasiloxane

Did not cause birth defects or any other fetal effects in laboratory animals.

Reproductive toxicity

In animal studies on component(s), effects on reproduction were seen only at doses that produced significant toxicity to the parent animals. Contains component(s) which have interfered with fertility in animal studies.

Information for components:

Poly(oxy-1,2-ethanediyl), .alpha.-[3,5-dimethyl-1-(2-methylpropyl)hexyl]-.omega.-hydroxy-

No relevant data found.

Propane-1,2-diol

In animal studies, did not interfere with reproduction. In animal studies, did not interfere with fertility.

Octamethyl Cyclotetrasiloxane

In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals. In animal studies, has been shown to interfere with fertility.

Mutagenicity

Contains component(s) which were negative in some in vitro genetic toxicity studies and positive in others. Genetic toxicity studies in animals were negative for component(s) tested.

Information for components:

Poly(oxy-1,2-ethanediyl), .alpha.-[3,5-dimethyl-1-(2-methylpropyl)hexyl]-.omega.-hydroxy-

No relevant data found.

Propane-1,2-diol

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Octamethyl Cyclotetrasiloxane

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity

Poly(oxy-1,2-ethanediyl), .alpha.-[3,5-dimethyl-1-(2-methylpropyl)hexyl]-.omega.-hydroxy-Acute toxicity to fish

Material is slightly toxic to aquatic organisms on an acute basis (LC50/EC50 between 10 and 100 mg/L in the most sensitive species tested).

LC50, Pimephales promelas (fathead minnow), 96 Hour, 39 mg/l

Acute toxicity to aquatic invertebrates

LC50, Daphnia magna (Water flea), 48 Hour, 81.2 mg/l

Toxicity to bacteria

EC50, Bacteria, > 1,000 mg/l

Propane-1,2-diol

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested). LC50, Oncorhynchus mykiss (rainbow trout), static test, 96 Hour, 40,613 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

LC50, Ceriodaphnia dubia (water flea), static test, 48 Hour, 18,340 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), 96 Hour, Growth rate inhibition, 19,000 mg/l, OECD Test Guideline 201

Toxicity to bacteria

NOEC, Pseudomonas putida, 18 Hour, > 20,000 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Ceriodaphnia dubia (water flea), semi-static test, 7 d, number of offspring, 13,020 mg/l

Octamethyl Cyclotetrasiloxane

Acute toxicity to fish

Not expected to be acutely toxic to aquatic organisms.

No toxicity at the limit of solubility

LC50, Oncorhynchus mykiss (rainbow trout), flow-through, 96 Hour, > 0.022 mg/l

No toxicity at the limit of solubility

LC50, Cyprinodon variegatus (sheepshead minnow), flow-through, 14 d, > 0.0063 mg/l

Acute toxicity to aquatic invertebrates

No toxicity at the limit of solubility

EC50, Mysidopsis bahia (opossum shrimp), flow-through test, 96 Hour, > 0.0091 mg/l

No toxicity at the limit of solubility

EC50, Daphnia magna (Water flea), flow-through test, 48 Hour, > 0.015 mg/l

Acute toxicity to algae/aquatic plants

No toxicity at the limit of solubility

ErC50, Pseudokirchneriella subcapitata (green algae), 96 Hour, Growth rate, > 0.022 mg/l No toxicity at the limit of solubility

EC10, Pseudokirchneriella subcapitata (green algae), 96 Hour, Growth rate, >= 0.022 mg/l

Chronic toxicity to fish

No toxicity at the limit of solubility

NOEC, Oncorhynchus mykiss (rainbow trout), 93 d, growth, >= 0.0044 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 21 d, survival, 0.0079 mg/l

Persistence and degradability

Poly(oxy-1,2-ethanediyl), .alpha.-[3,5-dimethyl-1-(2-methylpropyl)hexyl]-.omega.-hydroxy-

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail

Biodegradation: < 60 %

Exposure time: 28 d

Method: OECD Test Guideline 301E or Equivalent

Theoretical Oxygen Demand: 2.35 mg/mg

Chemical Oxygen Demand: 1.90 mg/mg

Propane-1,2-diol

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Biodegradation may occur under anaerobic conditions (in the absence of

oxygen).

10-day Window: Pass Biodegradation: 81 % Exposure time: 28 d

Method: OECD Test Guideline 301F or Equivalent

10-day Window: Not applicable

Biodegradation: 96 % Exposure time: 64 d

Method: OECD Test Guideline 306 or Equivalent

Theoretical Oxygen Demand: 1.68 mg/mg

Chemical Oxygen Demand: 1.53 mg/mg

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	69.000 %
10 d	70.000 %
20 d	86.000 %

Photodegradation

Atmospheric half-life: 10 Hour

Method: Estimated.

Octamethyl Cyclotetrasiloxane

Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails

to pass OECD/EEC tests for ready biodegradability.

10-day Window: Not applicable **Biodegradation:** 3.7 % **Exposure time:** 28 d

Method: OECD Test Guideline 310

Stability in Water (1/2-life)

Hydrolysis, DT50, 3.9 d, pH 7, Half-life Temperature 25 °C, OECD Test Guideline 111 Hydrolysis, DT50, 16.7 d, pH 7, Half-life Temperature 12 °C, OECD Test Guideline 111 Hydrolysis, DT50, 0.075 d, pH 4, Half-life Temperature 25 °C, OECD Test Guideline 111

Photodegradation

Atmospheric half-life: 16 d

Method: Estimated.

Page 13 of 17

Bioaccumulative potential

Poly(oxy-1,2-ethanediyl), .alpha.-[3,5-dimethyl-1-(2-methylpropyl)hexyl]-.omega.-hydroxy-

Bioaccumulation: No bioconcentration is expected because of the relatively high water solubility. May foam in water.

Propane-1,2-diol

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): -1.07 Measured

Bioconcentration factor (BCF): 0.09 Fish Estimated.

Octamethyl Cyclotetrasiloxane

Bioaccumulation: Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and 7).

Partition coefficient: n-octanol/water(log Pow): 6.49 Measured

Bioconcentration factor (BCF): 12,400 Pimephales promelas (fathead minnow) Measured

Mobility in soil

Poly(oxy-1,2-ethanediyl), .alpha.-[3,5-dimethyl-1-(2-methylpropyl)hexyl]-.omega.-hydroxy-

No specific, relevant data available for assessment.

Propane-1,2-diol

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Partition coefficient (Koc): < 1 Estimated.

Octamethyl Cyclotetrasiloxane

Partition coefficient (Koc): 16596 OECD Test Guideline 106

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section10 Regulatory Information, MSDS Section 15

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

Page 14 of 17

14. TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Not regulated for transport

Consult IMO regulations before transporting ocean bulk

Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Reproductive toxicity

Serious eye damage or eye irritation

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

U.S. Toxic Substances Control Act (TSCA)

A component of this product is subject to a TSCA Polymer Exemption (40 CFR 723.250).

Pennsylvania Right To Know

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components	CASRN
Water	7732-18-5
Dimethyl, methyl ((diethylamino)oxy) siloxane reaction with	189896-41-1
dimethyl siloxane, hydroxy-terminated	
Limestone	1317-65-3

Silicon dioxide 7631-86-9
Other Components Below Reportable Levels Not available
Titanium dioxide 13463-67-7
Talc 14807-96-6
Propane-1,2-diol 57-55-6

California Prop. 65

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

United States TSCA Inventory (TSCA)

The product contains an intentional component that is subject to a restriction. Production and/or use is limited by the conditions of the restriction.

16. OTHER INFORMATION

Hazard Rating System

NFPA

	Health	Flammability	Instability
	2	1	0
н	MIS		

HMIS

Health	Flammability	Physical Hazard
2*	1	0

^{* =} Chronic Effects (See Hazards Identification)

Revision

Identification Number: 99152193 / A001 / Issue Date: 05/20/2021 / Version: 3.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Leaend

3	
TWA	8-hr TWA
US WEEL	USA. Workplace Environmental Exposure Levels (WEEL)

Full text of other abbreviations

AlIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -

International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population: LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association: NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA -Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA -Superfund Amendments and Reauthorization Act: SDS - Safety Data Sheet: TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.