



SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY

Product name: DOWSIL™ IE-2404 Emulsion

Issue Date: 10/03/2025

Print Date: 10/04/2025

THE DOW CHEMICAL COMPANY encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: DOWSIL™ IE-2404 Emulsion

Recommended use of the chemical and restrictions on use

Identified uses: Coatings Additives Construction materials and additives Impregnation agents Textiles and leather treatment

COMPANY IDENTIFICATION

THE DOW CHEMICAL COMPANY
2211 H.H. DOW WAY
MIDLAND MI 48674
UNITED STATES

Customer Information Number:

800-258-2436
SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: CHEMTREC +1 800-424-9300

Local Emergency Contact: 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Silicone emulsion

This product is a mixture.

Component	CASRN	Concentration
Propane-1,2-diol	57-55-6	>= 0.5 - <= 1.5 %
Methanol	67-56-1	>= 0.29 - <= 1.5 %

4. FIRST AID MEASURES

Description of first aid measures

General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air and keep comfortable for breathing; consult a physician.

Skin contact: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Obtain medical attention without delay. Wash clothing before reuse. Properly dispose of contaminated leather items, such as shoes, belts, and watchbands. Suitable emergency safety shower facility should be immediately available.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: Do not induce vomiting. Seek medical attention immediately. If person is fully conscious give 1 cup or 8 ounces (240 ml) of water. If medical advice is delayed and if an adult has swallowed several ounces of chemical, then give 3-4 ounces (1/3-1/2 Cup) (90-120 ml) of hard liquor such as 80 proof whiskey. For children, give proportionally less liquor at a dose of 0.3 ounce (1 1/2 tsp.) (8 ml) liquor for each 10 pounds of body weight, or 2 ml per kg body weight [e.g., 1.2 ounce (2 1/3 tbsp.) for a 40 pound child or 36 ml for an 18 kg child].

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: In cases where several ounces (60 - 100 ml) have been ingested, consider the use of ethanol and hemodialysis in the treatment. Consult standard literature for details of treatment. If ethanol is used, a therapeutically effective blood concentration in the range of 100 - 150 mg/dl may be achieved by a rapid loading dose followed by a continuous intravenous infusion. Consult standard literature for details of treatment. 4-Methyl pyrazole (Antizol®) is an effective blocker of alcohol dehydrogenase and should be used in the treatment of ethylene glycol (EG), di- or triethylene glycol (DEG, TEG), ethylene glycol butyl ether (EGBE), or methanol intoxication if available. Fomepizole protocol (Brent, J. et al., New England Journal of Medicine, Feb. 8, 2001, 344:6, p. 424-9): loading dose 15 mg/kg intravenously, follow by bolus dose of 10 mg/kg every 12 hours; after 48 hours, increase bolus dose to 15 mg/kg every 12 hours. Continue fomepizole until serum methanol, EG, DEG, TEG or EGBE are undetectable. The signs and symptoms of poisoning include anion gap metabolic acidosis, CNS depression, renal tubular injury, and possible late stage cranial nerve involvement. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving

significant exposure should be observed 24-48 hours for signs of respiratory distress. In severe poisoning, respiratory support with mechanical ventilation and positive end expiratory pressure may be required. Maintain adequate ventilation and oxygenation of the patient. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam. Carbon dioxide (CO₂). Dry chemical. Water spray.

Unsuitable extinguishing media: None known..

Special hazards arising from the substance or mixture

Hazardous combustion products: Silicon oxides. Carbon oxides.

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to health..

Advice for firefighters

Fire Fighting Procedures: Use water spray to cool unopened containers.. Evacuate area.. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations..

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Remove undamaged containers from fire area if it is safe to do so.

Special protective equipment for firefighters: Wear self-contained breathing apparatus for firefighting if necessary.. Use personal protective equipment..

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions: Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Soak up with inert absorbent material. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.

See sections: 7, 8, 11, 12 and 13.

7. HANDLING AND STORAGE

Precautions for safe handling: Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all (M)SDS and label warnings even after container is emptied.

Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Conditions for safe storage: Keep in properly labelled containers. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents.
Unsuitable materials for containers: None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
Propane-1,2-diol	US WEEL	TWA	10 mg/m ³
Methanol	ACGIH	TWA	200 ppm
	Further information: Skin: Danger of cutaneous absorption		
	ACGIH	STEL	250 ppm
	Further information: Skin: Danger of cutaneous absorption		
	OSHA Z-1	TWA	260 mg/m ³ 200 ppm

The following substance(s), which have Occupational Exposure Limit(s) (OEL), may be formed during handling or processing: Methanol.

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI

Exposure controls

Engineering controls: Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. Local exhaust ventilation may be necessary for some operations. Lethal concentrations may exist in areas with poor ventilation.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields). If there is a potential for exposure to particles which could cause eye discomfort, wear chemical goggles.

Skin protection

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl chloride ("PVC" or "vinyl"). **NOTICE:** The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Atmospheric levels should be maintained below the exposure guideline. When respiratory protection is required, use an approved self-contained breathing apparatus or positive pressure air line with auxiliary self-contained air supply. For emergency and other conditions where the exposure guideline may be exceeded, use an approved positive-pressure self-contained breathing apparatus or positive-pressure air line with auxiliary self-contained air supply. In confined or poorly ventilated areas, use an approved self-contained breathing apparatus or positive pressure air line with auxiliary self-contained air supply.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	liquid
Color	white milky
Odor	slight
Odor Threshold	No data available
pH	No data available
Melting point/ range	No data available
Freezing point	No data available
Boiling point (760 mmHg)	100 °C (212 °F)
Flash point	Tag closed cup 93.4 °C (200.1 °F)
Evaporation Rate (Butyl Acetate = 1)	No data available
Flammability (solid, gas)	Not applicable
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapor Pressure	No data available
Relative Vapor Density (air = 1)	No data available
Relative Density (water = 1)	1.02
Water solubility	No data available
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No data available

Decomposition temperature	No data available
Dynamic Viscosity	1,000 mPa.s
Kinematic Viscosity	No data available
Explosive properties	Not explosive
Oxidizing properties	The substance or mixture is not classified as oxidizing.
Molecular weight	No data available
Particle size	not applicable

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents. Vapours may form explosive mixture with air.

Conditions to avoid: None known.

Incompatible materials: Avoid contact with oxidizing materials.

Hazardous decomposition products:

Decomposition products can include and are not limited to: Methanol. Acrolein. Acetic acid. Aldehydes. Alcohols. Ethers. Ketones. Low molecular weight hydrocarbons.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data are available.

Information on likely routes of exposure

Inhalation, Eye contact, Skin contact, Ingestion.

Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)

Acute Toxicity Endpoints:

Not classified based on available information.

Acute oral toxicity

Information for the Product:

Very low toxicity if swallowed. Methanol is highly toxic to humans and may cause central nervous system effects, visual disturbances up to blindness, metabolic acidosis, and degenerative damage to other organs including liver, kidney, and heart. Effects may be delayed.

As product: Single dose oral LD50 has not been determined.

Information for components:

Propane-1,2-diol

LD50, Rat, > 20,000 mg/kg

Methanol

Methanol is highly toxic to humans and may cause central nervous system effects, visual disturbances up to blindness, metabolic acidosis, and degenerative damage to other organs including liver, kidney, and heart. Effects may be delayed. LD50, Rat, > 5,000 mg/kg

ALD - Approximate Lethal Dose, Humans, 340 mg/kg Estimated.

ALD - Approximate Lethal Dose, Humans, 29 - 237 ml Estimated.

Acute dermal toxicity

Information for the Product:

Prolonged skin contact is unlikely to result in absorption of harmful amounts. Effects of methanol are the same as observed via oral and inhalation exposure and include central nervous system (CNS) depression, visual impairment up to blindness, metabolic acidosis, with effects on organ systems such as liver, kidneys and heart, even death.

As product: The dermal LD50 has not been determined.

Information for components:

Propane-1,2-diol

LD50, Rabbit, > 2,000 mg/kg No deaths occurred at this concentration.

Methanol

Effects of methanol are the same as observed via oral and inhalation exposure and include central nervous system (CNS) depression, visual impairment up to blindness, metabolic acidosis, with effects on organ systems such as liver, kidneys and heart, even death. LD50, Rabbit, 15,800 mg/kg

Acute inhalation toxicity

Information for the Product:

Brief exposure (minutes) is not likely to cause adverse effects. Excessive exposure may cause: Respiratory irritation Central nervous system depression Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness. Inhalation of methanol may cause effects ranging from headache, narcosis and visual impairment to metabolic acidosis, blindness, and even death. Effects may be delayed.

As product: The LC50 has not been determined.

Information for components:

Propane-1,2-diol

LC50, Rabbit, 2 Hour, dust/mist, 317.042 mg/l No deaths occurred at this concentration.

Methanol

Easily attainable vapor concentrations may cause serious adverse effects, even death. At lower concentrations: May cause respiratory irritation and central nervous system depression. Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness. Inhalation of methanol may cause effects ranging from headache, narcosis and visual impairment to metabolic acidosis, blindness, and even death. Effects may be delayed.

LC50, Rat, 4 Hour, vapour, 3 mg/l

Skin corrosion/irritation

Not classified based on available information.

Information for the Product:

Based on information for component(s):
Brief contact is essentially nonirritating to skin.

Information for components:

Propane-1,2-diol

Prolonged contact is essentially nonirritating to skin.
Repeated contact may cause flaking and softening of skin.

Methanol

Prolonged contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation

Not classified based on available information.

Information for the Product:

Based on information for component(s):
May cause slight temporary eye irritation.
Mist may cause eye irritation.

Information for components:

Propane-1,2-diol

May cause slight temporary eye irritation.
Corneal injury is unlikely.
Mist may cause eye irritation.

Methanol

May cause eye irritation.

Sensitization

For skin sensitization:

Not classified based on available information.

For respiratory sensitization:

Not classified based on available information.

Information for the Product:

For skin sensitization:
Contains component(s) which did not cause allergic skin sensitization in guinea pigs.

For respiratory sensitization:
No relevant data found.

Information for components:

Propane-1,2-diol

Did not cause allergic skin reactions when tested in humans.

For respiratory sensitization:
No relevant data found.

Methanol

For skin sensitization:
No relevant data found.

For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:

Propane-1,2-diol

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Methanol

Causes damage to organs.
Target Organs: Eyes, Central nervous system

Aspiration Hazard

Not classified based on available information.

Information for the Product:

Based on physical properties, not likely to be an aspiration hazard.

Information for components:

Propane-1,2-diol

Based on physical properties, not likely to be an aspiration hazard.

Methanol

May be harmful if swallowed and enters airways.

Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:

Propane-1,2-diol

In rare cases, repeated excessive exposure to propylene glycol may cause central nervous system effects.

Methanol

Methanol is highly toxic to humans and may cause central nervous system effects, visual disturbances up to blindness, metabolic acidosis, and degenerative damage to other organs including liver, kidney, and heart.

Carcinogenicity

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:

Propane-1,2-diol

Did not cause cancer in laboratory animals.

Methanol

Did not cause cancer in laboratory animals.

Teratogenicity

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:

Propane-1,2-diol

Did not cause birth defects or any other fetal effects in laboratory animals.

Methanol

Methanol has caused birth defects in mice at doses nontoxic to the mother as well as slight behavioral effects in offspring of rats.

Reproductive toxicity

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:

Propane-1,2-diol

In animal studies, did not interfere with reproduction. In animal studies, did not interfere with fertility.

Methanol

In animal studies, did not interfere with reproduction.

Mutagenicity

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:

Propane-1,2-diol

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Methanol

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative in some cases and positive in other cases.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data are available.

Toxicity

Information for the Product:

Product test data not available.

Information for components:

Propane-1,2-diol**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
LC50, Oncorhynchus mykiss (rainbow trout), static test, 96 Hour, 40,613 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

LC50, Ceriodaphnia dubia (water flea), static test, 48 Hour, 18,340 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), 96 Hour, Growth rate inhibition, 19,000 mg/l, OECD Test Guideline 201

Toxicity to bacteria

NOEC, Pseudomonas putida, 18 Hour, > 20,000 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Ceriodaphnia dubia (water flea), semi-static test, 7 d, number of offspring, 13,020 mg/l

Methanol**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
LC50, Bluegill sunfish (Lepomis macrochirus), flow-through test, 96 Hour, 15,400 mg/l

Acute toxicity to aquatic invertebrates

LC50, Daphnia magna (Water flea), 48 Hour, > 10,000 mg/l

Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), 96 Hour, Growth rate, 22,000 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

IC50, activated sludge, 3 Hour, Respiration rates., > 1,000 mg/l, OECD Test Guideline 209

Chronic toxicity to fish

NOEC, Oryzias latipes (Orange-red killifish), 200 Hour, 15,800 mg/l

Persistence and degradability**Information for the Product:**

Product test data not available.

Information for components:**Propane-1,2-diol**

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Biodegradation may occur under anaerobic conditions (in the absence of oxygen).

10-day Window: Pass
Biodegradation: 81 %
Exposure time: 28 d
Method: OECD Test Guideline 301F or Equivalent
10-day Window: Not applicable
Biodegradation: 96 %
Exposure time: 64 d
Method: OECD Test Guideline 306 or Equivalent

Theoretical Oxygen Demand: 1.68 mg/mg

Chemical Oxygen Demand: 1.53 mg/mg

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	69.000 %
10 d	70.000 %
20 d	86.000 %

Photodegradation
Atmospheric half-life: 10 Hour
Method: Estimated.

Methanol

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

Theoretical Oxygen Demand: 1.50 mg/mg

Chemical Oxygen Demand: 1.49 mg/mg Dichromates

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	72 %
20 d	79 %

Photodegradation
Test Type: Half-life (indirect photolysis)
Sensitization: OH radicals
Atmospheric half-life: 8 - 18 d
Method: Estimated.

Bioaccumulative potential

Information for the Product:

Product test data not available.

Information for components:**Propane-1,2-diol****Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).**Partition coefficient: n-octanol/water(log Pow):** -1.07 Measured**Bioconcentration factor (BCF):** 0.09 Fish Estimated.**Methanol****Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).**Partition coefficient: n-octanol/water(log Pow):** -0.77 Measured**Bioconcentration factor (BCF):** < 10 *Leuciscus idus* (Golden orfe) Measured**Mobility in soil****Information for the Product:**

Product test data not available.

Information for components:**Propane-1,2-diol**

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Partition coefficient (Koc): < 1 Estimated.**Methanol****Partition coefficient (Koc):** 0.44 Estimated.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN SDS SECTION 1: Identified Uses. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility of the waste generator. Do not re-use containers for any purpose.

14. TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	Not regulated for transport
	Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

No SARA Hazards

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

The following components are subject to reporting levels established by SARA Title III, Section 313:

Components	CASRN
Methanol	67-56-1

Pennsylvania Right To Know

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components	CASRN
Dimethyl Siloxane w/ Me Silsesquioxanes & n-Octyl Silsesquioxanes, Methoxy-term	897393-56-5
Water	7732-18-5
Vinyl alcohol polymer with vinyl acetate	25213-24-5
Propane-1,2-diol	57-55-6
Methanol	67-56-1

California Prop. 65

WARNING: This product can expose you to chemicals including Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System

NFPA

Health	Flammability	Instability
0	1	0

HMIS

Health	Flammability	Physical Hazard
0/	1	0

Revision

Identification Number: 4130395 / A001 / Issue Date: 10/03/2025 / Version: 12.0

In case this version of the SDS contains significant changes from the previous version, they are listed below or noted by bold, double bars in the left-hand margin throughout this document.

Changes encompass identification, hazards, tox/eco-tox information and the addition/removal of the ingredients, and regulatory information, hazard information, uses, risk management measures and other key regulatory changes of the product. Detailed explanation of the changes can be obtained upon request.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	ACGIH - Biological Exposure Indices (BEI)
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
STEL	Short-term exposure limit
TWA	8-hour, time-weighted average
US WEEL	USA. Workplace Environmental Exposure Levels (WEEL)

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International

Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US