



SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY

Product name: DOWSIL™ Primer-C

Issue Date: 11/03/2023

Print Date: 11/04/2023

THE DOW CHEMICAL COMPANY encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: DOWSIL™ Primer-C

Recommended use of the chemical and restrictions on use

Identified uses: Adhesive, binding agents

COMPANY IDENTIFICATION

THE DOW CHEMICAL COMPANY
2211 H.H. DOW WAY
MIDLAND MI 48674
UNITED STATES

Customer Information Number:

800-258-2436
SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: CHEMTREC +1 800-424-9300

Local Emergency Contact: 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids - Category 2

Skin irritation - Category 2

Eye irritation - Category 2A

Specific target organ toxicity - single exposure - Category 3

Specific target organ toxicity - repeated exposure - Category 2

Label elements

Hazard pictograms



Signal word: **DANGER!**

Hazards

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Precautionary statements

Prevention

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ ventilating/ lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe mist or vapours.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/ eye protection/ face protection.

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Get medical advice/ attention if you feel unwell.

If skin irritation occurs: Get medical advice/ attention.

If eye irritation persists: Get medical advice/ attention.

Take off contaminated clothing and wash before reuse.

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal

Dispose of contents and/or container to an approved waste disposal plant.

Other hazards

Static-accumulating flammable liquid.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Silicone in solvent
This product is a mixture.

Component	CASRN	Concentration
Ethyl acetate	141-78-6	>= 84.0 - <= 89.0 %
Methyl methacrylate, 3-(trimethoxysilyl)propyl methacrylate polymer	26936-30-1	>= 4.8 - <= 5.5 %
Xylene	1330-20-7	>= 3.2 - <= 3.7 %
Ethylbenzene	100-41-4	>= 2.7 - <= 3.2 %
Cyclohexanone	108-94-1	>= 1.1 - <= 1.4 %

4. FIRST AID MEASURES

Description of first aid measures

General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Skin contact: Wash off with plenty of water. Suitable emergency safety shower facility should be available in work area.

Eye contact: Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

Most important symptoms and effects, both acute and delayed:

Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Maintain adequate ventilation and oxygenation of the patient. If burn is present, treat as any thermal burn, after decontamination. No specific antidote. Treatment of exposure should

be directed at the control of symptoms and the clinical condition of the patient. Skin contact may aggravate preexisting dermatitis.

5. FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam. Dry sand.

Unsuitable extinguishing media: High volume water jet. Do not use direct water stream..

Special hazards arising from the substance or mixture

Hazardous combustion products: Carbon oxides. Silicon oxides. Formaldehyde.

Unusual Fire and Explosion Hazards: Flash back possible over considerable distance.. Exposure to combustion products may be a hazard to health.. Flammable concentrations of vapor can accumulate at temperatures above flash point; see Section 9.. Flammable mixtures may exist within the vapor space of containers at room temperature.. Closed containers may rupture via pressure build-up when exposed to fire or extreme heat.. Vapours may form explosive mixtures with air..

Advice for firefighters

Fire Fighting Procedures: Use water spray to cool unopened containers.. Evacuate area.. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage.. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed.. Do not use a solid water stream as it may scatter and spread fire.. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Remove undamaged containers from fire area if it is safe to do so.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus.. Use personal protective equipment..

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Remove all sources of ignition. Ventilate the area. Use personal protective equipment. Eliminate all sources of ignition in vicinity of spill or released vapor to avoid fire or explosion. Ground and bond all containers and handling equipment. Vapor explosion hazard. Keep out of sewers. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions: Do not release the product to the aquatic environment above defined regulatory levels. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapours/mists with a water spray jet. Clean up remaining materials from spill with suitable absorbant. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. See sections: 7, 8, 11, 12 and 13.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not get on skin or clothing. Do not breathe vapours or spray mist. Do not swallow. Do not get in eyes. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment. Non-sparking tools should be used. Handle in accordance with good industrial hygiene and safety practice. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all (M)SDS and label warnings even after container is emptied.

Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation. Ensure all equipment is electrically grounded before beginning transfer operations. This material can accumulate static charge due to its inherent physical properties and can therefore cause an electrical ignition source to vapors. In order to prevent a fire hazard, as bonding and grounding may be insufficient to remove static electricity, it is necessary to provide an inert gas purge before beginning transfer operations. Restrict flow velocity in order to reduce the accumulation of static electricity. Ground and bond container and receiving equipment.

Conditions for safe storage: Keep in properly labelled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

Do not store with the following product types: Strong oxidizing agents. Organic peroxides. Flammable solids. Pyrophoric liquids. Pyrophoric solids. Self-heating substances and mixtures. Substances and mixtures, which in contact with water, emit flammable gases. Explosives. Gases. Unsuitable materials for containers: None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
Ethyl acetate	Dow IHG	TWA	150 ppm
	Dow IHG	STEL	300 ppm
	ACGIH	TWA	400 ppm
	OSHA Z-1	TWA	1,400 mg/m3 400 ppm
Xylene	OSHA Z-1	TWA	435 mg/m3 100 ppm
	ACGIH	TWA	20 ppm
	Further information: Ototoxicant; A4: Not classifiable as a human carcinogen		
Ethylbenzene	ACGIH	TWA	20 ppm
	Further information: Ototoxicant; A3: Confirmed animal carcinogen with unknown relevance to humans		

	OSHA Z-1	TWA	435 mg/m3 100 ppm
Cyclohexanone	Dow IHG	TWA	7.5 ppm
	Further information: SKIN: Absorbed via skin		
	Dow IHG	STEL	15 ppm
	Further information: SKIN: Absorbed via skin		
	ACGIH	TWA	20 ppm
	Further information: A3: Confirmed animal carcinogen with unknown relevance to humans; Skin: Danger of cutaneous absorption		
	ACGIH	STEL	50 ppm
	Further information: A3: Confirmed animal carcinogen with unknown relevance to humans; Skin: Danger of cutaneous absorption		
	OSHA Z-1	TWA	200 mg/m3 50 ppm
Methanol	ACGIH	TWA	200 ppm
	Further information: Skin: Danger of cutaneous absorption		
	ACGIH	STEL	250 ppm
	Further information: Skin: Danger of cutaneous absorption		
	OSHA Z-1	TWA	260 mg/m3 200 ppm

The following substance(s), which have Occupational Exposure Limit(s) (OEL), may be formed during handling or processing:, Methanol.

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Xylene	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	0.3 g/g creatinine	ACGIH BEI
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI
Cyclohexanone	108-94-1	1,2-Cyclohexanediol	Urine	End of shift at end of workweek	80 mg/l	ACGIH BEI
		Cyclohexanol	Urine	End of shift (As soon as possible after exposure ceases)	8 mg/l	ACGIH BEI
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI

possible
after
exposure
ceases)

Exposure controls

Engineering controls: Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use chemical goggles. If exposure causes eye discomfort, use a full-face respirator.

Skin protection

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Chlorinated polyethylene. Neoprene. Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Examples of acceptable glove barrier materials include: Polyvinyl chloride ("PVC" or "vinyl"). Avoid gloves made of: Viton. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. When respiratory protection is required, use an approved positive-pressure self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	liquid
Color	colourless
Odor	solvent-like
Odor Threshold	No data available
pH	Not applicable, substance/mixture is non-polar/aprotic
Melting point/range	No data available
Freezing point	No data available
Boiling point (760 mmHg)	>= 75 °C (>= 167 °F)
Flash point	Tag closed cup -4 °C (25 °F)
Evaporation Rate (Butyl Acetate = 1)	No data available

Flammability (solid, gas)	Not applicable
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapor Pressure	No data available
Relative Vapor Density (air = 1)	No data available
Relative Density (water = 1)	0.9
Water solubility	No data available
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Kinematic Viscosity	1 cSt at 25 °C (77 °F)
Explosive properties	Not explosive
Oxidizing properties	The substance or mixture is not classified as oxidizing.
Molecular weight	No data available
Particle size	Not applicable

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents. Vapours may form explosive mixture with air. Highly flammable liquid and vapour.

Conditions to avoid: Avoid static discharge. Heat, flames and sparks.

Incompatible materials: Avoid contact with oxidizing materials.

Hazardous decomposition products:

Decomposition products can include and are not limited to: Methanol.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data are available.

Information on likely routes of exposure

Inhalation, Eye contact, Skin contact, Ingestion.

Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)

Acute Toxicity Endpoints:

Not classified based on available information.

Acute oral toxicity**Information for the Product:**

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury. Swallowing may result in gastrointestinal irritation.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):
LD50, Rat, > 4,900 mg/kg Estimated.

Information for components:**Ethyl acetate**

LD50, Rabbit, 4,934 mg/kg

Methyl methacrylate, 3-(trimethoxysilyl)propyl methacrylate polymer

Single dose oral LD50 has not been determined.

This substance may hydrolyze to release Methanol. Methanol is highly toxic to humans and may cause central nervous system effects, visual disturbances up to blindness, metabolic acidosis, and degenerative damage to other organs including liver, kidney, and heart.

Xylene

LD50, Rat, 4,300 mg/kg

Ethylbenzene

LD50, Rat, 3,500 mg/kg

Cyclohexanone

LD50, Rat, 1,890 mg/kg

Acute dermal toxicity**Information for the Product:**

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):
LD50, > 2,000 mg/kg Estimated.

Information for components:**Ethyl acetate**

LD50, Rabbit, > 17,900 mg/kg

Methyl methacrylate, 3-(trimethoxysilyl)propyl methacrylate polymer

The dermal LD50 has not been determined.

This substance may hydrolyze to release Methanol. Effects of methanol are the same as observed via oral and inhalation exposure and include central nervous system (CNS) depression, visual impairment up to blindness, metabolic acidosis, with effects on organ systems such as liver, kidneys and heart, even death.

Xylene

LD50, Rabbit, > 2,000 mg/kg

Ethylbenzene

LD50, Rabbit, 15,500 mg/kg

Cyclohexanone

The dermal LD50 has not been determined.

Acute inhalation toxicity**Information for the Product:**

Prolonged excessive exposure may cause adverse effects. May cause respiratory irritation and central nervous system depression. Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness. In humans, symptoms may include: Lethargy Alcohol consumed before or after exposure may increase adverse effects.

As product: The LC50 has not been determined.

Information for components:**Ethyl acetate**

LC50, Rat, 4 Hour, vapour, > 28.6 mg/l

Methyl methacrylate, 3-(trimethoxysilyl)propyl methacrylate polymer

The LC50 has not been determined.

This substance may hydrolyze to release Methanol. Inhalation of methanol may cause effects ranging from headache, narcosis and visual impairment to metabolic acidosis, blindness, and even death.

Xylene

Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness. LC50, Rat, 4 Hour, vapour, 27.5 mg/l

Ethylbenzene

LC50, Rat, 4 Hour, vapour, 17.2 mg/l

Cyclohexanone

Vapor concentrations are attainable which could be hazardous on single exposure. May cause central nervous system effects. Excessive exposure may cause severe irritation to upper respiratory tract (nose and throat) and lungs.

LC50, Rat, male and female, 4 Hour, vapour, > 6.2 mg/l No deaths occurred at this concentration.

Skin corrosion/irritation

Causes skin irritation.

Information for the Product:

Based on information for component(s):

Brief contact may cause skin irritation with local redness.

Prolonged contact may cause skin burns. Symptoms may include pain, severe local redness, swelling, and tissue damage.

Vapor may cause skin irritation.

May cause drying and flaking of the skin.

Information for components:**Ethyl acetate**

Essentially nonirritating to skin.

May cause drying and flaking of the skin.

Methyl methacrylate, 3-(trimethoxysilyl)propyl methacrylate polymer

Brief contact may cause moderate skin irritation with local redness.

Xylene

Prolonged contact may cause skin irritation with local redness.

Repeated contact may cause skin burns. Symptoms may include pain, severe local redness, swelling, and tissue damage.

Vapor may cause skin irritation.

May cause drying and flaking of the skin.

Ethylbenzene

Brief contact may cause moderate skin irritation with local redness.

Prolonged contact may cause skin burns. Symptoms may include pain, severe local redness, swelling, and tissue damage.

May cause drying and flaking of the skin.

Cyclohexanone

Brief contact may cause severe skin irritation with pain and local redness.

Prolonged contact may cause skin burns. Symptoms may include pain, severe local redness, swelling, and tissue damage.

Serious eye damage/eye irritation

Causes serious eye irritation.

Information for the Product:

Based on information for component(s):

May cause eye irritation.

May cause corneal injury.

Vapor may cause eye irritation experienced as mild discomfort and redness.

Vapor may cause lacrimation (tears).

In humans, eye irritation resulted from brief (minutes) exposure to cyclohexanone vapor concentration of 50 ppm and above.

Information for components:**Ethyl acetate**

May cause slight eye irritation.

May cause slight temporary corneal injury.

Vapor may cause eye irritation experienced as mild discomfort and redness.

Methyl methacrylate, 3-(trimethoxysilyl)propyl methacrylate polymer

May cause moderate eye irritation.

Xylene

May cause moderate eye irritation.

May cause slight temporary corneal injury.

Vapor may cause eye irritation experienced as mild discomfort and redness.

Ethylbenzene

May cause moderate eye irritation.

Vapor may cause lacrimation (tears).

Cyclohexanone

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

Vapor may cause severe eye irritation and corneal injury.

Vapor may cause lacrimation (tears).

In humans, eye irritation resulted from brief (minutes) exposure to cyclohexanone vapor concentration of 50 ppm and above.

Sensitization**For skin sensitization:**

Not classified based on available information.

For respiratory sensitization:

Not classified based on available information.

Information for the Product:

For skin sensitization:

Contains component(s) which did not cause allergic skin sensitization in guinea pigs.

For respiratory sensitization:

No relevant data found.

Information for components:**Ethyl acetate**

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Methyl methacrylate, 3-(trimethoxysilyl)propyl methacrylate polymer

For skin sensitization:

No relevant data found.

For respiratory sensitization:
No relevant data found.

Xylene

For skin sensitization:
No relevant data found.

For respiratory sensitization:
No relevant data found.

Ethylbenzene

Did not cause allergic skin reactions when tested in humans.

For respiratory sensitization:
No relevant data found.

Cyclohexanone

For skin sensitization:
Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

May cause drowsiness or dizziness.

Information for the Product:

Product test data not available.

Information for components:**Ethyl acetate**

May cause drowsiness or dizziness.
Route of Exposure: Inhalation
Target Organs: Nervous system

Methyl methacrylate, 3-(trimethoxysilyl)propyl methacrylate polymer

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Xylene

May cause respiratory irritation.
Route of Exposure: Inhalation
Target Organs: Respiratory system

Ethylbenzene

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Cyclohexanone

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Aspiration Hazard

Not classified based on available information.

Information for the Product:

Based on available information, aspiration hazard could not be determined.

Information for components:

Ethyl acetate

Based on physical properties, not likely to be an aspiration hazard.

Methyl methacrylate, 3-(trimethoxysilyl)propyl methacrylate polymer

Based on physical properties, not likely to be an aspiration hazard.

Xylene

May be fatal if swallowed and enters airways.

Ethylbenzene

Aspiration into the lungs may occur during ingestion or vomiting, causing lung damage or even death due to chemical pneumonia. May be fatal if swallowed and enters airways.

Cyclohexanone

Aspiration into the lungs may occur during ingestion or vomiting, causing lung damage or even death due to chemical pneumonia.

Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)

Specific Target Organ Systemic Toxicity (Repeated Exposure)

May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Information for the Product:

Product test data not available.

Information for components:

Ethyl acetate

In animals, effects have been reported on the following organs:

Liver.

Respiratory tract.

Methyl methacrylate, 3-(trimethoxysilyl)propyl methacrylate polymer

No relevant data found.

Xylene

In animals, effects have been reported on the following organs:

Liver

kidney

Blood

Xylene is reported to have caused hearing loss in laboratory animals upon exposure to high concentrations; such effects have not been reported in humans.

Ethylbenzene

In animals, effects have been reported on the following organs:

May cause hearing loss based on animal data.

Kidney.

Liver.

Lung.

Although one early inhalation study on ethylbenzene reported an adverse effect on the testes, recent, more comprehensive studies have not shown this effect.

Cyclohexanone

In animals, effects have been reported on the following organs:

Central nervous system.

Kidney.

Liver.

Carcinogenicity

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:**Ethyl acetate**

For the hydrolysis product: Ethanol when not consumed in an alcoholic beverage is not classifiable as a human carcinogen.

Methyl methacrylate, 3-(trimethoxysilyl)propyl methacrylate polymer

No relevant data found.

Xylene

Xylene was not found to be carcinogenic in a National Toxicology Program bioassay in rats and mice.

Ethylbenzene

Ethylbenzene has been shown to cause cancer in laboratory animals. There is no evidence that these findings are relevant to humans.

Cyclohexanone

Available data are inadequate to evaluate carcinogenicity.

Carcinogenicity**Component****List****Classification**

Ethylbenzene

IARC

Group 2B: Possibly carcinogenic to humans

ACGIH

A3: Confirmed animal carcinogen with unknown relevance to humans.

Cyclohexanone

ACGIH

A3: Confirmed animal carcinogen with unknown relevance to humans.

Teratogenicity

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:

Ethyl acetate

No relevant data found.

Methyl methacrylate, 3-(trimethoxysilyl)propyl methacrylate polymer

No relevant data found.

Xylene

Exaggerated doses of xylene given orally to pregnant mice resulted in an increase in cleft palate, a common developmental abnormality in mice. In animal inhalation studies, xylene caused toxicity to the fetus but did not cause birth defects. Available data are inadequate for evaluation of maternal toxicity.

Ethylbenzene

Has caused birth defects in laboratory animals only at doses toxic to the mother. Has been toxic to the fetus in lab animals at doses nontoxic to the mother.

Cyclohexanone

Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Did not cause birth defects in laboratory animals.

Reproductive toxicity

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:

Ethyl acetate

No relevant data found.

Methyl methacrylate, 3-(trimethoxysilyl)propyl methacrylate polymer

No relevant data found.

Xylene

In animal studies, did not interfere with reproduction.

Ethylbenzene

In animal studies, did not interfere with reproduction. In animal studies, did not interfere with fertility.

Cyclohexanone

Cyclohexanone caused reduced growth and survival of offspring in an animal reproduction study. Dose levels producing this effect also caused central nervous system effects in parental animals. In animal studies, has been shown to interfere with reproduction in males. Effects have been seen only at doses that produced significant toxicity to the parent animals.

Mutagenicity

Not classified based on available information.

Information for the Product:

Product test data not available.

Information for components:

Ethyl acetate

In vitro genetic toxicity studies were predominantly negative. Animal genetic toxicity studies were negative.

Methyl methacrylate, 3-(trimethoxysilyl)propyl methacrylate polymer

No relevant data found.

Xylene

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Ethylbenzene

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Cyclohexanone

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data are available.

Toxicity

Ethyl acetate

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
LC50, Pimephales promelas (fathead minnow), 96 Hour, 230 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 24 Hour, 3,090 mg/l, DIN 38412

Acute toxicity to algae/aquatic plants

NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, >100 mg/l, OECD Test Guideline 201

Toxicity to bacteria

EC50, Photobacterium phosphoreum, 0.25 Hour, 5,870 mg/l

Chronic toxicity to fish

NOEC, Pimephales promelas (fathead minnow), 32 d, < 9.65 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, 2.4 mg/l

Methyl methacrylate, 3-(trimethoxysilyl)propyl methacrylate polymer**Acute toxicity to fish**

Based on data from similar materials

LC50, Danio rerio (zebra fish), 96 Hour, > 100 mg/l

Not expected to be acutely toxic to aquatic organisms.

Acute toxicity to aquatic invertebrates

Based on data from similar materials

EC50, Daphnia sp. (water flea), 48 Hour, > 100 mg/l

Acute toxicity to algae/aquatic plants

Based on data from similar materials

EC50, Scenedesmus subspicatus, 72 Hour, > 100 mg/l

Xylene**Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, 2.6 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

IC50, Daphnia magna (Water flea), 24 Hour, 1 - 4.7 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (algae), Static, 73 Hour, Growth rate, 4.36 mg/l, OECD Test Guideline 201 or Equivalent

NOEC, Pseudokirchneriella subcapitata (green algae), 73 Hour, Growth rate, 0.44 mg/l, OECD Test Guideline 201 or Equivalent

Chronic toxicity to fish

NOEC, Oncorhynchus mykiss (rainbow trout), flow-through, 56 d, mortality, > 1.3 mg/l

Ethylbenzene**Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, 4.2 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), Static, 48 Hour, 1.8 - 2.4 mg/l

Acute toxicity to algae/aquatic plants

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth inhibition (cell density reduction), 3.6 - 4.6 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

EC50, Bacteria, 16 Hour, > 12 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Ceriodaphnia dubia (water flea), semi-static test, 7 d, 0.96 mg/l

Toxicity to soil-dwelling organisms

LC50, Eisenia fetida (earthworms), 2 d, survival, 0.047 mg/cm²

Cyclohexanone**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
LC50, Pimephales promelas (fathead minnow), static test, 96 Hour, 527 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

EC50, Desmodesmus subspicatus (green algae), Static, 72 Hour, Growth, > 100 mg/l, OECD Test Guideline 201

Toxicity to bacteria

EC50, activated sludge, 30 min, Respiration rates., > 1,000 mg/l, OECD 209 Test

Persistence and degradability**Ethyl acetate**

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

Biodegradation: 100 %

Exposure time: 28 d

Method: OECD Test Guideline 301D or Equivalent

Theoretical Oxygen Demand: 1.82 mg/mg

Methyl methacrylate, 3-(trimethoxysilyl)propyl methacrylate polymer

Biodegradability: No relevant data found.

Xylene

Biodegradability: Material is expected to be readily biodegradable.

10-day Window: Pass

Biodegradation: > 60 %

Exposure time: 10 d

Method: OECD Test Guideline 301F or Equivalent

Theoretical Oxygen Demand: 3.17 mg/mg

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	37.000 %
10 d	58.000 %
20 d	72.000 %

Photodegradation**Test Type:** Half-life (indirect photolysis)**Sensitization:** OH radicals**Atmospheric half-life:** 19.7 Hour**Method:** Estimated.**Ethylbenzene****Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

Biodegradation: 100 %**Exposure time:** 6 d**Method:** OECD Test Guideline 301E or Equivalent**Theoretical Oxygen Demand:** 3.17 mg/mg Estimated.**Chemical Oxygen Demand:** 2.62 mg/mg Dichromate**Biological oxygen demand (BOD)**

Incubation Time	BOD
5 d	31.5 %
10 d	38.5 %
20 d	45.4 %

Photodegradation**Sensitization:** OH radicals**Atmospheric half-life:** 55 Hour**Method:** Estimated.**Cyclohexanone****Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Not applicable

Biodegradation: 87 %**Exposure time:** 14 d**Method:** OECD Test Guideline 301C or Equivalent

10-day Window: Pass

Biodegradation: 90 - 100 %**Exposure time:** 28 d**Method:** OECD Test Guideline 301F**Theoretical Oxygen Demand:** 2.61 mg/mg**Photodegradation**

Test Type: Half-life (indirect photolysis)
Sensitization: OH radicals
Atmospheric half-life: 10.6 Hour
Method: Estimated.

Bioaccumulative potential

Ethyl acetate

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).
Partition coefficient: n-octanol/water(log Pow): 0.68 Measured
Bioconcentration factor (BCF): 30 Fish Measured

Methyl methacrylate, 3-(trimethoxysilyl)propyl methacrylate polymer

Bioaccumulation: No relevant data found.

Xylene

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).
Partition coefficient: n-octanol/water(log Pow): 3.12 Measured
Bioconcentration factor (BCF): 25.9 Rainbow trout (Salmo gairdneri) Measured

Ethylbenzene

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).
Partition coefficient: n-octanol/water(log Pow): 3.15 Measured
Bioconcentration factor (BCF): 15 Fish Measured

Cyclohexanone

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).
Partition coefficient: n-octanol/water(log Pow): 0.86 OECD Test Guideline 107 or Equivalent

Mobility in soil

Ethyl acetate

Partition coefficient (Koc): 3 Estimated.

Methyl methacrylate, 3-(trimethoxysilyl)propyl methacrylate polymer

No relevant data found.

Xylene

Partition coefficient (Koc): 443 Estimated.

Ethylbenzene

Partition coefficient (Koc): 518 Estimated.

Cyclohexanone

Partition coefficient (Koc): 39.48 Estimated.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local

laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN SDS SECTION 1: Identified Uses. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility of the waste generator. Do not re-use containers for any purpose.

14. TRANSPORT INFORMATION

DOT

Proper shipping name	Flammable liquids, n.o.s.(Ethyl acetate, Ethylbenzene)
UN number	UN 1993
Class	3
Packing group	II
Reportable Quantity	Xylene, Ethyl acetate

Classification for SEA transport (IMO-IMDG):

Proper shipping name	FLAMMABLE LIQUID, N.O.S.(Ethyl acetate, Ethylbenzene)
UN number	UN 1993
Class	3
Packing group	II
Marine pollutant	No
Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Proper shipping name	Flammable liquid, n.o.s.(Ethyl acetate, Ethylbenzene)
UN number	UN 1993
Class	3
Packing group	II

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Flammable (gases, aerosols, liquids, or solids)

Hazard not otherwise classified (physical hazards)

Specific target organ toxicity (single or repeated exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

The following components are subject to reporting levels established by SARA Title III, Section 313:

Components**CASRN**

Xylene

1330-20-7

Ethylbenzene

100-41-4

Pennsylvania Right To Know

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components**CASRN**

Ethyl acetate

141-78-6

Methyl methacrylate, 3-(trimethoxysilyl)propyl methacrylate
polymer

26936-30-1

Xylene

1330-20-7

Ethylbenzene

100-41-4

Cyclohexanone

108-94-1

California Prop. 65WARNING: This product can expose you to chemicals including Ethylbenzene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.**United States TSCA Inventory (TSCA)**

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System**NFPA**

Health	Flammability	Instability
2	3	0

HMIS

Health	Flammability	Physical Hazard
2*	3	0

* = Chronic Effects (See Hazards Identification)

Revision

Identification Number: 6018630 / A001 / Issue Date: 11/03/2023 / Version: 7.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	ACGIH - Biological Exposure Indices (BEI)
Dow IHG	Dow Industrial Hygiene Guideline
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
STEL	Short term exposure limit
TWA	Time weighted average

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US