



# TECHNICAL DATA SHEET

**WEATHERPRIME®**  
Color-Tinted Acrylic Primer For  
Weatherlastic Finishes  
DS436

---

## PRODUCT DESCRIPTION

Weatherprime is a water-based, color-tinted acrylic primer, which provides a flat, non-slip uniformly absorbent, color-coordinated surface for application of Dryvit exterior Weatherlastic finishes. Weatherprime is available in a variety of standard colors as well as custom colors.



---

## BASIC USES

Weatherprime is recommended for the surface preparation of stucco, concrete and masonry to color coordinate the substrate with the selected Dryvit Weatherlastic finish.

---

## FEATURES & BENEFITS

### FEATURE

- Tintable Acrylic Primer
- Water-based

### BENEFIT

- Unlimited color options
- Easy cleanup

---

## PROPERTIES

**Drying Time:** The drying time of Weatherprime is dependent upon the air temperature and relative humidity. Under average drying conditions [70 °F (21 °C), 55% R.H.], Weatherprime is dry to the touch in 1/2 hour and sufficiently dry for application of a Weatherlastic finish in 2 hours. Protect from rain for at least 4 hours.

**Job Conditions:** Air and surface temperature for application of Weatherprime must be 40 °F (4 °C) or higher and must remain so for a minimum of 24 hours.

**Temporary Protection:** Shall be provided at all times until all work is completed to protect the wall from weather and other damage.

---

## SURFACE PREPARATION

Surfaces shall not be below 40 °F (4 °C) and must be clean, dry, structurally sound and free of efflorescence, grease, oil, form release agents and curing compounds. On painted surfaces, remove all blistered or peeling paint to a sound substrate. Remove all gloss by sanding.

---

## MIXING

Stir to a smooth, homogeneous consistency.

---

## APPLICATION

Weatherprime can be applied using a brush, paint roller or spray equipment.

---

## COVERAGE

Approximately 1500 ft<sup>2</sup> (140 m<sup>2</sup>) per 50 lb (23 kg) pail, depending upon surface roughness and porosity of the substrate.

---

## STORAGE

Weatherprime must be stored at a minimum of 40 °F (4 °C) and a maximum of 100 °F (38 °C) in tightly sealed containers protected from weather and out of direct sunlight.

The shelf life is 2 years from date of manufacture when properly stored in unopened pails.

---

## CAUTIONS & LIMITATIONS

- Avoid applying Weatherprime in direct sunlight. Always work on the shady side of the wall or protect the area with appropriate shading material.

---

## CLEAN UP

Clean tools with water while Weatherprime is still wet.

---

## TECHNICAL AND FIELD SERVICES

Available on request.

Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of Dryvit products as of the date of publication of this document and is presented in good faith. Dryvit assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, contact Dryvit.

For more information on Dryvit or Continuous Insulation, [click here](#).

Printed in USA. Issued 1.1.2022

©Dryvit 2022

DS436

Tremco Construction Products Group (CPG) brings together the Commercial Sealants & Waterproofing and Roofing & Building Maintenance divisions of Tremco CPG Inc.; Dryvit and Willseal brands; Nudura Inc.; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc.; Weatherproofing Technologies Canada, Inc.; and Pure Air Control Services, Inc.



[dryvit.com](http://dryvit.com) | 800.556.7752



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122  
800.321.7906 | [tremcocpg.com](http://tremcocpg.com)