



BUILDING TRUST



Sika Emseal Safety Data Sheet Product Package

Emshield® DFR

The information contained in these Emseal-specific or Sika-specific Safety Data Sheets applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof.

Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika Emseal product, which are available at web site and/or telephone number listed in Section 1 of this SDS

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.



EMSEAL Joint Systems, Ltd.

25 Bridle Lane, Westborough, MA 01581 USA

www.emseal.com

Preparation Date March 15, 2015

Revision Date April 25, 2024

Safety Data Sheet DFR Foam

1. Identification of the Substance / Preparation

Product identifier	Emshield DFR
Other identifier or names	DFR, DFR2, DFR3
UN ID number	None
Manufacturer Address	EMSEAL LLC 111 Royal Group Crescent Woodbridge, Ontario L4H 1X9 Canada
Company Phone	(508) 836-0280 M-F 9am - 5pm
Emergency Phone	CHEMTREC (800) 424-9300 (24 Hours)

2. Hazardous Identification

Hazardous Classification	This product is not classified as hazardous when used as intended.
Signal Word	None
Pictograms	None
Emergency Overview:	No emergency requirements.

3. Composition / Information on Ingredients

EMSHIELD DFR is composed of polyurethane foam impregnated with a with a proprietary solid inorganic fire retardant bonded to a fully cured silicone sealant. It is classified as Non-Hazardous.

NOTE: Silicone facing is fully cured. The composition of the silicone in its liquid state is comprised of the following:

Chemical Name	CAS #	% by Weight	GHS Classification Hazard Statements
Polydimethyl Siloxane Diol	70131-67-8 3	0.0-60.0	SELF CLASSIFICATION Classification: Not Applicable
Calcium Carbonate (Limestone)	1317-65-3		SELF CLASSIFICATION
Synthetic Calcium Carbonate	371-34-1	10.0-40.0	Classification: Not Applicable
Phenyl Oximino Silane	34036-80-1	1.0-5.0	Classification: STOT RE Cat. 2, Skin Sensitization Cat. 1, Aquatic, Chronic Toxicity Cat. 3 Hazard Statement Codes: H373, H317, H412
Silicon Dioxide, Fumed	112945-52-5	1.0-5.0	SELF CLASSIFICATION Classification: Not Applicable
Mineral Spirits	8052-41-3	0.0-1.0	Classification: Carcinogenic Cat. 1B, Mutagenic Cat. 1B, Aspiration Hazard Cat. 1 Hazard Statement Codes: H350, H340, H304
Quartz	14808-60-7 14464-46-1	Trace	SELF CLASSIFICATION Classification: Carcinogenic Cat. 1B Hazard Statement Codes: H350

Water and other components.

Each of the other components is present in less than 1 percent concentration (0.1% concentration for potential carcinogens, reproductive toxins, respiratory tract sensitizers, and mutagens).

Classification: Not Applicable



4. First Aid Measures

- 4.1 EYES:** Flush with water for at least 15 minutes, and call physician if problems persist.
- 4.2 SKIN:** Product may leave a sticky residue, and mild irritation if prolonged exposure. Scrub with soapy water until adhesive is removed.
- 4.3 INGESTION:** Do not eat – call physician if ingested.

5. Fire-fighting Measures

- 5.2 FLAMMABILITY:** Slight. The material composition does not support combustion.
- 5.2 FLASH POINT:** Unknown.
- 5.3 AUTO-IGNITION TEMPERATURE:** Unknown.
- 5.4 EXTINGUISHING MEDIA:** Large volumes of water, or ABC chemical may be appropriate for initial control or small volumes of impregnated foam.
- 5.5 HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon di/mon oxides will be formed as well as other noxious and toxic fumes upon combustion – do not breath combustion products.

6. Accidental Release Measures

If material is unusable pick up pieces and dispose of in accordance with local regulations; material and all components are non-toxic and normal landfill will most often be acceptable.

7. Handling and Storage

Store in original packaging below 35°C. There are no special handling instructions.

8. Exposure Controls / Personal Protection

- 8.1 RESPIRATORY PROTECTION:** Not required
- 8.2 EYE PROTECTION:** Not required
- 8.3 SKIN PROTECTION:** Gloves of any material are suitable if desired, but not required. No other protection is required.

9. Physical and Chemical Properties

- 9.1 APPEARANCE:** Dark grey / charcoal colored foam and colored silicone with product identifying packaging.
- 9.2 ODOR:** Slight characteristic odor.
- 9.3 PERCENT SOLIDS BY WEIGHT:** 100%
- 9.4 PHYSICAL STATE:** Solid
- 9.5 PERCENT VOLATILE:** <1% wt/wt
- 9.6 DENSITY:** 0.4g/cm³
- 9.7 DECOMPOSITION:** > 300°C
- 9.8 SOLUBILITY IN WATER:** None



10. Stability and Reactivity

Stable under normal conditions – avoid temperatures in excess of 300°C, strong acids and bases, and open flame.

11. Toxicological Information

Unknown.

12. Ecological Information

Unknown

13. Disposal Considerations

No known hazard. Dispose of in accordance with local regulations; material and all components are non-toxic and disposal in normal landfill will most often be acceptable.

14. Transportation Information

Not hazardous – safe for non-hazardous shipping.

15. Regulatory Information

Unknown.

16. Other Information

No other information provided.

Northern Manufacturing Construction Grade Epoxy Part A

Revision Date 04/24/2024

Print Date 04/24/2024

1. Identification

Product name : Northern Manufacturing Construction Grade Epoxy Part A

Supplier : Northern Manufacturing
111 Royal Group Crescent, Unit NM
Woodbridge, ON L4H 1X9 Canada

Telephone : 416-740-2090 (8AM - 5PM EST) (M-F)

Emergency telephone : Chemtrec 1-800-424-9300 (24 Hours)


Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

2. Hazards identification

GHS Classification

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2A	H319: Causes serious eye irritation.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 1A (Inhalation)	H350i: May cause cancer by inhalation.
Specific target organ systemic toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ systemic toxicity - repeated exposure, Category 1, Lungs	H372: Causes damage to organs through prolonged or repeated exposure.

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H350i May cause cancer by inhalation.
H372 Causes damage to organs (Lungs) through prolonged or

Northern Manufacturing Construction Grade Epoxy Part A

Rev. Date 04/24/2024

Print Date 04/24/2024

repeated exposure.

Precautionary Statements

- Prevention:**
 - P201 Obtain special instructions before use.
 - P202 Do not handle until all safety precautions have been read and understood.
 - P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
 - P264 Wash skin thoroughly after handling.
 - P270 Do not eat, drink or smoke when using this product.
 - P271 Use only outdoors or in a well-ventilated area.
 - P272 Contaminated work clothing must not be allowed out of the workplace.
 - P280 Wear protective gloves/ eye protection/ face protection.
 - P281 Use personal protective equipment as required.
- Response:**
 - P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 - P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 - P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P308 + P313 IF exposed or concerned: Get medical advice/ attention.
 - P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
 - P337 + P313 If eye irritation persists: Get medical advice/ attention.
 - P362 Take off contaminated clothing and wash before reuse.
- Storage:**
 - P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 - P405 Store locked up.
- Disposal:**
 - P501 Dispose of contents/ container to an approved waste disposal plant.

See Section 11 for more detailed information on health effects and symptoms.
 There are no hazards not otherwise classified that have been identified during the classification process.
 There are no ingredients with unknown acute toxicity used in a mixture at a concentration $\geq 1\%$.

3. Composition/information on ingredients

Hazardous ingredients

Chemical name	CAS-No.	Concentration (%)
Quartz (SiO ₂)	14808-60-7	$\geq 25 - < 50 \%$
bisphenol-A-(epichlorhydrin) epoxy resin	25068-38-6	$\geq 10 - < 20 \%$
oxirane, mono[(C12-14-alkyloxy)methyl]derivatives	68609-97-2	$\geq 5 - < 10 \%$

Northern Manufacturing Construction Grade Epoxy Part A

Rev. Date 04/24/2024

Print Date 04/24/2024

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects
sensitizing effects
carcinogenic effects
- Cough
Respiratory disorder
Allergic reactions
Excessive lachrymation
Erythema
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
- Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause respiratory irritation.
May cause cancer by inhalation.
Causes damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- Notes to physician : Treat symptomatically.

Northern Manufacturing Construction Grade Epoxy Part A

Rev. Date 04/24/2024

Print Date 04/24/2024

5. Fire-fighting measures

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

6. Accidental release measures

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

7. Handling and storage

- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Prevent unauthorized access.
Store in original container.
Keep in a well-ventilated place.
Observe label precautions.
Store in accordance with local regulations.
- Materials to avoid : No data available

Northern Manufacturing Construction Grade Epoxy Part A

Rev. Date 04/24/2024

Print Date 04/24/2024

8. Exposure controls/personal protection

Component	CAS-No.	Basis **	Value	Exposure limit(s)* / Form of exposure
Quartz (SiO2)	14808-60-7	OSHA Z-3	TWA	10 mg/m3 / %SiO2+2 respirable
		OSHA Z-3	TWA	250 mppcf / %SiO2+5 respirable
		OSHA P0	TWA	0.1 mg/m3 Respirable fraction
		ACGIH	TWA	0.025 mg/m3 Respirable fraction
		OSHA Z-1	TWA	0.05 mg/m3 Respirable dust

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

**Basis

ACGIH. Threshold Limit Values (TLV)

OSHA P0. Table Z-1, Limit for Air Contaminat (1989 Vacated Values)

OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant

OSHA P2. Permissible Exposure Limits (PEL), Table Z-2

OSHA Z3. Table Z-3, Mineral Dust

Engineering measures

: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

Respiratory protection

: Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Northern Manufacturing Construction Grade Epoxy Part A

Rev. Date 04/24/2024

Print Date 04/24/2024

Hand protection Remarks	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eye protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Hygiene measures	: Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Remove contaminated clothing and protective equipment before entering eating areas. Wash thoroughly after handling.

9. Physical and chemical properties

Appearance	: paste
Color	: white
Odor	: aromatic
Odor Threshold	: No data available
Flash point	: > 212 °F (> 100 °C)
Ignition temperature	: No data available
Decomposition temperature	: No data available
Lower explosion limit (Vol%)	: No data available
Upper explosion limit (Vol%)	: No data available
Flammability (solid, gas)	: No data available
Oxidizing properties	: No data available
pH	: Note: Not applicable
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Vapor pressure	: 0.01 mmHg (0.01 hpa)
Density	: 1.99 g/cm3

Northern Manufacturing Construction Grade Epoxy Part A

Rev. Date 04/24/2024

Print Date 04/24/2024

Water solubility	:	Note: insoluble
Partition coefficient: n-octanol/water	:	No data available
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm ² /s
Relative vapor density	:	No data available
Evaporation rate	:	No data available
Burning rate	:	No data available
Volatile organic compounds (VOC) content	:	5 g/l A+B Combined

10. Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available

11. Toxicological information

Acute toxicity

Not classified based on available information.

Components:

bisphenol-A-(epichlorhydrin) epoxy resin:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization: May cause an allergic skin reaction.

Respiratory sensitization: Not classified based on available information.

Northern Manufacturing Construction Grade Epoxy Part A

Rev. Date 04/24/2024

Print Date 04/24/2024

Germ cell mutagenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation.

IARC	Group 1: Carcinogenic to humans	
	Quartz (SiO2)	14808-60-7
	Group 2B: Possibly carcinogenic to humans	
	titanium dioxide	13463-67-7
NTP	Known to be human carcinogen	
	Quartz (SiO2)	14808-60-7
	Titanium dioxide (13463-67-7)	

In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have been shown to cause an increase in lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. The potential for these adverse health effects appears to be closely related to the particle size and the amount of the exposed surface area that comes into contact with the lung. However, tests with other laboratory animals such as mice and hamsters, indicate that rats are significantly more susceptible to the pulmonary overload and inflammation that cause lung cancer. Epidemiology studies do not suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide. Titanium dioxide has been characterized by IARC as possibly carcinogenic to humans (Group 2B) through inhalation (not ingestion). It has not been characterized as a potential carcinogen by either NTP or OSHA.

12. Ecological information

Other information Do not empty into drains; dispose of this material and its container in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Component:

bisphenol-A-(epichlorhydrin) epoxy	25068-38-6	<u>Toxicity to fish:</u> LC50
------------------------------------	------------	----------------------------------

Northern Manufacturing Construction Grade Epoxy Part A

Rev. Date 04/24/2024

Print Date 04/24/2024

resin

Species: Oncorhynchus mykiss (rainbow trout)
Dose: 2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates:
EC50
Species: Daphnia magna (Water flea)
Dose: 1.8 mg/l
Exposure time: 48 h

13. Disposal considerations

Disposal methods

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

Special precautions for user

No data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

15. Regulatory information

TSCA list

: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

Northern Manufacturing Construction Grade Epoxy Part A

Rev. Date 04/24/2024

Print Date 04/24/2024

SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Chronic Health Hazard
 Skin corrosion or irritation
 Serious eye damage or eye irritation
 Respiratory or skin sensitization
 Carcinogenicity
 Specific target organ toxicity (single or repeated exposure)

SARA 302 : This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

Ozone-Depletion Potential This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).
 This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

California Prop 65  **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov

16. Other information

HMIS Classification

Health	*	3
Flammability		1
Physical Hazard		0
Personal Protection		x

Caution: HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

Notes to Reader

Northern Manufacturing Construction Grade Epoxy Part A

Rev. Date 04/24/2024

Print Date 04/24/2024

Revision Date

04/24/2024 Material

number: 577437

Northern Manufacturing Construction Grade Epoxy Part B

Print Date 04/24/2024

Print Date 04/24/2024

1. Identification

Product name : Northern Manufacturing Construction Grade Epoxy Part B

Supplier : Northern Manufacturing
111 Royal Group Crescent, Unit NM
Woodbridge, ON L4H 1X9 Canada

Telephone : 416-740-2090 (8AM - 5PM EST) (M-F)

Emergency telephone : Chemtrec 1-800-424-9300 (24 Hours)

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

2. Hazards identification

GHS Classification

Skin corrosion, Category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 1A (Inhalation)	H350i: May cause cancer by inhalation.
Specific target organ systemic toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ systemic toxicity - repeated exposure, Category 1, Lungs	H372: Causes damage to organs through prolonged or repeated exposure.

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H350i May cause cancer by inhalation.
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure.

Northern Manufacturing Construction Grade Epoxy Part B

Rev. Date 04/24/2024

Print Date 04/24/2024

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P281 Use personal protective equipment as required.
Response:
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P310 Immediately call a POISON CENTER/doctor.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P363 Wash contaminated clothing before reuse.
Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Warning : Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain,liver, kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal.

See Section 11 for more detailed information on health effects and symptoms.
There are no hazards not otherwise classified that have been identified during the classification process.
There are no ingredients with unknown acute toxicity used in a mixture at a concentration \geq 1%.

3. Composition/information on ingredients

Hazardous ingredients

Northern Manufacturing Construction Grade Epoxy Part B

Rev. Date 04/24/2024

Print Date 04/24/2024

Chemical name	CAS-No.	Concentration (%)
Quartz (SiO ₂)	14808-60-7	>= 25 - < 50 %
N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine	10563-29-8	>= 3 - < 5 %
m-phenylenebis(methylamine)	1477-55-0	>= 1 - < 2 %
Benzyl alcohol	100-51-6	>= 1 - < 2 %
salicylic acid	69-72-7	>= 1 - < 2 %
triethylenetetramine	112-24-3	>= 0.1 - < 1 %

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Health injuries may be delayed.
corrosive effects
irritant effects
sensitizing effects
carcinogenic effects
- Cough
Respiratory disorder
Allergic reactions
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
- May cause an allergic skin reaction.
Causes serious eye damage.

Northern Manufacturing Construction Grade Epoxy Part B

Rev. Date 04/24/2024

Print Date 04/24/2024

May cause respiratory irritation.
May cause cancer by inhalation.
Causes damage to organs through prolonged or repeated exposure.
Causes severe burns.

Protection of first-aiders : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.

Notes to physician : Treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

7. Handling and storage

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Northern Manufacturing Construction Grade Epoxy Part B

Rev. Date 04/24/2024

Print Date 04/24/2024

Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : Prevent unauthorized access.
Store in original container.
Keep in a well-ventilated place.
Observe label precautions.
Store in accordance with local regulations.

Materials to avoid : No data available

8. Exposure controls/personal protection

Component	CAS-No.	Basis **	Value	Exposure limit(s)* / Form of exposure
Quartz (SiO2)	14808-60-7	OSHA Z-3	TWA	10 mg/m3 / %SiO2+2 respirable
		OSHA Z-3	TWA	250 mppcf / %SiO2+5 respirable
		OSHA P0	TWA	0.1 mg/m3 Respirable fraction
		ACGIH	TWA	0.025 mg/m3 Respirable fraction
		OSHA Z-1	TWA	0.05 mg/m3 Respirable dust
m-phenylenebis(methylamine)	1477-55-0	ACGIH	C	0.1 mg/m3
		OSHA P0	C	0.1 mg/m3

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

****Basis**

- ACGIH. Threshold Limit Values (TLV)
- OSHA P0. Table Z-1, Limit for Air Contaminant (1989 Vacated Values)
- OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant
- OSHA P2. Permissible Exposure Limits (PEL), Table Z-2
- OSHA Z3. Table Z-3, Mineral Dust

Northern Manufacturing Construction Grade Epoxy Part B

Rev. Date 04/24/2024

Print Date 04/24/2024

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection
Remarks

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

Skin and body protection

: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Hygiene measures

: Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
Remove contaminated clothing and protective equipment before entering eating areas.
Wash thoroughly after handling.

9. Physical and chemical properties

Appearance : paste
Color : dark gray
Odor : amine-like
Odor Threshold : No data available
Flash point : > 212 °F (> 100 °C)
Ignition temperature : No data available
Decomposition temperature : No data available

Northern Manufacturing Construction Grade Epoxy Part B

Rev. Date 04/24/2024

Print Date 04/24/2024

Lower explosion limit (Vol%)	: No data available
Upper explosion limit (Vol%)	: No data available
Flammability (solid, gas)	: No data available
Oxidizing properties	: No data available
pH	: Note: Not applicable
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Vapor pressure	: 0.01 mmHg (0.01 hpa)
Density	: 2.01 g/cm3
Water solubility	: Note: slightly soluble
Partition coefficient: n- octanol/water	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 20.5 mm2/s
Relative vapor density	: No data available
Evaporation rate	: No data available
Burning rate	: No data available
Volatile organic compounds (VOC) content	: 5 g/l A+B Combined

10. Stability and reactivity

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions.
Conditions to avoid	: No data available
Incompatible materials	: No data available

11. Toxicological information**Acute toxicity**

Northern Manufacturing Construction Grade Epoxy Part B

Rev. Date 04/24/2024

Print Date 04/24/2024

Not classified based on available information.

Components:**m-phenylenebis(methylamine):**

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1.34 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): > 3,100 mg/kg

Benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

salicylic acid:

Acute oral toxicity : LD50 Oral (Rat): 891 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): > 2,000 mg/kg

triethylenetetramine:

Acute oral toxicity : LD50 Oral (Rat): 1,716 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1,465 mg/kg

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization: May cause an allergic skin reaction.

Respiratory sensitization: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure.

Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain, liver, kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Northern Manufacturing Construction Grade Epoxy Part B

Rev. Date 04/24/2024

Print Date 04/24/2024

Aspiration toxicity

Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation.

IARC

Group 1: Carcinogenic to humans

NTP

Quartz (SiO₂) 14808-60-7
Known to be human carcinogen

Quartz (SiO₂) 14808-60-7

12. Ecological information

Other information

Do not empty into drains; dispose of this material and its container in a safe way.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Component:

m-phenylenebis(methylamine)
1477-55-0

Toxicity to fish:
LC50
Species: Oryzias latipes (Japanese medaka)
Dose: > 10 - 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates:
EC50
Species: Daphnia magna (Water flea)
Dose: > 10 - 100 mg/l
Exposure time: 48 h

Benzyl alcohol 100-51-6

Toxicity to fish:
LC50
Species: Fish
Dose: > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates:
EC50
Species: Daphnia magna (Water flea)
Dose: > 100 mg/l
Exposure time: 48 h

triethylenetetramine 112-24-3

Toxicity to fish:
LC50
Species: Pimephales promelas (fathead minnow)
Dose: > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates:
EC50
Species: Daphnia
Dose: 10 - 100 mg/l
Exposure time: 48 h

Toxicity to algae:
EC50

Northern Manufacturing Construction Grade Epoxy Part B

Rev. Date 04/24/2024

Print Date 04/24/2024

Species: Pseudokirchneriella subcapitata (green algae)
 Dose: 10 - 100 mg/l
 Exposure time: 72 h

13. Disposal considerations

Disposal methods

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	1760
Description of the goods	Corrosive liquids, n.o.s. (N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine, m-phenylenebis(methylamine))
Class	8
Packing group	III
Labels	8
Emergency Response Guidebook Number	154

IATA

UN number	1760
Description of the goods	Corrosive liquid, n.o.s. (N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine, m-phenylenebis(methylamine))
Class	8
Packing group	III
Labels	8
Packing instruction (cargo aircraft)	856
Packing instruction (passenger aircraft)	852
Packing instruction (passenger aircraft)	Y841

IMDG

UN number	1760
Description of the goods	CORROSIVE LIQUID, N.O.S. (N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine, m-phenylenebis(methylamine))

Northern Manufacturing Construction Grade Epoxy Part B

Rev. Date 04/24/2024

Print Date 04/24/2024

Class	8
Packing group	III
Labels	8
EmS Number 1	F-A
EmS Number 2	S-B

Marine pollutant no

DOT: For Limited Quantity exceptions reference 49 CFR 173.154 (b)
IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

Special precautions for user

No data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

15. Regulatory information

TSCA list : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Chronic Health Hazard
Skin corrosion or irritation
Serious eye damage or eye irritation
Respiratory or skin sensitization
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)

SARA 302 : This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

Northern Manufacturing Construction Grade Epoxy Part B

Rev. Date 04/24/2024

Print Date 04/24/2024


Ozone-Depletion Potential

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

California Prop 65

 **WARNING:** Cancer – www.P65Warnings.ca.gov

16. Other information

HMIS Classification

Health	*	3
Flammability		1
Physical Hazard		0
Personal Protection		X

Caution: HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

Revision Date 12/05/2019

Material number: 579211



1. Identification

Product name : Sikasil® WS-295

Supplier : Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
USA
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887


Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

2. Hazards identification

GHS Classification

Flammable liquids, Category 4	H227: Combustible liquid.
Eye irritation, Category 2A	H319: Causes serious eye irritation.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361f: Suspected of damaging fertility.
Specific target organ systemic toxicity - repeated exposure, Category 2 (Oral)	H373: May cause damage to organs through prolonged or repeated exposure if swallowed.

GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : H227 Combustible liquid.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H361f Suspected of damaging fertility.
H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read

**SECTION 1. IDENTIFICATION**

Product name : Sikasil® WS-295

Company name : Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
USA
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300
INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Flammable liquids : Category 4


Eye irritation : Category 2A

Skin sensitization : Category 1

Reproductive toxicity : Category 2

Specific target organ toxicity - repeated exposure : Category 2

GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : H227 Combustible liquid.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H361 Suspected of damaging fertility or the unborn child.



H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements :

Prevention:

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
 P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
 P264 Wash skin thoroughly after handling.
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P362 + P364 Take off contaminated clothing and wash it before reuse.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 Store in a well-ventilated place.
 P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration $\geq 1\%$.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)



2-Butanone, O,O',O''-(phenylsilylidyne)trioxime	34036-80-1	Skin Sens. 1; H317 STOT RE 2; H373	>= 1 - < 5
butan-2-one O,O',O''-(methylsilylidyne)trioxime	22984-54-9	Eye Irrit. 2A; H319 Skin Sens. 1; H317 STOT RE 2; H373	>= 1 - < 5
N-(2-aminoethyl)-N'-[3-(trimethoxysilyl)propyl]ethylenediamine	35141-30-1	Acute Tox. 4; H332 Eye Dam. 1; H318 Skin Sens. 1A; H317	>= 1 - < 5
octamethylcyclotetrasiloxane	556-67-2	Flam. Liq. 3; H226 Repr. 2; H361	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects
sensitizing effects
Allergic reactions
Excessive lachrymation
May cause an allergic skin reaction.
Causes serious eye irritation.
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Carbon dioxide (CO₂)



- Unsuitable extinguishing media : Water
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapors or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Store in original container.
Keep in a well-ventilated place.
Observe label precautions.
Store in accordance with local regulations.
- Materials to avoid : Explosives



Oxidizing agents
Poisonous gases
Poisonous liquids

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
Remove respiratory and skin/eye protection only after vapors have been cleared from the area.
Remove contaminated clothing and protective equipment before entering eating areas.
Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES



Appearance	:	paste
Color	:	various
Odor	:	mild, musty
Odor Threshold	:	No data available
pH	:	Not applicable
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	185 °F / 85 °C (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	0.01 hpa
Relative vapor density	:	No data available
Density	:	ca. 1.12 g/cm ³ (73 °F / 23 °C)
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm ² /s (104 °F / 40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds	:	37 g/l



(VOC) content

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions.
Conditions to avoid	:	Extremes of temperature and direct sunlight.
Incompatible materials	:	No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Components:**N-(2-aminoethyl)-N'-[3-(trimethoxysilyl)propyl]ethylenediamine:**

Acute oral toxicity	:	LD50 Oral (Rat): 7,758 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 1.49 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 Dermal (Rat): 16,640 mg/kg

octamethylcyclotetrasiloxane:

Acute inhalation toxicity	:	LC50 (Rat): 36 mg/l Exposure time: 4 h Test atmosphere: vapor
---------------------------	---	---

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC	Group 2B: Possibly carcinogenic to humans titanium dioxide	13463-67-7
	Group 2B: Possibly carcinogenic to humans Carbon black	1333-86-4

OSHA Not applicable

NTP Not applicable

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified based on available information.

Further information**Product:**

Remarks : Carbon black (1333-86-4)
Animal Toxicity:
 Rat, oral, duration 2 year
 Effect: no tumors

 Mouse, oral, duration 2 years
 Effect: no tumors
 Mouse, dermal, duration 18 months
 Effect: no skin tumors
 Rat, inhalation, duration 2 years
 Target organ: lungs
 Effect: inflammation, fibrosis, tumors
 Note: Tumors in the rat lung are considered to be related to the "particle overload phenomenon" rather than to a specific chemical effect of carbon black itself in the lung. These effects in rats have been reported in many studies on other poorly soluble inorganic particles and appear to be rat specific. Tumors have not been observed in other species (i.e., mouse and hamster) for carbon black or other poorly soluble particles under similar circumstances and study conditions.
 Mortality studies (human data): A study on carbon black production workers in the UK (Sorahan, 2001) found an increased risk of lung cancer in two of the five plant studied; however, the increase was not related to the dose of carbon



black. Thus, the authors did not consider the increased risk in lung cancer to be due to carbon black exposure. A German study of carbon black workers at one plant (Morfeld, 2006; Buechte, 2006) found a similar increase in lung cancer risk but, like the Sorohan, 2001 (UK study) found no association with carbon black exposure. A large US study of 18 plants showed a reduction in lung cancer risk in carbon black production workers (DEll, 2006). Based upon these studies, the February 2006 Working Group at the International Agency for Research on Cancer (IARC) concluded that the human evidence for carcinogenicity was inadequate (IARC, 2010). Since the IARC evaluation of carbon black, Sorohan and Harrington (2007) have re-analyzed the UK study data using an alternative exposure hypothesis and found a positive association with carbon black exposure in two of the five plants. The same exposure hypothesis was applied by Morfeld and McCunney (2009) to the German cohort; in contrast, they found no association between carbon black exposure and lung cancer risk and, thus, no support for the alternative exposure hypothesis used by Sorohan and Harrington. Overall, as a result of these detailed investigations, no causative link between carbon black exposure and cancer risk in humans has been demonstrated.

IARC CANCER CLASSIFICATION: In 2006 IARC re-affirmed its 1995 finding that there is "inadequate evidence" from human health studies to assess whether carbon black causes cancer in humans. IARC concluded that there is "sufficient evidence" in experimental animal studies for the carcinogenicity of carbon black. IARC's overall evaluation is that carbon black is "possibly carcinogenic to humans" (Group 2B)". This conclusion was based on IARC's guidelines, which generally require such a classification if one species exhibits carcinogenicity in two or more animal studies (IARC, 2010).

Solvent extracts of carbon black were used in one study of rats in which skin tumors were found after dermal application and several studies of mice in which sarcomas were found following subcutaneous injection. IARC concluded that there was "sufficient evidence" that carbon black extracts can cause cancer in animals (Group 2B).

ICGIH CANCER CLASSIFICATION: Confirmed Animal Carcinogen with Unknown Relevance to Humans (Category A3 Carcinogen).

ASSESSMENT: Applying the guidelines of self-classification under the Globally Harmonized System of Classification and Labeling of Chemicals, carbon black is not classified as a carcinogen. Lung tumors are induced in rats as a result of repeated exposure to inert, poorly soluble particles like carbon black and other poorly soluble particles. Rats tumors are a result of a secondary non-genotoxic mechanism that has questionable relevance for classification in humans. In support of this opinion, the CLP Guidance for Specific Target Organ Toxicity - Repeated Exposure (STOT-RE), cites lung overload



under mechanisms not relevant to humans. Human health studies show that exposure to carbon black does not increase the risk to carcinogenicity.

Titanium dioxide (13463-67-7)

In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have shown to cause an increase in lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. The potential for these adverse health effects appears to be closely related to the particle size and the amount of the exposed surface area that comes into contact with the lung. However, tests with other laboratory animals such as mice and hamsters, indicate that rats are significantly more susceptible to the pulmonary overload and inflammation that causes lung cancer. Epidemiological studies do not suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide. Titanium dioxide has been characterized by IARC as possibly carcinogenic to humans (Group 2B) through inhalation (not ingestion). It has not been characterized as a potential carcinogen by either NTP or OSHA.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Components:

octamethylcyclotetrasiloxane:

Results of PBT and vPvB assessment : PBT substance
: vPvB substance



SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

- TSCA list** : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

- SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)
Respiratory or skin sensitization
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)
Serious eye damage or eye irritation

- SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.



Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop 65



WARNING: Cancer and Reproductive Harm -
www.P65Warnings.ca.gov

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 12/04/2020

000000608042
US / Z8



Safety Data Sheet

Copyright, 2014, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	09-5451-1	Version Number:	26.00
Issue Date:	06/20/14	Supersedes Date:	08/18/13

SECTION 1: Identification

1.1. Product identifier

3M Brand Fire Barrier CP-25WB+

Product Identification Numbers

42-0016-4710-8, 42-0016-4715-7, 42-0016-4716-5, 98-0400-5380-7, 98-0400-5381-5, 98-0400-5382-3, 98-0400-5383-1, 98-0400-5406-0, 98-0400-5456-5, 98-0400-5562-0, 98-0400-5573-7, 98-0400-5610-7, 98-0400-5629-7

1.2. Recommended use and restrictions on use

Recommended use

Fire Protection, Used as Firestop in buildings.

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Industrial Adhesives and Tapes Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

2.2. Label elements

Signal word

Warning

Symbols

Not applicable

Pictograms

Not applicable

Hazard Statements

Causes eye irritation.

Precautionary Statements

General:

Keep out of reach of children.

Prevention:

Wash thoroughly after handling.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

2.3. Hazards not otherwise classified

None.

25% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Zinc Borate 2335	138265-88-0	10 - 30 Trade Secret *
Polymer (NJTS Reg. No. 04499600-7270)	Trade Secret*	10 - 30 Trade Secret *
Water	7732-18-5	10 - 30 Trade Secret *
Sodium Silicate	1344-09-8	10 - 30 Trade Secret *
Ethylhexyldiphenyl phosphate	1241-94-7	3 - 7 Trade Secret *
Oxide glass chemicals	65997-17-3	1 - 5 Trade Secret *
Iron oxide	1309-37-1	1 - 5 Trade Secret *
Polyethylene Glycol	25322-68-3	1 - 5 Trade Secret *
Triphenyl phosphate	115-86-6	< 1.0 Trade Secret *
Di-2-ethylhexylphenyl phosphate	16368-97-1	< 1.0 Trade Secret *
Polyoxyethylene monoocetylphenyl ether	9036-19-5	< 1.0 Trade Secret *
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	55965-84-9	< 0.001 Trade Secret *

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Non-combustible. Use a fire fighting agent suitable for surrounding fire.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid eye contact. Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

7.2. Conditions for safe storage including any incompatibilities

Keep cool. Store away from heat. Store away from areas where product may come into contact with food or pharmaceuticals. Store in a dry place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Triphenyl phosphate	115-86-6	ACGIH	TWA:3 mg/m3	
Triphenyl phosphate	115-86-6	OSHA	TWA:3 mg/m3	

Iron oxide	1309-37-1	ACGIH	TWA(respirable fraction):5 mg/m3	
Iron oxide	1309-37-1	OSHA	TWA(as fume):10 mg/m3	
ROUGE	1309-37-1	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
Polyethylene Glycol	25322-68-3	AIHA	TWA(as particulate):10 mg/m3	
Oxide glass chemicals	65997-17-3	Manufacturer determined	TWA(as dust):10 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists
 AIHA : American Industrial Hygiene Association
 CMRG : Chemical Manufacturer's Recommended Guidelines
 OSHA : United States Department of Labor - Occupational Safety and Health Administration
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

Neoprene

Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form: Solid
Specific Physical Form: Paste
Odor, Color, Grade: Red with negligible odor

Odor threshold	<i>No Data Available</i>
Melting point	<i>No Data Available</i>
Flash Point	No flash point
Flammability (solid, gas)	Not Classified
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>

Specific Gravity	1.35 [<i>Ref Std: WATER=1</i>]
Solubility in Water	Complete
Solubility- non-water	<i>No Data Available</i>
Autoignition temperature	<i>Not Applicable</i>
Decomposition temperature	<i>No Data Available</i>
Volatile Organic Compounds	< 1 g/l
VOC Less H2O & Exempt Solvents	< 1 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified
Oxides of Phosphorus	Not Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient

classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
Polymer (NJTS Reg. No. 04499600-7270)	Ingestion	Rat	LD50 > 2,000 mg/kg
Zinc Borate 2335	Dermal	Rabbit	LD50 > 10,000 mg/kg
Zinc Borate 2335	Ingestion	Rat	LD50 > 10,000 mg/kg
Sodium Silicate	Dermal	Rabbit	LD50 > 4,640 mg/kg
Sodium Silicate	Ingestion	Rat	LD50 500 mg/kg
Ethylhexyldiphenyl phosphate	Dermal	Rabbit	LD50 > 7,940 mg/kg
Ethylhexyldiphenyl phosphate	Ingestion	Rat	LD50 > 24,000 mg/kg
Iron oxide	Dermal	Not available	LD50 3,100 mg/kg
Iron oxide	Ingestion	Not available	LD50 3,700 mg/kg
Polyethylene Glycol	Dermal	Rabbit	LD50 > 20,000 mg/kg
Polyethylene Glycol	Ingestion	Rat	LD50 32,770 mg/kg
Oxide glass chemicals	Dermal		LD50 estimated to be > 5,000 mg/kg
Oxide glass chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Polyoxyethylene monoocetylphenyl ether	Dermal	Rabbit	LD50 > 3,000 mg/kg
Polyoxyethylene monoocetylphenyl ether	Ingestion	Rat	LD50 > 500 mg/kg
Triphenyl phosphate	Dermal	Rabbit	LD50 > 7,900 mg/kg
Triphenyl phosphate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 50 mg/l
Triphenyl phosphate	Ingestion	Rat	LD50 > 3,000 mg/kg
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Dermal	Rabbit	LD50 87 mg/kg
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.33 mg/l

3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Ingestion	Rat	LD50 40 mg/kg
--	-----------	-----	---------------

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Polymer (NJTS Reg. No. 04499600-7270)	Rabbit	Minimal irritation
Sodium Silicate	Rabbit	Corrosive
Iron oxide	Rabbit	No significant irritation
Polyethylene Glycol	Rabbit	Minimal irritation
Oxide glass chemicals		No significant irritation
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Polymer (NJTS Reg. No. 04499600-7270)		Mild irritant
Sodium Silicate	Rabbit	Corrosive
Iron oxide	Rabbit	No significant irritation
Polyethylene Glycol	Rabbit	Mild irritant
Oxide glass chemicals		No significant irritation
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
Sodium Silicate	Mouse	Not sensitizing
Iron oxide	Human	Some positive data exist, but the data are not sufficient for classification
Polyethylene Glycol	Guinea pig	Not sensitizing
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Human and animal	Sensitizing

Photosensitization

Name	Species	Value
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Human and animal	Not sensitizing

Respiratory Sensitization

Name	Species	Value

Germ Cell Mutagenicity

Name	Route	Value
Sodium Silicate	In Vitro	Not mutagenic
Sodium Silicate	In vivo	Not mutagenic
Iron oxide	In Vitro	Not mutagenic
Polyethylene Glycol	In Vitro	Not mutagenic
Polyethylene Glycol	In vivo	Not mutagenic
Oxide glass chemicals	In Vitro	Some positive data exist, but the data are not sufficient for classification
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	In vivo	Not mutagenic
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Iron oxide	Inhalation	Human	Some positive data exist, but the data are not

			sufficient for classification
Polyethylene Glycol	Ingestion	Rat	Not carcinogenic
Oxide glass chemicals	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Dermal	Mouse	Not carcinogenic
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Sodium Silicate	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Mouse	NOAEL 200 mg/kg/day	during gestation
Polyethylene Glycol	Ingestion	Not toxic to female reproduction	Rat	NOAEL 1,125 mg/kg/day	during gestation
Polyethylene Glycol	Ingestion	Not toxic to male reproduction	Rat	NOAEL 5699 +/- 1341 mg/kg/day	5 days
Polyethylene Glycol	Not Specified	Some positive reproductive/developmental data exist, but the data are not sufficient for classification		NOEL N/A	
Polyethylene Glycol	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Mouse	NOAEL 562 mg/animal/day	during gestation
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Ingestion	Not toxic to female reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Ingestion	Not toxic to male reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Ingestion	Not toxic to development	Rat	NOAEL 15 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Sodium Silicate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
Polyethylene Glycol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.008 mg/l	2 weeks
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Sodium Silicate	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Dog	LOAEL 2,400 mg/kg/day	4 weeks
Sodium Silicate	Ingestion	endocrine system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 804 mg/kg/day	3 months
Sodium Silicate	Ingestion	blood	All data are negative	Rat	NOAEL 804	3 months

					mg/kg/day	
Sodium Silicate	Ingestion	heart liver	All data are negative	Rat	NOAEL 1,259 mg/kg/day	8 weeks
Iron oxide	Inhalation	pulmonary fibrosis pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Polyethylene Glycol	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.008 mg/l	2 weeks
Polyethylene Glycol	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 5,640 mg/kg/day	13 weeks
Polyethylene Glycol	Ingestion	heart endocrine system hematopoietic system liver nervous system	All data are negative	Rat	NOAEL 5,640 mg/kg/day	13 weeks
Oxide glass chemicals	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL not available	occupational exposure

Aspiration Hazard

Name	Value

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Test Organism	Test Type	Result
Water flea, Daphnia magna	48 hours Aquatic Toxicity - Acute	27 mg/l
Green algae, Pseudokirchneriella subcapitata	72 hours Aquatic Toxicity - Chronic	2.6 mg/l

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Zinc Borate 2335 (ZINC COMPOUNDS)	138265-88-0	10 - 30

15.2. State Regulations

15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA.

15.4. International Regulations

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 1 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 2 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® III) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® III ratings are to be used with a fully implemented HMIS® III program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document Group:	09-5451-1	Version Number:	26.00
Issue Date:	06/20/14	Supersedes Date:	08/18/13

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com