

Interior expansion joint covers from EMSEAL are designed to maximize durability and coordinate aesthetically.

*\*Stock Item: These are short-lead-time items stocked by EMSEAL in quantities usually sufficient to meet project demands. If not in stock EMSEAL will provide an import quote and lead time.*



Migutec FGH2 65/30 <span style="float: right; border: 1px solid white; padding: 2px 5px; border-radius: 3px;">Product Details &gt;</span>	
Description	Details
Alum/rubber Recessed mount Standard load rating	Joint sizes: 13/16" – 2" (20 – 50mm)  Movement: 3/4"= +3/8", -3/8" (20mm= +10mm, -10mm)



Migutec FP 55/35 <span style="float: right; border: 1px solid white; padding: 2px 5px; border-radius: 3px;">Product Details &gt;</span>	
Description	Details
Alum/elastomeric Recess mount Standard load rating	Joint size: 1/2" – 2" (13 – 50mm)  Movement: 5/8"= +5/16", -5/16" 16mm= +8mm, -8mm



Migutec KF 250/KFE 251 <span style="float: right; border: 1px solid white; padding: 2px 5px; border-radius: 3px;">Product Details &gt;</span>	
Description	Details
Solid aluminum Surface mount	Joint sizes: 1/2" – 3 1/4" (13 – 80mm)  Movement: Max open joint: 3 1/4" (80mm) Min closed joint: 1/4" (7mm)



Migutec FV 35/35 <span style="float: right; border: 1px solid white; padding: 2px 5px; border-radius: 3px;">Product Details &gt;</span>	
Description	Details
Alum/elastomeric Recess mount Standard load rating	Joint sizes: 3/16" – 1 1/4" (5 – 30mm)  Movement: 3/8"= +3/16", -3/16" (10mm= +5mm, -5mm)



## Migutec FN 20/12

[Product Details](#) >

### Description

Alum/rubber  
Surface mount  
Standard load rating

### Details

Joint sizes:  
3/4" - 1 1/4" (20 - 30mm)  
Movement:  
3/16"= + 1/8", - 1/16"  
(5mm= +3mm, -2mm)



## Migutec FN 35/15

[Product Details](#) >

### Description

Alum/elastomeric  
Surface mount  
Standard load rating

### Details

Joint sizes:  
1 3/8" - 1 7/8" (35 - 48mm)  
Movement:  
3/8"= + 3/16", - 3/16"  
(10mm= +5mm, -5mm)



## Migutec FN 50/20

[Product Details](#) >

### Description

Alum/elastomeric  
Surface mount  
Standard load rating

### Details

Joint size:  
2" - 2 1/2" (50 - 65mm)  
Movement:  
5/8"= + 5/16", - 5/16"  
(16mm= +8mm, -8mm)